The Sovereign Referee Protocol (SRP): A Stateless Architecture for Trustless Peer-to-Peer Poker

Sonia Kolasinska

February 2026

Abstract

For exactly 47 years, the realization of a purely decentralized, dealer-less card game has been constrained by the computational limitations of verifiable multi-party computation (MPC). This paper introduces the Sovereign Referee Protocol (SRP), a stateless, peer-to-peer architecture designed for Arbitrum Stylus. By utilizing commutative encryption over the BLS12-381 elliptic curve, threshold signatures, and a highly optimized on-chain Miller Loop verifier, SRP eliminates the need for a trusted house. The protocol introduces an economic heartbeat to solve the historical "liveness" problem of Mental Poker, creating the first commercially viable, purely sovereign digital casino environment.

1 Introduction

The theoretical foundation for dealer-less card games was established in 1979 with the publication of the original Mental Poker algorithm. However, practical implementations have consistently failed due to two insurmountable friction points: the exorbitant gas costs associated with verifying cryptographic shuffles on-chain, and the vulnerability of the game state to offline participants (the liveness problem). The Sovereign Referee Protocol (SRP) dismantles these barriers. By leveraging the Arbitrum Stylus WebAssembly (WASM) environment and the custom-built `crum_bls` cryptographic library, SRP offloads all state management to the peer-to-peer layer. The blockchain is relegated to the role of a "Stateless Referee," only executing mathematically complex audits when settling a hand or resolving a dispute.

2 Core Architecture

The SRP is built upon three foundational pillars that ensure complete privacy, autonomous consensus, and strict execution.

2.1 Pillar 1: The Collective Shuffled State

The deck does not exist as an array of integers on a centralized server. Instead, it is initialized as a vector of 52 distinct points on the G_1 elliptic curve. Each player generates a secret scalar sk_i and applies it to the deck commutatively. For a given card $C \in G_1$, the fully masked point M in an N-player game is:

$$M = C \cdot sk_1 \cdot sk_2 \cdots sk_N$$

Because the scalar multiplication is commutative, players can remove (peel) their cryptographic locks in any order using the modular inverse of their secret key (sk_i^{-1}).

2.2 Pillar 2: The Stateless Audit

To ensure that no player substitutes a card during the unmasking phase, SRP employs an on-chain verification engine. To maintain a minimal data footprint, card points and signatures reside in the G_1 group (48 bytes compressed), while player Public Keys (PK) reside in the G_2 group (96 bytes). When a player claims to unmask a card point M to produce point U, the Stylus smart contract verifies the integrity of the operation using a Bilinear Pairing (Miller Loop):

$$e(U, PK) = e(M, G_2)$$

If the player acted honestly, $U = M \cdot sk^{-1}$ and $PK = G_2 \cdot sk$, satisfying the pairing identity without ever revealing sk to the network.

2.3 Pillar 3: The Economic Heartbeat

To solve the liveness problem, SRP enforces game continuity through economic slashing. Every cryptographic transition is bound by a 120-second timeout mechanism. If a player fails to provide their unmasked point or threshold signature share, their stake is forfeited to the active participants.

3 Implementation: The `crum_bls` Kernel

The protocol relies on the `crum_bls` library, optimized specifically for Arbitrum Stylus. It bridges high-level cryptographic theory with native Ethereum standards via three key components:

- **Keccak-256 Adapter:** An implementation of the `digest::Digest` trait allows the native `alloy_primitives::Keccak256` hashing function to map arbitrary data directly to the BLS12-381 curve, ensuring zero-overhead compatibility with Ethereum wallets.
- **Lagrange Interpolation:** Players use M-of-N threshold signatures to reach consensus on betting rounds. If a player drops offline, the remaining threshold can mathematically reconstruct the Master Signature, allowing the game to settle gracefully.
- **Vector Unmasking:** The verifier is capable of batch-verifying multiple unmasking steps (e.g., a 5-card Texas Hold'em community flop) in a single atomic transaction.

4 The Lifecycle of a Poker Hand

To guarantee a trustless environment, the protocol strictly enforces the state machine of a Texas Hold'em hand. The blockchain does not store the deck; rather, it acts as a decentralized state channel where participants commit to actions.

- **Initialization:** The deck is initialized as a vector of 52 distinct points on the G_1 elliptic curve.
- **The Shuffle Phase:** Player 1 applies their secret scalar sk_1 to mask the deck and shuffles the order, privately recording a shuffle trace for later proof. Player 2 receives the deck, applies their secret scalar sk_2, shuffles, and records their own trace. Neither player knows the final card order.
- **Posting Blinds:** Players commit to the initial pot size using M-of-N threshold signatures to reach consensus on the betting state.

- **Dealing Hole Cards:** Two cards are dealt to each player. To reveal Player 1's cards, Player 2 must first peel their cryptographic lock. Player 1 then removes their own lock to view the plaintext card.
- **Community Rounds (Flop, Turn, River):** During each betting street, community cards are unmasked collectively. All active players must apply the modular inverse of their secret keys to reveal the public cards.
- **Showdown and Audit:** At the conclusion of the hand, players submit their ephemeral public keys and shuffle traces. The protocol performs a highly optimized batch verification to ensure no player manipulated the shuffle or unmasking phases.

5 Zero-Knowledge Shuffle Verification

To prevent a player from stacking the deck during their turn to shuffle, the protocol demands proof of fairness without leaking the card permutation during active gameplay.

- **Trace Generation:** When a player shuffles the masked deck, they generate a `ShuffleTrace` that maps the before index of a card to its after index.
- **Deferred Verification:** These traces are kept secret during the hand. At the showdown (or in the event of a dispute), the player reveals their ephemeral public key and the trace.
- **Validation:** The protocol uses the public key to mathematically verify that the output deck is a valid permutation of the input deck, ensuring no cards were duplicated, dropped, or swapped with unauthorized curve points.

6 Verifying the Unmasking via Bilinear Pairings

When a player unmasks a card, they must prove they used the correct secret key without actually revealing that key to the network. The Stylus smart contract acts as the "Stateless Referee" to verify this.

- **The Pairing Check:** When a player claims to unmask a card point M to produce point U, the contract verifies the integrity using a Miller Loop.
- **The Identity:** The pairing must satisfy $e(U, PK) = e(M, G_2)$. If the player acted honestly, $U = M \cdot sk^{-1}$ and $PK = G_2 \cdot sk$, satisfying the pairing identity without exposing the secret scalar.
- **Batch Optimization:** Instead of verifying every single unmasking action individually, the protocol constructs a massive batch for the Miller Loop. It performs a single $O(1)$ final exponentiation for the entire game's unmasking history. It only falls back to individual checks if the batch fails, precisely identifying the cheater.

7 Conclusions and Commercial Applications

The Sovereign Referee Protocol successfully maps a 47-year-old cryptographic theory into a modern, high-performance financial infrastructure. By treating the blockchain strictly as a stateless arbiter of the Miller Loop, SRP provides a blueprint for a fully decentralized, trustless, and infinitely scalable gaming ecosystem.

This architecture enables several highly viable deployment models for trustless gaming:

- **Robust On-Chain Poker (Arbitrum Stylus):** Players can commit deck hashes and state channels directly to an Arbitrum smart contract. The contract only executes the heavy cryptographic verifications when a hand goes to showdown or a timeout triggers the economic heartbeat slashing.
- **Completely Off-Chain P2P Poker:** Two players can establish a direct peer-to-peer connection, exchanging masked points and threshold signatures over WebRTC or standard TCP. The blockchain is used strictly as a fallback dispute resolution layer.
- **Server-Assisted Routing:** A central server can act purely as a message router and lobby generator to solve the UX hurdles of peer-to-peer discovery. Because the server does not possess the players' secret scalars, it is mathematically impossible for the house to see the cards or rig the deck, eliminating the need for trust in the operator.

8 Future Work: Commercializing Peer-to-Peer Poker

While the Sovereign Referee Protocol (SRP) successfully demonstrates the cryptographic foundation for trustless gameplay, translating this architecture into a mass-market consumer product requires further development at the application layer. Future iterations of this project will focus on the following productization strategies:

- **Account Abstraction (ERC-4337) Integration:** To provide a seamless user experience comparable to traditional Web2 poker platforms, gas fees and transaction signing must be abstracted away from the player. Implementing paymasters will allow players to fund their sessions using stablecoins (e.g., USDC) without needing native gas tokens.
- **Decentralized Lobbies and Matchmaking:** Currently, the protocol assumes players can discover each other and form a table off-chain. Future work will involve building a decentralized matchmaking layer, potentially utilizing a peer-to-peer gossip network or a lightweight server-assisted router to connect players globally without acting as a trusted intermediary.
- **Cross-Chain Liquidity and Settlement:** Extending the Arbitrum Stylus implementation to support bridging and settlement across multiple Layer 2 rollups. This would allow players with funds on different networks to sit at the same virtual table, settling balances atomically at the end of the session.
- **Verifiable Reputation and Leaderboards:** Developing an on-chain reputation system where player statistics, tournament wins, and behavior (e.g., not timing out) are cryptographically verifiable, paving the way for decentralized, high-stakes tournament ecosystems.