

B. Asymptotics and Computational Cost

We introduce Big-O, little-o and asymptotic notation and see how they can be used to describe computational cost.

1. Asymptotics as $n \rightarrow \infty$
2. Asymptotics as $x \rightarrow x_0$
3. Computational cost

1. Asymptotics as $n \rightarrow \infty$

Big-O, little-o, and "asymptotic to" are used to describe behaviour of functions at infinity.

Definition 1 (Big-O)

$$f(n) = O(\phi(n)) \quad (\text{as } n \rightarrow \infty)$$

means $\left| \frac{f(n)}{\phi(n)} \right|$ is bounded for sufficiently large n . That is, there exist constants C and N_0 such that, for all $n \geq N_0$, $\left| \frac{f(n)}{\phi(n)} \right| \leq C$.

Definition 2 (little-O)

$$f(n) = o(\phi(n)) \quad (\text{as } n \rightarrow \infty)$$

means $\lim_{n \rightarrow \infty} \frac{f(n)}{\phi(n)} = 0$.

Definition 3 (asymptotic to)

$$f(n) \sim \phi(n) \quad (\text{as } n \rightarrow \infty)$$

means $\lim_{n \rightarrow \infty} \frac{f(n)}{\phi(n)} = 1$.

Examples

1. \$

$$\left\{ \frac{\cos n}{n^2 - 1} \right\} = O(n^{-2}) \text{ as } \left| \frac{\cos n}{n^2 - 1} \right| \leq \left| \frac{n^2}{n^2 - 1} \right| \leq 2 \text{ for } n \geq N_0 = 2.$$

2. \$

$$\log n = o(n) \text{ as } \lim_{n \rightarrow \infty} \left\{ \frac{\log n}{n} \right\} = 0.$$

3. \$

$$n^2 + 1 \sim n^2 \text{ as } \{n^2 + 1 \over n^2\} \rightarrow 1.$$

Note we sometimes write $f(O(\phi(n)))$ for a function of the form $f(g(n))$ such that $g(n) = O(\phi(n))$.

Rules

We have some simple algebraic rules:

Proposition 1 (Big-O rules)

$$\begin{aligned} O(\phi(n))O(\psi(n)) &= O(\phi(n)\psi(n)) && (\text{as } n \rightarrow \infty) \\ O(\phi(n)) + O(\psi(n)) &= O(|\phi(n)| + |\psi(n)|) && (\text{as } n \rightarrow \infty). \end{aligned}$$

2. Asymptotics as $x \rightarrow x_0$

We also have Big-O, little-o and "asymptotic to" at a point:

Definition 4 (Big-O)

$$f(x) = O(\phi(x)) \quad (\text{as } x \rightarrow x_0)$$

means $|\frac{f(x)}{\phi(x)}|$ is bounded in a neighbourhood of x_0 . That is, there exist constants C and r such that, for all $0 \leq |x - x_0| \leq r$, $|\frac{f(x)}{\phi(x)}| \leq C$.

Definition 5 (little-O)

$$f(x) = o(\phi(x)) \quad (\text{as } x \rightarrow x_0)$$

means $\lim_{x \rightarrow x_0} \frac{f(x)}{\phi(x)} = 0$.

Definition 6 (asymptotic to)

$$f(x) \sim \phi(x) \quad (\text{as } x \rightarrow x_0)$$

means $\lim_{x \rightarrow x_0} \frac{f(x)}{\phi(x)} = 1$.

Example

$$\exp x = 1 + x + O(x^2) \quad \text{as } x \rightarrow 0$$

since $\exp x = 1 + x + \frac{\exp t}{2}x^2$ for some $t \in [0, x]$ and

$$\left| \frac{\frac{\exp t}{2}x^2}{x^2} \right| \leq \frac{3}{2}$$

provided $x \leq 1$.

3. Computational cost

We will use Big-O notation to describe the computational cost of algorithms. Consider the following simple sum

$$\sum_{k=1}^n x_k^2$$

which we might implement as:

```
In [1]: function sumsq(x)
        n = length(x)
        ret = 0.0
        for k = 1:n
            ret = ret + x[k]^2
        end
        ret
    end

n = 100
x = randn(n)
sumsq(x)
```

Out[1]: 90.95882254617737

Each step of this algorithm consists of one memory look-up (`z = x[k]`), one multiplication (`w = z*z`) and one addition (`ret = ret + w`). We will ignore the memory look-up in the following discussion. The number of CPU operations per step is therefore 2 (the addition and multiplication). Thus the total number of CPU operations is $2n$. But the constant 2 here is misleading: we didn't count the memory look-up, thus it is more sensible to just talk about the asymptotic complexity, that is, the *computational cost* is $O(n)$.

Now consider a double sum like:

$$\sum_{k=1}^n \sum_{j=1}^k x_j^2$$

which we might implement as:

```
In [2]: function sumsq2(x)
        n = length(x)
        ret = 0.0
        for k = 1:n
            for j = 1:k
                ret = ret + x[j]^2
            end
        end
        ret
    end
```

```
n = 100  
x = randn(n)  
sumsq2(x)
```

Out[2]: 5377.916656174812

Now the inner loop is $O(1)$ operations (we don't try to count the precise number), which we do k times for $O(k)$ operations as $k \rightarrow \infty$. The outer loop therefore takes

$$\sum_{k=1}^n O(k) = O\left(\sum_{k=1}^n k\right) = O\left(\frac{n(n+1)}{2}\right) = O(n^2)$$

operations.