



BlockSec

Security Audit Report for Impossible Finance Launchpad contract

Date: May 23, 2022

Version: 2.0

Contact: contact@blocksec.com

Contents

1	Introduction	1
1.1	About Target Contracts	1
1.2	Disclaimer	1
1.3	Procedure of Auditing	1
1.3.1	Software Security	2
1.3.2	DeFi Security	2
1.3.3	NFT Security	2
1.3.4	Additional Recommendation	2
1.4	Security Model	3
2	Findings	4
2.1	DeFi Security	4
2.1.1	Update Checkpoint after Emergency Withdraw	4
2.1.2	Potential Unfair Staking	5
2.1.3	Potential Unfair Claiming	6
2.1.4	Do Not Use Elastic Supply Tokens	7
2.2	Additional Recommendation	8
2.2.1	Unchecked Function Parameters	9

Report Manifest

Item	Description
Client	Impossible Finance
Target	Impossible Finance Launchpad contract

Version History

Version	Date	Description
2.0	May 23, 2022	Second version

About BlockSec The **BlockSec Team** focuses on the security of the blockchain ecosystem, and collaborates with leading DeFi projects to secure their products. The team is founded by top-notch security researchers and experienced experts from both academia and industry. They have published multiple blockchain security papers in prestigious conferences, reported several zero-day attacks of DeFi applications, and released detailed analysis reports of high-impact security incidents. They can be reached at **Email**, **Twitter** and **Medium**.

Chapter 1 Introduction

1.1 About Target Contracts

Information	Description
Type	Smart Contract
Language	Solidity
Approach	Semi-automatic and manual verification

The repository that has been audited includes launchpad-contracts (IFLaunchpad) ¹.

The auditing process is iterative. Specifically, we will audit the commits that fix the discovered issues. If there are new issues, we will continue this process. The commit SHA values during the audit are shown in the following. Our audit report is responsible for the only initial version ([Version 1](#)), as well as new codes (in the following versions) to fix issues in the audit report.

Project	Version	Commit SHA
IF Launchpad	Version 1	48644aa00587e46f32725c6b5094746cdc32d5c3
	Version 2	233a159d769564992677ea03dd7e1555152a4d94

1.2 Disclaimer

This audit report does not constitute investment advice or a personal recommendation. It does not consider, and should not be interpreted as considering or having any bearing on, the potential economics of a token, token sale or any other product, service or other asset. Any entity should not rely on this report in any way, including for the purpose of making any decisions to buy or sell any token, product, service or other asset.

This audit report is not an endorsement of any particular project or team, and the report does not guarantee the security of any particular project. This audit does not give any warranties on discovering all security issues of the smart contracts, i.e., the evaluation result does not guarantee the nonexistence of any further findings of security issues. As one audit cannot be considered comprehensive, we always recommend proceeding with independent audits and a public bug bounty program to ensure the security of smart contracts.

The scope of this audit is limited to the code mentioned in Section 1.1. Unless explicitly specified, the security of the language itself (e.g., the solidity language), the underlying compiling toolchain and the computing infrastructure are out of the scope.

1.3 Procedure of Auditing

We perform the audit according to the following procedure.

- **Vulnerability Detection** We first scan smart contracts with automatic code analyzers, and then manually verify (reject or confirm) the issues reported by them.

¹<https://github.com/ImpossibleFinance/launchpad-contracts>

- **Semantic Analysis** We study the business logic of smart contracts and conduct further investigation on the possible vulnerabilities using an automatic fuzzing tool (developed by our research team). We also manually analyze possible attack scenarios with independent auditors to cross-check the result.
 - **Recommendation** We provide some useful advice to developers from the perspective of good programming practice, including gas optimization, code style, and etc.
- We show the main concrete checkpoints in the following.

1.3.1 Software Security

- * Reentrancy
- * DoS
- * Access control
- * Data handling and data flow
- * Exception handling
- * Untrusted external call and control flow
- * Initialization consistency
- * Events operation
- * Error-prone randomness
- * Improper use of the proxy system

1.3.2 DeFi Security

- * Semantic consistency
- * Functionality consistency
- * Access control
- * Business logic
- * Token operation
- * Emergency mechanism
- * Oracle security
- * Whitelist and blacklist
- * Economic impact
- * Batch transfer

1.3.3 NFT Security

- * Duplicated item
- * Verification of the token receiver
- * Off-chain metadata security

1.3.4 Additional Recommendation

- * Gas optimization
- * Code quality and style



Note The previous checkpoints are the main ones. We may use more checkpoints during the auditing process according to the functionality of the project.

1.4 Security Model

To evaluate the risk, we follow the standards or suggestions that are widely adopted by both industry and academy, including OWASP Risk Rating Methodology ² and Common Weakness Enumeration ³. The overall *severity* of the risk is determined by *likelihood* and *impact*. Specifically, likelihood is used to estimate how likely a particular vulnerability can be uncovered and exploited by an attacker, while impact is used to measure the consequences of a successful exploit.

In this report, both likelihood and impact are categorized into two ratings, i.e., *high* and *low* respectively, and their combinations are shown in Table 1.1.

Table 1.1: Vulnerability Severity Classification

Impact	High	High	Medium
	Low	Medium	Low
		High	Low
		Likelihood	

Accordingly, the severity measured in this report are classified into three categories: **High**, **Medium**, **Low**. For the sake of completeness, **Undetermined** is also used to cover circumstances when the risk cannot be well determined.

Furthermore, the status of a discovered issue will fall into one of the following four categories:

- **Undetermined** No response yet.
- **Acknowledged** The issue has been received by the client, but not confirmed yet.
- **Confirmed** The issue has been recognized by the client, but not fixed yet.
- **Fixed** The issue has been confirmed and fixed by the client.

²https://owasp.org/www-community/OWASP_Risk_Rating_Methodology

³<https://cwe.mitre.org/>

Chapter 2 Findings

In total, we find **four** potential issues. We have **one** recommendation.

- High Risk: 0
- Medium Risk: 1
- Low Risk: 3
- Recommendations: 1

ID	Severity	Description	Category	Status
1	Medium	Update Checkpoint after Emergency Withdraw	DeFi Security	Fixed
2	Low	Potential Unfair Staking	DeFi Security	Confirmed
3	Low	Potential Unfair Claiming	DeFi Security	Confirmed
4	Low	Do Not Use Elastic Supply Tokens	DeFi Security	Confirmed
5	-	Unchecked Function Parameters	Recommendation	Fixed

The details are provided in the following sections.

2.1 DeFi Security

2.1.1 Update Checkpoint after Emergency Withdraw

Severity Medium

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description The function `emergencyWithdraw` can be invoked when a track is disabled. Normally a user can withdraw staked tokens according to the latest checkpoint. However, the checkpoint of this user is not updated in the function `emergencyWithdraw`.

As a result, an attacker can withdraw twice by calling the function `emergencyWithdraw` and then the function `unstake` when a track is disabled.

```
786 function emergencyWithdraw(uint24 trackId) external nonReentrant {
787     // require track is disabled
788     require(trackDisabled[trackId], 'track !disabled');
789
790     // require can only emergency withdraw once
791     require(
792         !hasEmergencyWithdrawn[trackId][_msgSender()],
793         'already called'
794     );
795
796     // set emergency withdrawn status to true
797     hasEmergencyWithdrawn[trackId][_msgSender()] = true;
798
799     // get track info
800     TrackInfo storage track = tracks[trackId];
801
```

```
802     /// get user latest checkpoint
803
804     // get number of user's checkpoints within this track
805     uint32 userCheckpointCount = userCheckpointCounts[trackId][
806         _msgSender()
807     ];
808
809     // get user's latest checkpoint
810     UserCheckpoint storage checkpoint = userCheckpoints[trackId][
811         _msgSender()
812     ][userCheckpointCount - 1];
813
814     // transfer the specified amount of stake token from this contract to user
815     track.stakeToken.safeTransfer(_msgSender(), checkpoint.staked);
816
817     // emit
818     emit EmergencyWithdraw(trackId, _msgSender(), checkpoint.staked);
819 }
```

Listing 2.1: IFAllocationMaster.sol

Impact Users' staking tokens may be stolen.

Suggestion Update checkpoints after the emergency withdraw.

2.1.2 Potential Unfair Staking

Severity Low

Status Confirmed

Introduced by [Version 1](#)

Description The user's allocation for the staking of a platform token is determined by the stake amount held over time. However, a user can listen to the `addTrack` transaction and immediately stake a platform token. Since the user is the first one who participates into the IDO, he or she can have a better opportunity to get a large allocation than later participants. Then the user can unstake and withdraw his/her stake tokens without purchasing before the ending of the sale. This can prevent other fair participants who want to buy into an IDO, causing a denial of service.

```
500     function addUserCheckpoint(
501         uint24 trackId,
502         uint104 amount,
503         bool addElseSub
504     ) internal {
505         // get track info
506         TrackInfo storage track = tracks[trackId];
507
508         // get user checkpoint count
509         uint32 nCheckpointsUser = userCheckpointCounts[trackId][_msgSender()];
510
511         // get track checkpoint count
512         uint32 nCheckpointsTrack = trackCheckpointCounts[trackId];
513     }
```



```
514     // get latest track checkpoint
515     TrackCheckpoint memory trackCp = trackCheckpoints[trackId][
516         nCheckpointsTrack - 1
517     ];
518
519     // if this is first checkpoint
520     if (nCheckpointsUser == 0) {
521         // check if amount exceeds maximum
522         require(amount <= track.maxTotalStake, 'exceeds staking cap');
```

Listing 2.2: IFAllocationMaster.sol

Although there is a limit on the maximum stake cap `TrackInfo.maxTotalStake` of a user, an attacker can bypass it easily by creating lots accounts and switching his/her accounts.

Impact The can potentially cause a denial of service to an IDO.

Suggestion Add timelock mechanism for unstaking.

Feedback from the Project One user can only KYC one wallet address, which is guaranteed by the manual review.

2.1.3 Potential Unfair Claiming

Severity Low

Status Confirmed

Introduced by Version 1

Description Some functions in the contract `IFAllocationSale` can be attacked by **Sybil Attack**.

When allocation of `saleToken` is overided, every user has a fixed limit to claim or purchase. However, an attacker can bypass it by creating many accounts.

Take the function `withdrawGiveaway` for example, every user can claim `saleTokenAllocationOverride` amounts of `saleToken`. An attacker can claim all `saleToken` in one transaction by invoking the function `withdrawGiveaway` repeatedly using different accounts.

```
433     function withdrawGiveaway(bytes32[] calldata merkleProof)
434         external
435         nonReentrant
436     {
437         // must be past end timestamp plus withdraw delay
438         require(
439             endTime + withdrawDelay < block.timestamp,
440             'cannot withdraw yet'
441         );
442         // prevent repeat withdraw
443         require(hasWithdrawn[_msgSender()] == false, 'already withdrawn');
444         // must be a zero price sale
445         require(salePrice == 0, 'not a giveaway');
446         // if there is whitelist, require that user is whitelisted by checking proof
447         require(
448             whitelistRootHash == 0 || checkWhitelist(_msgSender(), merkleProof),
449             'proof invalid'
450         );
```

```
451     uint256 saleTokenOwed;
452     // each participant in the zero cost "giveaway" gets a flat amount of sale token
453     if (saleTokenAllocationOverride == 0) {
454         // if there is no override, fetch the total payment allocation
455         saleTokenOwed = getUserStakeValue(_msgSender());
456     } else {
457         // if override, set the override amount
458         saleTokenOwed = saleTokenAllocationOverride;
459     }
460     // sale token owed must be greater than 0
461     require(saleTokenOwed != 0, 'withdraw giveaway amount 0');
462
463     // set withdrawn to true
464     hasWithdrawn[_msgSender()] = true;
465
466     // increment withdrawer count
467     withdrawerCount += 1;
468
469     // transfer giveaway sale token to participant
470     saleToken.safeTransfer(_msgSender(), saleTokenOwed);
471
472     // emit
473     emit Withdraw(_msgSender(), saleTokenOwed);
474 }
```

Listing 2.3: IFAllocationSale.sol

There exists a same issue in the function `_purchase`.

Impact All tokens can be claimed or purchased by a single malicious user.

Feedback from the Project In every sale the whitelist root hash will be set, which is guaranteed by the manual review.

2.1.4 Do Not Use Elastic Supply Tokens

Severity Low

Status Confirmed

Introduced by Version 1

Description Some functions do not consider the elastic supply tokens when performing the token transfer, such as:

The function `stake` in the contract `IFAllocationMaster`:

```
728     // transfer the specified amount of stake token from user to this contract
729     track.stakeToken.safeTransferFrom(_msgSender(), address(this), amount);
730
731     // add user checkpoint
732     addUserCheckpoint(trackId, amount, true);
733
734     // add track checkpoint
735     addTrackCheckpoint(trackId, amount, true, false);
```

Listing 2.4: IFAllocationMaster.sol

The function `fund` in the contract `IFAllocationSale`:

```
164 function fund(uint256 amount) external onlyFunder {
165     // sale must not have started
166     require(block.timestamp < startTime, 'sale already started');
167
168     // transfer specified amount from funder to this contract
169     saleToken.safeTransferFrom(_msgSender(), address(this), amount);
170
171     // increase tracked sale amount
172     saleAmount += amount;
173
174     // emit
175     emit Fund(_msgSender(), amount);
176 }
```

Listing 2.5: IFAllocationSale.sol

The function `_purchase` in the contract `IFAllocationSale`:

```
341 // transfer specified amount from user to this contract
342 paymentToken.safeTransferFrom(
343     address(_msgSender()),
344     address(this),
345     paymentAmount
346 );
347
348 // if user is paying for the first time to this contract, increase counter
349 if (paymentReceived[_msgSender()] == 0) purchaserCount += 1;
350
351 // increase payment received amount
352 paymentReceived[_msgSender()] += paymentAmount;
```

Listing 2.6: IFAllocationSale.sol

If the token is a deflation token, there will be a difference between the recorded amount of transferred token in the sale smart contract and the actual number of transferred tokens. That's because a small amount of tokens will be burned by the token smart contract.

This inconsistency could cause security impacts if some critical operations are based on the recorded amount of transferred tokens.

Impact This inconsistency could cause security impacts if some critical operations are based on the recorded number of transferred tokens. However, because all the tokens used in the IF launchpad are manually reviewed by IF to ensure that they are not deflation tokens, the launchpad will not be affected at the current stage

Suggestion Check the balance of the token again after the token transfer operation.

Feedback from the Project The deflation token will not be supported. We can run the manual review for the support tokens.

2.2 Additional Recommendation

2.2.1 Unchecked Function Parameters

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description Some parameters in the constructor of the contract [IFAllocationSale](#) are not checked to avoid a potential misuse, such as:

- 1) The [saleToken](#) should not be same as the [paymentToken](#).
- 2) When the [salePrice](#) is not zero, the [paymentToken](#) and the [maxTotalPayment](#) should not be zero.
- 3) The variables [allocationMaster](#), [trackId](#), [allocSnapshotBlock](#) should not be zero, if the allocation will not be overridden.
- 4) The [allocSnapshotBlock](#) should be greater than the block number in the earliest checkpoint of the track, if the allocation will not be overridden.

```
102     constructor(  
103         uint256 _salePrice,  
104         address _funder,  
105         ERC20 _paymentToken,  
106         ERC20 _saleToken,  
107         IFAllocationMaster _allocationMaster,  
108         uint24 _trackId,  
109         uint80 _allocSnapshotBlock,  
110         uint256 _startTime,  
111         uint256 _endTime,  
112         uint256 _maxTotalPayment  
113     ) {  
114         // funder cannot be 0  
115         require(_funder != address(0), '0x0 funder');  
116         // sale token cannot be 0  
117         require(address(_saleToken) != address(0), '0x0 saleToken');  
118         // start timestamp must be in future  
119         require(block.timestamp < _startTime, 'start timestamp too early');  
120         // end timestamp must be after start timestamp  
121         require(_startTime < _endTime, 'end timestamp before start');  
122  
123         salePrice = _salePrice; // can be 0 (for giveaway)  
124         funder = _funder;  
125         paymentToken = _paymentToken; // can be 0 (for giveaway)  
126         saleToken = _saleToken;  
127         allocationMaster = _allocationMaster; // can be 0 (with allocation override)  
128         trackId = _trackId; // can be 0 (with allocation override)  
129         allocSnapshotBlock = _allocSnapshotBlock; // can be 0 (with allocation override)  
130         startTime = _startTime;  
131         endTime = _endTime;  
132         maxTotalPayment = _maxTotalPayment; // can be 0 (for giveaway)  
133     }
```

Listing 2.7: IFAllocationSale.sol

Impact The wrong parameters cannot be fixed after being initialized.

Suggestion Verify these parameters in the constructor.