

CSE3241: Operating System and System Programming

Lecture-8

Sangeeta Biswas, Ph.D.

Assistant Professor

Dept. of Computer Science and Engineering (CSE)

Faculty of Engineering

University of Rajshahi (RU)


Rajshahi-6205, Bangladesh

E-mail: sangeeta.cse@ru.ac.bd / sangeeta.cse.ru@gmail.com

November 5, 2017

States of Process [1]


- As a process executes, it changes its state.
- In the **ready** and **waiting states**, processes build queues.
- Queues keep Process control block (PCB)s of processes.



Process Control Block (PCB) [1]

■ Process Control Block:

- ▶ is known as a **task control block**.
- ▶ contains many pieces of information associated with a specific process.
- ▶ is handled by the OS.



process state
process number
program counter
registers
memory limits
list of open files
...


Some Fields of a PCB (I)

- ▶ **Process ID:** a unique identification number given by the OS.
- ▶ **Parent ID:** parent's unique ID.
- ▶ **Process State:** new / ready / running / waiting / halted.
- ▶ **Values of CPU Registers:** information stored in program counter, accumulator, index register, stack pointer, etc.
- ▶ **CPU Scheduling Information:** process priority, pointers to scheduling queues and so on.
- ▶ **Memory-Management Information:** values of base and limit registers, page table, segment table, memory limits, etc.

Some Fields of a PCB (II)

- ▶ **Process Privileges:** allowed/disallowed access to system resources.
- ▶ **Interprocess Communication Information:** various flags, signals and messages associated with the communication among independent processes.
- ▶ **Process Structuring Information:** process's children id's, or the id's of other processes related to the current one.
- ▶ **Accounting Information:** time CPU spent for the process execution, time limits.
- ▶ **I/O Status Information:** lists of allocated I/O devices, lists of opened files, etc.

CPU Switch from Process to Process [1]




Process Representation in Linux [1]


■ Linux uses C structure `task_struct` to hold PCB. Some fields are:

- ▶ `pid_t pid`; [process identifier]
- ▶ `long state`; [state of the process]
- ▶ `unsigned int time_slice`; [scheduling information]
- ▶ `struct task_struct *parent`; [this process's parent]
- ▶ `struct list_head children`; [this process's children]


Figure: Doubly linked list of `task_struct` holding active processes in Linux



Various Queues [1]




Queueing Diagram of Process Scheduling [1]




What is System Call?

■ System Call is an instruction that:

- ▶ provides an interface between restricted processes (e.g., user process) and unrestricted processes (e.g., kernel process).
- ▶ generates a software interrupt to get services from the kernel process.
- ▶ is also called Kernel call.



Standard C Library Handling of write()



References



P. B. Galvin A. Silberschatz and G. Gagne.
Operating System Concepts.
John Wiley & Sons, 9 edition, 2012.