

**PRODUCT DETAILS**

- Fabric laying width between 1.60cm - 2.20cm
- Ability to lay roll and open rested fabrics
- Wrinkle correction and fabric loosening feature with one button
- With fabric feeding system with conveyor belt and servo motor;
- Ability to lay fabric at the desired tension with automatic tension control
- Ability to lay fabrics precisely without stretching
- Waste free cutting system with automatic cutting adjustment
- Automatic pastal height adjustment
- Ability to rewind the fabric
- Plc system,easy to use touch control screen
- Programmable pastal length and number
- Different speed options in different ways
- Automatic stop feature when the fabric is over
- Warning system when reaching the desired floor quantity
- Warning system in case of malfunctions to be happen
- Sensitive to electronic motion and side edge smoothness adjustment with photocell
- One-way and zigzag fabric laying with cutting apparatus and operator platform
- Speed adjustable cutting system
- Personal carrier platform with safety sensor

**FEATURES**

Standard roll dimension	: 50 cm
Standard roll weight	: 150 kg
Standard laying width	: 160 cm - 220 cm
Standard laying height	: 25 cm
Zigzag laying height	: 25 cm
Laying height with zigzag apparatus	: 20 cm
Maximum laying speed	: 105 mt / minute
General machine weight	: 410 kg
Electrical requirement	: 220 v ac 50 hz 3,5 kw