

# Connecting the App Store to RevenueCat

Parse · B8 Monetization · moving from the Test Store to real App Store purchases

## Where you are now

The Test Store path is working end to end: a purchase reached RevenueCat, the webhook wrote the subscription, and `can_scan()` granted 200 scans. Everything below **adds** the App Store alongside it. None of the RevenueCat entitlements or offerings you already built are replaced.

## What must already be true

| Prerequisite                                     | Status / note                                                                                          |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Apple Developer Program membership (\$99/yr)     | Required. Organization accounts need a D-U-N-S number and can take days.                               |
| App ID <code>com.imranfarid.parse</code>         | Already exists. Confirm <b>In-App Purchase</b> and <b>Sign in with Apple</b> capabilities are enabled. |
| App Store Connect app record                     | Created. The store listing name can be changed later; the bundle ID and SKU cannot.                    |
| RevenueCat project with entitlements + offerings | Already built for the Test Store. You will extend it, not rebuild it.                                  |

## Part 1 — App Store Connect

### 1 Paid Applications agreement

**Business** → **Agreements**. Sign it, then complete banking and tax details. Wait until the status reads **Active**.

#### Do this first

Until the agreement is Active, your products stay in *Missing Metadata* and the sandbox returns **no products at all**. The app simply shows no prices and nothing in the logs explains why. This single step is responsible for most lost days in store setup.

### 2 Create the subscription group

Your app → **Monetization** → **Subscriptions** → create **one** group named Parse. All eight products go inside it, so a user moves between plans instead of stacking two live subscriptions.

### 3 Create the 8 subscriptions

Identifiers must match exactly — they are permanent, and the B8 gate asserts them against `packages/contracts/src/products.ts` and the `products` table.

| Product ID               | Tier | Duration | Price (USD) | Price list |
|--------------------------|------|----------|-------------|------------|
| <code>parse_pro_m</code> | Pro  | 1 month  | 9.99        | Standard   |
| <code>parse_pro_y</code> | Pro  | 1 year   | 71.99       | Standard   |

| Product ID        | Tier | Duration | Price (USD) | Price list |
|-------------------|------|----------|-------------|------------|
| parse_max_m       | Max  | 1 month  | 15.99       | Standard   |
| parse_max_y       | Max  | 1 year   | 149.99      | Standard   |
| parse_pro_m_promo | Pro  | 1 month  | 6.99        | Promo      |
| parse_pro_y_promo | Pro  | 1 year   | 49.99       | Promo      |
| parse_max_m_promo | Max  | 1 month  | 10.99       | Promo      |
| parse_max_y_promo | Max  | 1 year   | 79.99       | Promo      |

- Each product needs a **localized display name and description**, or it stays in Missing Metadata.
- Set the US price; Apple localizes the rest. The app never formats a price — it prints what the store returns.
- **Rank Max above Pro** in the group. That is what makes Pro → Max an immediate upgrade rather than a crossgrade.
- Get every product to **Ready to Submit**. Sandbox purchases need that state, but not Apple's approval.

#### Why eight and not four

The Plan screen's "Early promotion discount" switch selects between two real RevenueCat offerings, because a client cannot change what Apple charges. Every price the user sees is therefore a price the store will actually take.

## 4 In-App Purchase key

**Users and Access** → **Integrations** → **In-App Purchase** → +. Download the .p8, and note the **Key ID** and **Issuer ID**. Required for StoreKit 2 — this is the screen that blocks you without a paid membership.

## 5 App-Specific Shared Secret

On the app's page in App Store Connect. RevenueCat needs it to validate receipts.

## 6 Sandbox tester

**Users and Access** → **Sandbox** → **Testers**. Use an email address that is **not** an existing Apple ID. Sign in with it on the device under Settings → App Store → Sandbox Account.

## 7 Sign in with Apple key (for account deletion)

**Certificates, Identifiers & Profiles** → **Keys** → +, enable *Sign in with Apple*. This is a **different key** from step 4. Download the .p8 — Apple lets you download it exactly once.

Apple requires an app offering Sign in with Apple to revoke the user's tokens on account deletion. Without these values, `account-delete` can only ever report `apple_revoked: false`, which fails gate test T8.5.

# Part 2 — RevenueCat

## 8 Configure the iOS app

**Project settings** → **Apps** → **your iOS app**. Set the bundle ID to `com.imranfarid.parse`, then upload the step 4 .p8 with its Key ID and Issuer ID, and paste the step 5 shared secret.

## 9 Import the App Store products

**Product catalog** → **Products**. Add the eight identifiers again, this time against the **App Store** app. RevenueCat will validate them against App Store Connect.

## 10 Attach them to the SAME entitlements

| Entitlement | Attach these App Store products                                |
|-------------|----------------------------------------------------------------|
| pro         | parse_pro_m, parse_pro_y, parse_pro_m_promo, parse_pro_y_promo |
| max         | parse_max_m, parse_max_y, parse_max_m_promo, parse_max_y_promo |

## 11 Add them to your EXISTING packages

### Do not create new offerings

This is the step most people get wrong. A RevenueCat **package holds one product per platform**. Your `pro_monthly` package already holds the Test Store `parse_pro_m`; you are adding the App Store `parse_pro_m` to *that same package*. The SDK then serves whichever product matches the running platform. Your default and promo offerings stay exactly as they are.

| Offering | Package           | App Store product to add |
|----------|-------------------|--------------------------|
| default  | pro_monthly       | parse_pro_m              |
| default  | pro_yearly        | parse_pro_y              |
| default  | max_monthly       | parse_max_m              |
| default  | max_yearly        | parse_max_y              |
| promo    | pro_monthly_promo | parse_pro_m_promo        |
| promo    | pro_yearly_promo  | parse_pro_y_promo        |
| promo    | max_monthly_promo | parse_max_m_promo        |
| promo    | max_yearly_promo  | parse_max_y_promo        |

Package identifiers do not matter to the app — it matches on the store product identifier, never on package type. That is deliberate: package type cannot distinguish Pro-monthly from Max-monthly, since both are “monthly”.

## 12 Copy the public Apple SDK key

**Project settings** → **API keys** → **Public app-specific API keys**. Take the one for the iOS app (it begins `appl_`).

# Part 3 — Keys and secrets

## Client — .env (gitignored)

```
EXPO_PUBLIC_RC_APPLE_KEY=appl_xxxxxxxxxxxx
```

### This switches iOS off the Test Store immediately

The platform key always wins: `revenueCatApiKey = platformKey ?? testStoreKey`. Once this is set, iOS builds talk to the real App Store and the Test Store is bypassed. Leave it out until your products reach *Ready to Submit*, or you will lose the working test path and gain nothing.

Note that `EXPO_PUBLIC_*` values are inlined at bundle time, so any change here needs a fresh build — a Metro reload will not pick it up. Expo does not read `.env.staging`; use `.env` or `.env.local`.

## Server — Supabase Edge Function secrets

```
supabase secrets set \
  APPLE_SIWA_TEAM_ID='...' \
  APPLE_SIWA_CLIENT_ID='com.imranfarid.parse' \
  APPLE_SIWA_KEY_ID='...' \
```

```
APPLE_SIWA_PRIVATE_KEY="$(cat AuthKey_XXXX.p8)" \
RC_SECRET_API_KEY='sk_...' \
--project-ref <staging-project-ref>
```

- APPLE\_SIWA\_\* come from step 7 — they enable Apple token revocation on account deletion.
- RC\_SECRET\_API\_KEY is the RevenueCat **V1 secret** key, used only by account -delete to unlink a subscriber. Never prefix it with EXPO\_PUBLIC\_.
- Once real purchases are live in production, **remove** RC\_ALLOW\_TEST\_STORE from that environment — a Test Store event grants an entitlement with no money paid.

## Part 4 — Build and verify

```
npm run prebuild:ios
npx expo run:ios --device
```

On the device, sign in to your sandbox tester under **Settings** → **App Store** → **Sandbox Account** before purchasing.

### Acceptance checklist

| # | Check                   | Expected                                                               |
|---|-------------------------|------------------------------------------------------------------------|
| 1 | Open the Plan tab       | Real prices; no “Sample pricing” caption; promo toggle visible         |
| 2 | Toggle the promo switch | Prices change to the promo offering's real prices                      |
| 3 | Buy Pro monthly         | Apple's sandbox purchase sheet appears                                 |
| 4 | After purchase          | Badge reads <b>Pro: 200 scans left</b> without restarting the app      |
| 5 | Database                | subscriptions.store = 'apple', status active, current_period_start set |
| 6 | payment_events          | environment = 'SANDBOX', type INITIAL_PURCHASE                         |
| 7 | Delete account          | apple_revoked: true in the response (needs step 7 keys)                |

### When it does not work

| Symptom                                  | Cause                                                                                                                          |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| No products / empty offerings in sandbox | Paid Applications agreement not Active, or products not yet <i>Ready to Submit</i> . This is the usual answer.                 |
| “Sample pricing” caption still shown     | Read the amber diagnostic line beneath it — it names the exact cause (missing key, missing native module, or empty offerings). |
| Purchase succeeds, plan does not change  | Webhook. Check the rc-webhook logs: 401 means the secret does not match byte for byte; 500 means the RPC failed.               |
| Entitlement never activates              | Product not attached to the pro/max entitlement in RevenueCat.                                                                 |
| apple_revoked stays false                | APPLE_SIWA_* secrets missing, or the user signed in before the authorization code was captured.                                |

Product IDs and bundle IDs are permanent once created. The store listing name, prices, descriptions and screenshots can all be changed later.