The Tests Passed.

Checking the checker in AI security repair

Imran Zakirov · Iosifova Nuriya

Kramich Anna — mentor & team member

The Grader Said No.

A LOCAL EXPERIMENT
NOVEMBER 2026

When should an AI stop trying?

AI → **Checker**

writes a fix

returns PASS or FAIL



Stop — or try again?

A misleading score makes that choice hard to judge.

We checked the checker.

40
saved sessions

1
local model

5
task types

INSIDE OUR CHECKER

01 Run the tests.

02 Reject everything.

Our hidden rule.
Used in 20 of 40 sessions.

We added the rule. The AI could not see it.

9 /20

Passed our tests. Still rejected.



Each block = one session with our hidden rule.

9 passed · 11 failed the tests

All 20 received FAIL.

Passing limited tests
does not prove security.

STOP was not the end.

The controller waited for another final signal.

0 further logged repair attempts

2:08

MINUTES : SECONDS

Stop acknowledgement → run end
Median of 13 post-PASS sessions.

1 additional timeout excluded.

14 repairable sessions requested termination immediately after PASS.

Check the grader.

DONE

Now: every check logged.
Immediate stopping tested.

NEXT

Review the tasks.
Compare true PASS / false FAIL.

Same code. Different feedback.

Small pilots are exploratory. The larger study is still ahead.