


Prepared by:
Imteyaz Ali

FIREWALL

A Comprehensive Study of Types, Features, and Working



Contents

1 Introduction	2
2 Firewall Types and Classifications	3
2.1 Packet Filtering Firewalls	3
2.2 Stateful Inspection Firewalls	3
2.3 Application-Level (Proxy) Firewalls	3
2.4 Next-Generation Firewalls and UTM	4
2.5 Other Classifications	4
3 Firewall Functionality and OSI Layers	4
4 Common Use Cases of Firewalls	5
5 Comparing Firewalls with Other Security Controls	6
5.1 Firewall vs. Intrusion Detection/Prevention (IDS/IPS)	6
5.2 Firewall vs. Router with ACLs	7
5.3 Firewall vs. Web Application Firewall (WAF)	7
6 Examples of Firewall Products and Vendors	7
7 Conclusion	8

1 Introduction

A **firewall** is a critical network security component that monitors and controls incoming and outgoing network traffic based on predetermined security rules. It establishes a barrier between a trusted internal network and untrusted external networks (such as the Internet), preventing unauthorized access while allowing legitimate communication. The concept of firewalls dates back to the late 1980s, with early implementations like the Secure External Access Link (SEAL) firewall by Digital Equipment Corporation (DEC) in 1988, which used packet-filtering rules to protect internal networks from external threats. Since then, firewall technology has evolved to address increasingly sophisticated threats.

Firewalls can be implemented as dedicated hardware appliances, software on general-purpose systems, or cloud-based services. They are essential in enforcing security policies, segmenting networks, and protecting assets. This guide covers the fundamental principles of firewalls, including definitions, types, operation within the OSI model, use cases, comparisons with related technologies, and real-world examples of firewall products and vendors.




Figure 1: Firewall network architecture diagram.

2 Firewall Types and Classifications

Modern firewalls are categorized by their deployment scope and filtering techniques. One broad classification distinguishes between *network-based* and *host-based* firewalls. Network-based firewalls are dedicated devices (or virtual appliances) that filter traffic between different networks or network segments, protecting all devices on that network. In other words, a firewall deployed at a network perimeter is a network-based firewall. Host-based firewalls are software programs installed on individual machines (such as servers or workstations) to protect that single device. For example, the built-in Windows Defender Firewall on Microsoft Windows is host-based and protects only that PC, whereas a Cisco ASA or Fortinet appliance deployed at a network edge acts as a network-based firewall for the entire office network.

2.1 Packet Filtering Firewalls

Packet filtering firewalls operate at the Network (OSI Layer 3) and Transport (Layer 4) layers. They examine packet headers for source/destination IP addresses, ports, and protocol information, and then apply access control lists (ACLs) or rules to decide whether to forward or drop the packet. These firewalls are typically *stateless*, meaning each packet is inspected independently without memory of previous packets. While stateless packet filters are fast and efficient for basic filtering, they cannot inspect payload data or remember connection state, making it difficult to prevent certain attacks (for example, IP spoofing or fragmented packets) without careful rule configuration.

2.2 Stateful Inspection Firewalls

Stateful inspection firewalls also filter packets at Layers 3 and 4, but they track the *state* of active connections. By maintaining a state table of all active sessions, these firewalls allow return traffic for legitimate sessions while blocking unsolicited traffic. For example, once an internal host initiates an outbound TCP connection, the firewall records that session in its state table. Return packets matching this session are then automatically permitted. This stateful behavior enables more secure and dynamic rule enforcement (for example, automatically allowing return traffic of established sessions) without manual rule changes.

2.3 Application-Level (Proxy) Firewalls

Application-level gateways, often called proxy firewalls, operate at the Application layer (OSI Layer 7). They act as intermediaries for specific applications such as HTTP, FTP, or SMTP. When a client requests a service, the proxy firewall terminates the client session and establishes a new session on behalf of the client to the destination server. This design allows the firewall to deeply inspect the entire content of the traffic (including application data) and apply protocol-specific

filtering. For instance, an HTTP proxy firewall can inspect the contents of web requests and block malicious payloads or inappropriate commands at the application level.

2.4 Next-Generation Firewalls and UTM

Next-Generation Firewalls (NGFW) extend traditional firewall capabilities by integrating additional security features. NGFWs commonly include deep packet inspection (DPI), intrusion prevention system (IPS) functionality, and application awareness. They can identify and control applications (regardless of port or protocol) and apply user- or group-based policy rules. For example, a NGFW might block a peer-to-peer file sharing application even if it runs over HTTP port 80, because it recognizes the application’s signature. NGFWs often use updatable signature databases, integrated malware scanning, and can apply policies based on user identity or content.

Unified Threat Management (UTM) devices bundle multiple security services (firewall, VPN, IPS, antivirus, content filtering, etc.) into a single platform, simplifying deployment for small to medium networks. NGFW and UTM functions often overlap: NGFW emphasizes advanced inspection and application control, while UTM emphasizes the integration of many security functions. In practice, many modern firewalls offer both NGFW and UTM features.

2.5 Other Classifications

Additional distinctions include *wireless firewalls* (integrated into wireless routers or access points), *cloud firewalls* (implemented as firewall-as-a-service in cloud environments), and deployment modes such as transparent (bridge) mode versus routed mode. Some firewalls specialize in network address translation (NAT) and VPN gateway functions. Overall, firewalls can operate across multiple OSI layers and can be implemented in hardware, software, or virtual form.

Table 1: Comparison of common firewall types.

Type	OSI Layer(s)	Key Characteristics
Packet-Filtering	3–4	Fast, stateless, filters by IP address/port
Stateful Inspection	3–4	Tracks connection state, dynamic rules
Application Proxy	7	Deep inspection, proxies specific protocols
Next-Generation (NGFW)	3–7	DPI, application-aware, integrates IPS/AV
Host-Based	3–7	Software on a host, protects a single device

3 Firewall Functionality and OSI Layers

Firewalls primarily operate at the lower layers of the OSI model, but some also extend to the application layer. The table below summarizes typical firewall types and their OSI layer focus:

Table 2: Firewall types mapped to OSI layers.

Firewall Type	OSI Layer(s)	Description
Packet-Filtering	3, 4 (Network/Transport)	Examines IP addresses and ports, stateless rules
Stateful Inspection	3, 4	Tracks session state, dynamic allow/deny based on connection
Application Proxy	7 (Application)	Intermediates traffic, inspects application payloads
Next-Generation	3–7 (Multi-layer)	Integrates deep packet inspection and multiple security functions
Host-Based	3–7 (Depends)	Software on a host, can filter at network and application level

TCP/IP & OSI in Relation to Firewalls




Figure 2: Conceptual diagram of firewall functions across OSI layers.

For example, a packet filtering firewall checks network-layer fields (IP addresses) and transport-layer fields (TCP/UDP ports) against a rule base. An application-level proxy, by contrast, inspects the actual data of HTTP or DNS packets at Layer 7. Because firewalls can span layers 3 to 7, they are an essential enforcement point for both network-level and application-level security policies.

Some firewalls also provide additional services at other layers. At Layer 2 (Data Link), a firewall might filter traffic by MAC address in some deployments. Network address translation (NAT) is often a function of perimeter firewalls at Layer 3. At higher layers, firewalls may terminate encrypted sessions (e.g., decrypting SSL/TLS to inspect content), or integrate with authentication and directory services at Layer 7.

4 Common Use Cases of Firewalls

Firewalls are deployed in many scenarios to enforce network security. Key use cases include:

- **Perimeter Security:** Placing a firewall at the edge of a corporate network controls access to the Internet. It blocks malicious traffic from external sources while permitting legitimate outbound and inbound communication according to policy.
- **Network Segmentation:** Firewalls can divide a network into security zones (e.g., separate networks for different departments or functions). For instance, an organization may use firewalls to isolate the finance department’s network from the general corporate network, enforcing stricter rules between them.
- **Demilitarized Zone (DMZ):** A DMZ is a semi-public network (for web servers, email servers, etc.) that sits between the internal LAN and the Internet. Firewalls on both sides of the DMZ regulate traffic, allowing external users to access DMZ services (like a web server) while protecting the internal network.
- **Remote Access VPN:** Many firewalls act as VPN gateways, allowing secure remote connections into the internal network using encryption (e.g., IPsec or SSL/TLS VPN). The firewall authenticates VPN users and enforces access policies on the encrypted traffic.
- **Cloud and Virtualized Environments:** In cloud infrastructures (public or private), virtual firewalls or cloud-native security groups enforce isolation between virtual networks and instances. Firewalls protect workloads in virtual data centers, similar to on-premises deployments.
- **Host Protection:** Host-based firewalls protect individual endpoints (workstations, servers, mobile devices) by controlling applications’ network access at the device level. This is important for endpoint security, especially for remote work or bring-your-own-device (BYOD) scenarios.
- **Industrial and IoT Networks:** Specialized firewalls (often called industrial firewalls) protect critical infrastructure networks, filtering traffic between operational technology (OT) and IT networks. They enforce strict rules to prevent disruptions in SCADA or IoT systems.

5 Comparing Firewalls with Other Security Controls

Firewalls are often compared with or used alongside other security solutions:

5.1 Firewall vs. Intrusion Detection/Prevention (IDS/IPS)

An IDS (Intrusion Detection System) passively monitors network traffic for known threats or anomalies and generates alerts, but it does not block traffic. An IPS (Intrusion Prevention System)

extends IDS by actively dropping malicious packets. Modern NGFWs often include IPS functionality. Compared to IDS/IPS devices, firewalls provide broad traffic control but may not have deep signature-based threat detection.

For example, a firewall blocks or allows traffic based on policy rules, whereas an IDS would alert if it detects a pattern matching a known attack signature. Firewalls are the front line and prevent many basic attacks (such as blocking unused ports), while IDS/IPS provide deeper analysis and can detect or block more sophisticated threats. In practice, organizations often deploy firewalls together with IDS/IPS to enforce security policies and detect intrusions.

5.2 Firewall vs. Router with ACLs

Routers direct traffic between networks and can implement basic access control lists (ACLs). However, routers typically do not track connection state or inspect packet content deeply. A firewall includes similar packet-filtering ACL capabilities but adds session state tracking (in stateful firewalls) and often deeper inspection. In essence, every firewall is a specialized router with enhanced security features. Conversely, a standard router (with stateless ACLs) cannot guarantee that a packet is part of a valid session without state information.

5.3 Firewall vs. Web Application Firewall (WAF)

A WAF is a specialized firewall designed to protect web applications by analyzing HTTP/HTTPS traffic for application-layer attacks like SQL injection or cross-site scripting. While a traditional firewall might permit or block web traffic based on IP/port, a WAF inspects the content of web traffic at Layer 7. WAFs and traditional firewalls complement each other: the network firewall enforces general traffic rules, and the WAF defends specific web services against code-level attacks.

Table 3: Comparison of firewalls with IDS/IPS and basic routers.

	Firewall	IDS/IPS	Router (ACL)
Traffic Control	Blocks/Allows based on policy	Monitors/Alerts (IPS can block)	Basic stateless filtering
State Awareness	Yes (stateful)	No	Typically No
Inspection Depth	Up to Application (NGFW)	Deep packet with signatures	Header fields only
Primary Role	Prevent unauthorized access	Detect or prevent intrusions	Route packets between n

6 Examples of Firewall Products and Vendors

Many vendors offer firewall solutions for different needs. Some notable examples include:

Practitioners should choose firewalls based on organizational size, performance needs, and feature requirements (e.g., SSL/TLS inspection, high throughput, ease of management). Open-source

Table 4: Popular firewall vendors and products.

Vendor/Product	Description
Cisco ASA / Firepower	Classic enterprise firewall (ASA) and next-generation (Firepower)
Palo Alto Networks (PA-Series)	Industry-leading NGFW with application-level control
Fortinet FortiGate	UTM/NGFW with integrated IPS, antivirus, and more
Check Point Firewall-1	Enterprise firewall and UTM solutions
Juniper SRX	Firewall/UTM series for enterprise networks
pfSense (Netgate)	Open-source firewall distribution (FreeBSD-based)
iptables / nftables (Linux)	Built-in Linux kernel firewall frameworks
Windows Defender Firewall	Built-in host firewall for Windows OS

solutions like pfSense or Linux-based firewalls offer flexibility and transparency, while commercial vendors provide specialized hardware, unified management, and vendor support.

7 Conclusion

Firewalls remain a foundational element of cybersecurity, adapting over time to address evolving threats. This guide has outlined the key concepts of firewalls: a firewall is a device or software that enforces security policies by filtering network traffic. Firewalls come in various forms (packet filters, stateful inspection, proxies, next-generation) and operate primarily at the network and transport layers, with some extending to the application layer.

By segmenting networks and applying rules, firewalls protect internal systems from both external and internal threats. They are commonly deployed at network perimeters, between security zones, and on endpoints. Modern firewalls integrate with intrusion prevention, VPN, and cloud security, blurring lines with other technologies like IDS and WAFs.

Understanding the different firewall types, their placement in the OSI model, and how they compare to related tools is essential for cybersecurity learners and professionals. With this knowledge, practitioners can design robust, layered defenses. Firewalls, whether physical appliances or software-based, will continue to serve as a critical front line in the defense of digital assets.