

KasSee User Guide

Watch-only companion for KasSigner

1. Role of KasSee

KasSee is the online/watch-only companion. It imports public wallet identity, derives addresses, queries Kasper nodes, constructs transactions and supported protocol workflows, displays unsigned QR payloads, validates signed responses, and broadcasts. It does not need the wallet spending private key.

KasSee is not the final trust display. Treat the online device, browser, node, and network as potentially hostile; the hardware signer must independently parse and present the transaction being authorized.

2. Build and run

```
make kassee
```

The canonical deployable site is staged under `target/kassee-web/site/`. For local development, generated WASM is also mirrored into `apps/kassee-web/web/pkg/`. Use HTTPS when browser camera policy requires it.

3. Pair a wallet

- Export the current kpub/watch-only identity from KasSigner.
- Import it into KasSee and select the intended Kasper network.
- Allow address discovery to populate receive/change addresses and UTXOs.
- Use a trusted/private node when address-query privacy or node trust matters.

4. Send, sign, broadcast

- Enter destination and amount, choose fee priority and optional UTXO controls, and review planned outputs.
- For multisig, KasSee distinguishes recipient spend from locally bound multisig change context; the signer independently proves descriptor-backed P2SH ownership before excluding change from Send.
- Display the unsigned PSKT/PSKB or compact KSPT v4 request. Animated QR provides frame progress plus previous/next and pause/play controls.
- On KasSigner, scan every frame and verify hardware address, amount, fee, change, network, multisig/covenant context, and warnings.
- Scan the signed response into KasSee. Partial multisig signatures can be relayed; finalization/broadcast occurs only when threshold is satisfied.

5. Transaction and wallet tools

Area	Current behavior
Fees	Low / Normal / Priority plus signed-shape standardness and storage-mass checks.
UTXOs	Manual selection, consolidation, ordering controls, Send Max.
Addresses	Receive/change list, reuse/funded markers, verification workflow.
Multisig	Descriptor-based receive/change, deterministic sorted keys, co-sign relay, final broadcast.
Advanced protocols	Covenants, Private Swap, crowdfunding/oracle workflows, stealth payments.
Assets	KRC-20, KRC-721, and KNS watch-only views.

6. Node and browser safety

- KasSee can resolve a public Kaspas WebSocket node automatically or use a custom ws:// / wss:// endpoint from Settings.
- A malicious node can lie about network state and learn queried addresses; hardware review protects authorization, not query privacy.
- Do not import spending private keys into KasSee. Raw private-key restore belongs on the offline signer.

7. Android and iOS

Android and iOS are native platform/security shells around the same KasSee Rust/WASM runtime rather than separate wallet engines. Both application paths have been tested. Formal release evidence additionally requires signed Release builds and physical-device smoke.