

OCaml core

EBNF grammar defining a simplified syntax

`Prog ::= (DecOrExp ';;') *`

`DecOrExp ::= Dec | Exp`

`Dec ::= 'let' Pat '=' Exp | 'let' ID Pat+ '=' Exp`

`Exp ::= ID | NUM | Exp Exp | 'fun' Pat+ '->' Exp | UOP Exp |
Exp BOP Exp | '(' Exp ')'`

`Pat ::= ID | '_' | '(' Pat ')' // simplified pattern`

Extended BNF (EBNF) grammars

- BNF is extended with the regular expressions operators `*`, `+`, `?`
- Example: `Pat+` means `Pat` concatenated one or more times
- **Remark:** `+` (reg-exp operator) is different from `'+'` (terminal symbol)

OCaml core

EBNF grammar defining a simplified syntax

```
Prog ::= (DecOrExp ';;') *  
DecOrExp ::= Dec | Exp  
Dec ::= 'let' Pat '=' Exp | 'let' ID Pat+ '=' Exp  
Exp ::= ID | NUM | Exp Exp | 'fun' Pat+ '->' Exp | UOP Exp |  
       Exp BOP Exp | '(' Exp ')'  
Pat ::= ID | '_' | '(' Pat ')' // simplified pattern
```

Quick comments

- ID **variable identifiers** $(_ [\backslash w'] | [a-zA-Z]) [\backslash w']^*$
- NUM **natural numbers**
 $0 [bB] [01] [01_]* | 0 [oO] [0-7] [0-7_]* | 0 [xX] [\backslash da-fA-F] [\backslash da-fA-F_]* | \backslash d [\backslash d_]*$
- UOP **unary arithmetic operators** $[+-]$
- BOP **binary arithmetic operators** $[+ - * /] | \text{mod}$
- Pat **patterns**: very simple for now, a more complete definition will be considered later on

OCaml core

EBNF grammar defining a simplified syntax

```
Prog ::= (DecOrExp ';;')*
DecOrExp ::= Dec | Exp
Dec ::= 'let' Pat '=' Exp | 'let' ID Pat+ '=' Exp
Exp ::= ID | NUM | Exp Exp | 'fun' Pat+ '->' Exp | UOP Exp |
       Exp BOP Exp | '(' Exp ')'
Pat ::= ID | '_' | '(' Pat ')'
```

// simplified pattern

Functions and application

- examples of functions

```
let inc = fun x -> x+1 (* the increment function *)
let inc2 x = x+1 (* a more compact syntax *)
```

- function application (= function call)

```
inc 3 (* syntax inc(3) optional, evaluation returns 4 *)
inc2 3 (* syntax inc2(3) optional, evaluation returns 4 *)
```

OCaml core

EBNF grammar defining a simplified syntax

```
Prog ::= (DecOrExp ';;') *  
DecOrExp ::= Dec | Exp  
Dec ::= 'let' Pat '=' Exp | 'let' ID Pat+ '=' Exp  
Exp ::= ID | NUM | Exp Exp | 'fun' Pat+ '->' Exp | UOP Exp |  
       Exp BOP Exp | '(' Exp ')'  
Pat ::= ID | '_' | '(' Pat ')'
```

// simplified pattern

Functions and application

- examples of **anonymous function**

```
fun x -> x+1 (* the increment function *)
```

- function application** (= function call)

```
(fun x -> x+1) 3 (* evaluation returns 4 *)
```

EBNF grammar defining a simplified syntax

```
Prog ::= (DecOrExp ';;') *  
DecOrExp ::= Dec | Exp  
Dec ::= 'let' Pat '=' Exp | 'let' ID Pat+ '=' Exp  
Exp ::= ID | NUM | Exp Exp | 'fun' Pat+ '->' Exp | UOP Exp |  
       Exp BOP Exp | '(' Exp ')'  
Pat ::= ID | '_' | '(' Pat ')' // simplified pattern
```

Semantics of function application

exp1 exp2

- exp1 is evaluated in a function f
- exp2 is evaluated in the argument a of f
- exp1 exp2 is evaluated in $f(a)$ (f applied to a)

Precedence and associativity rules

- standard rules for arithmetic expressions
- application has higher precedence than binary operators

```
inc 1+2  (* equivalent to (inc 1)+2 *)  
1+inc 2  (* equivalent to 1+(inc 2) *)
```

- anonymous functions have lower precedence

```
fun x->x+1  (* equivalent to fun x->(x+1) *)  
fun f->f 2  (* equivalent to fun f->(f 2), not (fun f->f) 2 *)
```

- more critical cases: application and unary operators

```
inc + 3  (* addition *)      inc (+3)  (* application *)  
inc - 3  (* subtraction *)   inc (-3)  (* application *)  
+ inc 3  (* is +(inc 3) *)    - inc 3  (* is -(inc 3) *)
```

OCaml type inference

A simple interpreter session (Read Eval Print Loop)

Types can be **automatically deduced (=inferred)** by the interpreter!

```
# 42;;  
- : int = 42  
# let inc x = x+1;;  
val inc : int -> int = <fun>  
# inc 2;;  
- : int = 3
```

Simplified syntax of OCaml core type expressions

BNF Grammar

Type ::= 'int' | Type '->' Type | '(' Type ')'

OCaml core types

Terminology

- `int` is a **built-in simple type**: the type of integers
- `int -> int` is a **built-in composite type**
- `->` is a type **constructor**: it is used for building composite types from simpler types
- types built with the `->` (arrow) constructor are called *arrow types* or *function types*

Meaning of arrow types

$t_1 \rightarrow t_2$ is the type of functions from t_1 to t_2 that

- can only be applied to a single argument of type t_1
- always returns values of type t_2

OCaml core types

Remarks

- the arrow type constructor is **right-associative**

`int->int->int = int->(int->int)`

- a type constructor always builds a type **different** from its type components

$t_1 \neq t_1 \rightarrow t_2$ and $t_2 \neq t_1 \rightarrow t_2$

- two arrow types are equal if they are built with the **same** type components

$t_1 \rightarrow t_2 = t$ if and only if $t = t_3 \rightarrow t_4$, $t_3 = t_1$, $t_4 = t_2$

- Remark:** from the items above

`int->(int->int) \neq (int->int)->int`

Types and type expressions

Remarks

- $\text{int} \rightarrow \text{int} \rightarrow \text{int}$ is a type expressions, but is also called a type, because it represents a specific type
- $\text{int} \rightarrow \text{int} \rightarrow \text{int}$ and $\text{int} \rightarrow (\text{int} \rightarrow \text{int})$ are **different** type expressions which represent the **same** type

Higher order functions in OCaml

A useful syntactic abbreviation

`fun pat1 pat2 ... patn -> exp`

is an abbreviation for

`fun pat1 -> fun pat2 -> ... fun patn -> exp`

Examples

```
# fun x y->x+y
- : int -> int -> int = <fun>
# fun x->fun y->x+y
- : int -> int -> int = <fun>
# fun x y z->x*y*z
- : int -> int -> int -> int = <fun>
# fun x->fun y->fun z->x*y*z
- : int -> int -> int -> int = <fun>
```

Higher order functions in OCaml

Examples

- $(\text{int} \rightarrow \text{int}) \rightarrow \text{int}$: a function that takes a function $\text{int} \rightarrow \text{int}$ and returns an integer int
- $\text{int} \rightarrow (\text{int} \rightarrow \text{int})$: a function that takes an integer int and returns a function $\text{int} \rightarrow \text{int}$
- $(\text{int} \rightarrow \text{int}) \rightarrow (\text{int} \rightarrow \text{int})$: a function that takes a function $\text{int} \rightarrow \text{int}$ and returns a function $\text{int} \rightarrow \text{int}$

Recall

\rightarrow is right associative, therefore

- $\text{int} \rightarrow (\text{int} \rightarrow \text{int}) = \text{int} \rightarrow \text{int} \rightarrow \text{int}$
- $(\text{int} \rightarrow \text{int}) \rightarrow (\text{int} \rightarrow \text{int}) = (\text{int} \rightarrow \text{int}) \rightarrow \text{int} \rightarrow \text{int}$

Higher order functions in OCaml

Examples

```
# let apply_f_to_0_and_inc = fun f -> 1+f 0;;  
val apply_f_to_0_and_inc : (int -> int) -> int = <fun>
```

```
# let add x y = x+y ;; (* let add = fun x->fun y->x+y *)  
val add : int -> int -> int = <fun>
```

```
# add 3 4;;  
- : int = 7
```

```
# let apply_f_to_x_square_and_inc = fun f -> fun x -> 1+f (x*x) ;;  
val apply_f_to_x_square_and_inc : (int -> int) -> int -> int = <fun>
```

```
# let mul x y z = x*y*z ;; (* let mul = fun x->fun y->fun z->x*y*z *)  
val mul : int -> int -> int -> int = <fun>
```

```
# mul 2 3 4 ;;  
- : int = 24
```

Tuples in OCaml

Syntax

New productions for `Exp` and `Pat`

```
Exp ::= '(' ')' | Exp (',' Exp) +
```

```
Pat ::= '(' ')' | Pat (',' Pat) +
```

New production for `Type`

```
Type ::= 'unit' | Type ('*' Type) +
```

Precedence and associativity rules

- the tuple constructor `,` has higher precedence than anonymous functions
- the tuple constructor `,` has lower precedence than the other operators
- the tuple constructor `,` is **neither left nor right associative**
- the `*` type constructor has higher precedence than the `->` constructor
- the `*` type constructor is **neither left nor right associative**

Tuples in OCaml

, is a value constructor with arity ≥ 2

- $(v_1, \dots, v_n) \neq v_i$ for all $i = 1 \dots n$
- $(v_1, \dots, v_n) = v$ if and only if $v = (v'_1, \dots, v'_n)$ and $v_i = v'_i$ for all $i = 1 \dots n$

***** is a type constructor with arity ≥ 2

- $t_1 * \dots * t_n \neq t_i$ for all $i = 1 \dots n$
- $t_1 * \dots * t_n = t$ if and only if $t = t'_1 * \dots * t'_n$ and $t_i = t'_i$ for all $i = 1 \dots n$

Tuples in OCaml

Examples

```
# ()  
- : unit = () (* this is the void value *)  
# print_int;; (* predefined, prints an integer on stdout *)  
- : int -> unit = <fun>  
# 1,2,3  
- : int * int * int = (1, 2, 3)  
# (1,2),3  
- : (int * int) * int = ((1, 2), 3)  
# 1,(2,3)  
- : int * (int * int) = (1, (2, 3))
```


Functions with tuple arguments

Examples

```
# let const3() = 3;; (* let const3 = fun ()->3 *)  
val const3 : unit -> int = <fun>
```

```
# let add(x,y) = x+y;; (* let add = fun (x,y) -> x+y *)  
val add : int * int -> int = <fun>
```

```
# add (3,4);;  
- : int = 7
```

```
# let mul(x,y,z) = x*y*z;; (* let mul = fun (x,y,z)->x*y*z *)  
val mul : int * int * int -> int = <fun>
```

```
# mul (2,3,5);;  
- : int = 30
```

Declarations of global “variables”

Grammar

$\text{Dec} ::= \text{'let' Pat '=' Exp} \mid \text{'let' ID Pat+ '=' Exp}$

A simple example

```
# let x=2;;  
val x : int = 2  
# let y=x+40;;  
val y : int = 42  
# x+y;;  
- : int = 44
```

Remarks

- variables are **global** because they are declared at the **top level**
- **local** variables can be declared as well at inner levels (see later)
- the content of **variables cannot be changed**, variables are **constant**
- there is **no** variable assignment

Declarations of global “variables”

More elaborate examples

```
# let x=2;;  
val x : int = 2  
# let y=x+40;;  
val y : int = 42  
# x+y;;  
- : int = 44  
# let x=3;; (* previous declaration is shadowed *)  
val x : int = 3  
# x+y;;  
- : int = 45  
# let x,y = 3+2,3*2;;  
val x : int = 5  
val y : int = 6
```

Remark

a new declaration with the same name **shadows** the previous declaration

Declarations of global “variables”

Examples of global function declarations

```
# let inc x = x+1;;  
val inc : int -> int = <fun>  
# let add (x,y) = x+y;;  
val add : int * int -> int = <fun>  
# let add2 x y = x+y;;  
val add2 : int -> int -> int = <fun>
```

A useful syntactic abbreviation

`let id pat1 pat2 ... patn = exp`

is an abbreviation for

`let id = fun pat1 pat2 ... patn -> exp`

which is an abbreviation for

`let id = fun pat1 -> fun pat2 -> ... fun patn -> exp`

Curried/uncurried functions

Multiple arguments can be handled in two different ways

- **Curried function** (from Haskell Curry) with n arguments:
a higher-order function returning a “chain” of (higher order) functions

$$\text{fun } pat_1 \rightarrow \text{fun } pat_2 \rightarrow \dots \text{fun } pat_n \rightarrow exp$$

- **Uncurried function** with n arguments:
a function taking as argument a tuple of size n

$$\text{fun } (pat_1, pat_2, \dots, pat_n) \rightarrow exp$$

Correspondence between curried and uncurried function

- an **uncurried function** can be **transformed** in the **equivalent curried** version
- a **curried function** can be **transformed** in the **equivalent uncurried** version
- **isomorphism** between type $t_1 \rightarrow t_2 \rightarrow \dots \rightarrow t_n \rightarrow t$ and type $t_1 * t_2 * \dots * t_n \rightarrow t$

Curried/uncurried functions

Examples

(addition of two integers *)*

fun x y->x+y;; *(* curried version *)*

- : int -> int -> int = fun>

fun (x,y)->x+y;; *(* uncurried version *)*

- : int * int -> int = fun>

(multiplication of three integers *)*

fun x y z->x*y*z;; *(* curried version *)*

- : int -> int -> int -> int = fun>

fun (x,y,z)->x*y*z;; *(* uncurried version *)*

- : int * int * int -> int = fun>

Partial application

Curried functions and partial application

- curried functions allow **partial** application:
arguments can be passed once at time
- uncurried functions do **not** allow partial application:
arguments must be passed altogether

Partial application

Example

```
# let uncurried_add(x,y)=x+y;;  
val uncurried_add : int * int -> int = <fun>  
  
# uncurried_add(1,2);; (both arguments must be passed)  
- : int = 3  
  
# let curried_add x y=x+y;;  
val curried_add : int -> int -> int = <fun>  
  
# let inc=curried_add 1;; (only argument 1 is passed)  
val inc : int -> int = <fun>  
  
# inc 2;; (argument 2 is passed to compute the final result)  
- : int = 3
```

Remark: the result of the partial evaluation is saved in `inc` as a useful by-product, `1+2` can always be computed with the single expression `curried_add 1 2`

Partial application

Partial application promotes generic programming

Partial application allows **function specialization**: from a generic function it is possible to generate more specific ones with **no code duplication**.

- **software reuse** and **maintenance** are favored
- interesting examples will be shown later on