

Bioinformatics session

4th annual workshop on
bioinformatics and variant
interpretation in InPreD

https://inpred.github.io/26-09_bioinfo_ws/



2. Containerization



A brief history

1979	<code>chroot</code> system call (changing the root directory of a process and its children to a new location in the filesystem) in Uni V7 considered as beginning of process isolation
2000	FreeBSD Jails allows administrators to partition FreeBSD computer system into several independent, smaller systems (<i>jails</i>) – with the ability to assign IP address for each system and configuration
2001	Linux VServer is jail mechanism that can partition resources, similar to FreeBSD Jails

2004	First public beta of Solaris Containers released - combines system resource controls and boundary separation provided by zones
2005	Open Virtuozzo is operating system-level virtualization technology for Linux which uses patched Linux kernel for virtualization, isolation, resource management and checkpointing
2006	Process Containers, launched by Google, was designed for limiting, accounting and isolating resource usage of collection of processes - renamed to <i>Control Groups (cgroups)</i> and merged into Linux kernel
2008	LinuX Containers (LXC) was first, most complete implementation of Linux container manager - implemented using cgroups and Linux namespaces

2011	CloudFoundry started Warden can isolate environments on any operating system running as daemon and providing API for container management
2013	Let Me Contain That For You (LMCTFY) kicked off as open-source version of Google's container stack - providing Linux application containers
2013	Docker emerged
2016	Singularity (later Apptainer) was released

Docker

What is it? 🔍

- containerization technology to package application and dependencies into a container
- the container image can be shipped and run consistently across different computing environments

Which benefits does it provide?



1. Consistency
2. Isolated environments
3. Portability
4. Efficiency



How is it different from virtual machines?

- containers use and share host OS's kernel making them more lightweight and efficient
- virtual machines emulate entire physical machine, including OS making it possible to run multiple OS instances on single physical machine

Application A

Application A

Operating System A

Docker

Virtual Machine Hypervisor

Operating System B

Infrastructure

Key Concepts 🔑

1. **Image:** standardized package that includes all files, binaries, libraries, and configurations to run container
2. **Container:** running instance of image providing isolated runtime environment
3. **Dockerfile:** instructions on how to build image
4. **Docker Hub:** public registry where developers can share and access pre-built images

Key Components 🔑

1. **Docker Engine:** core, open-source technology that builds and runs containers
2. **Docker Client:** command-line tool that sends instructions to the Docker Daemon using REST APIs
3. **Docker Daemon (`dockerd`):** receives and processes API requests and calls container runtime
4. **Container Runtime (`containerd`):** turns static container image into running, isolated application on host OS; industry standard

Let's explore! 🌐

Start by going to https://github.com/InPreD/26-09_bioinfo_ws_docker_and_ci and create a fork.

The screenshot shows the GitHub interface for the repository `26-09_bioinfo_ws_docker_and_ci`. At the top, there are buttons for `Edit Pins`, `Watch 0`, `Fork 0`, and `Star 0`. Below these, a dropdown menu is open, showing the option `+ Create a new fork` highlighted with a red rectangle. The repository is owned by `marrip` and has a commit history table with columns for file name, commit message, and time ago. The commit history table lists files like `.devcontainer`, `src/greeter`, `.gitignore`, `LICENSE`, `README.md`, and `pyproject.toml`. Below the commit history, there is a section for the `README` file, which contains the text `codespace template for docker and ci workshop`. On the right side, there are links for `workshop`, `Readme`, `AGPL-3.0 license`, `Activity`, `Custom properties`, `0 stars`, `0 watching`, `0 forks`, `Audit log`, `Report repository`, `Releases`, and `Packages`.

File	Commit Message	Time Ago
<code>.devcontainer</code>	chore: add devcontainer setup	9 minutes ago
<code>src/greeter</code>	feat: add simple python project	8 minutes ago
<code>.gitignore</code>	chore: add devcontainer setup	9 minutes ago
<code>LICENSE</code>	Initial commit	1 hour ago
<code>README.md</code>	Initial commit	1 hour ago
<code>pyproject.toml</code>	feat: add simple python project	8 minutes ago


Create your own fork by clicking on **Create fork**.

Create a new fork

A *fork* is a copy of a repository. Forking a repository allows you to freely experiment with changes without affecting the original project.

Required fields are marked with an asterisk ().*

Owner *



Repository name *

/ 26-09_bioinfo_ws_docker_

✓ 26-09_bioinfo_ws_docker_and_ci is available.

By default, forks are named the same as their upstream repository. You can customize the name to distinguish it further.

Description

codespace template for docker and ci workshop

45 / 350 characters

☒ Copy the **main** branch only

Contribute back to InPreD/26-09_bioinfo_ws_docker_and_ci by adding your own branch. [Learn more.](#)

You are creating a fork in your personal account.

Create fork

In the forked repository, navigate to **Code** > **Codespaces** > **Create codespace on main**.

The screenshot shows a GitHub repository page for '26-09_bioinfo_ws_docker_and_ci'. The repository is public and has 1 branch and 0 tags. The 'Code' button is highlighted with a green background. A dropdown menu is open, showing 'Local' and 'Codespaces' options. The 'Codespaces' option is selected, and a sub-menu is displayed with the text 'No codespaces' and 'You don't have any codespaces with this repository checked out'. A green button labeled 'Create codespace on main' is highlighted with a red border. Below this button is a link 'Learn more about codespaces...'. The repository's README is visible at the bottom, stating 'codespace template for docker and ci workshop'.

26-09_bioinfo_ws_docker_and_ci Public

Edit Pins Watch 0 Fork 0 Star 0

main 1 Branch 0 Tags

Go to file

Add file <> Code

Local Codespaces

Codespaces
Your workspaces in the cloud

No codespaces
You don't have any codespaces with this repository checked out

Create codespace on main

Learn more about codespaces...

Codespace usage for this repository is paid for by marrip.

marrip feat: add simple python project

- .devcontainer chore: add devconta
- src/greeter feat: add simple pyth
- .gitignore chore: add devconta
- LICENSE Initial commit
- README.md Initial commit
- pyproject.toml feat: add simple pyth

README AGPL-3.0 license

26-09_bioinfo_ws_docker_and_ci

codespace template for docker and ci workshop

About
codespace template for docker and ci workshop

- Readme
- AGPL-3.0 license
- Activity
- Custom properties
- 0 stars
- 0 watching
- 0 forks
- Audit log
- Report repository

Releases
No releases published
[Create a new release](#)

Packages
No packages published
[Publish your first package](#)

Inside the terminal, run the following commands:

```
# check for running docker containers
$ docker ps
# check for existing images
$ docker images
# pull image
$ docker pull ubuntu:26.04
# run image
$ docker run ubuntu:26.04
```

Run an interactive container:

```
# start interactive container
$ docker run -it ubuntu:26.04
# print container os version
@ cat /etc/lsb-release
# exit container
@ exit
# print os version
$ lsb_release -a
```

Instruct docker to remove containers after use:

```
# check for any docker container
$ docker ps -a
# remove stopped container
$ docker rm <container hash>
# run docker with --rm flag
$ docker run -it --rm ubuntu:26.04
# exit container
@ exit
# check for all docker containers
$ docker ps -a
```

Remove the docker image:

```
# remove docker image
$ docker rmi ubuntu:26.04
# alternatively
$ docker rmi <container image hash>
```

Building an image

We start off by creating a `Dockerfile` in the root directory of our repository. We add the following to our file:

```
FROM python:3.14-slim-trixie
RUN echo 'Hello world' > greetings.txt
```

And then we build and run our docker image:

```
# build tagged docker image
$ docker build . -t greeter:test
# run tagged docker image
$ docker run --rm greeter:test cat greetings.txt
```

Let us add a label to our `Dockerfile` to indicate who the author and maintainer is:

```
FROM python:3.14-slim-trixie
LABEL org.opencontainers.image.authors="martin.rippin@helse-bergen.no"
RUN echo 'Hello world' > greetings.txt
```

And then we build and inspect our docker image:

```
# build tagged docker image
$ docker build . -t greeter:test
# run tagged docker image
$ docker inspect greeter:test
```

Next, we are setting `cat greetings.txt` as a default command that is run whenever the container is started:

```
FROM python:3.14-slim-trixie
LABEL org.opencontainers.image.authors="martin.rippin@helse-bergen.no"
RUN echo 'Hello world' > greetings.txt
CMD ["cat", "greetings.txt"]
```

And then we build and run our docker image:

```
# build tagged docker image
$ docker build . -t greeter:test
# run tagged docker image
$ docker run --rm greeter:test
```

There is a small python application in this repository that we would like to include in our docker image:

```
FROM python:3.14-slim-trixie
LABEL org.opencontainers.image.authors="martin.rippin@helse-bergen.no"
WORKDIR /usr/src/greeter
COPY pyproject.toml ./
COPY src/ ./src/
RUN pip install .
CMD ["greeter"]
```

A full list of `Dockerfile` instructions can be found here:

<https://docs.docker.com/reference/dockerfile#overview>

Apptainer

What is it?

- container platform designed for ease-of-use on shared systems and in high performance computing (HPC) environments

How is it different from Docker? 🐳

Apptainer	Docker
without root-privileges by default	requires root privileges for most operations
SIF (Singularity Image Format) – immutable, portable, cryptographically signed	Docker/OCI images – layered file systems, mutable by default
can run Docker/OCI images	cannot run SIF images

Let's explore! 🌐

Similar to Docker, Apptainer provides a cli:

```
# check for any apptainer container
$ apptainer instance list -a
# pull image
$ apptainer pull docker://ubuntu:26.04
# check identity
$ whoami
# check identity in container
$ apptainer exec docker://ubuntu:26.04 whoami
```

The container image is saved as a `.sif` -file to the working directory.

Building an image 🛠️

We are creating a file called `greeter.def` in the root of our repository and add the following lines:

```
Bootstrap: docker
From: python:3.14-slim-trixie

%setup
    echo "Hello world" > greetings.txt
```

And then we build and run our apptainer image:

```
# build apptainer image
$ apptainer build greeter.sif greeter.def
# execute apptainer image
$ apptainer exec greeter.sif cat greetings.txt
```

A full list of apptainer definition file sections can be found here:

https://apptainer.org/docs/user/main/definition_files.html#sections

3. Continuous Integration (CI)



