## 1 | Problem 1

#### 1.1 | **KE**

Given a distance from axis  $l_i$ , mass  $m_i$ , relative position  $\vec{r_i}'$  and angular velocity  $\omega$ , you can get rotational KE via  $\frac{1}{2}\sum m_i(l_i\omega)$ .  $l_i\theta$  would give arclength of the path of the mass, its so time derivative  $l_i\omega$  would give its velocity. Additionally, this checks out in terms of dimensional analysis: radians are dimensionless so it's 1/s times meters to get m/s.

$$KE_r = \frac{1}{2} \sum m_i(v_i')$$

$$= \frac{1}{2} \sum m_i(l_i\omega)$$

$$= \frac{1}{2} \sum m_i l_i^2 \omega^2$$

$$= \frac{1}{2} \omega^2 \underbrace{\sum m_i l_i^2}_{I}$$

$$= \frac{1}{2} I \omega^2$$

### 1.2 | Rotational Inertia of Ring

$$I = \sum m_i l_i^2$$

 $l_i$  is constant on a ring and equal to R.

$$I = \sum m_i R^2$$

$$I = R^2 \sum m_I$$

 $\sum m_i$  is defined to be M in previous problems.

$$I = MR^2$$

# 1.3 | Rotational Inertia of Sphere

I would expect it to be less than  $I_{\text{disk}}$  because more of the mass is spread out across the volume of the sphere, and more of it has a smaller  $l_i$ , meaning that  $\sum m_i l_i^2$  will be smaller and therefore  $I_{\text{sphere}}$  is smaller.

# 2 | Problem 2

2.1 | v(t) and y(t)

$$a(t)=a_0$$
 
$$\int a(t)dt=\int a_0$$
 
$$v(t)=a_0t+C$$
 We know that  $v(0)=v_0=C$  
$$\boxed{v(t)=a_0t+v_0}$$

$$v(t)=a_0t+v_0$$
 
$$\int v(t)dt=\int a_0t+v_0dt$$
 
$$y(t)=\frac{a_0}{2}t^2+v_0t+C$$
 We know that  $y(0)=y_0=C$  
$$\boxed{y(t)=\frac{a_0}{2}t^2+v_0t+y_0}$$

# 2.2 | Equation for $v^2(t)$

$$v(t) = a_0 t + v_0$$
 
$$v^2(t) = (a_0 t + v_0)^2$$
 
$$v^2(t) = a_0^2 t^2 + 2a_0 t v_0 + v_0^2$$
 
$$v^2(t) = v_0^2 + 2a_0(\frac{1}{2}a_0 t^2 + v_0 t)$$
 
$$v^2(t) = v_0^2 + 2a_0(\frac{1}{2}a_0 t^2 + v_0 t + y_0 - y_0)$$
 We know from the previous problem that  $\frac{1}{2}a_0 t^2 + v_0 t + y_0$  is equal to  $y(t)$ .

$$v^{2}(t) = v_{0}^{2} + 2a_{0}(y(t) - y_{0})$$

### 2.3 | Equation for $\Delta y$

$$v(t) = a_0t + v_0$$
 
$$\int_{t_1}^{t_2} v(t) = \int_{t_1}^{t_2} a_0t + v_0$$
 
$$y(t_2) - y(t_1) = \left(\frac{a_0}{2}t_2^2 + v_0t_2\right) - \left(\frac{a_0}{2}t_1^2 + v_0t_1\right)$$
 
$$\Delta y = \frac{(a_0t_2^2 + 2v_0t_2) - (a_0t_1^2 + 2v_0t_1)}{2}$$
 
$$\Delta y = \frac{(a_0t_2 + v_0) + (a_0t_1 + v_0)}{2}(t_2 - t_1)$$
 We know from earlier that  $v(t) = a_0t + v_0$ . 
$$\Delta y = \frac{v(t_2) - v(t_1)}{2}(t_2 - t_1)$$
 
$$\Delta y = \frac{v(t_2) - v(t_1)}{2}\Delta t$$

## 3 | Problem 3

The constants that are flipped are  $a_0$ ,  $v_0$ , and  $y_0$ . The equations for v(t) and y(t) become flipped as a result:

$$a(t)=-a_0$$
 
$$\int a(t)dt=\int -a_0$$
 
$$v(t)=-a_0t+C$$
 We know that  $v(0)=-v_0=C$  
$$\boxed{v(t)=-a_0t-v_0}$$

$$v(t)=-a_0t-v_0$$
 
$$\int v(t)dt=\int -a_0t+-v_0dt$$
 
$$y(t)=-\frac{a_0}{2}t^2+-v_0t+C$$
 We know that 
$$y(0)=-y_0=C$$
 
$$\boxed{y(t)=-\frac{a_0}{2}t^2-v_0t-y_0}$$

The sign change initially doesn't matter during the  $v^2(t)$  derivation due to the square, but the substitution

with y(x) is flipped (see above) so part of the answer is flipped.

$$v(t) = -a_0t - v_0$$
 
$$v^2(t) = (-a_0t - v_0)^2$$
 
$$v^2(t) = a_0^2t^2 + 2a_0tv_0 + v_0^2$$
 
$$v^2(t) = v_0^2 + 2a_0(\frac{1}{2}a_0t^2 + v_0t)$$
 
$$v^2(t) = v_0^2 + 2a_0(\frac{1}{2}a_0t^2 + v_0t + y_0 - y_0)$$
 We know from the previous problem that 
$$-\frac{1}{2}a_0t^2 - v_0t - y_0 \text{ is equal to } y(t).$$
 
$$v^2(t) = v_0^2 + 2a_0(-y(t) - y_0)$$

Finally, the final equation in problem 2 would stay the same because it is for the *change* in position and addition is commutative.