# 1 | Position of $m_i$

In a rigid body consisting of N point masses, the vector to the position of  $m_i$  is defined as  $r_i(t)$ , which is defined as follows:

$$\vec{r_i(t)} = \vec{R_{CM}(t)} + \vec{r_i'(t)}$$
 (1)

whereas,  $\vec{R_{CM}(t)}$  is the position vector of the center of mass of the rigid body as a whole, and  $\vec{r_i}'(t)$  the vector from the center of mass to  $m_i$ .

## 2 | Velocity of $m_i$

The velocity of  $m_i$  is simply determined by the first derivative of the position equation as per above. Namely, that:

$$\vec{v_i(t)} = \vec{V_{CM}(t)} + \vec{v_i}'(t)$$
 (2)

where,  $\vec{v_i(t)}$  is the velocity vector of  $m_i$ , and  $\vec{V_{CM}(t)}$  is the velocity vector of the center of mass of the rigid body, and  $\vec{v_i}'(t)$  is the velocity vector from center of mass to  $m_i$ .

# 3 | Deriving $KE_{total}$

### 3.1 | Setting up

From definition of  $KE_{total}$  itself,  $KE_{total}$  is the sum of all energies of each point mass in the rigid body.

$$\sum_{i=1}^{N} \frac{1}{2} m_i v_i^2 \tag{3}$$

### 3.2 | Derivation, part 1

Expanding this equation and substituting the value of  $v_i$ , and additionally setting  $M = \sum m_i$  (namely, that M represents the total mass of the rigid body) we could derive:

$$\sum_{i=1}^{N} \frac{1}{2} m_i v_i^2 = \sum_{i=1}^{N} \frac{1}{2} m_i (v_i \cdot v_i)$$
(4)

$$=\sum_{i=1}^{N} \frac{1}{2} m_i ((\vec{V_{CM}} + \vec{v_i}') \cdot (\vec{V_{CM}} + \vec{v_i}'))$$
 (5)

$$= \sum_{i=1}^{N} \frac{1}{2} m_i (\vec{V_{CM}}^2 + 2 \times (\vec{v_i}' \cdot \vec{V_{CM}}) + \vec{v_i}'^2))$$
 (6)

$$= \sum_{i=1}^{N} \frac{1}{2} m_i \vec{V_{CM}}^2 + \sum_{i=1}^{N} m_i \times (\vec{v_i}' \cdot \vec{V_{CM}}) + \sum_{i=1}^{N} \frac{1}{2} m_i \vec{v_i}'^2$$
 (7)

$$= \frac{1}{2} \vec{V_{CM}}^2 \sum_{i=1}^{N} m_i + \vec{V_{CM}} \sum_{i=1}^{N} m_i \vec{v_i}' + \sum_{i=1}^{N} \frac{1}{2} m_i \vec{v_i}'^2$$
(8)

#### 3.3 | Dealing with the Middle Term

At this point, we must note that  $\sum_{i=1}^{N} m_i \vec{v_i}' = 0$ . Per the definition of the center of mass, the following holds:

$$r_{CM} = \left(\frac{1}{M}\right) \sum_{i} m_i \vec{r_i} \tag{9}$$

Changing reference frame to that of the center of mass itself, this equation therefore becomes:

$$r_{\vec{CM}}' = (\frac{1}{M}) \sum_{i} m_i \vec{r_i}'$$
 (10)

It is important to realize here that  $r_{\vec{CM}}' = 0$  because of the fact that — at the reference point of the center of mass, the center of mass is at a zero-vector distance away from itself.

In order to figure a statement with respect to the *velocity* of  $r'_i$ , we take the derivative of the previous equation with respect to time.

$$0 = (\frac{1}{M}) \sum_{i} m_i \vec{r_i}'$$
 (11)

$$\Rightarrow \frac{d}{dt}(\frac{1}{M})\sum_{i}m_{i}\vec{r_{i}}'$$
(12)

$$=\left(\frac{1}{M}\right)\sum_{i}m_{i}\vec{v_{i}}'\tag{13}$$

Given that  $\frac{1}{M}$  could not be zero for an object with non-zero mass, it is concluded therefore that  $\sum_i m_i \vec{v_i}' = 0$ .

#### 3.4 | Derivation, part 2

As  $\sum_i m_i \vec{v_i}' = 0$ , the  $KE_{total}$  work-in-progress equation's middle term (which contains the statement  $\sum_i m_i \vec{v_i}'$ ) is therefore zero. Substituting that in and removing the term, we therefore result in:

$$\sum_{i=1}^{N} \frac{1}{2} m_i v_i^2 = \frac{1}{2} \vec{V_{CM}}^2 \sum_{i=1}^{N} m_i + \sum_{i=1}^{N} \frac{1}{2} m_i \vec{v_i}^2$$
(14)

Replacing the definition of  $M=\sum m_i$ , we result in

$$\sum_{i=1}^{N} \frac{1}{2} m_i v_i^2 = \frac{1}{2} M \vec{V_{CM}}^2 + \sum_{i=1}^{N} \frac{1}{2} m_i \vec{v_i}^2$$
(15)

$$KE_{total} = \frac{1}{2}M\vec{V_{CM}}^2 + \sum_{i=1}^{N} \frac{1}{2}m_i\vec{v_i}^2$$
 (16)

The left term of this equation  $(\frac{1}{2}M\vec{V_{CM}}^2)$  is the clear original statement for  $KE_{translational}$ . As component masses of a rigid body cannot experience translational motion about its center of origin, the second term is therefore rotational only and so  $KE_{rotational}$ .

Therefore:

$$KE_{total} = KE_{translational} + KE_{rotational}$$
 (17)