EX.	NO	.4
L/\.	$\cdot \cdot \cdot \circ$	. —

#### **JOIN OPERATIONS**

#### <u>AIM</u>

To execute the join operations.

#### **CREATING THE TABLE**

SQL> create table customers(CustomerID int primary key,Name varchar(10),City varchar(12));

Table created.

SQL> create table Orders(OrderID int primary key,CustomerID int,

Product varchar(12));

Table created.

#### **INSERTING VALUES TO THE TABLE**

SQL> insert into customers values(1,'Alex','Chennai');

1 row created.

SQL> insert into customers values(2,'Bob','Mumbai');

1 row created.

SQL> insert into customers values(3,'Charlie','Delhi');

1 row created.

SQL> insert into customers values(4,'David','Kolkata');

1 row created.

SQL> insert into customers values(5, 'Emma', 'Bangalore');

1 row created.

SQL> insert into Orders values(101,1,'Pizza');

1 row created.

SQL> insert into Orders values(102,2,'Burger');

1 row created.

SQL> insert into Orders values(103,3,'Pasta');

1 row created.

SQL> insert into Orders values(104,5,'Ice Cream');

1 row created.

SQL> insert into Orders values(105,6,'Sandwich');

1 row created.

## **DISPLAYING THE TABLE**

SQL> select \* from customers;

#### CUSTOMERID NAME CITY

-----

1 Alex Chennai

2 Bob Mumbai

3 Charlie Delhi

4 David Kolkata

5 Emma Bangalore

SQL> Select \* from Orders;

# ORDERID CUSTOMERID PRODUCT

101	1 Pizza
102	2 Burger
103	3 Pasta
104	5 Ice Cream
105	6 Sandwich

#### **INNER JOIN**

SQL> select Customers.CustomerID,Customers.Name,Orders.OrderID,

Orders.Product from Customers inner join Orders on

Customers.CustomerID=Orders.CustomerID;

CUSTOMERID NAME ORDERID PRODUCT

1	Alex	101 Pizza
2	Bob	102 Burger
3	Charlie	103 Pasta
5	Fmma	104 Ice Cream

### **FULL JOIN**

SQL> SELECT Customers.CustomerID, Customers.Name, Orders.OrderID, Orders.Product

**FROM Customers** 

FULL JOIN Orders ON Customers.CustomerID = Orders.CustomerID;

#### CUSTOMERID NAME ORDERID PRODUCT

1	Alex	101	Pizza
2	Bob	102	Burger
3	Charlie	103	Pasta
4	David		
5	Emma	104	Ice Cream
		105	Sandwich

6 rows selected.

#### **LEFT JOIN**

SQL> select Customers.CustomerID,Customers.Name,Orders.OrderID,

Orders.Product from Customers left join Orders on Customers.CustomerID=Orders.CustomerID;

CUSTOMERID	NAME	ORDERID PRODUCT
1	Alex	101 Pizza
2	Bob	102 Burger
3	Charlie	103 Pasta
5	Emma	104 Ice Cream
4	David	

#### RIGHT JOIN

SQL> select Customers.CustomerID,Customers.Name,Orders.OrderID,

Orders.Product from customers right join Orders on

Customers.CustomerID=Orders.CustomerID;

CUSTOMERID	NAME	ORDERID	PRODUCT
1	Alex	101	Pizza
2	Bob	102	Burger
3	Charlie	103	Pasta
5	Emma	104	Ice Cream
		105	Sandwich

#### **EQUI JOIN**

SQL> SELECT customers.CustomerID, customers.Name, customers.City, Orders.OrderID, Orders.Product

**FROM** customers

#### **JOIN Orders**

ON customers.CustomerID = Orders.CustomerID;

CUSTOMERID	NAME	CITY	ORDERID	PRODUCT
1	Alex	Chennai	101	Pizza
2	Bob	Mumbai	102	Burger
3	Charlie	Delhi	103	Pasta
5	Emma	Bangalor	e 104	Ice Cream

## **Natural Join**

SQL>SELECT \*FROM customers NATURAL JOIN Orders;

CUSTOMERID	NAME	CITY	ORDERID	PRODUCT
1	Alex	Chennai	101	Pizza
2	Bob	Mumbai	102	Burger
3	Charlie	Delhi	103	Pasta
5	Emma	Bangalore	e 104	Ice Cream

#### **Condition Join**

SQL> SELECT Customers.CustomerID, Customers.Name, Orders.OrderID, Orders.Product

**FROM Customers** 

JOIN Orders ON Customers.CustomerID > Orders.CustomerID;

#### CUSTOMERID NAME ORDERID PRODUCT

2	Bob	101 Pizza
3	Charlie	101 Pizza

4	David	101 Pizza
5	Emma	101 Pizza
3	Charlie	102 Burger
4	David	102 Burger
5	Emma	102 Burger
4	David	103 Pasta
5	Emma	103 Pasta

9 rows selected.

CONTENTS	MARKS ALLOTED	MARKS OBTAINED
Aim,Algorithm,SQL,PL/SQL	30	
Execution and Result	20	
Viva	10	
Total	60	

## **RESULT**

Thus, the inner join, full join, left join, right join, equi join, natural join, and condition join operations were executed successfully. This experiment helped in understanding how SQL joins work to retrieve meaningful insights from relational databases.