


{ggstatsplot}: Informative Statistical Visualizations

Indrajeet Patil



Genesis

Why a new package?

Life in the trenches (c. 2017)

(as an academic researcher)

⚠ Large-scale problems

- **Reporting errors:**

“half of all published psychology papers contained at least one p -value that was inconsistent”¹

- **Interpretation errors:**

“in 72% of cases, nonsignificant results were misinterpreted [to mean] that effect was absent”²

- **Replication crisis:**

“39% of effects were subjectively rated to have replicated the original result”³

and more...

⚠ Personal challenges




- How to avoid reporting errors?
- How to make visualizing data effortless?
- How to emphasize the importance of the effect?
- How to interpret null results?
- How to easily assess validity of model assumptions?
- How to increase reproducibility?

Proposal

Information-rich, ready-made statistical visualizations


Defaulting to a rich graphic



Visualizations reveal problems not discernible from descriptive statistics!

Avoiding cooking a new plot

The grammar of graphics is a powerful framework and can help you make **any** data visualization!



💡 Using ready-made plots lowers the activation energy for visualizing data!

Action Plan


{ggstatsplot} was born!

(started out as loose scripts, which were later consolidated into a package)

Example function

E.g., for hypothesis about group differences ([ggbetweenstats\(\)](#))

```
1 ggbetweenstats(  
2   data = iris,  
3   x     = Species,  
4   y     = Sepal.Length,  
5   title = "Distribution of sepal length across Iris species"  
6 )
```



Important





Information-rich defaults

- raw data + distributions
- descriptive statistics
- inferential statistics
- effect size + uncertainty
- pairwise comparisons
- Bayesian hypothesis-testing
- Bayesian estimation

Statistical approaches available

- parametric
- parametric
- robust
- Bayesian

And there is more!



Appendix provides more details.

Promised Land

Does it deliver?

Show, don't tell

Without `{ggstatsplot}`


Pearson's correlation test revealed that, across 142 participants, variable `x` was negatively correlated with variable `y`:

$t(140) = -0.76, p = 0.446$. The effect size ($r = -0.06, 95\%CI[-0.23, 0.10]$) was small, as per Cohen's (1988) conventions. The Bayes Factor for the same analysis revealed that the data were 5.81 times more probable under the null hypothesis as compared to the alternative hypothesis. This can be considered moderate evidence (Jeffreys, 1961) in favor of the null hypothesis (absence of any correlation between `x` and `y`).

With `{ggstatsplot}`


Relationship between x and y

$t_{Student}(140) = -0.76, p = 0.446, \hat{r}_{Pearson} = -0.06, CI_{95\%} [-0.23, 0.10], n_{pairs} = 142$



No need to worry about reporting or interpretation errors!

Simplified data analysis workflow




Quick insight into data by combining visualization and modeling!


Thoughtful Defaults

>Data Visualization


Second Edition
Show Me the Numbers
Designing Tables and Graphs to Enlighten




Stephen Few



SECOND EDITION
The Visual Display
of Quantitative Information
EDWARD R. TUFTÉ



THE
ELEMENTS
OF GRAPHING
DATA



O'REILLY®
Fundamentals
of Data
Visualization
A Primer on Making Informative
and Compelling Figures

Claus O. Wilke

Statistical Reporting



Results from Welch's t-test with {statsExpressions}

Template for Frequentist analysis

test parameter statistic significance effect size type + estimate + confidence intervals number of observations
 $t_{\text{Welch}}(281.95) = -10.75, p = 8.31e-23, \hat{g}_{\text{Hedges}} = -1.27, \text{CI}_{99\%}[-1.61, -0.94], n_{\text{obs}} = 284$

Template for Bayesian analysis

evidence in favor of null over alternative hypothesis natural logarithm of Bayes Factor posterior type + estimate + credible intervals prior type and value
 $\log_e(\text{BF}_{01}) = -6.20, \delta_{\text{difference}}^{\text{posterior}} = -5.06, \text{CI}_{95\%}^{\text{HDI}} [-6.75, -3.53], r_{\text{cauchy}}^{\text{JZS}} = 0.71$

<<https://indrajeetpatil.github.io/statsExpressions/>>

src: @patilindrajeets

(Doorn et al., 2020; APA Manual)




Encourages best practices in data visualization and statistical reporting!

A grain of salt

The "Golem of Prague" problem

✗ Promotes mindless application of statistical tests.



Clunky API


- Not a “real” `{ggplot2}` extension.
- Not interactive.
- Statistical proficiency needed.
- No stable (`1.0`) release yet.

Pleasant Side Effects

Maybe the real treasure was the technical skills we picked up along the way!

Software Architecture

Breaking down the monolith: $20K_{(2017)} \rightarrow 1K_{(2024)}$ lines of code



💡 Team sport

While re-architecting `{ggstatsplot}`, I decided to contribute to upstream open-source dependencies:

- joined the core `{easystats}` team and contributing to its ten component packages
- became a co-maintainer of `{ggsignif}`
- contributed to `{WRS2}` and `{ggcorrplot}`

Quality Assurance

CI Checks (GitHub Actions)

- Unit tests (random-order)
- Code coverage (100%)
- Linting (0 lints)
- Formatting (0 issues)
- Documentation (website, no link rot, many examples)
- CRAN checks (0 E, 0 W, 0 N)
- Pre-commit hooks (0 issues)
- Portability (Linux, macOS, Windows)
- Robustness (dependencies, R versions)

Healthy and active code base



All checks have passed


24 successful checks

Show all checks



IndrajeetPatil

1,571 commits 1,033,322 ++ 965,615 --



Team sport

While improving QA tools for `{ggstatsplot}`, in the spirit of open-source, I decided to contribute to upstream dependencies:


- became co-author of `{lintr}` (linter) and `{styler}` (formatter)

Impact

I can haz users?!

User Love

! Total downloads > 500K (97 percentile)



Second most starred {ggplot2}-extension!

git ggstatsplot Public

Enhancing {ggplot2} plots with statistical analysis 📈

R ★ 2k ⚡ 190

💡 Total citations > 1000



The Journal of Open Source Software

Visualizations with statistical details: The 'ggstatsplot' approach

Indrajeet Patil¹

¹ Center for Humans and Machines, Max Planck Institute for Human Development, Berlin, Germany

Summary

Graphical displays can reveal problems in a statistical model that might not be apparent from purely numerical summaries. Such visualizations can also be helpful for the reader to evaluate the validity of a model if it is reported in a scholarly publication or report. But, given the onerous costs involved, researchers often avoid preparing information-rich graphics and exploring several statistical approaches or tests available. The `ggstatsplot` package in the R programming language (R Core Team, 2021) provides a one-line syntax to enrich `ggplot2`-based visualizations with the results from statistical analysis embedded in the visualization itself. In doing so, the package helps researchers adopt a rigorous, reliable, and robust data exploratory and reporting workflow.

Visualizations with statistical details: The 'ggstatsplot' approach

1277

*

I Patil

Journal of Open Source Software 6 (61), 3167, 2021

Community Involvement

! Communication

Multiple [talks](#) on best practices in software development to help community contribute to `{ggstatsplot}` (or its dependency).

Preventive Care for R Packages

Indrajeet Patil




Dealing with the Second Hardest Thing in Computer Science

Indrajeet Patil



DRY PACKAGE DEVELOPMENT IN R

Indrajeet Patil



Introduction to Snapshot Testing in R

Indrajeet Patil



💡 Reception

- [Improving Psychological Science Award \(2020\)](#)
- 11 contributors
- 3 reverse dependencies
- Widely covered in [YouTube videos](#) and [social media posts](#)
- Almost 100% resolution rate on [StackOverflow](#)
- Over 100 daily visitors on [GitHub repo](#)
- Usage in a wide [range of fields](#): psychology, biology, medicine, economics, etc.
- Usage in data science training programs

Conclusion

The `{ggstatsplot}` package provides accessible interface to create rich statistical visualizations, and helps users adopt a rigorous, reliable, and robust data exploratory and reporting workflow.

Thank You 😊

For more

Source code for these slides can be found [on GitHub](#).

If you are interested in good programming and software development practices, check out my other [slide decks](#).

Find me at...

 Twitter

 LinkedIn

 GitHub

 Website

 E-mail

Session information

```
1 sessioninfo::session_info(include_base = TRUE)

- Session info -----
  setting  value
  version   R version 4.4.2 (2024-10-31)
  os        Ubuntu 22.04.5 LTS
  system    x86_64, linux-gnu
  hostname  fv-az1456-565
  ui         X11
  language  (EN)
  collate   C.UTF-8
  ctype     C.UTF-8
  tz         UTC
  date      2024-11-14
  pandoc   3.5 @ /opt/hostedtoolcache/pandoc/3.5/x64/ (via rmarkdown)
  quarto    1.6.33 @ /usr/local/bin/quarto
```

```
- Packages -----
  package      * version    date (UTC) lib source
  base          * 4.4.2      2024-10-31 [3] local
  BayesFactor    0.9.12-4.7 2024-01-24 [1] RSPM
  bayestestR     0.15.0     2024-10-17 [1] RSPM
  . . . . .
```


Appendix

Examples of other functions

ggwithinstats()

Hypothesis about group differences: repeated measures design

```
1 ggwithinstats(  
2   data = WRS2::WineTasting,  
3   x = Wine,  
4   y = Taste  
5 )
```



! Important

Defaults

- raw data + distributions
- descriptive statistics
- inferential statistics
- effect size + uncertainty
- pairwise comparisons
- Bayesian hypothesis-testing
- Bayesian estimation


Statistical approaches available

- parametric
- parametric
- robust
- Bayesian

gghistostats()

Distribution of a numeric variable

```
1 gghistostats(  
2   data = movies_long,  
3   x = budget,  
4   test.value = 30  
5 )
```



! Important

💡 Defaults

- counts + proportion for bins
- descriptive statistics
- inferential statistics
- effect size + uncertainty
- pairwise comparisons
- Bayesian hypothesis-testing
- Bayesian estimation


Statistical approaches available

- parametric
- parametric
- robust
- Bayesian

ggdotplotstats()

Labeled numeric variable

```
1 ggdotplotstats(  
2   data = movies_long,  
3   x = budget,  
4   y = genre,  
5   test.value = 30  
6 )
```



! Important

Defaults

- descriptive statistics
- inferential statistics
- effect size + uncertainty
- pairwise comparisons
- Bayesian hypothesis-testing
- Bayesian estimation


Statistical approaches available

- parametric
- parametric
- robust
- Bayesian

ggscatterstats()

Hypothesis about correlation: Two numeric variables

```
1 ggscatterstats(  
2   data = movies_long,  
3   x = budget,  
4   y = rating  
5 )
```



! Important

Defaults

- joint distribution
- marginal distribution
- effect size + uncertainty
- pairwise comparisons
- Bayesian hypothesis-testing
- Bayesian estimation


Statistical approaches available

- parametric
- parametric
- robust
- Bayesian

ggcorrmat()

Hypothesis about correlation: Multiple numeric variables

```
1 ggcorrmat(dplyr::starwars)
```



! Important

Defaults

- inferential statistics
- effect size + uncertainty
- careful handling of NAs
- partial correlations


Statistical approaches available

- parametric
- parametric
- robust
- Bayesian

ggpiestats()

Hypothesis about composition of categorical variables

```
1 ggpiestats(  
2   data = mtcars,  
3   x = am,  
4   y = cyl  
5 )
```



! Important


Defaults

- descriptive statistics
- inferential statistics
- effect size + uncertainty
- goodness-of-fit tests
- Bayesian hypothesis-testing
- Bayesian estimation

ggbarstats()

Hypothesis about composition of categorical variables

```
1 ggbarstats(  
2   data = mtcars,  
3   x = am,  
4   y = cyl  
5 )
```



! Important


Defaults

- descriptive statistics
- inferential statistics
- effect size + uncertainty
- goodness-of-fit tests
- Bayesian hypothesis-testing
- Bayesian estimation

ggcoefstats()

Hypothesis about regression coefficients

```
1 mod <- lm(  
2   formula = rating ~ mpaa,  
3   data = movies_long  
4 )  
5  
6 ggcoefstats(mod)
```



! Important

Defaults

- estimate + uncertainty
- inferential statistics (t, z, F, χ^2)
- model fit indices (AIC + BIC)

Supports all regression models supported in `{easystats}` ecosystem.


Meta-analysis is also supported!

grouped_ variants

Iterating over a grouping variable

grouped_ functions

```
1 grouped_ggpiestats(  
2   data = mtcars,  
3   x = cyl,  
4   grouping.var = am  
5 )
```



Available **grouped_** variants:

- `grouped_ggbetweenstats()`
- `grouped_ggwithinstats()`
- `grouped_gghistostats()`
- `grouped_ggdotplotstats()`
- `grouped_ggscatterstats()`
- `grouped_ggcorrmat()`
- `grouped_ggpiestats()`
- `grouped_ggbarstats()`

Customizability


“What if I don’t like the default plots?” 🤔

Modify the look




By changing **theme** and **palette**

```
1 ggbetweenstats(  
2   data = movies_long,  
3   x = mpaa,  
4   y = rating,  
5   ggtheme = ggthemes::theme_economist(),  
6   palette = "Darjeeling2",  
7   package = "wesanderson"  
8 )
```



By using `{ggplot2}` functions

```
1 ggbetweenstats(  
2   data = mtcars,  
3   x = am,  
4   y = wt,  
5   type = "bayes"  
6 ) +  
7   scale_y_continuous(sec.axis = dup_axis())
```




Too much information




Get only plots:

```
1 ggbetweenstats(
2   data = iris,
3   x = Species,
4   y = Sepal.Length,
5   # turn off statistical analysis
6   centrality.plotting = FALSE,
7   results.subtitle = FALSE,
8   bf.message = FALSE,
9   # turn off pairwise comparisons
10 pairwise.display = "none"
11 )
```



Get only expressions:

```
1 stats_expr <- ggpiestats(
2   Titanic_full, Survived, Sex,
3 ) %>%
4   extract_subtitle()
5
6 ggiraphExtra:::ggSpine(
7   data = Titanic_full,
8   aes(x = Sex, fill = Survived)
9 ) +
10 labs(subtitle = stats_expr)
```



`{ggstatsplot}`: Details about
statistical reporting

Supports different statistical approaches

Note

Functions	Description	Parametric	Non-parametric	Robust	Bayesian
<code>ggbetweenstats()</code>	Between group comparisons	✓	✓	✓	✓
<code>ggwithinstats()</code>	Within group comparisons	✓	✓	✓	✓
<code>gghistostats()</code> , <code>gddotplotstats()</code>	Distribution of a numeric variable	✓	✓	✓	✓
<code>ggcorrrmat()</code>	Correlation matrix	✓	✓	✓	✓
<code>ggscatterstats()</code>	Correlation between two variables	✓	✓	✓	✓
<code>ggpiestats()</code> , <code>ggbarstats()</code>	Association between categorical variables	✓	NA	NA	✓
<code>ggpiestats()</code> , <code>ggbarstats()</code>	Equal proportions for categorical variable levels	✓	NA	NA	✓
<code>ggcoefstats()</code>	Regression modeling	✓	✓	✓	✓
<code>ggcoefstats()</code>	Random-effects meta-analysis	✓	NA	✓	✓

Toggling statistical approaches



Parametric

```
1 # anova
2 ggbetweenstats(
3   data = mtcars,
4   x = cyl,
5   y = wt,
6   type = "p"
7 )
8
9 # correlation analysis
10 ggscatterstats(
11   data = mtcars,
12   x = wt,
13   y = mpg,
14   type = "p"
15 )
16
17 # t-test
18 gghistostats(
19   data = mtcars,
20   x = wt,
21   test.value = 2,
22   type = "p"
23 )
```

Non-parametric

```
1 # anova
2 ggbetweenstats(
3   data = mtcars,
4   x = cyl,
5   y = wt,
6   type = "np"
7 )
8
9 # correlation analysis
10 ggscatterstats(
11   data = mtcars,
12   x = wt,
13   y = mpg,
14   type = "np"
15 )
16
17 # t-test
18 gghistostats(
19   data = mtcars,
20   x = wt,
21   test.value = 2,
22   type = "np"
23 )
```

Alternative: Pure Pain



Hunting for packages

- 📦 for inferential statistics (`{stats}`)
- 📦 computing effect size + CIs (`{effectsize}`)
- 📦 for descriptive statistics (`{skimr}`)
- 📦 pairwise comparisons (`{multcomp}`)
- 📦 Bayesian hypothesis testing (`{BayesFactor}`)
- 📦 Bayesian estimation (`{bayestestR}`)
- 📦 ...



Inconsistent APIs

- 🤔 accepts data frame, vector, matrix?
- 🤔 long/wide format data?
- 🤔 works with `NAs`?
- 🤔 returns data frame, vector, matrix?
- 🤔 works with tibbles?
- 🤔 has all necessary details?
- 🤔 ...



Benefits in details

`{ggstatsplot}` combines data visualization and statistical analysis in a single step.

It...

- provides ready-made plots with information-rich defaults
- minimizes the chances of making errors in statistical reporting
- follows best practices in data visualization and statistical reporting
- helps evaluate statistical analysis in the context of the underlying data
- highlights the importance of the effect by providing effect size measures
- provides an easy way to evaluate *absence* of an effect using Bayesian framework
- extremely beginner-friendly

Footnotes

1. (Nuijten et al., *Behavior Research Methods*, 2016)
2. (Aczel et al., *AMPPS*, 2018)
3. Open Science Collaboration, *Science*, 2015