

Agenda

- Map
- Java 8 Interfaces
- Functional Interfaces
- Anonymous Inner Classes
- Lambda Expressions
- Method references
- Local and Nested classes
- ~~Stream Programming~~

HashTable Data structure

- Hashtable stores data in key-value pairs so that for the given key, value can be searched in fastest possible time.
- Internally hash-table is a table(array), in which each slot(index) has a bucket(collection).
- Load factor = Number of entries / Number of buckets.
- Multiple keys can compete for the same slot which can cause the collision
- To avoid the collision two techniques are used
 1. Open Addressing
 2. Separate Chaining
- In Separate Chaining mechanism to avoid the collision Key-value entries are stored in the same bucket depending on hash code of the "key".
- In java we have readymade/ built-in hashtables
 1. HashMap
 2. LinkedHashMap
 3. TreeMap
 4. Hashtable (Legacy)
 5. Properties (Legacy)
- Here we need to calculate the hash value of the key using hash function(Override hashCode method).
- The slot in the table is calculated internally by $\text{slot} = \text{key.hashCode()} \% \text{size}$
- Examples
 - Key=pincode, Value=city/area
 - Key=Employee, Value=Manager
 - Key=Department, Value=list of Employees

hashCode() method

- Object class has hashCode() method, that returns a unique number for each object (by converting its address into a number).
- To use any hash-based data structure hashCode() and equals() method must be implemented.

- If two distinct objects yield same hashCode(), it is referred as collision. More collisions reduce performance.
- Most common technique is to multiply field values with prime numbers to get uniform distribution and lesser collisions.
- hashCode() overriding rules
 - hash code should be calculated on the fields that decides equality of the object.
 - hashCode() should return same hash code each time unless object state is modified.
 - If two objects are equal (by equals()), then their hash code must be same.
 - If two objects are not equal (by equals()), then their hash code may be same (but reduce performance).

Map interface

- Collection of key-value entries (Duplicate "keys" not allowed).
- Implementations: HashMap, LinkedHashMap, TreeMap, Hashtable, ...
- The data can be accessed as set of keys, collection of values, and/or set of key-value entries.
- Map.Entry<K,V> is nested interface of Map<K,V>.
 - K getKey()
 - V getValue()
 - V setValue(V value)
- Abstract methods

```
* boolean isEmpty()
* int size()
* V put(K key, V value)
* V get(Object key)
* Set<K> keySet()
* Collection<V> values()
* Set<Map.Entry<K,V>> entrySet()
* boolean containsValue(Object value)
* boolean containsKey(Object key)
* V remove(Object key)
* void clear()
* void putAll(Map<? extends K,? extends V> map)
```

- Maps not considered as true collection, because it is not inherited from Collection interface.

HashMap class

- Non-ordered map (entries stored in any order -- as per hash code of key)
- Keys must implement equals() and hashCode()
- Fast execution
- Mostly used Map implementation

LinkedHashMap class

- Ordered map (preserves order of insertion)
- Keys must implement equals() and hashCode()

- Slower than HashSet
- Since Java 1.4

TreeMap class

- Sorted navigable map (stores entries in sorted order of key)
- Keys must implement Comparable or provide Comparator
- Slower than HashMap and LinkedHashMap
- Internally based on Red-Black tree.
- Doesn't allow null key (allows null value though).

Hashtable class

- Similar to HashMap class.
- Legacy collection class (since Java 1.0), modified for collection framework (Map interface).
- Synchronized collection -- Thread safe but slower performance
- Inherited from java.util.Dictionary abstract class (it is Obsolete).

Similarity between Set and Map

- Set is internally using map implementation where it has all the values as null.
- In set the elements are stored as keys and the corresponding values are null.
- HashSet = HashMap<K,null>
- LinkedHashSet = LinkedHashMap<K,null>
- TreeSet = TreeMap<K,null>
- In set duplicate elements are not allowed, in map duplicate keys are not allowed
- For HashSet, HashMap, LinkedHashSet, LinkedHashMap duplication is based on equals() and hashCode() of key
- For TreeSet and TreeMap the duplication is based on comparable of K or Comparator of K given in constructor

Java 8 Interface

- Before Java 8 interfaces were used to design specification/standards. It contains only declarations – public abstract.

```
interface Geometry {  
    /*public static final*/ double PI = 3.14;  
    /*public abstract*/ int calcRectArea(int length, int breadth);  
    /*public abstract*/ int calcRectPeri(int length, int breadth);  
}
```

- As interfaces don't contain method implementations, multiple interface inheritance is supported (no ambiguity error).
- Interfaces are immutable. One should not modify interface once published.
- Java 8 added many new features in interfaces in order to support functional programming in Java. Many of these features also contradict earlier Java/OOP concepts.

1. Default methods

- Java 8 allows default methods in interfaces. If method is not overridden, its default implementation in interface is considered.
- This allows adding new functionalities into existing interfaces without breaking old implementations e.g. Collection, Comparator, ...

```
interface Emp {
    double getSal();
    default double calcIncentives() {
        return 0.0;
    }
}

class Manager implements Emp {
    // ...
    // calcIncentives() is overridden
    double calcIncentives() {
        return getSal() * 0.2;
    }
}

class Clerk implements Emp {
    // ...
    // calcIncentives() is not overridden -- so method of interface is
    // considered
}
```

```
new Manager().calcIncentives(); // return sal * 0.2
new Clerk().calcIncentives(); // return 0.0
```

- However default methods will lead to ambiguity errors as well, if same default method is available from multiple interfaces. Error: Duplicate method while declaring class.
- Superclass same method get higher priority. But super-interfaces same method will lead to error.
- A class can invoke methods of super interfaces using InterfaceName.super.

2. Functional Interfaces

- If interface contains exactly one abstract method (SAM), it is said to be functional interface.
- It may contain additional default & static methods. E.g. Comparator, Runnable, ...
- @FunctionalInterface annotation does compile time check, whether interface contains single abstract method. If not, raise compile time error.

```
@FunctionalInterface // okay
interface Foo {
    void foo(); // SAM
}
```

```
@FunctionalInterface // okay
interface FooBar1 {
    void foo(); // SAM
    default void bar() {
        /*... */
    }
}
```

```
@FunctionalInterface // NO -- error
interface FooBar2 {
    void foo(); // AM
    void bar(); // AM
}
```

```
@FunctionalInterface // NO -- error
interface FooBar3 {
    default void foo() {
        /*... */
    }
    default void bar() {
        /*... */
    }
}
```

```
@FunctionalInterface // okay
interface FooBar4 {
    void foo(); // SAM
    public static void bar() {
        /*... */
    }
}
```

- Functional interfaces forms foundation for Java lambda expressions and method references.

Built-in functional interfaces

- New set of functional interfaces given in java.util.function package.
 - `Predicate<T>`: test: T -> boolean
 - `Function<T,R>`: apply: T -> R
 - `BiFunction<T,U,R>`: apply: (T,U) -> R
 - `UnaryOperator<T>`: apply: T -> T
 - `BinaryOperator<T>`: apply: (T,T) -> T
 - `Consumer<T>`: accept: T -> void

- `Supplier<T>`: `get: () -> T`
- For efficiency primitive type functional interfaces are also supported e.g. `IntPredicate`, `IntConsumer`, `IntSupplier`, `IntToDoubleFunction`, `ToIntFunction`, `ToIntBiFunction`, `IntUnaryOperator`, `IntBinaryOperator`.

Anonymous Inner Class

- Creates a new class inherited from the given class/interface and its object is created.
- If in static context, behaves like static member class. If in non-static context, behaves like non-static member class.
- Along with Outer class members, it can also access (effectively) final local variables of the enclosing method.

```
// (named) local class
class EmpnoComparator implements Comparator<Employee> {
    public int compare(Employee e1, Employee e2) {
        return e1.getEmpno() - e2.getEmpno();
    }
}
Arrays.sort(arr, new EmpnoComparator());    // anonymous obj of local class
```

```
// Anonymous inner class
Comparator<Employee> cmp = new Comparator<Employee>() {
    public int compare(Employee e1, Employee e2) {
        return e1.getEmpno() - e2.getEmpno();
    }
};
Arrays.sort(arr, cmp);
```

```
// Anonymous object of Anonymous inner class.
Arrays.sort(arr, new Comparator<Employee>() {
    public int compare(Employee e1, Employee e2) {
        return e1.getEmpno() - e2.getEmpno();
    }
});
```

Lambda expressions

- Traditionally Java uses anonymous inner classes to compact the code. For each inner class separate .class file is created.
- However code is complex to read and un-efficient to execute.
- Lambda expression is short-hand way of implementing functional interface.
- Its argument types may or may not be given. The types will be inferred.
- Lambda expression can be single liner (expression not statement) or multi-liner block { ... }.

```
// Anonymous inner class
Arrays.sort(arr, new Comparator<Emp>() {
    public int compare(Emp e1, Emp e2) {
        int diff = e1.getEmpno() - e2.getEmpno();
        return diff;
    }
});
```

```
// Lambda expression -- multi-liner
Arrays.sort(arr, (Emp e1, Emp e2) -> {
    int diff = e1.getEmpno() - e2.getEmpno();
    return diff;
});
```

```
// Lambda expression -- multi-liner -- Argument types inferred
Arrays.sort(arr, (e1, e2) -> {
    int diff = e1.getEmpno() - e2.getEmpno();
    return diff;
});
```

```
// Lambda expression -- single-liner -- with block { ... }
Arrays.sort(arr, (e1, e2) -> {
    return e1.getEmpno() - e2.getEmpno();
});
```

```
// Lambda expression -- single-liner
Arrays.sort(arr, (e1,e2) -> e1.getEmpno() - e2.getEmpno());
```

- Practically lambda expressions are used to pass as argument to various functions.
- Lambda expression enable developers to write concise code (single liners recommended).

Non-capturing lambda expression

- If lambda expression result entirely depends on the arguments passed to it, then it is non-capturing (self-contained).

```
BinaryOperator<Integer> op1 = (a,b) -> a + b;
testMethod(op);
```

```
static void testMethod(BinaryOperator<Integer> op) {  
    int x=12, y=5, res;  
    res = op.apply(x, y); // res = x + y;  
    System.out.println("Result: " + res)  
}
```

- In functional programming, such functions/lambda expressions are referred to as pure functions.

Capturing lambda expression

- If lambda expression result also depends on additional variables in the context of the lambda expression passed to it, then it is capturing.

```
int c = 2; // must be effectively final  
BinaryOperator<Integer> op = (a,b) -> a + b + c;  
testMethod(op);
```

```
static void testMethod(BinaryOperator<Integer> op) {  
    int x=12, y=5, res;  
    res = op.apply(x, y); // res = x + y + c;  
    System.out.println("Result: " + res);  
}
```

- Here variable `c` is bound (captured) into lambda expression. So it can be accessed even out of scope (effectively). Internally it is associated with the method/expression.
- In some functional languages, this is known as Closures.

Method references

- lambda expression is a short-hand implementation of Single Abstract Method (Functional Interface)
- Method reference is short-hand of lambda-expression
- If lambda expression involves single method call, it can be shortened by using method reference.
- Method references are converted into instances of functional interfaces.
- Method reference can be used for class static method, class non-static method, object non-static method or constructor.

Member/Nested classes

- By default all Java classes are top-level.
- In Java, classes can be written inside another class/method. They are Member classes.
- Four types of member/nested classes
 - Static member classes --
 - Non-static member class --
 - Local class --
 - Anonymous Inner class --

- When .java file is compiled, separate .class file created for outer class as well as inner class.

Static member classes

- Like other static members of the class (belong to the class, not the object).
- Accessed using outer class (Doesn't need the object of outer class).
- Can access static (private/public) members of the outer class directly.
- Static member class cannot access non-static members of outer class directly.
- The outer class can access all members (including private) of inner class directly (no need of getter/setter).
- The static member classes can be private, public, protected, or default.

```
class Outer {
    private int nonStaticField = 10;
    private static int staticField = 20;

    public static class Inner {
        public void display() {
            System.out.println("Outer.nonStaticField = " + nonStaticField);
// error
            System.out.println("Outer.staticField = " + staticField); // ok
        }
    }
}

- 20

public class Main {
    public static void main(String[] args) {
        Outer.Inner obj = new Outer.Inner();
        obj.display();
    }
}
```

Non-static member classes/Inner classes

- Like other non-static members of the class (belong to the object/instance of Outer class).
- Accessed using outer class object (Object of outer class is MUST).
- Can access static & non-static (private) members of the outer class directly.
- The outer class can access all members (including private) of inner class directly (no need of getter/setter).
- The non-static member classes can be private, public, protected, or default.

```

class Outer {
    private int nonStaticField = 10;
    private static int staticField = 20;
    public class Inner {
        public void display() {
            System.out.println("Outer.nonStaticField = " + nonStaticField);
        }
    }
}

// ok-10
System.out.println("Outer.staticField = " + staticField); // ok-20

}

}

public class Main {
    public static void main(String[] args) {
        //Outer.Inner obj = new Outer.Inner(); // compiler error
        // create object of inner class
        //Outer outObj = new Outer();
        //Outer.Inner obj = outObj.new Inner();
        Outer.Inner obj = new Outer().new Inner();
        obj.display();
    }
}

```

- If Inner class member has same name as of outer class member, it shadows (hides) the outer class member. Such Outer class members can be accessed explicitly using `Outer.this`.

Static member class and Non-static member class -- Application

```

// top-level class
class LinkedList {
    // static member class
    static class Node {
        private int data;
        private Node next;
        // ...
    }
    private Node head;
    // non-static member class
    class Iterator {
        private Node trav;
        // ...
    }
    // ...
    public void display() {
        Node trav = head;
        while(trav != null) {
            System.out.println(trav.data);
            trav = trav.next;
        }
    }
}

```

```

    }
}

```

Local class

- Like local variables of a method.
- The class scope is limited to the enclosing method.
- If enclosed in static method, behaves like static member class. If enclosed in non-static method, behaves like non-static member class.
- Along with Outer class members, it can also access (effectively) final local variables of the enclosing method.
- We can create any number of objects of local classes within the enclosing method.

```

public class Main {
    private int nonStaticField = 10;
    private static int staticField = 20;
    public static void main(String[] args) {
        final int localVar1 = 1;
        int localVar2 = 2;
        int localVar3 = 3;
        localVar3++;
        // local class (in static method) -- behave like static member class
        class Inner {
            public void display() {
                System.out.println("Outer.nonStaticField = " +
nonStaticField); // error
                System.out.println("Outer.staticField = " + staticField); //
ok 20

                System.out.println("Main.localVar1 = " + localVar1); // ok 1
                System.out.println("Main.localVar2 = " + localVar2); // ok 2
                System.out.println("Main.localVar3 = " + localVar3); //
error

            }
        }
        Inner obj = new Inner();
        obj.display();
        //new Inner().display();
    }
}

```

Anonymous Inner class

- Creates a new class inherited from the given class/interface and its object is created.
- If in static context, behaves like static member class. If in non-static context, behaves like non-static member class.
- Along with Outer class members, it can also access (effectively) final local variables of the enclosing method.

```
// (named) local class
class EmpnoComparator implements Comparator<Employee> {
    public int compare(Employee e1, Employee e2) {
        return e1.getEmpno() - e2.getEmpno();
    }
}
Arrays.sort(arr, new EmpnoComparator());    // anonymous obj of local class
```

```
// Anonymous inner class
Comparator<Employee> cmp = new Comparator<Employee>() {
    public int compare(Employee e1, Employee e2) {
        return e1.getEmpno() - e2.getEmpno();
    }
};
Arrays.sort(arr, cmp);
```