

```
=====
pycrtools TUTORIAL
=====
```

Version History:

- 2010-03-01 - started (H. Falcke)
- 2010-03-24 - added hArray description (HF)

The library makes use of algorithms and code developed by Andreas Horneffer, Lars Bahren, Martin vd Akker, Heino Falcke, ...

To create a PDF version of the tutorial.py script use

```
./prettypy tutorial.py
```

in the \$LOFARSOFT/src/CR-Tools/implement/Pypline directory.

Table of Contents

```
=====
```

1. StartUp
2. Getting Help
3. Vectors
 - 3.1. Some Basics
 - 3.2. Construction of STL Vectors
 - 3.2.1. Referencing, memory allocation, indexing, slicing
 - 3.2.2. Vector arithmetic
 - 3.3. Working with the hArray class
 - 3.3.1. Creating Arrays and basic operations
 - 3.3.2. Changing Dimensions
 - 3.3.3. Memory sharing
 - 3.3.4. Basic Slicing
 - 3.3.5. Applying Methods to Slices
 - 3.3.6. Units and Scale Factors
 - 3.3.7. Keywords and Values
 - 3.3.8. History Logbook
4. File I/O
 - 4.1. Opening and Closing a CR Data File
 - 4.2. Setting and retrieving metadata (parameters)
 - 4.3. Reading in Data
5. Fourier Transforms (FFT)
6. Basic Plotting
 - 6.1. Mathgl
 - 6.2. Matplotlib
 - 6.3. Plotting Using the hArray Plotting Method
7. CR Pipeline Modules
 - 7.1. Quality Checking of Time Series Data
8. Coordinates
9. Appendix: Listing of all Functions:

1. StartUp

```
-----
```

First one needs to load the library. This can be done by "from hftools import *" which makes all the c++ functions and their python wrappers available.

In addition there are some helpful definitions in python as well, which

are stored in "pycrtools.py". This file actually imports hftools for you. Hence, all you actually need to do is (make sure the file is in your search path)

```
>>> from pycrtools import *
```

The most convenient way is probably to define an alias in your .bashrc or .profile files, like

```
alias pycr='/sw/bin/python2.6 -i $LOFARSOFT/src/CR-Tools/implement/Pyipeline/pycrinit.py'
```

then you can simply start the pyrtools with 'pycr'.

The file pycrinit.py also allows you to read in a second file to be executed, like this one here. So, you can run the tutorial with

```
pycr -i tutorial.py
```

from the UNIX prompt.

2. Getting Help

=====

The pycrtools have a built-in help system, which can be accessed with:

```
>>> help()
```

To get information on a specific function or method type help(func). This will essentially print the docstring of the python object and list all its methods. Hence, help will work on any decently implemented python object, including the standard ones.

For example,

```
>>> help(IntVec)
```

will give documentation on the integer vector, while

```
>>> help(IntVec.sin)
```

will give the documentation on the "sin" method associated with it.

For a listing of all available functions in the pycrtools type

```
>>> help(all).
```

3. Vectors

=====

3.1. Some Basics

The fundamental data structure we use is a standard c++ vector defined in the c++ standard template library (STL). This is wrapped and exposed to python using the Boost Python system.

(NB: Unfortunately different systems provide different python data structures. Hence a function exposed to python with SWIG or SIP is not

directly able to accept a BOOST PYTHON wrapped vector as input or vice versa. If you want to do this you have to provide extra conversion routines.)

In line with the basic python philosophy, vectors are passed as references. Since we are working with large sets of data processing time is as important as convenience. Hence the basic principle is that we try to avoid copying large chunks of data as much as possible.

The basic functions operating on the data in c++ either take STL iterators as inputs (i.e. pointers to the begin and end of the memory where the data in the STL vector is stored) or `casa::Vectors`, which are created with shared memory (i.e. their physical memory is the same as that of the STL vector).

For that reason MEMORY ALLOCATION is done almost exclusively in the Python layer. The fast majority of c++ functions is not even able to allocate or free any memory. This allows for very efficient memory management and processing, but also means that the user is responsible for providing properly sized vectors as inputs AND output vectors. I.e.: you need to know beforehand what sized vector you expect in return!

That may be annoying, but forces you to think carefully about how to use memory. For example, if there is a processing done multiple times using a scratch vector of fixed size, you reuse the same vector over and over again, thus avoiding a lot of unnecessary allocation and deallocation of memory and creation of vectors.

Also, the basic vectors are inherently one-dimensional and not multi-dimensional. On the other hand, multi-dimensional data is always simply written sequentially into the memory - you just need to know (and think about) how your data is organized. Some rudimentary support for multi-dimensions has been added (if the data you need is contiguous), but needs further work (see `setDim`, `getDim`, `elem`).

3.2. Construction of STL Vectors

A number of vector types are provided: `bool`, `int`, `float`, `complex`, and `str`.

To create a vector most efficiently, use the original vector constructors:

- `BoolVec()`
- `IntVec()`
- `FloatVec()`
- `ComplexVec()`
- `StringVec()`

e.g.

```
>>> v=FloatVec(); v
      Vec(float,0)=[]
```

will create a floating point vector of size 0.

The vector can be filled with a python list or tuple, by using the `extend` attribute:

```
>>> v.extend([1,2,3,4])
```

```
v => Vec(float,4)=[1.0,2.0,3.0,4.0]
```

Note, that python has automatically converted the integers into floats, since the STL vector does not allow any automatic typing.

The STL vector can be converted back to a python list by using the python list creator:

```
list(v) => [1.0, 2.0, 3.0, 4.0]
```

or use the list or val methods of the vector (where the latter has the extra twist that it will return a scalar value, if the vector has a length of one).

```
v.val() => [1.0, 2.0, 3.0, 4.0]
v.list() => [1.0, 2.0, 3.0, 4.0]
```

However, the basic Boost Python STL vector constructor takes no arguments and is a bit cumbersome to use in the long run. Here we provide a wrapper function that is useful for interactive use.

Usage:

Vector(Type) - will create an empty vector of type "Type", where Type is a basic Python type, i.e. bool, int, float, complex, str.

Vector(Type,size) - will create an vector of type "Type", with length "size".

Vector(Type,size,fill) - will create an vector of type "Type", with length "size" and initialized with the value "fill"

Vector([1,2,3,...]) or Vector((1,2,3,...)) - if a list or a tuple is provided as first argument then a vector is created of the type of the first element in the list or tuple (here an integer) and filled with the contents of the list or tuple.

So, what we will now use is:

```
>>> v=Vector([1.,2,3,4]); v
Vec(4)=[1.0,2.0,3.0,4.0]
```

Note, that size and fill take precedence over the list and tuple input. Hence if you create a vector with Vector([1,2,3],size=2) it will contain only [1,2]. Vector([1,2,3],size=2,fill=4) will give [4,4].

Some simple support for multiple dimensions had been implemented, using the methods:

```
vector.setDim([n1,n2,...])
vector.getDim()
vector.elem(n)
```

However, this is already depreciated, since there is an array class to do this better.

3.2.1. Referencing, memory allocation, indexing, slicing
.....

Following basic python rules, the STL vector will persist in memory as long as there is a python reference to it. If you destroy v also the c++ memory will disappear. Hence, if you keep a pointer to the vector in c++ and try to work on it after the python object was destroyed, your programme may crash. That's why by default memory management is done ONLY on one side, namely the python side!

To illustrate how Python deals with references, consider the following example:

```
>>> x=v
>>> x[0]=3
>>> v
      Vec(4)=[3.0,2.0,3.0,4.0]
```

Hence, the new python object x is actually a reference to the same c++ vector that was created in v. Modifying elements in x modifies elements in v. If you destroy v or x, the vector will not be destroyed, since there is still a reference to it left. Only if you destroy x and v the memory will be freed.

As note above, this vector is subscriptable and sliceable, using the standard python syntax.

```
>>> v[1:3]
      Vec(2)=[2.0,3.0]
```

We can also resize vectors and change their memory allocation:

```
>>> v1=Vector([0.0,1,2,3,4,5]);v1
      Vec(float,6)=[0.0,1.0,2.0,3.0,4.0,5.0]
>>> v2=Vector(float,len(v1),2.0);v2
      Vec(float,6)=[2.0,2.0,2.0,2.0,2.0,2.0]
```

With the resize attribute you allocate new memory while keeping the data. It is not guaranteed that the new memory actually occupies the same physical space.

```
>>> v2.resize(8);
>>> v2
      Vec(float,8)=[2.0,2.0,2.0,2.0,2.0,2.0,0.0,0.0]
```

Resize a vector and fill with non-zero values:

```
>>> v2.resize(10,-1)
>>> v2
      Vec(float,10)=[2.0,2.0,2.0,2.0,2.0,2.0,0.0,0.0,-1.0,-1.0]
```

Resize a vector to same size as another vector:

```
>>> v2.resize(v1)
>>> v2
      Vec(float,6)=[2.0,2.0,2.0,2.0,2.0,2.0]
```

Make a new vector of same size and type as the original one:

```
>>> v3=v2.new()
>>> v3
```

```
Vec(float,6)=[0.0,0.0,0.0,0.0,0.0,0.0]
```

Fill a vector with values

```
>>> v3.fill(-2)
>>> v3
Vec(float,6)=[-2.0,-2.0,-2.0,-2.0,-2.0,-2.0]
```

3.2.2. Vector arithmetic

.....

The vectors have a number of mathematical functions attached to them. A full list can be seen by typing

```
>>> dir(v1)
['__add__', '__class__', '__contains__', '__delattr__', '__delitem__', '__dict__', '__di
v__', '__doc__', '__format__', '__getattribute__', '__getitem__', '__hash__', '__iadd__',
 '__idiv__', '__imul__', '__init__', '__instance_size__', '__isub__', '__iter__', '__len__
', '__module__', '__mul__', '__new__', '__reduce__', '__reduce_ex__', '__repr__', '__setatt
r__', '__setitem__', '__sizeof__', '__str__', '__sub__', '__subclasshook__', '__weakref__'
, 'abs', 'acos', 'add', 'addadd', 'append', 'asin', 'atan', 'ceil', 'convert', 'copy', 'co
s', 'cosh', 'countgreaterequal', 'countgreaterequalabs', 'countgreaterthan', 'countgreater
thanabs', 'countlessequal', 'countlessequalabs', 'countlessthan', 'countlessthanabs', 'dim
ension', 'div', 'divadd', 'downsample', 'elem', 'exp', 'extend', 'extendflat', 'fft', 'fil
l', 'findgreaterequal', 'findgreaterequalabs', 'findgreaterthan', 'findgreaterthanabs', 'f
indlessequal', 'findlessequalabs', 'findlessthan', 'findlessthanabs', 'findlowerbound', 'f
loor', 'getDim', 'list', 'log', 'log10', 'mean', 'median', 'mul', 'muladd', 'mulsum', 'ndi
m', 'negate', 'new', 'norm', 'normalize', 'random', 'resize', 'setDim', 'sin', 'sinh', 'so
rt', 'sortmedian', 'sqrt', 'square', 'stddev', 'sub', 'subadd', 'sum', 'tan', 'tanh', 'typ
e', 'val', 'vec']
```

Some of the basic arithmetic is available in an intuitive way.

You can add a scalar to a vector by

```
>>> v1+3
Vec(float,6)=[3.0,4.0,5.0,6.0,7.0,8.0]
```

This will actually create a new vector (and destroy it right away, since no reference was kept). The original vector is unchanged.

A technical limitation is that - even though addition and multiplication is commutative, the scalar (i.e., non-vector) values has to come as the second argument.

You can also add two vectors (which is commutative):

```
>>> v1+v2
Vec(float,6)=[2.0,3.0,4.0,5.0,6.0,7.0]
```

In order to change the vector, you can use the "in place" operators +=, -=, /=, *= :

Adding a vector in place:

```
>>> v1+=v2
v1 => Vec(float,6)=[2.0,3.0,4.0,5.0,6.0,7.0]
```

now v1 was actually modified such that v2 was added to the content of v1 and the results is stored in v1.

Similarly you can do

```
- v1-=v2
- v1*=v2
- v1/=v2
```

Here are examples of some basic statistics functions one can use

Mean:

```
v1.mean() => 4.5
```

Median:

```
v1.median() => 5.0
```

Summing all elements in a vector:

```
v1.sum() => 27.0
```

Standard Deviation:

```
v1.stddev() => 1.87082869339
```

3.3. Working with the hArray class

3.3.1. Creating Arrays and basic operations

.....

While the basic underlying data structures are plain STL vectors, in many cases, however, one has to deal with multi-dimensional data. For this case we introduce a new wrapper class, named hArrays, that mimicks a multi-dimensional array, but still operates on an underlying vector with essentially a flat, horizontal data structure. Given that a major concern is to minimize duplication of large data structures, the array class will share memory with its associated vector and also with arrays that are derived from it. Explicit copying will have to be done in order to avoid this. Access to various dimensions (rows, columns, etc...) is done via slices that need to be contiguous in memory! Since the array is vector-based, all methods defined for vectors are also inherited by hArrays and can be applied to slices or even automatically loop over multiple slices (e.g., rows or columns).

An array is defined using the hArray function. This is a constructor function and not a class of its own. It will return array classes of different types, such as IntArray, FloatArray, ComplexArray, StringArray, BoolArray, referring to the different data types they contain. As for vectors, each array can only contain one type of data.

```
hArray(Type=float,dimensions=[n1,n2,n3...],fill=None) -> FloatArray
```

where Type can be a Python type, a Python list/tuple (where the first element determines the type), an STL vector, or another hArray.

Dimensions are given as a list of the form [dim1,dim2,dim3, ...]. The size of the underlying vector will automatically be resized to dim1*dim2*dim3* ... to be able to contain all elements. Alternatively, one can provide another array, whose dimensions will be copied.

The array can be filled with an initialization values that can be either a single value, a list, a tuple, or an STL vector of the same type.

```
>>> v=Vector(range(10))
```

```
>>> a=hArray(v,[3,3])
```

```
a => hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
```

One may wonder what the representation of the Array actually means.

```
a => hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,0,0,0]
```

After "hArray(" first the data type is given, then the array dimensions and total vector size, and finally the currently active slice (given as start and end index of the vector). An optional asterisk indicates that the next operation will actually loop the previously specified slices (see below). At the end the currently selected slice is displayed (while the array may actually hold more data).

The underlying vector of an array can be retrieved with the .vec() method. I.e.,

```
>>> a.vec()
Vec(int,9)=[0,1,2,3,4,5,6,7,8]
```

The arrays have most of the vector methods defined, so you can also add, multiply, etc. with scalars or other arrays.

```
a*2 => hArray(int, [3, 3]=9, [0:9]) -> [0,2,4,6,8,10,12,14,16]
```

```
a*a => hArray(int, [3, 3]=9, [0:9]) -> [0,1,4,9,16,25,36,49,64]
```

Underlying these operations are the basic hftools functions, e.g. the multiplication is essentially a python method that first creates a new array and then calls hMul.

```
>>> tmp_array=a.new()
>>> tmp_array.mul(a,2)
```

```
a => hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
```

BTW, this could also be done calling the function hMul(tmp_array,a,2), rather than the corresponding method.

An important constraint is that all these functions or methods only work with either vector or array classes, a mix in the parameters between vectors and arrays is currently not supported.

3.3.2. Changing Dimensions

.....

The dimensions can be obtained and set, using the getDim and setDim methods. If the length of the underlying vector changes due to a change in the dimensions, the vector will be resized and padded with zeros, if necessary.


```
>>> a.getDim()
[3, 3]

>>> a.setDim([3,3,2])
hArray(int, [3, 3, 2]=18, [0:18]) -> [0,1,2,3,4,5,6,7,8,0,...]

>>> a.setDim([3,3])
hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
```

3.3.3. Memory sharing

Note, that the array and vector point share the same memory. Changing an element in the vector

```
>>> v[0]=-1

v => Vec(int,9)=[-1,1,2,3,4,5,6,7,8]
a => hArray(int, [3, 3]=9, [0:9]) -> [-1,1,2,3,4,5,6,7,8]
```

will also change the corresponding element in the array. The same is, btw, true if one creates an array from an array. Both will share the same underlying data vector. They will, btw, also share the same size and dimensions.

```
>>> b=hArray(a)

>>> b[0,0]=-2

b => hArray(int, [3, 3]=9, [0:9]) -> [-2,1,2,3,4,5,6,7,8]
a => hArray(int, [3, 3]=9, [0:9]) -> [-2,1,2,3,4,5,6,7,8]
v => Vec(int,9)=[-2,1,2,3,4,5,6,7,8]

>>> v[0]=0
```

```
a => hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
```

To actually make a pyhsically distinct copy, you need to explicitly copy the data over.

```
>>> c=hArray(int,a)

>>> a.copy(c)
```

or more simply

```
>>> c=hArray(int,a,a)
```

(the 2nd parameter is for the dimensions, the third one is the fill parameter that initates the copying).

3.3.4. Basic Slicing

The main purpose of these arrays is, of course, to be able to access multiple dimensions. This is done using the usual `__getitem__` method of python.

Let us take our two-dimensional array from before:

```
a => hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
```

The vector followed by a single number in square brackets will "in principle" obtain the first column of the array.

```
a[0] => hArray(int, [3, 3]=9, [0:3]) -> [0,1,2]
```

It says "in principle", because the only thing which that command does is to return a new hArray python object, which will point to the same data vector, but contain a different data slice which is then returned whenever a method tries to operate on the vector.

```
>>> a[0].vec()  
Vec(int,3)=[0,1,2]
```

This retrieves a copy of the data, since assigning a sub-slice of a vector to another vector actually requires copying the data - as vectors do not know about slicing (yet). Use one-dimensional arrays if you want to have are reference to a slice only.

In contrast, `a.vec()`, without slicing, will give you a reference to the underlying vector.

Similarly,

```
>>> a[0,1].vec()  
Vec(int,1)=[1]
```

will access a slice consisting of a single element (returned as a vector). To obtain it as a scalar value, use

```
>>> a[0,1].val()  
1
```

One may wonder, why one has to use the extra methods `vec` and `val` to access the data. The reason is that slicing on its own will return an array (and not a vector), which we need for other purposes still.

Slicing can also be done over multiple elements of one dimension, using the known python slicing syntax:

```
>>> a[0,0:2].val()  
[0, 1]
```

however, currently this is restricted to the last dimension only, in order to point to a contiguous memory slice. Hence:

```
>>> a[0:2]  
hArray(int, [3, 3]=9, [0:6]) -> [0,1,2,3,4,5]
```

is possible, but not

```
>>> a[0:2,0:2]  
hArray(int, [3, 3]=9, [0:2]) -> [0,1]
```

where the first slice is simply ignored.

3.3.5. Applying Methods to Slices

.....

First, of all, we can now apply the known vector functions also to array slices directly. E.g.,

```
>>> a[0].sum()
Vec(int,1)=[3]
```

will return the sum over the first row of the array, i.e. the first three elements of the underlying vector. While

```
>>> a[0].negate()
a => hArray(int, [3, 3]=9, [0:9]) -> [0,-1,-2,3,4,5,6,7,8]
>>> a[0].negate()
a => hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
```

returns nothing, but will actually change the sign of the first three elements in the underlying vector.

In principle one could now loop over all slices using a for loop:

```
>>> for i in range(a.getDim()[0]): print "Row",i,":",a[i].val(), " => a =", a
Row 0 : [0, 1, 2] => a = hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
Row 1 : [3, 4, 5] => a = hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
Row 2 : [6, 7, 8] => a = hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
```

However, looping over slices in simple way is already built into the arrays, by appending the Ellipsis symbol "..." to the dimensions. This will actually put the array in "looping mode".

```
>>> l=a[0:3,...]
l => hArray(int, [3, 3]=9, [0:3]*) -> [0,1,2]
```

which is indicated in the screen representation of the array by an extra asterisk and actually means that one can loop over all the elements of the respective dimension.

```
>>> iterate=True
>>> while iterate:
...     print "Row",l.loop_nslice(),":",l.val(), " => l =", l
...     iterate=l.next().doLoopAgain()
Row 0 : [0, 1, 2] => l = hArray(int, [3, 3]=9, [0:3]*) -> [0,1,2]
Row 1 : [3, 4, 5] => l = hArray(int, [3, 3]=9, [3:6]*) -> [3,4,5]
Row 2 : [6, 7, 8] => l = hArray(int, [3, 3]=9, [6:9]*) -> [6,7,8]

l => hArray(int, [3, 3]=9, [0:3]*) -> [0,1,2]
```

This will do exactly the same as the for-loop above.

Here doLoopAgain() will return True as long as the array is in looping mode and has not yet reached the last slice. loop_nslice() returns the current slice the array is set to (see also loop_i, loop_start, loop_end). next() will advance to the next slice until the end is reached (and doLoopAgain is set to false). The loop will be reset at the next call of next(). Hence, as written above the loop could be called multiple times where the loop will be automatically reset each time.

We could also explicitly reset the loop in using to its starting values, but that should not be necessary most of the time.

```
>>> l.resetLoop()  
hArray(int, [3, 3]=9, [0:3]*) -> [0,1,2]
```

Now, since this is still a bit too much work, you can actually apply (most of) the available vector methods to multiple slices at once, by just applying it to an array in looping mode.

As an example, let's calculate the mean value of each slice at the to level of our example array, which is simply:

```
>>> l.mean()  
Vec(float,3)=[1.0,4.0,7.0]
```

In contrast to the same method applied to vectors, where a single value is returned, the return value is now a vector of values, each of which corresponds to the mean of one top-level slice. Hence, the vector has looped automatically over all the slices specified in the definition of the array.

The looping over slices can be more complex taking start, stop, and increment values into account:

```
>>> a[1:,...].mean()  
Vec(float,2)=[4.0,7.0]
```

will loop over all top-level slices starting at the 2nd slice (slice #1) until the last.

```
>>> a[:2,...].mean()  
Vec(float,2)=[1.0,4.0]
```

will loop over the first two top-level slices.

```
>>> a[0:3:2,...].mean()  
Vec(float,2)=[1.0,7.0]
```

will loop over the two top-level slices using an increment of 2, i.e. here take the first and third only (so, here non contiguous slices can be put to work).

To loop over all slices in one dimensions, a short-cut can be used by leaving away the slice specification. Hence,

```
>>> a[...].mean()  
Vec(float,3)=[1.0,4.0,7.0]
```

will do the same as `a[0:,...].mean()`.

Finally, it is even possible to specify an array of indices for the slicing.

```
>>> a[[0,2],...].mean()  
Vec(float,2)=[1.0,7.0]
```

will loop over slices 0 and 2.

Looping can also be done for methods that require multiple arrays as inputs (remember a mix of vectors and arrays is not implemented). In this case the `next()` method will be applied to every array in the parameter list and looping proceeds until the first array has reached the

end. Hence, care has to be taken that the same slice looping is applied to all arrays in the parameter list.

As an example we create a new array of the dimensions of a

```
>>> x=hArray(int,a)
```

and fill it with slices from "a" multiplied by the scalar value 2

```
>>> x[[0,2],...].mul(a[[0,2],...],2)
```

```
x => hArray(int, [3, 3]=9, [0:9]) -> [0,2,4,0,0,0,12,14,16]
```

and indeed now the first and last slice were operated on and filled with the results of the operation.

Forgetting slicing in a parameter can lead to unexpected results, e.g., in the following example "a" is looped over but x is not. Hence, the result will always be written (and overwritten) into the first three elements of x, containing at the end only the results of the multiplication of the last slice in a.

```
>>> x.fill(0); x[...].mul(a,2)
```

```
x => hArray(int, [3, 3]=9, [0:9]) -> [0,2,4,0,2,4,0,2,4]
```

3.3.6. Units and Scale Factors

.....

Numerical arrays allow one to set a (single) unit for the data. With `setUnit(prefix, unit_name)` one can specify the name of the unit and the scale factor, which is specified as a string being one of "f", "p", "n", "micro", "m", "c", "d", "", "h", "k", "M", "G", "T", "P", "E", "Z".

```
>>> a.setUnit("M","Hz")
hArray(int, [3, 3]=9, [0:9]) -> [0,1,2,3,4,5,6,7,8]
```

will set the unitname to MHz without modifying the values in the array (assuming that the values were delivered initially in this unit). However, the scaling can be changed by calling `setUnit` again (with or without a unit name), e.g.:

```
>>> a.setUnit("k","")
hArray(int, [3, 3]=9, [0:9]) -> [0,1000,2000,3000,4000,5000,6000,7000,8000]
```

Which has converted the values to kHz. The name of the unit can be retrieved with

```
>>> a.getUnit()
'kHz'
```

and cleared with `clearUnit()`.

3.3.7. Keywords and Values

.....

For documenting the vector further and to store certain values, one can store keywords and values in the array. This is done with

```
>>> a.setKey("name","TestArray")
TestArray(int, [3, 3]=9, [0:9]) -> [0,1000,2000,3000,4000,5000,6000,7000,8000]
```

The keywords can be arbitrary strings and the values also arbitrary strings. Thus numbers need to be converted to strings and back. The keyword "name" is special in the sense that it is a default key, that is recognized by a number of other modules (including the `__repr__` method governing array output) to briefly describe the data.

The keyword values can be retrieved using `getKey`:

```
>>> a.getKey("name")
'TestArray'
```

3.3.8. History Logbook

.....

The array keeps a history of most operations performed with it. This can be viewed by using the `getHistory` (retrieves a vector of strings) or simply the `.history()` method, which prints the activity log.

```
>>> a.history()
2010-03-28 16:56:29 [initialize_storage]: Vector of type St6vectorIiSaIiEE created.
2010-03-28 16:56:29 [delVector]: Vector of typeSt6vectorIiSaIiEE and size=0 deleted.
2010-03-28 16:56:29 [initialize_storage]: Vector of type St6vectorIiSaIiEE created.
2010-03-28 16:56:29 [setDimension]: Dimensions set to [10]
2010-03-28 16:56:29 [setDimension]: Dimensions set to [3,3]
2010-03-28 16:56:29 [setDimension]: Dimensions set to [3,3,2]
2010-03-28 16:56:29 [setDimension]: Dimensions set to [3,3]
2010-03-28 16:56:29 [hFill]:   Par 0: vec = array[T,9] : [-1,1,...]
2010-03-28 16:56:29 [hFill]:   Par 1: fill_value = -2
2010-03-28 16:56:29 [hCopy]:   Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [hCopy]:   Par 1: outvec = array[T,9] : [0,0,...]
2010-03-28 16:56:29 [hSum]:    Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [hNegate]:  Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [hNegate]:  Par 0: vec = array[T,9] : [0,-1,...]
2010-03-28 16:56:29 [hMean]:    Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [hMean]:    Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [hMean]:    Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [hMean]:    Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [hMean]:    Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [hMean]:    Par 0: vec = array[T,9] : [0,1,...]
2010-03-28 16:56:29 [setUnit]:  Unit set to MHz.
2010-03-28 16:56:29 [setUnit]:  Unit set to kHz.
2010-03-28 16:56:29 [setKey]:   name = TestArray
```

You can add a line to the history log yourself with

```
>>> a.addHistory("TEST","This is a test.")
TestArray(int, [3, 3]=9, [0:9]) -> [0,1000,2000,3000,4000,5000,6000,7000,8000]
```

and clear the entire log with `.clearHistory()`.

History tracking can be switched off with

```
>>> a.setHistory(False)
```

4. File I/O

4.1. Opening and Closing a CR Data File

Let's see how we can open a file. First define a filename, e.g.:

```
>>> LOFARSOFT=os.environ["LOFARSOFT"]
>>> filename_sun=LOFARSOFT+"/data/lopes/example.event"
>>> filename_lofar=LOFARSOFT+"/data/lofar/trigger-2010-02-11/triggered-pulse-2010-02-11-TB
B1.h5"
    filename_sun => /Users/falcke/LOFAR/usg/data/lopes/example.event
    filename_lofar => /Users/falcke/LOFAR/usg/data/lofar/trigger-2010-02-11/triggered-puls
e-2010-02-11-TBB1.h5
```

We can create a new file object, using the "cfile" class, which is an interface to the LOFAR CRTTOOLS datareader class and was defined in pycrtools.py.

The following will open a data file and return a DataReader object:

```
>>> datafile=cfile(filename_lofar).set("blocksize",1024*2)
```

The associated filename can be retrieved with

```
>>> datafile.filename
'/Users/falcke/LOFAR/usg/data/lofar/trigger-2010-02-11/triggered-pulse-2010-02-11-TBB1.h
5'
```

The file will be automatically closed (and the DataReader object be destroyed), whenever the cfile object is deleted, e.g. with "file=0".

4.2. Setting and retrieving metadata (parameters)

Now we need to access the meta data in the file. This is can be done in multiple ways. One way is by using the get method. This method actually calls the function "hFileGetParameter" defined in the c++ code.

Which observatory did we actually use?

```
>>> obsname=datafile.get("observatory");
    obsname => LOFAR
```

There are more keywords, of course. A list of implemented parameters we can access is obtained by

```
>>> keywords=datafile.get("help")
    hFileGetParameter - available keywords: nofAntennas, nofSelectedChannels, nofSelectedAnt
ennas, nofBaselines, block, blocksize, stride, fftLength, nyquistZone, sampleInterval, ref
erenceTime, sampleFrequency, antennas, selectedAntennas, selectedChannels, positions, incr
ement, frequencyValues, frequencyRange, Date, Observatory, Filesize, presync, TL, LTL, Eve
ntClass, SampleFreq, StartSample, AntennaIDs, keywords, help
```

Note, that the results are returned as PythonObjects. Hence, this makes use of the power of python with automatic typing. For, example

```
>>> datafile.get("frequencyRange")
    Vec(float,2)=[0.0,100000000.0]
```

actually returns a vector.

Here no difference is made where the data comes from. The keyword

Observatory accesses the header record in the data file while the frequencyRange accesses a method of the DataReader.

A second way to retrieve data is to use square brackets. Hence datafile[key] is equivalent to datafile.get(key).

```
>>> datafile["blocksize"]
2048
```

Now we will define a number of useful variables that contain essential parameters that we later will use.

```
>>> obsdate    =datafile["Date"]
>>> filesize   =datafile["Filesize"]
>>> blocksize  =datafile["blocksize"]
>>> nAntennas  =datafile["nofAntennas"]
>>> antennas   =datafile["antennas"]
>>> antennaIDs =datafile["AntennaIDs"]
>>> selectedAntennas=datafile["selectedAntennas"]
>>> nofSelectedAntennas=datafile["nofSelectedAntennas"]
>>> fftlength  =datafile["fftLength"]
>>> sampleFrequency =datafile["sampleFrequency"]
>>> maxblocksize=min(filesize,1024*1024);
>>> nBlocks=filesize/blocksize;

obsdate => 1265926154
filesize => 132096
blocksize => 2048
nAntennas => 16
antennas => Vec(int,16)=[0,1,2,3,4,5,6,7,8,9,...]
antennaIDs => Vec(int,16)=[128002016,128002017,128002018,128002019,128002020,128002021,128002022,128002023,128003024,128003025,...]
selectedAntennas => Vec(int,16)=[0,1,2,3,4,5,6,7,8,9,...]
nofSelectedAntennas => 16
fftlength => 1025
sampleFrequency => 200000000.0
maxblocksize => 132096
nBlocks => 64
```

Luckily, you do not have to do this all the time, since all the parameters will be read out at the beginning and will be stored as attributes to the file object.

```
>>> for kw in datafile.keywords: p_("datafile."+kw)
datafile.observatory => LOFAR
datafile.blocksize => 2048
datafile.antennaIDs => Vec(int,16)=[128002016,128002017,128002018,128002019,128002020,128002021,128002022,128002023,128003024,128003025,...]
datafile.nyquistZone => 1
datafile.antennas => Vec(int,16)=[0,1,2,3,4,5,6,7,8,9,...]
datafile.nofBaselines => 120
datafile.filesize => 132096
datafile.increment => Vec(float,2)=[5e-09,195312.5]
datafile.selectedAntennas => Vec(int,16)=[0,1,2,3,4,5,6,7,8,9,...]
datafile.selectedChannels => Vec(int,513)=[0,1,2,3,4,5,6,7,8,9,...]
datafile.nofAntennas => 16
datafile.sampleFrequency => 200000000.0
datafile.nofSelectedAntennas => 16
datafile.referenceTime => 0.0
```



```

datafile.frequencyValues => Vec(float,513)=[0.0,195312.5,390625.0,585937.5,781250.0,97
6562.5,1171875.0,1367187.5,1562500.0,1757812.5,...]
datafile.nofSelectedChannels => 513
datafile.stride => 0
datafile.sampleInterval => 5e-09
datafile.frequencyRange => Vec(float,2)=[0.0,100000000.0]
datafile.fftLength => 513
datafile.date => 1265926154
datafile.block => 0

```

They will be updated whenever you do a `file.set(key,value)`, however, assigning a new value to the attribute will NOT automatically change the parameter in the file. For this, you have to use the `"set"` method, which is an implementation of the `"hFileSetParameter"` function. E.g. changing the blocksize we already did before. This is simply

```
>>> datafile.set("blocksize",2048);
```

again the list of implemented keywords is visible with using

```
>>> datafile.set("help",0);
```

Here the listed keywords actually start with capital letters, however, to spare you some annoyance, you can use a spelling which starts with either an upper or a lower case letter.

Another useful feature: The `set` method actually returns the `crfile` object itself. Hence, you can append multiple `set` commands after each other.

```
>>> datafile.set("block",2).set("selectedAntennas",[0,2,3]);
```

Alternatively you can also use square brackets:

```
>>> datafile["selectedAntennas"]=[0,2]
```

but then it is not possible to append multiple `set` commands in one line, so you need to provide lists of keywords and list of values, like

```
>>> datafile["blocksize","selectedAntennas"]=[2048,[0,2]]
>>> datafile["blocksize","selectedAntennas"]
[2048, Vec(int,2)=[0,2]]
```

Note, that we have now reduced the number of antennas to two: namely antenna 0 and 2 and the number of selected antennas is

```
>>> datafile["nofSelectedAntennas"]
2
```

However, now we want to work on all antennas again:

```
>>> datafile.set("block",0).set("selectedAntennas",range(nAntennas))
```

4.3. Reading in Data

The next step is to actually read in data. This is done with the `read` method (accessing `"hFileRead"`). The data is read flatly into a 1D

vector. This is also true if multiple antennas are read out at once. Here simply the data from the antennas follow each other.

Also, by default memory allocation of the vectors has to be done in python before calling any of the functions. This improves speed and efficiency, but requires one to programme carefully and to understand the data structure.

First we create a FloatArray of the correct dimensions, naming it Voltage and setting the Unit to counts.

```
>>> fxdata=hArray(float,[nofSelectedAntennas,blocksize],name="E-Field").setUnit("", "Counts")
```

This is now a large vector filled with zeros.

Now we can read in the raw time series data, either using "datafile.read" and a keyword, or actually better, use the read method of arrays, as they then store filename and history information in the array.

Currently implemented keywords for reading data fields are: "Fx", "Voltage", "FFT", "CalFFT", "Time", "Frequency".

So, let us read in the raw time series data, i.e. the electric field in the antenna as digitized by the ADC. This is provided by the keyword "Fx" (means $f(x)$).

```
>>> fxdata.read(datafile,"Fx")
fxdata => E-Field(float, [16, 2048]=32768, [0:32768]) -> [16.0,17.0,10.0,18.0,17.0,6.0,16.0,17.0,-1.0,0.0,...]
```

and voila the vector is filled with time series data from the data file. Note that we had to use the .vec method for the array, since datafile.read does not yet accept arrays (since it can't handle c++ iterators).

No, you can access the individual antennas as single vectors through slicing

```
>>> ant0data=fxdata[0].vec()
```

To get the x-Axis we create a second vector

```
>>> times=hArray(float,[blocksize],name="Time").setUnit("", "s")
>>> times.read(datafile,"Time")
```

This is the time relative to the trigger in seconds. So, let's have that in microseconds, by using setUnit

```
>>> times.setUnit("\\mu", "")
Time(float, [2048]=2048, [0:2048]) -> [0.0,0.005,0.01,0.015,0.02,0.025,0.03,0.035,0.04,0.045,...]
```

We do the same now for the frequency axis, which we convert to MHz. As length we have to take the length of the Fourier transformed time block (which is $blocksize/2+1$).

```
>>> frequencies=hArray(float,dimensions=[fftlength],name="Frequency").setUnit("", "Hz")
```

```
>>> frequencies.read(datafile,"Frequency")
Frequency(float, [1025]=1025, [0:1025]) -> [0.0,97656.25,195312.5,292968.75,390625.0,488
281.25,585937.5,683593.75,781250.0,878906.25,...]

>>> frequencies.setUnit("M","Hz")
Frequency(float, [1025]=1025, [0:1025]) -> [0.0,0.09765625,0.1953125,0.29296875,0.390625
,0.48828125,0.5859375,0.68359375,0.78125,0.87890625,...]
```

5. Fourier Transforms (FFT)

We can make a FFT of a float vector. This function will only return the non-redundant part of the FFT (i.e., just one half). Again we need to provide a properly sized output vector (input length/2+1). We also have to specify as a second parameter in which NyquistZone the data was take.

Nyquist sampling means that one needs, for example, 200 MHz sampling rate to digitize a bandwidth of 100 MHz. The first Nyquist zone is then 0-100 MHz, and the second is 100-200 MHz.

So, let's do the transform:

```
>>> fftdata=hArray(complex,[nofSelectedAntennas,fftlength],name="FFT(E)")
>>> fxdata[...].fft(fftdata[...],1)

fftdata => FFT(E)(complex, [16, 1025]=16400, [0:16400]) -> [(14776+0j),(-78.0619954633
+23.5840915053j),(49.6800536667+19.8582762045j),(-69.6240335619+15.9113124235j),(2.2813132
1087-46.0593431603j),(-50.7134694718-6.38083930207j),(-11.8103929808+4.5431205938j),(-52.0
847348972+52.0362484443j),(72.7593935051-54.1910307411j),(-30.9353873089+10.1986827514j),.
..]
```

Here we have used the fft method of the float array, which is just a call to the stand-alone function hFFT defined in hftools.cc.

We can convert the data back into the time domain by using the inverse Fourier transform.

```
>>> fxinvdata=hArray(float,dimensions=fxdata,name="E-Field").setUnit("", "Counts")
>>> fftdata[...].invfft(fxinvdata[...],1)
```

To get the spectral power from the FFTed vector, we have to square the complex data and convert it to floats. This can be done using the complex function "norm" (unusual name, but used in c++).

```
>>> spectrum=hArray(float,dimensions=fftdata,name="E-field Spectrum")
>>> fftdata[...].norm(spectrum)
```

We can now try to calculate the average spectrum of the data set for one antenna, by looping over all blocks.

```
>>> avspectrum=hArray(float,dimensions=fftdata,name="avg. Spectrum")
>>> for block in range(nBlocks):
...     fftdata.read(datafile.set("Block",block),"FFT").none()
...     fftdata[...].spectralpower(avspectrum[...])
```

(The .none() method is appended to suppress unwanted output in generating the tutorial, when an operation returns an array or vector.)

6. Basic Plotting

In order to plot the data, we can use external packages. Two packages are being provided here: matplotlib and mathgl. The former is specifically designed for python and thus slightly easier to use interactively. Since version 0.99 it is supposed to be capable of 3D plots (at the time of writing we use 0.98). Mathgl is perhaps a little faster and convenient for real time applications and hence is used in our GUI programming.

6.1. Mathgl -----

Here is a simple example on how to use mathgl code (here without a widget)

```
from mathgl import *

width=800
height=600
size=1024
gr=mglGraph(mglGraphPS,width,height)
y=mglData(size)
y.Modify("cos(2*pi*x)")
x=mglData(size)
x.Modify("x*1024");
ymax=y.Maximal()
ymin=y.Minimal()
gr.Clf()
gr.SetRanges(0,0.5,ymin,ymax)
gr.Axis("xy")
gr.Title("Test Plot x")
gr.Label("x","x-Axis",1)
gr.Label("y","y-Axis",1)
gr.Plot(x,y);
gr.WriteEPS("test-y.eps","Test Plot")
```

6.2. Matplotlib -----

Now, in principle, we need to import matplotlib

```
>>> import matplotlib.pyplot as plt
```

however, that should have been done already for you.

Depending on the system you may have to use

```
>>> plt.show()
```

and an empty plot window should pop up somewhere (in the background?)
!! On the Mac it seems to pop up automatically.

(NB: At least on a Mac the window likes to stubbornly hide behind other windows, so search your screen carefully if no window pops up.)

Depending on the system, the program could hang here and wait for input. In this case you need to kill the window and re-issue the command!!!

Now, we can use some of the plotting commands.

```
>>> plt.subplot(1,2,1)
>>> plt.title("Average Spectrum for Two Antennas")
>>> plt.semilogy(frequencies.vec(),avspectrum[0].vec())
>>> plt.semilogy(frequencies.vec(),avspectrum[1].vec())
>>> plt.ylabel(avspectrum.getKey("name")+" [" +avspectrum.getUnit()+""]")
>>> plt.xlabel(frequencies.getKey("name")+" [" +frequencies.getUnit()+""]")
```

To plot the time series of the entire data set, we first read in all sample from all antennas

```
>>> datafile["block","blocksize"]=(0,maxblocksize)
>>> fxall=Vector(); fxall.setDim([datafile.nofSelectedAntennas,maxblocksize])
Vec(float,2113536)=[0.0,0.0,0.0,0.0,0.0,0.0,0.0,0.0,0.0,0.0,...]
>>> timeall=Vector(float,maxblocksize)
>>> datafile.read("Time",timeall); timeall *= 10**6.
<hftools.DataReader object at 0x539b20>
>>> datafile.read("Fx",fxall)
<hftools.DataReader object at 0x77308>
```

and then we plot it

```
>>> plt.subplot(1,2,2)
>>> plt.title("Time Series of Antenna 0")
>>> plt.plot(timeall,fxall.elem(0))
>>> plt.ylabel("Electric Field [ADC counts]")
>>> plt.xlabel("Time [ $\mu$ s]")
So, for a linear plot use .plot, for a loglog plot use .loglog and for
a log-linear plot use .semilogx or .semilogy ...
```

Note, that we have used vectors here instead of hArrays - this is actually deprecated in normal interactive use (but may be faster in automatic pipelines)

6.3. Plotting Using the hArray Plotting Method

There is also a simpler way to make the kind of plots described above, using the built-in plot method of array.

```
>>> avspectrum.par.xvalues=frequencies
>>> avspectrum.par.title="Average Spectrum"
>>> avspectrum[0].plot(logplot="y").none()
```

This creates a semilog-plot with appropriate labels and units (if they were provided beforehand.)

You can either provide the parameters directly (precedence), or set the plotting parameters as attributes to the .par class of the array, e.g., "array.par.xvalues=x_vector; array.plot()"

If the array is in looping mode, multiple curves are plotted in one windows. Hence,

```
>>> avspectrum.par.logplot="y"
>>> avspectrum[...].plot()
avg. Spectrum(float, [16, 1025]=16400, [0:1025]*) -> [13868864905.0,186600.668168,163848
.440523,135588.910231,171181.713829,125052.341697,149167.47994,191654.209722,168893.679542
,138273.603106,...]
```

will simply plot all spectra of all antennas (=highest array index) in

the array.

The available parameters are:

Parameters:

xvalues: an array with corresponding x values, if "None" numbers from 0 to length of the array are used

xlabel: the x-axis label, if not specified, use the "name" keyword of the xvalues array - units will be added automatically

ylabel: the y-axis label, if not specified, use the "name" keyword of the array - units will be added automatically

title: a title for the plot

clf: if True (default) clear the screen beforehand (use False to compose plots with multiple lines from different arrays.

logplot: can be used to make loglog or semilog plots:

"x" ->semilog in x

"y" ->semilog in y

"xy"->loglog plot

7. CR Pipeline Modules

7.1. Quality Checking of Time Series Data

For an automatic pipeline it is essential to check whether the data is of good quality, or whether one needs to flag particular antennas. Here we demonstrate a simple, but effective way to do this.

The basic parameters to look at are the mean value of the time series (indicating potential DC offsets), the root-mean-square (RMS) deviation (related to the power received), and the number of peaks in the data (indicating potential RFI problems).

For cosmic ray data, we expect spikes and peaks to be in the middle of a trace, so we will just look at the first or/and last quarter of a data set and set the block size accordingly.

```
>>> blocksize=min(filesize/4,maxblocksize)
```

We will then read this block of data into an appropriately sized data array.

```
>>> dataarray=hArray(float,[nofSelectedAntennas,blocksize])
>>> dataarray.read(datafile.set("blocksize",blocksize).set("block",3),"Voltage")
hArray(float, [16, 33024]=528384, [0:528384]) -> [6.0,15.0,1.0,8.0,19.0,11.0,11.0,23.0,1
6.0,8.0,...]
```

The array now contains all the measured voltages of the selected antennas in the file.

First we calculate the mean over all samples for each antennas (and make use of the looping through the Ellipsis object).

```
>>> datamean = dataarray[...].mean()
```

```
datamean => Vec(float,16)=[7.17281371124,-7.79051598837,-1.9765625,-0.283490794574,5.2
2622940891,-1.5335816376,0.44046753876,-6.22256540698,1.53373304264,4.74460998062,...]
```

Similarly we get the rms (where we spare the algorithm from recalculating the mean, by providing it as input - actually a list of means).

```
>>> datarms = dataarray[...].stddev(datamean)
datarms => Vec(float,16)=[10.4218369439,10.3521070448,10.1878041442,11.9229119576,10.0
156780471,11.8848006355,9.56962788658,10.0075920432,10.7717471629,10.1781039241,...]
```

and finally we get the total number of peaks 5 sigma above the noise.

```
>>> datanpeaks = dataarray[...].countgreaterthanabs(datarms*5)
datanpeaks => Vec(int,16)=[45,3,32,0,53,0,46,0,43,4,...]
```

To see whether we have more peaks than expected, we first calculate the expected number of peaks for a Gaussian distribution and our blocksize, as well as the error on that number.

```
>>> npeaksexpected=funcGaussian(5,1,0)*blocksize
npeaksexpected => 0.0490974252546
>>> npeakerror=sqrt(npeaksexpected)
npeakerror => 0.221579388154
```

So, that we can get a normalized quantity

```
G = (Npeaks_detected - Npeaks_expected)/Npeaks_error
```

which should be of order unity if we have roughly a Gaussian distribution. If it is much larger or less than unity we have more or less peaks than expected and the data is clearly not Gaussian noise.

We do the calculation of G using our STL vectors (even though speed it no of the essence here)

```
>>> dataNonGaussianity = Vector(float,nAntennas)
>>> dataNonGaussianity.sub(datanpeaks,npeaksexpected)
>>> dataNonGaussianity /= npeakerror
```

The next step is to make a nice table of the results and check whether these parameters are within the limits we have imposed (based on empirical studies of the data).

To ease the operation we combine all the data into one python array (using the zip function - zip, as in zipper).

```
>>> dataproperties=zip(selectedAntennas,datamean,datarms,datanpeaks,dataNonGaussianity)
```

which is a rather nasty collection of numbers. So, we print a nice table (restricting it to the first 5 antennas).

```
>>> for prop in dataproperties[0:5]: print "Antenna {0:3d}: mean={1: 6.2f}, rms={2:6.1f},
npeaks={3:5d}, nonGaussianity={4: 7.2f}".format(*prop)
Antenna 0: mean= 7.17, rms= 10.4, npeaks= 45, nonGaussianity= 202.87
Antenna 1: mean= -7.79, rms= 10.4, npeaks= 3, nonGaussianity= 13.32
Antenna 2: mean= -1.98, rms= 10.2, npeaks= 32, nonGaussianity= 144.20
Antenna 3: mean= -0.28, rms= 11.9, npeaks= 0, nonGaussianity= -0.22
Antenna 4: mean= 5.23, rms= 10.0, npeaks= 53, nonGaussianity= 238.97
```

Clearly this is a spiky dataset, with only one antenna not being

affected by too many peaks (which is in fact not the case for the first block of that dataset).

To check automatically whether all parameters are in the allowed range, we can use a little python helper function, using a python "dict" as database for allowed parameters.

```
>>> qualitycriteria={"mean":(-15,15),"rms":(5,15),"nonGaussianity":(-3,3)}
>>> CheckParameterConformance(dataproperties[0],{"mean":1,"rms":2,"nonGaussianity":4},qualitycriteria)
['nonGaussianity']
```

The first parameter is just the list of numbers of the mean, rms, etc. of one antenna we created above. The second parameter is a dict, describing which parameter to find at which position in the input list, and the third parameter is yet another dict specifying for each parameter the range of allowed upper and lower values. The result is a list of parameter names, where the antennas failed the test. The list is empty if the antenna passed it.

Finally, we do not want to do this manually all the time. So, a little python function is available, that does the quality checking for you and returns a list with failed antennas and their properties.

```
>>> badantennalist=CRQualityCheck(qualitycriteria,datafile,dataarray,verbose=False)

badantennalist[0] => [15, 0, (0.46990067829457366, 214.1564187430852, 463, 2089.322957
4834572), ['rms', 'nonGaussianity']]
```

(first the antenna number, then the block, then a list with the mean, rms, npeaks, and nonGaussianity, and finally the failed fields)

Note, that this function can be called with "file=None". In this case the data provided in the datararray will be used.

8. Coordinates

We also have access to a few functions dealing with astronomical coordinates. Assume, we have a source at an Azmiut/Elevation position of (178 Degree,28 Degree) and we want to convert that into Cartesian coordinates (which, for example, is required by our beamformer).

We first turn this into std vector and create a vector that is supposed to hold the Cartesian coordinates. Note that the AzEL vector is actually AzElRadius, where we need to set the radius to unity.

```
>>> azel=FloatVec()
>>> azel.extend((178,28,1))
>>> cartesian=azel.new()
>>> azel
Vec(float,3)=[178.0,28.0,1.0]
>>> cartesian
Vec(float,3)=[0.0,0.0,0.0]
```

We then do the conversion, using

```
>>> hCoordinateConvert(azel,CoordinateTypes.AzElRadius,cartesian,CoordinateTypes.Cartesian,
,True)
True
```


<code>hSqrt(vec)</code>	- Take the sqrt of all the elements in the vector.
<code>hSqrt(vec, vecout)</code>	- Take the sqrt of all the elements in the vector and return results in a second vector.
<code>hSquare(vec)</code>	- Take the square of all the elements in the vector.
<code>hSquare(vec, vecout)</code>	- Take the square of all the elements in the vector and return results in a second vector.
<code>hTan(vec)</code>	- Take the tan of all the elements in the vector.
<code>hTan(vec, vecout)</code>	- Take the tan of all the elements in the vector and return results in a second vector.
<code>hTanh(vec)</code>	- Take the tanh of all the elements in the vector.
<code>hTanh(vec, vecout)</code>	- Take the tanh of all the elements in the vector and return results in a second vector.
<code>hAbs(vec)</code>	- Take the abs of all the elements in the vector.
<code>hAbs(vec, vecout)</code>	- Take the abs of all the elements in the vector and return results in a second vector.
<code>hCos(vec)</code>	- Take the cos of all the elements in the vector.
<code>hCos(vec, vecout)</code>	- Take the cos of all the elements in the vector and return results in a second vector.
<code>hCosh(vec)</code>	- Take the cosh of all the elements in the vector.
<code>hCosh(vec, vecout)</code>	- Take the cosh of all the elements in the vector and return results in a second vector.
<code>hCeil(vec)</code>	- Take the ceil of all the elements in the vector.
<code>hCeil(vec, vecout)</code>	- Take the ceil of all the elements in the vector and return results in a second vector.
<code>hFloor(vec)</code>	- Take the floor of all the elements in the vector.
<code>hFloor(vec, vecout)</code>	- Take the floor of all the elements in the vector and return results in a second vector.
<code>hRound(vec)</code>	- Take the round of all the elements in the vector.
<code>hRound(vec, vecout)</code>	- Take the round of all the elements in the vector and return results in a second vector.
<code>hAcos(vec)</code>	- Take the acos of all the elements in the vector.
<code>hAcos(vec, vecout)</code>	- Take the acos of all the elements in the vector and return results in a second vector.
<code>hAsin(vec)</code>	- Take the asin of all the elements in the vector.
<code>hAsin(vec, vecout)</code>	- Take the asin of all the elements in the vector and return results in a second vector.

hAtan(vec)	- Take the atan of all the elements in the vector.
hAtan(vec, vecout)	- Take the atan of all the elements in the vector and return results in a second vector.
hSub(vec1, vec2)	- Performs a Sub between the two vectors, which is returned in the first vector. If the second vector is shorter it will be applied multiple times.
hSub(vec1, operand)	- Performs a Sub between the vector and a scalar (applied to each element), which is returned in the first vector.
hSub(vec, vec1, vec2)	- Performs a sub between the last two vectors, which is returned in the first vector.
hSubAdd(vec, vec1, vec2)	- Performs a sub between the last two vectors, and add the result to the first vector which can be of different type.
hSub(vec, vec1, scalar1)	- Performs a sub between the vector and a scalar, where the result is returned in the first vector (with automatic casting).
hMul(vec1, vec2)	- Performs a Mul between the two vectors, which is returned in the first vector. If the second vector is shorter it will be applied multiple times.
hMul(vec1, operand)	- Performs a Mul between the vector and a scalar (applied to each element), which is returned in the first vector.
hMul(vec, vec1, vec2)	- Performs a mul between the last two vectors, which is returned in the first vector.
hMulAdd(vec, vec1, vec2)	- Performs a mul between the last two vectors, and add the result to the first vector which can be of different type.
hMul(vec, vec1, scalar1)	- Performs a mul between the vector and a scalar, where the result is returned in the first vector (with automatic casting).
hAdd(vec1, vec2)	- Performs a Add between the two vectors, which is returned in the first vector. If the second vector is shorter it will be applied multiple times.
hAdd(vec1, operand)	- Performs a Add between the vector and a scalar (applied to each element), which is returned in the first vector.
hAdd(vec, vec1, vec2)	- Performs a add between the last two vectors, which is returned in the first vector.
hAddAdd(vec, vec1, vec2)	- Performs a add between the last two vectors, and add the result to the first vector which can be of different type.
hAdd(vec, vec1, scalar1)	- Performs a add between the vector and a scalar,

where the result is returned in the first vector
(with automatic casting).

<code>hDiv(vec1, vec2)</code>	- Performs a Div between the two vectors, which is returned in the first vector. If the second vector is shorter it will be applied multiple times.
<code>hDiv(vec1, operand)</code>	- Performs a Div between the vector and a scalar (applied to each element), which is returned in the first vector.
<code>hDiv(vec, vec1, vec2)</code>	- Performs a div between the last two vectors, which is returned in the first vector.
<code>hDivAdd(vec, vec1, vec2)</code>	- Performs a div between the last two vectors, and add the result to the first vector which can be of different type.
<code>hDiv(vec, vec1, scalar1)</code>	- Performs a div between the vector and a scalar, where the result is returned in the first vector (with automatic casting).
<code>hConj(vec)</code>	- Calculate the complex conjugate of all elements in the complex vector.
<code>hCrossCorrelateComplex(vec1, vec2)</code>	- Multiplies the elements of the first vector with the complex conjugate of the elements in the second and returns the results in the first.
<code>hReal(vec, vecout)</code>	- Take the real of all the elements in the complex vector and return results in a float vector.
<code>hArg(vec, vecout)</code>	- Take the arg of all the elements in the complex vector and return results in a float vector.
<code>hImag(vec, vecout)</code>	- Take the imag of all the elements in the complex vector and return results in a float vector.
<code>hNorm(vec, vecout)</code>	- Take the norm of all the elements in the complex vector and return results in a float vector.
<code>hNegate(vec)</code>	- Multiplies each element in the vector with -1 in place, i.e. the input vector is also the output vector.
<code>hSum(vec)</code>	- Performs a sum over the values in a vector and returns the value.
<code>hMulSum(vec1, vec2)</code>	- Piecewise multiplication of the elements in a vector and summing of the results
<code>hProduct(vec)</code>	- Multiplies all elements in the vector with each other and return the result
<code>hNorm(vec)</code>	- Returns the lengths or norm of a vector (i.e. $\text{Sqrt}(\text{Sum}_i(x_i^2))$).
<code>hNormalize(vec)</code>	- Normalizes a vector to length unity.

SECTION: Statistics Functions

`hRandom(vec, minimum, maximum)` - Fills a vector with random values between minimum and maximum limits

`hMean(vec)` - Returns the mean value of all elements in a vector.

`hSort(vec)` - Sorts a vector in place.

`hSortMedian(vec)` - Sorts a vector in place and returns the median value of the elements.

`hMedian(vec)` - Returns the median value of the elements.

`hStdDev(vec, mean)` - Calculates the standard deviation around a mean value.

`hStdDev(vec)` - Calculates the standard deviation of a vector of values.

SECTION: Comparison and Selection

`hFindLessEqual(vec, threshold, vecout)` - Find the samples that are LessEqual a certain threshold value and returns the number of samples found and the positions of the samples in a second vector.

`hFindLessEqualAbs(vec, threshold, vecout)` - Find the samples whose absolute values are LessEqual a certain threshold value and returns the number of samples found and the positions of the samples in a second vector.

`hCountLessEqual(vec, threshold)` - Count the samples that are LessEqual a certain threshold value and returns the number of samples found.

`hCountLessEqualAbs(vec, threshold)` - Find the samples whose absolute values are LessEqual a certain threshold value and returns the number of samples found.

`hFindGreaterThan(vec, threshold, vecout)` - Find the samples that are GreaterThan a certain threshold value and returns the number of samples found and the positions of the samples in a second vector.

`hFindGreaterThanAbs(vec, threshold, vecout)` - Find the samples whose absolute values are GreaterThan a certain threshold value and returns the number of samples found and the positions of the samples in a second vector.

`hCountGreaterThan(vec, threshold)` - Count the samples that are GreaterThan a certain threshold value and returns the number of samples found.

`hCountGreaterThanAbs(vec, threshold)` - Find the samples whose absolute values are GreaterThan a certain threshold value and returns the number of samples found.

`hFindGreaterEqual(vec, threshold, vecout)` - Find the samples that are

GreaterEqual a certain threshold value and returns the number of samples found and the positions of the samples in a second vector.

hFindGreaterEqualAbs(vec, threshold, vecout) - Find the samples whose absolute values are GreaterEqual a certain threshold value and returns the number of samples found and the positions of the samples in a second vector.

hCountGreaterEqual(vec, threshold) - Count the samples that are GreaterEqual a certain threshold value and returns the number of samples found.

hCountGreaterEqualAbs(vec, threshold) - Find the samples whose absolute values are GreaterEqual a certain threshold value and returns the number of samples found.

hFindLessThan(vec, threshold, vecout) - Find the samples that are LessThan a certain threshold value and returns the number of samples found and the positions of the samples in a second vector.

hFindLessThanAbs(vec, threshold, vecout) - Find the samples whose absolute values are LessThan a certain threshold value and returns the number of samples found and the positions of the samples in a second vector.

hCountLessThan(vec, threshold) - Count the samples that are LessThan a certain threshold value and returns the number of samples found.

hCountLessThanAbs(vec, threshold) - Find the samples whose absolute values are LessThan a certain threshold value and returns the number of samples found.

hDownsample(vec1, vec2) - Downsample the input vector to a smaller output vector.

hDownsample(vec, downsample_factor) - Downsample the input vector by a certain factor and return a new vector.

hFindLowerBound(vec, value) - Finds the location (i.e., returns integer) in a monotonically increasing vector, where the input search value is just above or equal to the value in the vector.

hFlatWeights(wlen) - Returns vector of weights of length len with constant weights normalized to give a sum of unity. Can be used by hRunningAverageT.

hLinearWeights(wlen) - Returns vector of weights of length wlen with linearly rising and decreasing weights centered at len/2.

hGaussianWeights(wlen) - Returns vector of weights of length wlen with Gaussian distribution centered at len/2 and sigma=len/4 (i.e. the Gaussian extends over 2 sigma in both directions).

hWeights(wlen, wtype) - Create a normalized weight vector.

hRunningAverage(idata, odata, weights) - Calculate the running average of an input vector using a weight vector.

hRunningAverage(idata, odata, wlen, wtype) - Overloaded function to automatically calculate weights.

SECTION: RF (Radio Frequency) Function

hGeometricDelayFarField(antPosition, skyDirection, length) - Calculates the time delay in seconds for a signal received at an antenna position relative to a phase center from a source located in a certain direction in farfield (based on L. Bahren).

hGeometricDelayNearField(antPosition, skyPosition, distance) - Calculates the time delay in seconds for a signal received at an antenna position relative to a phase center from a source located at a certain 3D space coordinate in nearfield (based on L. Bahren).

hGeometricDelays(antPositions, skyPositions, delays, farfield) - Calculates the time delay in seconds for signals received at various antenna positions relative to a phase center from sources located at certain 3D space coordinates in near or far field.

hGeometricPhases(frequencies, antPositions, skyPositions, phases, farfield) - Calculates the phase gradients for signals received at various antenna positions relative to a phase center from sources located at certain 3D space coordinates in near or far field and for different frequencies.

hGeometricWeights(frequencies, antPositions, skyPositions, weights, farfield) - Calculates the phase gradients as complex weights for signals received at various antenna positions relative to a phase center from sources located at certain 3D space coordinates in near or far field and for different frequencies.

hSpectralPower(vec, outvec) - Calculates the power of a complex spectrum and add it to an output vector.

hADC2Voltage(vec, adc2voltage) - Convert the ADC value to a voltage.

hGetHanningFilter(vec, Alpha, Beta, BetaRise, BetaFall) - Create a Hanning filter.

hGetHanningFilter(vec, Alpha, Beta) - Create a Hanning filter.

hGetHanningFilter(vec, Alpha) - Create a Hanning filter.

hGetHanningFilter(vec) - Create a Hanning filter.

hApplyFilter(data, filter) - Apply a predefined filter on a vector.

hApplyHanningFilter(data) - Apply a Hanning filter on a vector.

hFFT(data_in, data_out, nyquistZone) - Apply an FFT on a vector.

hInvFFT(data_in, data_out, nyquistZone) - Apply an Inverse FFT on a vector.

SECTION: I/O Function (DataReader)

hFileSummary(dr) - Print a brief summary of the file contents and
current settings.

hFileOpen(Filename) - Function to open a file based on a filename and
returning a datareader object.

hFileGetParameter(dr, keyword) - Return information from a data file as a
Python object.

hFileSetParameter(dr, keyword, pyob) - Set parameters in a data file with a
Python object as input.

hFileRead(dr, Datatype, vec) - Read data from a Datareader object (pointer in
iptr) into a vector, where the size should be
pre-allocated.

hCalTable(filename, keyword, date, pyob) - Return a list of antenna positions
from the CalTables - this is a test.

SECTION: Coordinate Conversion (VectorConversion.cc)

hCoordinateConvert(source, sourceCoordinate, target, targetCoordinate,
anglesInDegrees) - Converts a 3D spatial vector into
a different Coordinate type (e.g. Spherical to
Cartesian).

hReadFileOld(vec, iptr, Datatype, Antenna, Blocksize, Block, Stride, Shift) -
Read data from a Datareader object (pointer in iptr)
into a vector.