Tour and Travel Agency Operations System

Class Diagram — Detailed Class Reference

User and Access Management

AccountAction

Domain	User and Access Management
Description	Logs each lifecycle action performed on a user account — creation, edit, disable, or reactivation — with the before and after status.

Attributes

Attribute	Type
actionType	AccountActionType
reason	String
performedAt	DateTime
previousStatus	AccountStatus
newStatus	AccountStatus

Methods

Method Signature	Return Type
+ record()	void
+ getActionsForUser(userId: int)	List

Connected Classes

Connected Class	Relationship	Description
User	*— Association*	Associated with User
Administrator	*⟶ Dependency*	Used by Administrator (records)

Administrator

Domain	User and Access Management
Description	System administrator who manages user accounts, assigns and revokes roles, views customer profiles, and monitors the audit log.

Attributes

Attribute	Type
adminLevel	int
canAccessAuditLog	Boolean

Methods

Method Signature	Return Type
+ createUserAccount()	void
+ editUserAccount(userId: int)	void
+ disableUserAccount(userId: int)	void
+ reactivateUserAccount(userId: int)	void
+ viewCustomerProfile(customerId: int)	void
+ assignRole(userId: int)	void
+ revokeRole(userId: int)	void
+ browseAuditLog()	List

Connected Classes

Connected Class	Relationship	Description
Employee	▲ *Generalisation*	Inherits from Employee
RoleAssignment	⟶ *Dependency*	Uses / depends on RoleAssignment (manages)
AccountAction	⟶ *Dependency*	Uses / depends on AccountAction (records)

AttendanceRecord

Domain	User and Access Management
Description	Tracks daily attendance entries for an employee including check-in time, check-out time, and attendance status.

Attributes

Attribute	Type
date	Date
checkIn	Time
checkOut	Time
status	AttendanceStatus
notes	String

Methods

Method Signature	Return Type
+ logEntry()	void
+ checkDuplicate()	Boolean

Connected Classes

Connected Class	Relationship	Description
Employee	— *Association*	Associated with Employee
HRStaff	⟶ *Dependency*	Used by HRStaff (manages)

AuditLog

Domain	User and Access Management
Description	System-wide log of significant actions for traceability and compliance, recording the actor, action type, and timestamp.

Attributes

Attribute	Type
action	String
entityType	String
timestamp	DateTime
ipAddress	String
details	String

Methods

Method Signature	Return Type
+ logAction()	void
+ getLogsByUser()	List
+ filterByDateRange()	List

Connected Classes

Connected Class	Relationship	Description
User	— *Association*	Associated with User

BrowseSession

Domain	User and Access Management
Description	Records a customer's browsing activity including filters applied, packages viewed, and session duration for analytics support.

Attributes

Attribute	Type
startedAt	DateTime
endedAt	DateTime
filtersApplied	String
packagesViewed	int
resultCount	int

Methods

Method Signature	Return Type
+ startSession(customerId: int)	void
+ recordView(packageId: int)	void
+ endSession()	void
+ getSummary()	Map

Connected Classes

Connected Class	Relationship	Description
Customer	— *Association*	Associated with Customer
PackageSearchFilter	— *Association*	Associated with PackageSearchFilter

Customer

Domain	User and Access Management
Description	A person who interacts with the agency to browse packages, make bookings, and manage their travel history.

Attributes

Attribute	Type
firstName	String
lastName	String
phone	String
address	String
dateOfBirth	Date
passportNumber	String
nationality	String
preferredLanguage	String
loyaltyPoints	int
loyaltyStatus	LoyaltyTier

Methods

Method Signature	Return Type
+ register()	void
+ updateProfile()	void
+ viewBookingHistory()	List
+ savePackage(packageId: int)	void
+ submitBookingRequest()	Booking
+ submitCancellationRequest()	void
+ checkEligibility(packageId: int)	Boolean

Connected Classes

Connected Class	Relationship	Description
User	▲ *Generalisation*	Inherits from User
TravelerProfile	— *Association*	Associated with TravelerProfile
Booking	— *Association*	Associated with Booking
SavedPackage	— *Association*	Associated with SavedPackage
LoyaltyProgram	— *Association*	Associated with LoyaltyProgram

ReferralProgram	— *Association*	Associated with ReferralProgram
CustomizationRequest	— *Association*	Associated with CustomizationRequest
Inquiry	— *Association*	Associated with Inquiry
BrowseSession	— *Association*	Associated with BrowseSession
PackageSearchFilter	— *Association*	Associated with PackageSearchFilter
SupportedLanguage	— *Association*	Associated with SupportedLanguage

Employee

Domain	User and Access Management
Description	Abstract supertype for all agency staff. Holds shared employment details such as department, hire date, and salary. Never instantiated directly.

Attributes

Attribute	Type
firstName	String
lastName	String
email	String
phone	String
department	String
hireDate	Date
employmentStatus	EmploymentStatus
salary	Decimal

Methods

Method Signature	Return Type
+ login()	void
+ logout()	void
+ updateContactInfo()	void
+ getAssignedTasks()	List

Connected Classes

Connected Class	Relationship	Description
User	▲ *Generalisation*	Inherits from User
TravelAgent	▲ *Generalisation*	Supertype / generalised by TravelAgent
Staff	▲ *Generalisation*	Supertype / generalised by Staff
Administrator	▲ *Generalisation*	Supertype / generalised by Administrator
HRStaff	▲ *Generalisation*	Supertype / generalised by HRStaff
FinanceStaff	▲ *Generalisation*	Supertype / generalised by FinanceStaff
ManagerOwner	▲ *Generalisation*	Supertype / generalised by ManagerOwner
Guide	▲ *Generalisation*	Supertype / generalised by Guide
AttendanceRecord	— *Association*	Associated with AttendanceRecord
LeaveRequest	— *Association*	Associated with LeaveRequest

FinanceStaff

Domain	User and Access Management
Description	Finance team member who records payments, generates and reissues receipts, tracks refunds, reconciles records, and produces financial reports.

Attributes

Attribute	Type
financeCode	String
canApproveRefunds	Boolean
canExportReports	Boolean

Methods

Method Signature	Return Type
+ recordIncomingPayment()	void
+ recordOutgoingPayment()	void
+ updatePaymentStatus(paymentId: int)	void
+ generateReceipt(bookingId: int)	Receipt
+ reissueReceipt(receiptId: int)	Receipt
+ reconcilePayments()	void
+ trackRefund(refundId: int)	void
+ generateFinancialReport()	Report

Connected Classes

Connected Class	Relationship	Description
Employee	▲ *Generalisation*	Inherits from Employee
PaymentRecord	⟶ *Dependency*	Uses / depends on PaymentRecord (records)
FinancialReport	⟶ *Dependency*	Uses / depends on FinancialReport (generates)
ReconciliationRecord	⟶ *Dependency*	Uses / depends on ReconciliationRecord (performs)

Guide

Domain	User and Access Management
Description	A tour guide or trip coordinator who can be assigned to specific scheduled departures. Tracks availability, languages, and specialisations.

Attributes

Attribute	Type
firstName	String
lastName	String
phone	String
email	String
languages	String
specialization	String
isAvailable	Boolean
rating	Decimal

Methods

Method Signature	Return Type
+ assignToTrip(scheduleId: int)	void
+ checkAvailability(date: Date)	Boolean
+ updateProfile()	void

Connected Classes

Connected Class	Relationship	Description
Employee	▲ *Generalisation*	Inherits from Employee

HRStaff

Domain	User and Access Management
Description	HR team member who manages employee records, logs attendance entries, and processes leave requests including approval and rejection.

Attributes

Attribute	Type
hrCode	String
canApproveLeave	Boolean

Methods

Method Signature	Return Type
+ createEmployeeRecord()	void
+ updateEmployeeRecord(empId: int)	void
+ logAttendance(empId: int)	void
+ approveLeaveRequest(requestId: int)	void
+ rejectLeaveRequest(requestId: int)	void
+ notifyEmployee(empId: int)	void

Connected Classes

Connected Class	Relationship	Description
Employee	▲ *Generalisation*	Inherits from Employee
AttendanceRecord	⟶ *Dependency*	Uses / depends on AttendanceRecord (manages)
LeaveRequest	⟶ *Dependency*	Uses / depends on LeaveRequest (approves)

LeaveRequest

Domain	User and Access Management
Description	A formal leave request submitted by an employee, tracking leave type, dates, reason, and the approval or rejection outcome.

Attributes

Attribute	Type
leaveType	LeaveType
startDate	Date
endDate	Date
reason	String
status	LeaveStatus
decidedAt	DateTime
clarificationNote	String

Methods

Method Signature	Return Type
+ submit()	void
+ approve()	void
+ reject()	void
+ requestClarification()	void

Connected Classes

Connected Class	Relationship	Description
Employee	— *Association*	Associated with Employee
HRStaff	⟶ *Dependency*	Used by HRStaff (approves)

ManagerOwner

Domain	User and Access Management
Description	Agency manager or owner who views the operations dashboard, generates and reviews financial reports, and monitors overall business performance.

Attributes

Attribute	Type
managerCode	String
canViewAllReports	Boolean
canAccessDashboard	Boolean

Methods

Method Signature	Return Type
+ viewDashboard()	DashboardSummary
+ generateReport()	Report
+ reviewReport(reportId: int)	void
+ approveReport(reportId: int)	void
+ exportReport(reportId: int)	void
+ filterSalesByPeriod()	void
+ viewActiveBookings()	List
+ reviewPackagePerformance()	void

Connected Classes

Connected Class	Relationship	Description
Employee	▲ *Generalisation*	Inherits from Employee
DashboardSummary	⟶ *Dependency*	Uses / depends on DashboardSummary (views)
FinancialReport	⟶ *Dependency*	Uses / depends on FinancialReport (reviews)

Notification

Domain	User and Access Management
Description	A message sent to a customer or staff member triggered by a system event such as booking confirmation or status change.

Attributes

Attribute	Type
recipientType	String
subject	String
message	String
channel	NotificationChannel
sentAt	DateTime
isRead	Boolean
triggerEvent	String

Methods

Method Signature	Return Type
+ send()	void
+ markAsRead()	void
+ getUnread(recipientId: int)	List

Connected Classes

Connected Class	Relationship	Description
NotificationTemplate	— *Association*	Associated with NotificationTemplate

NotificationTemplate

Domain	User and Access Management
Description	Defines the subject and body template for a specific notification event and channel for consistent automated messaging.

Attributes

Attribute	Type
eventType	String
channel	NotificationChannel
subjectTemplate	String
bodyTemplate	String
isActive	Boolean
createdAt	DateTime

Methods

Method Signature	Return Type
+ render(context: Map)	Notification
+ activate()	void
+ deactivate()	void

Connected Classes

Connected Class	Relationship	Description
Notification	— *Association*	Associated with Notification

Role

Domain	User and Access Management
Description	Defines a named system role with associated permissions. Used by administrators for role-based access control.

Attributes

Attribute	Type
roleName	String
description	String
permissions	String
isActive	Boolean

Methods

Method Signature	Return Type
+ getPermissions()	List
+ hasPermission(perm: String)	Boolean
+ activate()	void
+ deactivate()	void

Connected Classes

Connected Class	Relationship	Description
RoleAssignment	— *Association*	Associated with RoleAssignment

RoleAssignment

Domain	User and Access Management
Description	Records the event of assigning or revoking a role from a user, capturing who acted, when, and the reason given.

Attributes

Attribute	Type
assignedAt	DateTime
revokedAt	DateTime
reason	String
isActive	Boolean

Methods

Method Signature	Return Type
+ assign()	void
+ revoke()	void
+ getHistory(userId: int)	List

Connected Classes

Connected Class	Relationship	Description
User	— *Association*	Associated with User
Role	— *Association*	Associated with Role
Administrator	⟶ *Dependency*	Used by Administrator (manages)

Staff

Domain	User and Access Management
Description	Operational staff who manage travel packages, maintain schedules, assign guides, close trips, and coordinate with business partners.

Attributes

Attribute	Type
staffCode	String
operationalArea	String

Methods

Method Signature	Return Type
+ createPackage()	TravelPackage
+ updatePackage(packageId: int)	void
+ archivePackage(packageId: int)	void
+ publishPackage(packageId: int)	void
+ maintainSchedule()	void
+ assignGuide(tripId: int)	void
+ closeTrip(tripId: int)	void
+ manageBusinessPartner()	void

Connected Classes

Connected Class	Relationship	Description
Employee	▲ *Generalisation*	Inherits from Employee
TravelSchedule	⟶ *Dependency*	Uses / depends on TravelSchedule (maintains)
TripAssignment	⟶ *Dependency*	Uses / depends on TripAssignment (assigns)
TripClosure	⟶ *Dependency*	Uses / depends on TripClosure (closes)

SupportedLanguage

Domain	User and Access Management
Description	Defines the interface languages the system supports with locale codes and active status, used for the language preference feature.

Attributes

Attribute	Type
languageCode	String
languageName	String
isActive	Boolean
isDefault	Boolean

Methods

Method Signature	Return Type
+ activate()	void
+ deactivate()	void
+ getActive()	List

Connected Classes

Connected Class	Relationship	Description
Customer	— *Association*	Associated with Customer

TravelAgent

Domain	User and Access Management
Description	Staff responsible for reviewing and processing bookings, handling cancellations, issuing itineraries, and managing the customer-facing sales workflow.

Attributes

Attribute	Type
agentCode	String
commissionRate	Decimal
totalBookingsHandled	int

Methods

Method Signature	Return Type
+ reviewBooking(bookingId: int)	void
+ approveBooking(bookingId: int)	void
+ rejectBooking(bookingId: int)	void
+ placeOnHold(bookingId: int)	void
+ addBookingNote(bookingId: int)	void
+ processCancellationRequest()	void
+ issueItinerary(bookingId: int)	void
+ reviewCustomizationRequest()	void

Connected Classes

Connected Class	Relationship	Description
Employee	▲ *Generalisation*	Inherits from Employee
SalesRecord	— *Association*	Associated with SalesRecord
Booking	⟶ *Dependency*	Uses / depends on Booking (processes)
CancellationRequest	⟶ *Dependency*	Uses / depends on CancellationRequest (processes)
CustomizationRequest	⟶ *Dependency*	Uses / depends on CustomizationRequest (reviews)
Inquiry	⟶ *Dependency*	Uses / depends on Inquiry (handles)
Quotation	⟶ *Dependency*	Uses / depends on Quotation (prepares)

TravelerProfile

Domain	User and Access Management
Description	A saved traveler record stored on a customer account with passport details and special needs for reuse across multiple bookings.

Attributes

Attribute	Type
firstName	String
lastName	String
dateOfBirth	Date
passportNumber	String
passportExpiry	Date
nationality	String
specialNeeds	String
isDefault	Boolean

Methods

Method Signature	Return Type
+ saveProfile()	void
+ updateProfile()	void
+ applyToBooking(bookingId: int)	void

Connected Classes

Connected Class	Relationship	Description
Customer	— *Association*	Associated with Customer
Traveler	— *Association*	Associated with Traveler

User

Domain	User and Access Management
Description	Abstract supertype for all system users. Holds shared authentication credentials, account status, and role. Never instantiated directly.

Attributes

Attribute	Type
username	String
passwordHash	String
email	String
role	Role
accountStatus	AccountStatus
createdAt	DateTime
lastLoginAt	DateTime

Methods

Method Signature	Return Type
+ login()	void
+ logout()	void
+ resetPassword()	void
+ getRole()	Role

Connected Classes

Connected Class	Relationship	Description
Customer	▲ *Generalisation*	Supertype / generalised by Customer
Employee	▲ *Generalisation*	Supertype / generalised by Employee
AuditLog	— *Association*	Associated with AuditLog
UserSession	— *Association*	Associated with UserSession
RoleAssignment	— *Association*	Associated with RoleAssignment
AccountAction	— *Association*	Associated with AccountAction

UserSession

Domain	User and Access Management
Description	Represents an active authenticated session. Tracks IP address, device info, session expiry, and last activity for security and timeout management.

Attributes

Attribute	Type
role	Role
ipAddress	String
deviceInfo	String
createdAt	DateTime
expiresAt	DateTime
isActive	Boolean
lastActivityAt	DateTime

Methods

Method Signature	Return Type
+ create(userId: int)	void
+ invalidate()	void
+ checkExpiry()	Boolean
+ refresh()	void

Connected Classes

Connected Class	Relationship	Description
User	— *Association*	Associated with User

Pre-Booking

Inquiry

Domain	Pre-Booking
Description	A customer's initial request captured before a formal booking, including destination, travel dates, traveler count, and budget.

Attributes

Attribute	Type
destination	String
travelDateFrom	Date
travelDateTo	Date
travelerCount	int
budget	Decimal
specialRequirements	String
channel	String
status	InquiryStatus
receivedAt	DateTime
resolvedAt	DateTime

Methods

Method Signature	Return Type
+ create()	void
+ assignToAgent(agentId: int)	void
+ convertToQuotation()	Quotation
+ close()	void

Connected Classes

Connected Class	Relationship	Description
Quotation	◆ *Composition*	Composed of Quotation (owns, part cannot exist independently)
Customer	— *Association*	Associated with Customer
Quotation	— *Association*	Associated with Quotation
TravelAgent	⟶ *Dependency*	Used by TravelAgent (handles)

PackageSearchFilter

Domain	Pre-Booking
Description	Stores the filter parameters a customer applied during a package search session — destination, dates, budget, and category.

Attributes

Attribute	Type
destination	String
dateFrom	Date
dateTo	Date
budgetMin	Decimal
budgetMax	Decimal
category	String
appliedAt	DateTime

Methods

Method Signature	Return Type
+ apply()	List
+ save()	void
+ clearFilters()	void

Connected Classes

Connected Class	Relationship	Description
Customer	— *Association*	Associated with Customer
BrowseSession	— *Association*	Associated with BrowseSession

Quotation

Domain	Pre-Booking
Description	A formal price estimate prepared by a travel agent in response to an inquiry, with price breakdown, validity date, and version number.

Attributes

Attribute	Type
quotedPrice	Decimal
priceBreakdown	String
validUntil	Date
version	int
status	QuotationStatus
createdAt	DateTime
notes	String

Methods

Method Signature	Return Type
+ prepare()	void
+ revise()	void
+ accept()	Booking
+ reject()	void
+ expire()	void

Connected Classes

Connected Class	Relationship	Description
Inquiry	◆ *Composition*	Owned by Inquiry (composition part)
Booking	— *Association*	Associated with Booking
Inquiry	— *Association*	Associated with Inquiry
TravelPackage	— *Association*	Associated with TravelPackage
TravelAgent	→ *Dependency*	Used by TravelAgent (prepares)

Travel Package Management

CapacityAdjustment

Domain	Travel Package Management
Description	Logs every change to a schedule's available capacity triggered by confirmations, cancellations, or overrides for consistency auditing.

Attributes

Attribute	Type
previousCapacity	int
newCapacity	int
delta	int
reason	AdjustmentReason
adjustedAt	DateTime

Methods

Method Signature	Return Type
+ record()	void
+ getAdjustmentsForSchedule(scheduleId: int)	List

Connected Classes

Connected Class	Relationship	Description
TravelSchedule	◇ *Aggregation*	Part of TravelSchedule (aggregation)

CustomizationRequest

Domain	Travel Package Management
Description	A customer's request to customise a standard package, reviewed manually by a travel agent for feasibility.

Attributes

Attribute	Type
requestDetails	String
submittedAt	DateTime
status	CustomizationStatus
reviewNotes	String
resolvedAt	DateTime

Methods

Method Signature	Return Type
+ submit()	void
+ approve()	void
+ reject()	void
+ assessFeasibility()	Boolean

Connected Classes

Connected Class	Relationship	Description
Customer	— *Association*	Associated with Customer
TravelPackage	— *Association*	Associated with TravelPackage
TravelAgent	⟶ *Dependency*	Used by TravelAgent (reviews)

DocumentChecklist

Domain	Travel Package Management
Description	Defines the required travel documents for a package — passport, visa, medical certificate, etc. — and whether each is mandatory.

Attributes

Attribute	Type
documentName	String
documentType	String
isMandatory	Boolean
description	String

Methods

Method Signature	Return Type
+ linkToPackage(packageId: int)	void
+ listRequiredDocs()	List
+ validateCompletion()	Boolean

Connected Classes

Connected Class	Relationship	Description
TravelPackage	◆ *Composition*	Owned by TravelPackage (composition part)
TravelerDocumentSubmission	◇ *Aggregation*	Aggregates TravelerDocumentSubmission (whole-part, part can exist independently)

EligibilityCheck

Domain	Travel Package Management
Description	The recorded outcome of validating a customer against a package's eligibility rules, capturing the pass or fail result and reason.

Attributes

Attribute	Type
checkedAt	DateTime
result	Boolean
failReason	String

Methods

Method Signature	Return Type
+ perform()	Boolean
+ getResultsForBooking(bookingId: int)	List

Connected Classes

Connected Class	Relationship	Description
EligibilityRule	◇ *Aggregation*	Part of EligibilityRule (aggregation)
Booking	— *Association*	Associated with Booking

EligibilityRule

Domain	Travel Package Management
Description	Defines a rule restricting package access or visibility based on nationality, age, or required document type.

Attributes

Attribute	Type
ruleType	EligibilityRuleType
requirementDescription	String
destinationCountry	String
requiredDocumentType	String
minimumAge	int
nationalityRestriction	String
isActive	Boolean

Methods

Method Signature	Return Type
+ validateCustomer(customerId: int)	Boolean
+ isPackageVisibleTo(customerId: int)	Boolean
+ getRulesForPackage(packageId: int)	List

Connected Classes

Connected Class	Relationship	Description
TravelPackage	◆ *Composition*	Owned by TravelPackage (composition part)
EligibilityCheck	◇ *Aggregation*	Aggregates EligibilityCheck (whole-part, part can exist independently)

Itinerary

Domain	Travel Package Management
Description	The structured day-by-day plan associated with a travel package, containing overall title, total days, and highlights.

Attributes

Attribute	Type
title	String
totalDays	int
highlights	String
lastUpdatedAt	DateTime

Methods

Method Signature	Return Type
+ create()	void
+ update()	void
+ addDay(day: ItineraryDay)	void
+ getDays()	List

Connected Classes

Connected Class	Relationship	Description
TravelPackage	◆ *Composition*	Owned by TravelPackage (composition part)
ItineraryDay	◆ *Composition*	Composed of ItineraryDay (owns, part cannot exist independently)

ItineraryDay

Domain	Travel Package Management
Description	A single day entry within an itinerary describing the location, activities, meals, and accommodation for that day.

Attributes

Attribute	Type
dayNumber	int
title	String
location	String
description	String
meals	String
accommodation	String
activities	String

Methods

Method Signature	Return Type
+ addActivity(activity: String)	void
+ update()	void

Connected Classes

Connected Class	Relationship	Description
Itinerary	◆ *Composition*	Owned by Itinerary (composition part)

PromoCampaign

Domain	Travel Package Management
Description	A promotional code campaign linked to a package, tracking usage limits, discount type and value, and active dates.

Attributes

Attribute	Type
promoCode	String
discountType	DiscountType
discountValue	Decimal
startDate	Date
endDate	Date
usageLimit	int
usageCount	int
isActive	Boolean

Methods

Method Signature	Return Type
+ validateCode(code: String)	Boolean
+ applyDiscount(price: Decimal)	Decimal
+ incrementUsage()	void
+ deactivate()	void

Connected Classes

Connected Class	Relationship	Description
TravelPackage	◆ *Composition*	Owned by TravelPackage (composition part)
PromoCodeUsage	◇ *Aggregation*	Aggregates PromoCodeUsage (whole-part, part can exist independently)

PromoCodeUsage

Domain	Travel Package Management
Description	Records each instance of a promo code applied by a specific customer on a specific booking for usage enforcement and audit.

Attributes

Attribute	Type
usedAt	DateTime
discountApplied	Decimal

Methods

Method Signature	Return Type
+ record()	void
+ getUsageByCustomer(customerId: int)	List
+ getUsageByCampaign(campaignId: int)	List

Connected Classes

Connected Class	Relationship	Description
PromoCampaign	◇ *Aggregation*	Part of PromoCampaign (aggregation)
Booking	— *Association*	Associated with Booking

SavedPackage

Domain	Travel Package Management
Description	A package saved to a customer's favourites list for later review, with save timestamp and optional notes.

Attributes

Attribute	Type
savedAt	DateTime
notes	String

Methods

Method Signature	Return Type
+ save()	void
+ remove()	void
+ getSavedByCustomer(customerId: int)	List

Connected Classes

Connected Class	Relationship	Description
Customer	— *Association*	Associated with Customer
TravelPackage	— *Association*	Associated with TravelPackage

SeasonalPricing

Domain	Travel Package Management
Description	A time-bounded pricing rule applying an adjusted price or discount percentage to a package for a specific date range.

Attributes

Attribute	Type
label	String
startDate	Date
endDate	Date
adjustedPrice	Decimal
discountPercent	Decimal
isActive	Boolean

Methods

Method Signature	Return Type
+ validateDateRange()	Boolean
+ computeEffectivePrice()	Decimal
+ deactivate()	void

Connected Classes

Connected Class	Relationship	Description
TravelPackage	◆ *Composition*	Owned by TravelPackage (composition part)

TravelPackage

Domain	Travel Package Management
Description	The core catalog entity representing a tour or travel product. Holds destination, duration, pricing, capacity, and eligibility restrictions.

Attributes

Attribute	Type
title	String
destination	String
durationDays	int
basePrice	Decimal
inclusions	String
capacity	int
remainingCapacity	int
category	String
packageStatus	PackageStatus
createdAt	DateTime
publishedAt	DateTime
isVisible	Boolean
eligibilityRestrictions	String

Methods

Method Signature	Return Type
+ create()	void
+ update()	void
+ archive()	void
+ publish()	void
+ checkAvailability()	Boolean
+ updateCapacity(delta: int)	void
+ getActivePrice()	Decimal
+ applyPromoCode(code: String)	Decimal
+ validateEligibility(customerId: int)	Boolean

Connected Classes

Connected Class	Relationship	Description

SeasonalPricing	◆ *Composition*	Composed of SeasonalPricing (owns, part cannot exist independently)
PromoCampaign	◆ *Composition*	Composed of PromoCampaign (owns, part cannot exist independently)
DocumentChecklist	◆ *Composition*	Composed of DocumentChecklist (owns, part cannot exist independently)
EligibilityRule	◆ *Composition*	Composed of EligibilityRule (owns, part cannot exist independently)
CancellationPolicy	◆ *Composition*	Composed of CancellationPolicy (owns, part cannot exist independently)
Itinerary	◆ *Composition*	Composed of Itinerary (owns, part cannot exist independently)
TravelSchedule	◇ *Aggregation*	Aggregates TravelSchedule (whole-part, part can exist independently)
PackagePartnerLink	◇ *Aggregation*	Aggregates PackagePartnerLink (whole-part, part can exist independently)
CustomizationRequest	— *Association*	Associated with CustomizationRequest
Booking	— *Association*	Associated with Booking
SavedPackage	— *Association*	Associated with SavedPackage
Quotation	— *Association*	Associated with Quotation

TravelerDocumentSubmission

Domain	Travel Package Management
Description	Tracks whether a specific traveler on a booking has submitted each required document, recording verification status.

Attributes

Attribute	Type
submittedAt	DateTime
verifiedAt	DateTime
status	SubmissionStatus
rejectionReason	String

Methods

Method Signature	Return Type
+ submit()	void
+ verify()	void
+ reject()	void
+ isComplete(bookingId: int)	Boolean

Connected Classes

Connected Class	Relationship	Description
DocumentChecklist	◇ *Aggregation*	Part of DocumentChecklist (aggregation)

Booking and Reservation

Booking

Domain	Booking and Reservation
Description	The central transactional entity representing a reservation. Links a customer, package, schedule, and agent with all associated records.

Attributes

Attribute	Type
bookingReference	String
submittedAt	DateTime
confirmedAt	DateTime
status	BookingStatus
totalTravelers	int
totalPrice	Decimal
promoCodeApplied	String
specialRequests	String
paymentStatus	PaymentStatus
itineraryIssued	Boolean
eligibilityChecked	Boolean

Methods

Method Signature	Return Type
+ submit()	void
+ approve()	void
+ reject()	void
+ placeOnHold()	void
+ confirm()	void
+ cancel()	void
+ generateReference()	String
+ updateCapacityOnConfirm()	void
+ getAuditHistory()	List
+ validateSubmission()	Boolean

Connected Classes		
Connected Class	**Relationship**	**Description**
Traveler	◆ *Composition*	Composed of Traveler (owns, part cannot exist independently)
BookingNote	◆ *Composition*	Composed of BookingNote (owns, part cannot exist independently)
BookingHistory	◆ *Composition*	Composed of BookingHistory (owns, part cannot exist independently)
PaymentRecord	◆ *Composition*	Composed of PaymentRecord (owns, part cannot exist independently)
CancellationRequest	◆ *Composition*	Composed of CancellationRequest (owns, part cannot exist independently)
DigitalItinerary	◆ *Composition*	Composed of DigitalItinerary (owns, part cannot exist independently)
BookingReviewQueue	◆ *Composition*	Composed of BookingReviewQueue (owns, part cannot exist independently)
Customer	— *Association*	Associated with Customer
TravelPackage	— *Association*	Associated with TravelPackage
TravelSchedule	— *Association*	Associated with TravelSchedule
Quotation	— *Association*	Associated with Quotation
LoyaltyProgram	— *Association*	Associated with LoyaltyProgram
ReferralProgram	— *Association*	Associated with ReferralProgram
EligibilityCheck	— *Association*	Associated with EligibilityCheck
SalesRecord	— *Association*	Associated with SalesRecord
PromoCodeUsage	— *Association*	Associated with PromoCodeUsage
TravelAgent	⟶ *Dependency*	Used by TravelAgent (processes)

BookingHistory

Domain	Booking and Reservation
Description	An audit trail entry recording every status change on a booking — what changed, who changed it, and when.

Attributes

Attribute	Type
action	String
previousStatus	String
newStatus	String
changedAt	DateTime
notes	String

Methods

Method Signature	Return Type
+ recordChange()	void
+ getHistoryForBooking(bookingId: int)	List

Connected Classes

Connected Class	Relationship	Description
Booking	◆ *Composition*	Owned by Booking (composition part)

BookingNote

Domain	Booking and Reservation
Description	A note or special request added to a booking by a staff member, capturing the author, timestamp, and note type.

Attributes

Attribute	Type
noteText	String
createdAt	DateTime
noteType	NoteType

Methods

Method Signature	Return Type
+ addNote()	void
+ getNotesForBooking(bookingId: int)	List

Connected Classes

Connected Class	Relationship	Description
Booking	◆ *Composition*	Owned by Booking (composition part)

BookingReviewQueue

Domain	Booking and Reservation
Description	Represents a booking awaiting staff review, tracking assignment to an agent, queue time, and review priority.

Attributes

Attribute	Type
queuedAt	DateTime
reviewedAt	DateTime
priority	int
status	ReviewStatus

Methods

Method Signature	Return Type
+ enqueue(bookingId: int)	void
+ assignToAgent(agentId: int)	void
+ dequeue()	Booking
+ escalate()	void

Connected Classes

Connected Class	Relationship	Description
Booking	◆ *Composition*	Owned by Booking (composition part)

CancellationPolicy

Domain	Booking and Reservation
Description	Defines the rules governing whether a booking can be cancelled and what refund or penalty applies based on days before departure.

Attributes

Attribute	Type
policyName	String
daysBeforeDeparture	int
refundPercentage	Decimal
cancellationAllowed	Boolean
penaltyAmount	Decimal
conditionDescription	String
isDefault	Boolean

Methods

Method Signature	Return Type
+ validate(bookingId: int)	Boolean
+ computeRefund(bookingId: int)	Decimal
+ isWithinAllowedWindow(depDate: Date)	Boolean

Connected Classes

Connected Class	Relationship	Description
TravelPackage	◆ *Composition*	Owned by TravelPackage (composition part)
CancellationRequest	— *Association*	Associated with CancellationRequest

CancellationRequest

Domain	Booking and Reservation
Description	A request to cancel an existing booking, submitted by the customer and processed by a travel agent against the cancellation policy.

Attributes

Attribute	Type
reason	String
submittedAt	DateTime
outcome	CancellationOutcome
refundEligible	Boolean
processedAt	DateTime

Methods

Method Signature	Return Type
+ submit()	void
+ approve()	void
+ reject()	void
+ validateAgainstPolicy()	Boolean
+ releaseCapacity()	void

Connected Classes

Connected Class	Relationship	Description
Booking	◆ *Composition*	Owned by Booking (composition part)
RefundRecord	◆ *Composition*	Composed of RefundRecord (owns, part cannot exist independently)
CancellationPolicy	— *Association*	Associated with CancellationPolicy
TravelAgent	⟶ *Dependency*	Used by TravelAgent (processes)

DigitalItinerary

Domain	Booking and Reservation
Description	The issued travel summary document for a confirmed booking, generated by a travel agent and delivered to the customer.

Attributes

Attribute	Type
generatedAt	DateTime
deliveredAt	DateTime
content	String
deliveryStatus	DeliveryStatus
version	int

Methods

Method Signature	Return Type
+ generate(bookingId: int)	void
+ deliver()	void
+ regenerate()	void

Connected Classes

Connected Class	Relationship	Description
Booking	◆ *Composition*	Owned by Booking (composition part)

DocumentDistribution

Domain	Booking and Reservation
Description	Records the distribution of trip-related documents to internal staff members after a trip is closed, with delivery confirmation.

Attributes

Attribute	Type
documentType	String
sentAt	DateTime
deliveryConfirmed	Boolean
confirmedAt	DateTime

Methods

Method Signature	Return Type
+ distribute()	void
+ confirmDelivery()	void
+ getDistributionsForTrip(closureId: int)	List

Connected Classes

Connected Class	Relationship	Description
TripClosure	◆ *Composition*	Owned by TripClosure (composition part)

EscalationRecord

Domain	Booking and Reservation
Description	Captures an escalation raised during financial reconciliation — who escalated, to whom, the reason, and the resolution outcome.

Attributes

Attribute	Type
reason	String
escalatedAt	DateTime
status	EscalationStatus
resolvedAt	DateTime
resolution	String

Methods

Method Signature	Return Type
+ escalate()	void
+ resolve(resolution: String)	void
+ getOpenEscalations()	List

Connected Classes

Connected Class	Relationship	Description
ReconciliationRecord	◆ *Composition*	Owned by ReconciliationRecord (composition part)

SalesRecord

Domain	Booking and Reservation
Description	Records each confirmed sale event — booking, agent, package, amount, and commission — used for sales analytics.

Attributes

Attribute	Type
saleAmount	Decimal
commissionAmount	Decimal
saleDate	DateTime
channel	String

Methods

Method Signature	Return Type
+ record()	void
+ getTotalByAgent(agentId: int)	Decimal
+ getTotalByPeriod(start: Date, end: Date)	Decimal

Connected Classes

Connected Class	Relationship	Description
Booking	— *Association*	Associated with Booking
TravelAgent	— *Association*	Associated with TravelAgent

Traveler

Domain	Booking and Reservation
Description	An individual traveler linked to a booking, holding passport details, nationality, lead traveler flag, and special needs.

Attributes

Attribute	Type
firstName	String
lastName	String
dateOfBirth	Date
passportNumber	String
nationality	String
isLeadTraveler	Boolean
specialNeeds	String

Methods

Method Signature	Return Type
+ addToBooking(bookingId: int)	void
+ validateEligibility()	Boolean
+ linkProfile(profileId: int)	void

Connected Classes

Connected Class	Relationship	Description
Booking	◆ *Composition*	Owned by Booking (composition part)
TravelerProfile	— *Association*	Associated with TravelerProfile

Scheduling and Operations

TravelSchedule

Domain	Scheduling and Operations
Description	A specific departure date instance of a travel package, tracking available slots, departure location, and status.

Attributes

Attribute	Type
departureDate	Date
returnDate	Date
availableSlots	int
departureLocation	String
status	ScheduleStatus
lastUpdatedAt	DateTime

Methods

Method Signature	Return Type
+ create()	void
+ update()	void
+ remove()	void
+ validateDates()	Boolean
+ checkConflict()	Boolean
+ markDeparted()	void
+ close()	void

Connected Classes

Connected Class	Relationship	Description
TripAssignment	◆ *Composition*	Composed of TripAssignment (owns, part cannot exist independently)
TripClosure	◆ *Composition*	Composed of TripClosure (owns, part cannot exist independently)
TravelPackage	◇ *Aggregation*	Part of TravelPackage (aggregation)
CapacityAdjustment	◇ *Aggregation*	Aggregates CapacityAdjustment (whole-part, part can exist independently)
Booking	— *Association*	Associated with Booking
Staff	⟶ *Dependency*	Used by Staff (maintains)

TripAssignment

Domain	Scheduling and Operations
Description	The assignment of a guide or coordinator to a specific scheduled departure, with role and confirmation status.

Attributes

Attribute	Type
assignedAt	DateTime
role	String
confirmationStatus	ConfirmStatus

Methods

Method Signature	Return Type
+ assign()	void
+ checkConflict()	Boolean
+ confirm()	void
+ notifyGuide()	void

Connected Classes

Connected Class	Relationship	Description
TravelSchedule	◆ *Composition*	Owned by TravelSchedule (composition part)
Staff	⟶ *Dependency*	Used by Staff (assigns)

TripClosure

Domain	Scheduling and Operations
Description	Records the formal closure of a completed trip, including completion notes, document distribution status, and archive timestamp.

Attributes

Attribute	Type
closedAt	DateTime
completionNotes	String
documentsDistributed	Boolean
archivedAt	DateTime

Methods

Method Signature	Return Type
+ markCompleted()	void
+ distributeDocuments()	void
+ archiveOperationalData()	void

Connected Classes

Connected Class	Relationship	Description
TravelSchedule	◆ *Composition*	Owned by TravelSchedule (composition part)
DocumentDistribution	◆ *Composition*	Composed of DocumentDistribution (owns, part cannot exist independently)
Staff	⟶ *Dependency*	Used by Staff (closes)

Partner Management

BusinessPartner

Domain	Partner Management
Description	An external supplier such as a hotel, transport provider, or tour operator, tracked with contact details and partner status.

Attributes

Attribute	Type
companyName	String
partnerType	PartnerType
contactPerson	String
phone	String
email	String
address	String
status	PartnerStatus
notes	String

Methods

Method Signature	Return Type
+ addPartner()	void
+ updatePartner()	void
+ deactivate()	void
+ getLinkedPackages()	List

Connected Classes

Connected Class	Relationship	Description
PackagePartnerLink	◇ *Aggregation*	Aggregates PackagePartnerLink (whole-part, part can exist independently)
PartnerContract	◇ *Aggregation*	Aggregates PartnerContract (whole-part, part can exist independently)
PartnerServiceRate	◇ *Aggregation*	Aggregates PartnerServiceRate (whole-part, part can exist independently)
PartnerContract	— *Association*	Associated with PartnerContract

PackagePartnerLink

Domain	Partner Management
Description	The association between a travel package and one or more business partners, recording the service role each partner plays.

Attributes

Attribute	Type
linkedAt	DateTime
serviceRole	String

Methods

Method Signature	Return Type
+ link()	void
+ unlink()	void
+ validateUniqueness()	Boolean

Connected Classes

Connected Class	Relationship	Description
TravelPackage	◇ *Aggregation*	Part of TravelPackage (aggregation)
BusinessPartner	◇ *Aggregation*	Part of BusinessPartner (aggregation)

PartnerContract

Domain	Partner Management
Description	The formal contract between the agency and a business partner, capturing terms, commission rate, and validity period.

Attributes

Attribute	Type
contractTitle	String
startDate	Date
endDate	Date
terms	String
commissionRate	Decimal
status	ContractStatus
createdAt	DateTime

Methods

Method Signature	Return Type
+ activate()	void
+ terminate()	void
+ renew()	void
+ isActive()	Boolean

Connected Classes

Connected Class	Relationship	Description
BusinessPartner	◇ *Aggregation*	Part of BusinessPartner (aggregation)
BusinessPartner	— *Association*	Associated with BusinessPartner

PartnerServiceRate

Domain	Partner Management
Description	A negotiated rate for a specific service from a partner, with per-unit cost, currency, validity dates, and markup.

Attributes

Attribute	Type
serviceType	String
ratePerUnit	Decimal
currency	String
validFrom	Date
validTo	Date
isNegotiated	Boolean
markup	Decimal

Methods

Method Signature	Return Type
+ getActiveRate(partnerId: int)	PartnerServiceRate
+ applyMarkup()	Decimal
+ deactivate()	void

Connected Classes

Connected Class	Relationship	Description
BusinessPartner	◇ *Aggregation*	Part of BusinessPartner (aggregation)

Financial Management

ExportedReport

Domain	Financial Management
Description	The exported file artifact of a financial report, storing format, file size, download URL, and archive status.

Attributes

Attribute	Type
exportedAt	DateTime
fileFormat	String
fileSize	int
downloadUrl	String
isArchived	Boolean

Methods

Method Signature	Return Type
+ export()	void
+ archive()	void
+ download()	void

Connected Classes

Connected Class	Relationship	Description
FinancialReport	◇ *Aggregation*	Part of FinancialReport (aggregation)

FinancialReport

Domain	Financial Management
Description	A generated summary of revenue, expenses, and net profit for a selected period, supporting review, approval, and export.

Attributes

Attribute	Type
reportType	ReportType
periodStart	Date
periodEnd	Date
totalRevenue	Decimal
totalExpenses	Decimal
netProfit	Decimal
status	ReportStatus
generatedAt	DateTime
exportedAt	DateTime

Methods

Method Signature	Return Type
+ generate()	void
+ review()	void
+ approve()	void
+ export()	void
+ archive()	void

Connected Classes

Connected Class	Relationship	Description
ReportConfiguration	◇ *Aggregation*	Aggregates ReportConfiguration (whole-part, part can exist independently)
ExportedReport	◇ *Aggregation*	Aggregates ExportedReport (whole-part, part can exist independently)
FinanceStaff	⟶ *Dependency*	Used by FinanceStaff (generates)
ManagerOwner	⟶ *Dependency*	Used by ManagerOwner (reviews)

PaymentInstalment

Domain	Financial Management
Description	An individual instalment within a partial payment arrangement, tracking amount, due date, paid date, and sequence number.

Attributes

Attribute	Type
amount	Decimal
dueDate	Date
paidDate	Date
status	InstalmentStatus
sequenceNumber	int

Methods

Method Signature	Return Type
+ record()	void
+ markPaid()	void
+ getRunningBalance(paymentId: int)	Decimal

Connected Classes

Connected Class	Relationship	Description
PaymentRecord	◆ *Composition*	Owned by PaymentRecord (composition part)

PaymentRecord

Domain	Financial Management
Description	A recorded financial transaction linked to a booking, tracking amount, method, status, due date, and transaction reference.

Attributes

Attribute	Type
paymentType	PaymentType
direction	PaymentDirection
amount	Decimal
currency	String
paymentMethod	String
status	PaymentStatus
transactionRef	String
recordedAt	DateTime
dueDate	Date
notes	String

Methods

Method Signature	Return Type
+ record()	void
+ updateStatus(status: PaymentStatus)	void
+ matchToBooking()	void
+ flagForFollowUp()	void

Connected Classes

Connected Class	Relationship	Description
Booking	◆ *Composition*	Owned by Booking (composition part)
Receipt	◆ *Composition*	Composed of Receipt (owns, part cannot exist independently)
PaymentInstalment	◆ *Composition*	Composed of PaymentInstalment (owns, part cannot exist independently)
FinanceStaff	⟶ *Dependency*	Used by FinanceStaff (records)

Receipt

Domain	Financial Management
Description	A receipt generated for a completed customer transaction, with support for automatic generation and manual reissue.

Attributes

Attribute	Type
generatedAt	DateTime
receiptNumber	String
totalAmount	Decimal
isReissued	Boolean
deliveredToCustomer	Boolean

Methods

Method Signature	Return Type
+ generate()	void
+ reissue()	void
+ deliver()	void

Connected Classes

Connected Class	Relationship	Description
PaymentRecord	◆ *Composition*	Owned by PaymentRecord (composition part)

ReconciliationRecord

Domain	Financial Management
Description	The record of a payment reconciliation exercise comparing expected versus recorded totals, with discrepancy and resolution tracking.

Attributes

Attribute	Type
periodStart	Date
periodEnd	Date
totalExpected	Decimal
totalRecorded	Decimal
discrepancyAmount	Decimal
status	ReconStatus
escalatedTo	int
reconciledAt	DateTime

Methods

Method Signature	Return Type
+ reviewRecords()	void
+ detectDiscrepancy()	Boolean
+ correctDiscrepancy()	void
+ escalate()	void
+ logReconciliation()	void

Connected Classes

Connected Class	Relationship	Description
EscalationRecord	◆ *Composition*	Composed of EscalationRecord (owns, part cannot exist independently)
FinanceStaff	⟶ *Dependency*	Used by FinanceStaff (performs)

RefundRecord

Domain	Financial Management
Description	Tracks a refund issued as a result of a cancellation, including amount, reason, processing details, and final status.

Attributes

Attribute	Type
refundAmount	Decimal
adjustmentReason	String
status	RefundStatus
processedAt	DateTime
notes	String

Methods

Method Signature	Return Type
+ initiate()	void
+ process()	void
+ adjustAmount()	void
+ updateStatus()	void

Connected Classes

Connected Class	Relationship	Description
CancellationRequest	◆ *Composition*	Owned by CancellationRequest (composition part)

ReportConfiguration

Domain	Financial Management
Description	Defines the parameters and schedule for a recurring or one-off financial report, including period type and filters.

Attributes

Attribute	Type
reportType	ReportType
periodType	PeriodType
filters	String
isRecurring	Boolean
scheduleExpression	String
lastRunAt	DateTime
isActive	Boolean

Methods

Method Signature	Return Type
+ activate()	void
+ deactivate()	void
+ generateReport()	FinancialReport
+ getNextRunTime()	DateTime

Connected Classes

Connected Class	Relationship	Description
FinancialReport	◇ *Aggregation*	Part of FinancialReport (aggregation)

Customer Experience and Loyalty

LoyaltyProgram

Domain	Customer Experience and Loyalty
Description	A customer's loyalty account tracking current points balance, total earned and redeemed, and current tier status.

Attributes

Attribute	Type
currentPoints	int
totalEarned	int
totalRedeemed	int
tier	LoyaltyTier
enrolledAt	Date
lastUpdatedAt	DateTime

Methods

Method Signature	Return Type
+ awardPoints(amount: int)	void
+ redeemPoints(amount: int)	Boolean
+ updateTier()	void
+ getLoyaltyStatus()	LoyaltyTier

Connected Classes

Connected Class	Relationship	Description
LoyaltyTransaction	◆ *Composition*	Composed of LoyaltyTransaction (owns, part cannot exist independently)
LoyaltyReward	◇ *Aggregation*	Aggregates LoyaltyReward (whole-part, part can exist independently)
Customer	— *Association*	Associated with Customer
Booking	— *Association*	Associated with Booking

LoyaltyReward

Domain	Customer Experience and Loyalty
Description	A reward item available for loyalty point redemption, defining point cost, reward type, value, and validity period.

Attributes

Attribute	Type
rewardName	String
description	String
pointCost	int
rewardType	RewardType
value	Decimal
validFrom	Date
validTo	Date
isActive	Boolean

Methods

Method Signature	Return Type
+ activate()	void
+ deactivate()	void
+ canRedeem(currentPoints: int)	Boolean

Connected Classes

Connected Class	Relationship	Description
LoyaltyProgram	◇ *Aggregation*	Part of LoyaltyProgram (aggregation)

LoyaltyTransaction

Domain	Customer Experience and Loyalty
Description	An individual point-earning or redemption event linked to a booking, recording points amount and running balance.

Attributes

Attribute	Type
txType	LoyaltyTxType
points	int
balanceAfter	int
description	String
createdAt	DateTime

Methods

Method Signature	Return Type
+ record()	void
+ getTransactionsByProgram(loyaltyId: int)	List

Connected Classes

Connected Class	Relationship	Description
LoyaltyProgram	◆ *Composition*	Owned by LoyaltyProgram (composition part)

ReferralProgram

Domain	Customer Experience and Loyalty
Description	Tracks a customer referral including referrer, referred customer, referral code, status, expiry, and reward application.

Attributes

Attribute	Type
referralCode	String
status	ReferralStatus
submittedAt	DateTime
confirmedAt	DateTime
expiresAt	DateTime
rewardApplied	Boolean
rewardAmount	Decimal

Methods

Method Signature	Return Type
+ submit()	void
+ confirm()	void
+ expire()	void
+ applyReward()	void

Connected Classes

Connected Class	Relationship	Description
Customer	— *Association*	Associated with Customer
Booking	— *Association*	Associated with Booking

Reporting and Analytics

DashboardSummary

Domain	Reporting and Analytics
Description	An aggregated operations snapshot for a manager covering active sales, booking counts, cancellations, and revenue figures.

Attributes

Attribute	Type
generatedAt	DateTime
totalActiveSales	int
totalActiveBookings	int
totalCancellations	int
packagePerformanceSummary	String
salesByPeriod	String
revenueSnapshot	Decimal

Methods

Method Signature	Return Type
+ generateSummary()	void
+ filterSalesByPeriod(start: Date, end: Date)	void
+ viewActiveBookings()	List
+ viewCancellations()	List
+ reviewPackagePerformance()	void

Connected Classes

Connected Class	Relationship	Description
ManagerOwner	⟶ *Dependency*	Used by ManagerOwner (views)