Swap - format and project guide

FILESYSTEM BUILD GUIDE

Portable Debian package and locally compiled native installer.

WHAT IS IT?

A block-based paging/swap format, not a conventional directory-and-file filesystem.

CONCEPTUAL ON-DISK STRUCTURE

Format-specific structures vary; this is not a sector map.

MEDIA	METADATA	ALLOCATION	PAYLOAD
stage 1	stage 2	stage 3	stage 4

SOURCE AND QUALIFICATION

Filesystem-Swap has an independent Infiltrator-Projects source repository. The Debian package records the source revision and payload checksums. Driver capabilities and media compatibility are described in the source qualification reports.

TARGET INSTALLATION LAYOUT

/System/Filesystems/SWAP.so

/System/Resources/Documentation/

Swap.pdf

The installation page gives the exact packaged file paths.

Engineering source and qualification reports belong in GitHub.

Build and installation

Filesystem-Swap

Release 1.0.4

Installed files

```
/System/Filesystems/SWAP.so

/System/Resources/Documentation/Filesystem-Swap.pdf
```

Debian package

Install the prebuilt files with dpkg -i followed by the Debian filename.

Manual RUN

Run bash followed by the native installer filename.

The installer compiles the shared object and generates this manual locally.

This provider currently packages the shared object and this manual.

A standalone Linux kernel module remains outside this release.

InfiltratorOS installation

The OS installer builds a missing or older shared object.

It verifies the manual independently and repairs it from its matching release.

The package metadata records the source revision and SHA-256 checksums.