

Hazard Analysis  
SFWRENG 4G06 Capstone Design Project

Team #18, InfiniView-AI

Anhao Jiao

Kehao Huang

Qianlin Chen

Qi Shu

Xunzhou Ye

20 October 2023

Table 1: Revision History

<b>Date</b>	<b>Developer(s)</b>	<b>Change</b>
17 October 2023	AJ, KH, QC, QS, XY	Initial draft

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Scope and Purpose of Hazard Analysis</b>	<b>1</b>
<b>3</b>	<b>System Boundaries and Components</b>	<b>1</b>
3.1	System Components . . . . .	1
3.2	Environment Components . . . . .	2
<b>4</b>	<b>Critical Assumptions</b>	<b>2</b>
<b>5</b>	<b>Failure Mode and Effect Analysis</b>	<b>2</b>
<b>6</b>	<b>Safety and Security Requirements</b>	<b>4</b>
6.1	Performance Requirements . . . . .	4
6.1.1	Speed Requirements . . . . .	4
6.1.2	Reliability and Availability Requirements . . . . .	4
6.1.3	Scalability of Extensibility Requirements . . . . .	6
6.1.4	Health and Safety Requirements . . . . .	6
6.2	Security Requirements . . . . .	7
<b>7</b>	<b>Roadmap</b>	<b>7</b>
<b>8</b>	<b>Appendix</b>	<b>8</b>
8.1	Glossary . . . . .	8
8.2	Symbolic Constants . . . . .	8

# 1 Introduction

In alignment with the foundational principles laid out by Nancy Leveson, a "hazard" within the context of our Tai Chi instruction platform can be identified as any inherent property or external condition. It could potentially cause the system to deviate from its intended functionality, particularly when interacting with various environmental factors.

This document is dedicated to a comprehensive hazard analysis of our innovative Tai Chi video conferencing application, identifying the hazards and emphasizing the appropriate actions for the hazards.

## 2 Scope and Purpose of Hazard Analysis

This document describes the scope and purpose of hazard analysis for our WebRTC-based Tai Chi instruction application, focusing on identifying potential hazards within specific system boundaries and components, and prescribing comprehensive mitigation strategies. While acknowledging that users' diverse hardware configurations are beyond our control, the system is designed for broad compatibility, assuming standard web browser functionality on the user's device. Our analysis operates under the critical assumption that all application functionalities, particularly those related to real-time instructional mechanics, are performing as intended, thereby circumventing the need to predict various user inputs. Emphasis is placed on fortifying key components—backend server and UI—against potential failures. Through this analysis, we commit to ensuring an uninterrupted, secure, and user-centric experience, essential for the virtual dissemination and mastery of Tai Chi practices.

## 3 System Boundaries and Components

The system's boundaries are carefully defined to provide a clear understanding of the components that interact with and are integral to our Tai Chi video-conferencing application. These boundaries primarily encompass two categories of components: System Components and Environment Components.

By outlining system boundaries and components, we aim to establish a framework for hazard analysis that emphasizes the interplay between these key components and the broader environmental factors. This holistic approach allows us to identify and address potential hazards effectively while working to maintain the application's integrity and user satisfaction.

### 3.1 System Components

- Client application
- Signaling and media stream routing unit
- Machine learning annotation pipeline

System Components comprise the essential elements that constitute our application. These components are at the core of the system's functionality, facilitating user interactions, data routing, and real-time machine learning-based annotations.

### 3.2 Environment Components

- Personal computing devices
- Media capturing device

Environment Components encompass the external factors that influence the system's operation. These components are external to the system but play a critical role in ensuring a seamless and productive user experience.

## 4 Critical Assumptions

To ensure that the hazard assessment and analysis process remains transparent, accountable, and adaptable to changing circumstances, the following assumptions are made:

1. The user does not intentionally attempt to break the system, such as providing deceptive inputs that aim to trick machine learning models (adversarial attacks).
2. Only legal content is shared on the conferencing platform. The user does not deliberately exploit the system to spread abusive, criminal, pornographic content.
3. The user has no physical disability, meaning that users are presumed to have the physical capability to interact with and operate the system without encountering any limitations related to physical disabilities.
4. Hazard analysis for the media capturing device component only applies to instructors.

## 5 Failure Mode and Effect Analysis

In the Failure Mode and Effect Analysis (FMEA) section, we employ a structured methodology to systematically identify potential failure modes, assess their effects, and prioritize recommended actions to mitigate hazards and enhance the safety and performance of our Tai Chi video conferencing application.

Table 3: FMEA table

Component	Failure Mode	Effects of Failure	Causes of Failure	Recommended Action	SR	Ref
Client Application	Unauthorized access to media capturing devices	Invasion of user privacy	Lack of considerations for user privacy in the design process	<ul style="list-style-type: none"> <li>• Ask for permission to access media capturing devices</li> <li>• Have an indicator when a media capturing device is in use</li> <li>• Revoke access as soon as the capturing device is no longer needed</li> </ul>	<b>SR4</b> , <b>SR5</b>	H1-1
	Unresponsive UI	The user interface is unresponsive to the user interaction	<ul style="list-style-type: none"> <li>• Delayed response from the server</li> <li>• Insufficient client-side resource</li> </ul>	<ul style="list-style-type: none"> <li>• Design the system with redundant processing capacity in mind</li> <li>• Test with workload larger than that in the expected usage scenario</li> </ul>	<b>PR1</b>	H1-2
Signaling and Stream Routing Unit	Signaling server down	New WebRTC connections cannot be established	Server hardware failures	Configure the system to automatically switch to a backup signaling server when the primary server experiences downtime.	<b>PR9</b>	H2-1
	SFU overload	<ul style="list-style-type: none"> <li>• Decreased video and audio quality</li> <li>• Session crashes</li> </ul>	<ul style="list-style-type: none"> <li>• Unexpected spikes in number of participants</li> <li>• Insufficient resource</li> </ul>	<ul style="list-style-type: none"> <li>• Conduct stress tests to determine the system's maximum capacity.</li> <li>• Once reaches the maximum capacity, the system will put new requests for creating or joining sessions on hold.</li> </ul>	<b>PR2</b> , <b>PR6</b>	H2-2

## 6 Safety and Security Requirements

New requirements identifiers are highlighted in bold.

### 6.1 Performance Requirements

#### 6.1.1 Speed Requirements

**PR1** The system shall respond to user interactions (e.g. button clicks, menu selections) within 1 second.

**Rationale** To provide a responsive and smooth user experience.

**Fit Criteria** User interactions result in near-instantaneous system responses under typical conditions.

**Priority** Medium

**PR14** The system shall provide annotations with minimal delay, ensuring real-time alignment with the instructor's live stream.

**Rationale** To ensure the highest quality of instructional annotations that effectively enhance the user experience and learning process. The latency of annotation should not be noticeable.

**Fit Criteria** The generated annotation should have less than MAX\_DELAY latency between the stream image and annotation.

**Priority** High

#### 6.1.2 Reliability and Availability Requirements

**PR2** The signaling server, SFU, and STUN/TURN servers shall operate with high reliability, minimizing service interruptions during live sessions.

**Rationale** To ensure a consistent and uninterrupted learning experience for users.

**Fit Criteria** Real-time communication services are always available.

**Priority** High

**PR7** The system shall be able to resume the previous session when the session is accidentally terminated due to an application crash or internet interruption.

**Rationale** To enhance the overall user experience by minimizing disruptions caused by unforeseen events.

**Fit Criteria** The system shall automatically save snapshots of conference metadata, try reconnecting after the application successfully restarts or internet access resumes.

**Priority** Medium

**PR8** The system shall monitor the user's network quality while the user is using the application.

**Rationale** To ensure the conference quality of other users.

**Fit Criteria** The system shall warn the user if network instability is detected, and put the user on hold if the issue persists.

**Priority** Medium

**PR9** The system shall be running when the primary signaling server is down.

**Rationale** To enhance system resilience and reliability and reduce system downtime.

**Fit Criteria** A redundant signaling server shall be maintained alongside the primary signaling server, and shall be deployed when the primary signaling server is down.

**Priority** Medium

**PR10** The system shall send warnings to users when video/audio capturing devices are disconnected.

**Rationale** The source video stream from the instructor is essential for a demonstrational conference session. If these devices become disconnected without warning, users may not be aware of the issue, leading to confusion and frustration.

**Fit Criteria** The system should send clear and user-friendly warnings or notifications when it detects the disconnection of video or audio capturing devices.

**Priority** Critical

**PR11** The system shall ensure that the quality of the video stream captured meets the minimum resolution requirement.

**Rationale** To ensure the quality of the input data to the ML pipeline.

**Fit Criteria** The system shall perform hardware capability examination in any detected and authorized video capturing device, and notify users of the required resolution rate of MIN\_RES.

**Priority** Critical

**PR12** The system shall generate accurate annotation on top of the user's live stream.

**Rationale** To ensure the highest quality of instructional annotations that effectively enhance the user experience and learning process. The generated annotation should be accurate enough.

**Fit Criteria** The system should generate annotation that meets 4 out of 5 team members' accuracy expectations. The accuracy expectations can be met by team members manually checking the annotation.

**Priority** High

**PR13** The system shall use the media capturing devices the user specified when multiple types of capturing devices are detected.

**Rationale** To ensure the user experience, users should be able to specify the media capturing device they want to use.



**Fit Criteria** When the system detects the presence of multiple media capturing devices of the same type (e.g. cameras, microphones), it shall display a notification to inform the user of this condition. The system will then prompt the user to select which media capturing device to utilize through a device selection form. This form shall allow the user to choose between the available devices of each type that were detected. Upon submission of the form, the chosen media capturing devices will be activated for use within the application.

**Priority** Medium

**PR15** The system shall make sure the view of the subject is within the field of view of the media capturing device.

**Rationale** Having a complete view of the subject's body ensures the quality of data feeding into the system for analyzing human body motions.

**Fit Criteria** The system shall present detailed instructions for the user to properly set up the media capturing device, making sure the body of the subject is fully visible from the perspective of the camera.

**Priority** Critical

### 6.1.3 Scalability of Extensibility Requirements

**PR6** The Selective Forwarding Unit (SFU) shall be scalable to accommodate an increasing number of simultaneous video streams as the user base grows.

**Rationale** To support a growing user community without performance degradation.

**Fit Criteria** The SFU can handle AT least 10 simultaneous video streams during peak usage.

**Priority** Medium

### 6.1.4 Health and Safety Requirements

**HS1** The system shall not cause the computers to overload.

**Rationale** The system should not overload the users' computers.

**Fit Criteria** The hardware running the system is under normal temperature.

**Priority** Medium

**HS2** The system shall not affect users' physical and mental health.

**Rationale** The system must not harm users' health and safety.

**Fit Criteria** Users feel comfortable using the system in various situations.

**Priority** Critical

## 6.2 Security Requirements

**SR4** The system shall access media capturing devices only when user permission is granted.

**Rationale** To protect user privacy

**Fit Criteria** A dialogue shall be displayed to ask for user permission to access media capturing devices.

**Priority** Critical

**SR5** The system shall ensure the user is always aware of any active media capturing device.

**Rationale** To protect user privacy

**Fit Criteria** An indicator shall be presented for each active media capturing device.

**Priority** Critical

**SR6** The system shall not retain access to any media capturing device when they are not needed for video conferencing sessions.

**Rationale** To protect user privacy

**Fit Criteria** The access to any media capturing device is terminated as soon as the session ends or the user exits the session.

**Priority** Critical

## 7 Roadmap

In the hazard analysis documentation for our Tai Chi video conferencing application, we have identified and prioritized a comprehensive set of safety and security requirements together with other non-functional requirements through the process of discovering potential hazards. These requirements are essential for mitigating potential hazards, ensuring the reliability and integrity of our system, and creating a secure and user-centric experience.

Requirements that address fundamental safety and security concerns, such as user privacy, system reliability, and user well-being, are given critical priority. These requirements include [PR10](#), [PR11](#), [PR15](#), [HS2](#), [SR4](#), [SR5](#), and [SR6](#). Requirements related to the seamless operation of our system during both normal and unforeseen events, such as system crashes or network interruptions, are considered high priority. These requirements include [PR14](#), [PR2](#), and [PR12](#). Requirements that focus on system performance, scalability, and the quality of user experience are rated as medium priority. [PR1](#), [PR6](#), [PR7](#), [PR8](#), [PR9](#), [PR13](#), and [HS1](#) fall under this category.

Given the limited time and human resource within the capstone project timeline, all requirements of “critical” priority shall be implemented by the end of the capstone project. Other requirements with lower priorities could be met by future implementations. This roadmap will serve as a guide to ensure that our Tai Chi video conferencing application evolves in a way that aligns with our commitment to safety, security and user satisfaction.

## 8 Appendix

### 8.1 Glossary

**Tai Chi** A classical Chinese martial art system practiced for health promotion and rehabilitation.

**Instructor** A person who teaches a Tai Chi class through an online conference system.

**Practitioner** A person who learns Tai Chi through an online conference system.

### 8.2 Symbolic Constants

Table 4: Symbolic constants in Hazard Analysis

Symbol	Value
MAX_DELAY	500 ms
MIN_RES	720p