Plagiarism - Report

Originality Assessment

23%

Overall Similarity

Date: Mar 22, 2024
Matches: 1707 / 7519 words
Sources: 66

Remarks: Moderate similarity detected, you better improve the document (if needed).

Verify Report:

SMART GLASS CLEANING ROBOT

Vivekanandan P

Department of Mechatronics Engineering, SNS College of Technology, Coimbatore, Tamilnadu

vp.academics@snsct.org

Athik Nagappan V

Department of Mechatronics Engineering, SNS College of Technology, Coimbatore, Tamilnadu

athik2002@gmail.com

Amsaveni C

Department of Mechatronics Engineering, SNS College of Technology, Coimbatore, Tamilnadu

Pommakutty01090410@gmail.com

Nallathambi N

Department of Mechatronics Engineering, SNS College of Technology, Coimbatore, Tamilnadu

karthi15102002@gmail.com

Surendar V

Department of Mechatronics Engineering, SNS College of Technology, Coimbatore, Tamilnadu

surendarvelu2003@gmail.com

ABSTRACT - The Glass Cleaning Robot for High-Rise Buildings represents a pioneering venture into the domain of vertical maintenance, seeking to revolutionize the traditional methods of high-rise window cleaning. As urban landscapes evolve with towering structures and expansive glass facades, the challenges associated with the upkeep of these architectural marvels demand innovative solutions. Our project addresses this demand through the development of an autonomous robot designed specifically for the cost-effective and efficient cleaning of glass surfaces in high-rise buildings. The key objectives encompass enhancing safety by minimizing human exposure to potential hazards associated with high-altitude window cleaning. In conclusion, our project stands at the intersection of

safety, efficiency, and technological innovation, aiming to redefine standards in high-rise building maintenance.

Keywords – Glass Cleaning Robot, High – Rise Buildings, Arduino Mega 2560 microcontroller, 2450 KV BLDC, 300 RPM Johnson motor, and a 1.2 kg/cm torque servo motor, L9110S 4-channel Motor Driver.

INTRODUCTION

In the ever-evolving landscape of urban architecture, where towering structures define skylines and shape cityscapes, the challenge of maintaining the pristine appearance of high-rise building exteriors looms large. Window cleaning in these soaring structures poses a unique set of challenges, from accessibility and safety concerns to the sheer scale of the task. In response to these challenges, we proudly present our groundbreaking project—the 58 "Glass Cleaning Robot for High-Rise Buildings with Wheeled Locomotion. High-rise buildings, with their towering glass facades, symbolize modernity and architectural prowess. However, the upkeep of these architectural marvels often involves daunting tasks, none more precarious than the maintenance of expansive glass surfaces. 24 Traditional methods of window cleaning in such structures are not only labour - intensive but also come with inherent safety risks for human workers navigating vertiginous heights. Our project delves into this critical domain, seeking to redefine the norms 5 of high-rise building maintenance. By introducing 45 an autonomous Glass Cleaning Robot, we aim to address the challenges posed by traditional methods, offering an innovative solution that combines technological prowess, cost-effectiveness, and a commitment to ensuring the safety of workers and the integrity of architectural excellence.

Cost-Effective Glass Cleaning:

 Our foremost objective is to engineer a cost-effective robot designed specifically for the efficient cleaning of 5 glass surfaces in high-rise buildings. By providing an economical alternative, we aim to make building maintenance more accessible and sustainable.

Enhanced Safety Protocols:

 The project places a strong emphasis on human safety. With a vision to minimize risks associated with high-altitude window cleaning, the introduction of a robotic solution is poised to create a safer working environment.

Augmented Cleaning Efficiency:

 Traditional window cleaning methods are not only labour-intensive but are also time-consuming. The Glass Cleaning Robot is conceived to enhance the efficiency of the cleaning process by eliminating the need for human rest intervals, resulting in a continuous and meticulous cleaning regimen.

While fatalities in high-rise window cleaning are statistically rare, the project stems from a deep-rooted commitment to further reducing the exposure of human workers to potential hazards. By harnessing robotic technology, we aim to strike a balance between human safety and the pressing need for an efficient, cost-effective, and streamlined approach to high-rise window maintenance.

Problem statement:

 There are more than 363 high rise buildings in Coimbatore and more than 5600 tall buildings in all over india which comprises of buildings with glass windows.

 Workers or Cleaners struggle to clean the glasses at heights and work with a fear of falling from the height.

 Its dangerous for humans work at such heights which could cause dizziness due to lack of oxygen at heights, falling from such heights could cause deaths, inefficient cleaning due to long cleaning times, etc.

 Humans get tired of cleaning for long time and often they are reluctant to go to such heights.

Existing Methodology:

Manual Cleaning:

 Traditional Squeegees: Window cleaners use handheld squeegees to manually clean glass surfaces. This method is effective but requires skilled labour and time.

 Rope Access: Professional window cleaners use ropes and harnesses to access and clean windows on high-rise buildings.

 Water-Fed Pole Systems: Water-fed pole systems use extendable poles with brushes at the end to scrub and rinse windows. Purified water is usually fed through the pole, and the windows are left to air-dry, minimizing the need for manual drying.

 Cradle Systems: Some high-rise buildings are equipped with cradle systems that allow workers to be suspended from the roof, providing access to windows. These systems are controlled manually.

Fig: Worker Hanging in a cradle

Automated Robotic Systems:

 High-Rise Window Cleaning Robots: Specialized robots designed for cleaning tall buildings are equipped with cleaning tools and are often remotely controlled. They can move vertically and horizontally on the building's facade.

 Magnetic Climbing Robots: These robots use magnetic wheels or suction cups to cling to the window surface as they move. They are controlled by an operator and are suitable for vertical glass surfaces.

 Aerial Platforms: Aerial work platforms, such as cherry pickers or scissor lifts, are used to lift workers to the necessary height for window cleaning. These platforms are controlled by an operator.

 Drones: Unmanned Aerial Vehicles (UAVs) or drones equipped with cleaning mechanisms can be used for cleaning windows on high-rise buildings. However, this method is still in the experimental stage in many places.

 Nano-Coatings: Nano-coatings can be applied to glass surfaces to make them self-cleaning. These coatings use hydrophobic or photocatalytic properties to repel dirt and break down organic matter.

 Pneumatic Platforms: Pneumatic platforms use air pressure to lift the cleaning platform to the required height. They are suitable for both horizontal and vertical surfaces.

 Building-Integrated Cleaning Systems: Some modern buildings incorporate cleaning systems directly into their design. This may involve automated systems that move along tracks built into the structure.

 Ultrasonic Cleaning: Ultrasonic cleaning systems use high-frequency sound waves to remove dirt and debris from glass surfaces. This method is more common in industrial settings.

Proposed Methodology:

 This project aims to provide a low-cost cleaner robot for cleaning glasses in a high rise building so that the workers or cleaners don't have to reach great heights and struggle to clean the glasses in such heights.

The Specifications of the robot include:

 Microcontroller: Arduino Mega 2560 with 16MHz clock speed.

 Motors: 2450 KV BLDC motor for vacuum suction and downforce generation, 300 RPM johnson motor for powering the wheels, and 1.2 kg/cm torque servo motor for controlling wiper movements. All these motors will be controlled by the L9110S 4 channel Motor Driver which takes commands from microcontroller.

 Receiver and Transmitter: 2.4 GHz Wi-Fi module as receiver with smartphone as the transmitter.

 Battery: 12V 10000mAh Lithium-ion to increase the maximum battery life of the robot.

Advantages:

 Small sized cleaner robot with a maximum length of up to 2 feet and breadth of 1.5 feet.

 Controllable using smartphone Wi-Fi technology and with range more than 300 meters (average height of a High rise building) and can be extended using antennas.

 The robot is made using simple and low priced components like Arduino microcontroller, Johnson motors, Servo motors, and lithium ion battery. The costs can extend up to 20000 rupees (250 dollars).

 A built-in water tank is also provided and the robot will be powered by a 12v battery which gives a estimated battery life up to 4 hours.

MODELLING:

Robot Chassis:

The chassis of a glass cleaning robot is the main body of the robot that houses all of its components, including the motor, battery, control system, and cleaning mechanisms. The chassis is typically made of a durable material, such as aluminium or plastic, to protect the internal components and provide a sturdy platform for the robot to move around. It has a rectangular shape with four rounded corners. The chassis is divided into two sections by a central ridge. The front section of the chassis houses the motor and battery, while the rear section houses the control system and cleaning mechanisms.

The chassis also has a number of openings for ventilation, sensors, and other components. The openings are strategically placed to ensure that the robot can operate efficiently and safely.

 The chassis has a relatively low profile, which allows the robot to easily access and clean hard-to-reach areas.

 The chassis is well-balanced, which helps to prevent the robot from tipping over.

 The chassis has a smooth surface, which makes it easy to clean and maintain.

 The chassis has a number of mounting points for attaching various components, such as the

cleaning head, sensors, and navigation system.

Fig: Model of the chassis of the robot

Dimensions:

1. Length: 500 mm
2. Breadth: 350mm
3. Height: 100 mm
4. Thickness: 10 mm

Model of Water storage for Robot:

This tank made of plastic. It has a rectangular shape with rounded corners and a lid on top. The lid is made of metal and has a handle for easy opening and closing. The tank has a number of features that make it ideal for water storage, including:

- Durable construction: The tank is made of high-quality plastic that is durable and resistant to cracking and wear.
- UV protection: The tank has UV protection to prevent algae and bacteria growth.
- Airtight seal: The lid of the tank has an airtight seal to prevent water contamination.
- Easy installation: The tank is easy to install and does not require any special tools or expertise.

Fig: Model of Water tank for the Robot

Dimensions:

1. Length: 300 mm
2. Width: 70 mm
3. Height: 35 mm
4. Thickness: 5 mm

SOFTWARES INCORAPATED

Arduino IDE:

The Arduino IDE stands as a pivotal tool in the realm of embedded systems, offering a streamlined environment for programming Arduino microcontrollers. With a user-friendly interface, it facilitates code creation, compilation, and uploading onto Arduino boards seamlessly. Designed for compatibility with Windows, macOS, and Linux, it ensures accessibility across diverse operating systems. Its programming language, a simplified version of C and C++, incorporates beginner-friendly structures like setup() and loop(), making it approachable for those new to coding.

The IDE features a built-in library manager for easy integration of additional functionalities, while the Board Manager simplifies the process of selecting and configuring Arduino boards. The Serial Monitor aids in debugging by enabling communication between the Arduino board and the computer. Furthermore, the IDE supports a vast array of Arduino boards and provides a rich repository of examples for users to explore. As an open-source platform, it encourages community contributions and extensibility, allowing users to customize their development environment. With a commitment to user-friendly design, 48 the Arduino IDE remains a vital resource, fostering innovation and collaboration within the expansive Arduino community.

Beyond its foundational features, 64 the Arduino IDE empowers users with a dynamic and extensible environment. Its open-source nature invites developers to contribute and adapt the IDE to specific project requirements. The inclusion of a library manager facilitates the incorporation of pre-built code

modules, streamlining the development process. The Board Manager not only simplifies the selection of Arduino boards but also ensures seamless integration of necessary drivers. This compatibility extends to a diverse range of Arduino boards and clones, providing flexibility for various hardware projects. The Serial Monitor, a key debugging tool, establishes a communication bridge between the Arduino board and the computer, aiding in real-time data analysis and troubleshooting. For both novices and seasoned developers, the IDE's rich collection of built-in examples serves as an invaluable resource. These examples cover a spectrum of functionalities, enabling users to grasp different aspects of programming and hardware interaction.

1. Installation:

- You can download the Arduino IDE from the official Arduino website (https://www.arduino.cc/en/Main/Software).
- It's available for Windows, macOS, and Linux, making it versatile for various operating systems.

2. User Interface:

- The Arduino IDE has a simple and user-friendly interface.
- It consists of a text editor for writing code, a toolbar for common functions, and a message area that displays compilation and upload status.

3. Programming Language:

- Arduino programming uses a simplified version of C and C++ languages. The code structure includes setup() and loop() functions, making it accessible for beginners.

4. Libraries:

- The IDE includes a library manager, allowing users to easily add and manage libraries that provide additional functionalities.

5. Board Manager:

- The Board Manager in the Arduino IDE allows users to select the type of Arduino board they are using and install the necessary drivers.

6.Serial Monitor:

- The Serial Monitor is a tool within the IDE that helps in debugging by allowing communication between the Arduino board and the computer via serial communication.

7. Upload and Compile:

- Once the code is written, users can compile and upload it to the Arduino board directly from the IDE through a USB connection.

8. Examples:

- The IDE comes with a variety of built-in examples that users can explore to understand different functionalities and components.

9. Open Source:

- Arduino IDE is open source, allowing users to contribute to its development and customize it according to their needs.

10. Extensibility:

- The IDE can be extended with plugins and additional tools, providing flexibility for users with specific requirements.

11. Community Support:

- The Arduino community is active and supportive, making it easy for users to find help, tutorials, and resources online.

12. Compatibility:

- Arduino IDE supports a wide range of Arduino boards and clones, making it a versatile choice for various hardware projects.

SolidWorks 2023:

SolidWorks 2023 is a powerful computer-aided design (CAD) software package that allows engineers and designers to create, design, and simulate 3D models of products, parts, and assemblies. It is a popular choice for a wide range of industries, including automotive, aerospace, electronics, and manufacturing.

SolidWorks 2023 includes a number of new features and enhancements, including:

- Enhanced productivity: New tools and workflows to help you design and engineer faster.
- Improved performance: Significant performance improvements to help you work with large and complex models.
- Enhanced collaboration: New tools to help you collaborate with colleagues and stakeholders.

Key features of SolidWorks 2023 include:

- Part modelling: Create 3D models of parts using a variety of features, including extrudes, revolves, blends, and sweeps.
- Assembly modelling: Create 3D models of assemblies by combining parts together.
- Drawing creation: Create 2D drawings of parts and assemblies.
- Simulation: Simulate the behaviour of parts and assemblies using finite element analysis (FEA) and computational fluid dynamics (CFD).
- Data management: Manage your CAD data using PDM (Product Data Management) software.

Benefits of using SolidWorks 2023 include:

- Improved product quality: Create high-quality products that meet your design and engineering requirements.
- Reduced development time: Design and engineer products faster and more efficiently.
- Reduced costs: Save money by reducing the need for physical prototypes.

 Improved communication: Communicate your design intent effectively with colleagues and stakeholders.

Overall, SolidWorks 2023 is a powerful and versatile CAD software package that can help you create innovative and high-quality products. 1 It is a valuable tool for engineers and designers in a wide range of industries.

Ultimaker Cura:

UltiMaker Cura is a free, open-source 3D printing software that is widely used by hobbyists and professionals alike. It 9 is known for its user-friendly interface and powerful features, making it a popular choice for slicing 3D models into G-code instructions.

Key features of UltiMaker Cura include:

 User-friendly interface: Cura has a drag-and-drop interface 11 that is easy to learn and use.

1 Powerful slicing engine: Cura's slicing engine is one of the most powerful on the market, and it can handle a variety of complex models and materials.

 11 Wide range of settings: Cura has a wide range of settings that can be customized to control the quality of your prints.

 Support for multiple printers: Cura supports a wide range of 3D printers, from desktop printers to professional machines.

Benefits of using Ultima Ker Cura include:

 High-quality prints: Cura's slicing engine can produce high-quality prints with consistent results.

 Easy to use: Cura's user-friendly 10 interface makes it easy to learn and use, even for beginners.

 15 Wide range of features: Cura's wide range of features makes it a versatile tool that can be used for a variety of projects.

 Free and open-source: Cura is free and open-source, so you can use it without any restrictions.

1 Overall, UltiMaker Cura is a powerful and versatile 3D printing software that is well-suited for

both beginners and experienced users. It is a great choice for anyone who wants to create high-quality 3D prints with a user-friendly interface.

Here are some additional points to consider:

- Cura is constantly being updated with new features and improvements.
- There is a large and active Cura community that can provide support and assistance.
- Cura is available for Windows, macOS, and Linux.

TECHNOLOGY STACK

Embedded C:

Embedded C refers to a specific subset of the C programming language that is tailored for embedded systems development. Embedded systems are specialized computing systems dedicated to performing specific functions within a larger system. These systems can be found in a wide range of devices, from household appliances and consumer electronics to industrial machinery and automotive systems.

Key aspects of Embedded C:

1.Resource Constraints:

- Embedded systems often operate with limited resources such as memory, processing power, and storage. Embedded C is designed to be efficient and to work within these constraints, optimizing code size and execution speed.

2. Real-time Operation:

- Many embedded systems require real-time operation, meaning they must respond to external events within a predefined timeframe. Embedded C is often used to write code that meets real-time constraints, ensuring timely and predictable system responses.

3. Low-level Programming:

 Embedded C allows developers to work at a low level, directly accessing and manipulating hardware registers and memory. 4 This level of control is essential for tasks like configuring microcontroller peripherals and interfacing with sensors and actuators.

4. Portability:

 Embedded C code is often written to be highly portable across different hardware platforms. This is achieved by adhering to standard C syntax and e drivers to isolate hardware-specific functionality.

5.Interrupt Handling:

 Embedded systems frequently rely on interrupts to handle external events. Embedded C provides mechanisms for writing 4 interrupt service routines (ISRs) that respond to these interrupts efficiently.

6. Cross-Compilation:

 In many cases, the development and compilation of embedded C code occur on a host machine, with the resulting binary code then transferred to the target embedded system. Cross-compilation tools are commonly used to generate code for the target architecture.

7.Memory Management:

 Efficient memory management is critical in embedded systems. 4 Embedded C allows developers to have precise control over memory allocation and deallocation, minimizing memory usage and avoiding memory leaks.

8.Peripheral Access:

 Embedded systems often involve interfacing with various peripherals like sensors, displays, and communication interfaces. Embedded C provides mechanisms to interact with these peripherals directly, allowing for efficient utilization of hardware features.

9.Toolchains and IDEs:

 Embedded C development typically involves the use of specialized toolchains and Integrated Development Environments (IDEs). These tools are designed to support cross-compilation, debugging, and programming of embedded systems.

10.RTOS (Real-Time Operating Systems):

 Many embedded systems use Real-Time Operating Systems, and Embedded C is often employed to write code that interacts with and takes advantage of RTOS features. This includes tasks scheduling, inter-task communication, and synchronization.

Embedded C programming requires a solid understanding of both C programming fundamentals and the specific characteristics and constraints of the target embedded system. It is a specialized skill set often used by engineers working in fields such as embedded systems development, IoT (Internet of Things), and automotive electronics.

ESPNOW PROTOCOL

ESPNOW, or ESPNOW Protocol, stands for "Espressif Serial Peripheral Network Over Wi-Fi." It is a proprietary communication protocol developed by Espressif Systems, a company known for its contributions to the Internet of Things (IoT) and wireless communication solutions.

Espressif Systems is the manufacturer of the popular ESP8266 and ESP32 series of Wi-Fi and Bluetooth-enabled microcontrollers.

1.Purpose:

 ESPNOW is designed for efficient communication between ESP8266 or ESP32 devices over a Wi-Fi network. It enables peer-to-peer communication without the need for a traditional Wi-Fi access point (AP) infrastructure.

2.Peer-to-Peer Communication:

 ESPNOW is particularly useful 8 for scenarios where multiple ESP devices need to communicate directly with each other in a local network without connecting to a central router or access point. This is beneficial in applications where a standalone network is desired, such as sensor networks or home automation systems.

3.Low Latency:

 ESPNOW 8 is optimized for low-latency communication, making it suitable for applications that require quick and reliable data exchange between devices.

4.Efficiency:

 The protocol is designed to be lightweight and efficient, minimizing the overhead associated with communication. This makes it well-suited for resource-constrained devices like microcontrollers.

5.Security:

 ESPNOW focuses on simplicity and efficiency, and its primary use case is local communication within a trusted network. However, it is important to note that, 41 as of my last knowledge update in January 2022, ESPNOW does not provide encryption by default. If security is a critical requirement, additional measures such as data encryption and authentication may 20 need to be implemented on top of ESPNOW.

6.Espressif SDK Integration:

 To use ESPNOW, developers typically leverage the Espressif 55 IoT Development Framework (ESP-IDF), which is the official development framework for ESP32 and ESP8266. The protocol is integrated into the Espressif SDK to simplify the implementation of peer-to-peer communication between ESP devices.

7.Compatibility:

 ESPNOW is primarily associated with Espressif's 8 ESP8266 and ESP32 microcontrollers. Devices equipped with these chips 65 can communicate with each other using the ESPNOW protocol.

8.Application Areas:

 ESPNOW is commonly used in IoT projects and applications where local communication between ESP devices is essential. Examples include home automation, sensor networks, and projects that involve multiple ESP microcontrollers working together.

Arduino Mega Microcontroller:

The Arduino Mega is a microcontroller board based on the ATmega2560 microcontroller. It is an extended 3 version of the popular Arduino Uno, designed for projects that require more I/O pins, more memory, and more processing power. 1 The Arduino Mega provides a versatile platform for a wide range of applications, from simple projects to more complex and demanding tasks.

Key Features:

 Microcontroller: The heart 3 of the Arduino Mega is the Atmega2560 microcontroller, which is an 8-bit AVR (Advanced Virtual RISC) microcontroller.

 14 Digital I/O Pins: The Arduino Mega has 54 digital I/O pins, allowing for a high degree of connectivity with external devices, sensors, and actuators.

 Analog Inputs: It features 16 analog input pins, enabling the measurement of analog signals such as sensor outputs.

 PWM Outputs: There are 15 PWM (Pulse Width Modulation) outputs, which are useful for controlling devices like motors and LEDs.

 Communication Interfaces: Multiple communication interfaces, including 4 UARTs (Universal Asynchronous Receiver/Transmitter), 56 I2C (Inter-Integrated Circuit), and SPI (Serial Peripheral

Interface), provide versatile connectivity options.

- USB Connection: The board can be connected to a computer or other USB-enabled devices using a USB-B connector for programming and communication.
- 27 Power Supply: The Arduino Mega can be powered via USB or an external power supply. It supports a wide voltage range (7-12V).
- Clock Speed: The microcontroller 3 operates at a clock speed of 16 MHz.
- Flash Memory: It has a generous 256 KB of flash memory for storing the program code.
- SRAM and EEPROM: The Arduino Mega has 8 KB of SRAM (Static Random-Access Memory) and 4 KB of EEPROM (Electrically Erasable Programmable Read-Only Memory).
- Reset Button: A reset button allows for the easy restarting of the microcontroller.

Applications:

- Large Scale Projects: The Arduino Mega is well-suited for projects that require a large number of sensors, actuators, or input/output devices.
- Data Acquisition Systems: With its numerous analog and digital pins, the Arduino Mega is suitable for data acquisition applications.
- Robotics: The board's multiple PWM outputs make it suitable for controlling motors and servos in robotics projects.
- Prototyping: It is often used in prototyping due to its versatility and ample connectivity options.
- 34 3D Printers and CNC Machines: Arduino Mega is commonly used in controlling 3D printers and CNC (Computer Numerical Control) machines.
- Programming: Arduino Mega can be programmed 10 using the Arduino IDE (Integrated Development Environment), making it accessible to beginners and experienced developers alike. The IDE supports a simplified version of the C++ programming language.

3 In summary, the Arduino Mega is a powerful microcontroller board that extends the capabilities of the Arduino platform, providing a versatile solution for a wide range of electronic projects and applications.

Fig: Arduino Mega Microcontroller

Servo Motors:

A servo motor is a type of rotary actuator that allows for precise control of angular position, velocity, and acceleration. It is a closed-loop system, meaning it continuously receives feedback and adjusts its position to achieve and maintain the desired output. Servo motors are commonly used in a variety of applications, including robotics, automation, RC (remote control) vehicles, and industrial machinery, where accurate and controlled movement is essential.

Here are some key characteristics and features of servo motors:

- Construction: A typical servo motor consists of a DC motor, a feedback device (such as a potentiometer or an encoder), control circuitry, and a gearbox. The DC motor is responsible for generating the motion, and the feedback device provides information about the motor's current position.
- Working Principle: Servo motors work based on the feedback they receive. The control circuit compares the actual position (feedback) with the desired position (input), and the motor adjusts its position until the two match. The feedback mechanism allows servo motors to provide accurate and controlled movement.
- Control Signal: Servo motors are typically controlled by sending a control signal in the form of a pulse-width modulation (PWM) signal. The duration of the pulse determines the position of the motor shaft. A pulse of a certain length rotates the shaft to a specific angle.
- Rotation Range: Servo motors are designed for limited rotation, typically around 180 degrees. Some servo motors offer continuous rotation, allowing them to rotate indefinitely.
- Torque: Servo motors come in various sizes and torque ratings. Torque is the force that the motor can exert to rotate an object. Higher torque servos are capable of moving larger loads or

overcoming resistance.

 2 Speed: The speed of a servo motor is determined by its response time to changes in the control signal. Faster response times result in quicker and more precise movements.

Applications:

 Robotics: Servo motors are widely used in robotics for controlling joint movements and end-effector positions.

 RC Vehicles: They are commonly used in remote-controlled vehicles (cars, airplanes, boats) to control steering, throttle, and other functions.

 Industrial Automation: 2 Servo motors are employed in various industrial automation applications, such as conveyor systems and robotic arms.

 Camera Stabilization: They are used in camera gimbals for stabilizing camera movements.

Advantages:

 Precise Control: Servo motors offer accurate and repeatable control over position and movement.

 Compact Design: They are often compact and lightweight, making them suitable for applications with limited space.

 30 Energy Efficiency: Servo motors are energy-efficient, as they only consume power when adjusting their position.

Limitations:

 Limited Rotation: Most servo motors have a limited rotation range, typically around 180 degrees.

 Cost: High-precision 2 servo motors can be more expensive than other types of motors.

Types of Servo Motors:

 Analog Servos: Traditional servo motors with analog control signals.

 Digital Servos: Provide higher 57 precision and faster response times compared to analog servos.

 Continuous Rotation Servos: Modified servo motors that can rotate continuously.

[1] Servo motors play a crucial role in achieving precision and accuracy in various electromechanical systems, making them a popular choice in many applications across different industries.

Fig: Servo motor

2450KV BLDC Motor:

A 2450kV (kilovolt) brushless DC (BLDC) motor refers to an electric motor commonly used in radio-controlled (RC) vehicles, particularly in electric-powered model aircraft, cars, boats, and other similar applications. The "kV" rating indicates the motor's velocity constant, representing the RPM (revolutions per minute) that the motor will turn per volt applied to it when there's no load.

Here are some key features and characteristics of a 2450kV BLDC motor:

1. Type:

 Brushless DC Motor (BLDC): Unlike brushed DC motors, BLDC motors use electronic commutation instead of brushes to control the direction of current flow in the motor windings.

2. kV Rating:

 2450kV: The kV rating indicates the motor's speed constant. [9] In this case, the motor will theoretically rotate at 2450 RPM for every volt applied to it under no load conditions.

3. Application:

 RC Vehicles: 2450kV BLDC motors are [12] commonly used in high-performance RC vehicles, such as cars, airplanes, helicopters, and boats.

4. Power and Torque:

 Power Output: The power output of the motor is determined by the voltage applied and the current drawn. Higher voltage generally results in higher power output.

 Torque: The torque produced by the motor is influenced by the design and construction of the motor, as well as the current flowing through it.

5. ESC (Electronic Speed Controller):

 BLDC motors are typically paired with an ESC, which is responsible for controlling the speed and direction of the motor by varying the timing and intensity of the electrical signals it sends to the motor.

6. Efficiency:

 BLDC motors are known for their high efficiency and reliability. They offer a good power-to-weight ratio and are capable of providing a significant amount of power for their size.

7. Sensor less Operation:

 Many BLDC motors operate sensor lessly, meaning they don't require external sensors to determine the rotor's position. Sensor less control is often used in RC applications for simplicity.

8. Cooling:

 Some high-performance BLDC motors feature built-in cooling mechanisms, such as fins or cooling fans, to dissipate heat generated during operation.

9. Customization:

 Many BLDC motors are available with various winding configurations, allowing users to choose motors that suit their specific performance requirements and voltage preferences.

10. Maintenance:

 BLDC motors are generally considered low maintenance because they lack brushes, which can wear out over time in brushed motors. This contributes to their longer lifespan.

11. Control Systems:

 BLDC motors are commonly used with 2 advanced control systems, such as pulse-width modulation (PWM), to precisely control the speed and direction of the motor.

12. Voltage Range:

 The motor 51 is designed to operate within a specific voltage range, and it’s crucial to stay within these limits to ensure proper performance and prevent damage.

When using a 34 2450kV BLDC motor in an RC vehicle, it’s essential to pair it with an appropriate ESC, battery, and propeller or gearing system to optimize performance and efficiency for the intended application. Additionally, users should adhere to the manufacturer’s guidelines and specifications for 7 safe and effective operation.

Fig: Brushless DC Motor

Johnson Motor:

Type:

 DC Motor: Johnson motors, like many others, can be direct current (DC) motors, which means they are powered by a direct current electrical source.

1 RPM Rating:

 300 RPM: This indicates the motor's speed, specifically the number of revolutions it can make in

one minute when operating under its specified voltage and load conditions.

Voltage Rating:

 DC motors usually operate within a certain voltage range. To achieve the specified 300 RPM, the motor needs to be powered within this voltage range.

Torque:

 The torque produced by the motor is influenced by the design and construction of the motor, as well as the current flowing through it. Torque is the rotational force that the motor can exert.

Application:

 The application of a 300 RPM Johnson motor can vary. Motors with this RPM rating are often used in applications where a moderate rotational speed is required, such as in small robotics projects, hobbyist applications, or certain industrial devices.

Size and Form Factor:

 Johnson motors can come in various sizes and form factors. The physical dimensions and mounting options of the motor may vary based on the specific model.

Construction:

 The construction of Johnson motors involves a rotor and a stator, and they may use brushes and a commutator for electrical connection and commutation in the case of brushed DC motors. Brushless variants exist as well.

Efficiency:

 The efficiency of the motor is a measure of how effectively it converts electrical power into mechanical power. Higher efficiency motors are generally more desirable.

Control Systems:

 DC motors, including Johnson 12 motors, are often used with electronic control systems such as PWM (Pulse-Width Modulation) for speed control and direction.

Applications:

 Johnson motors with a 300 RPM rating could be 8 suitable for applications like small robotic systems, conveyor belts, electric vehicles, or other scenarios where moderate speed and torque are required.

Fig: Johnson Motor

L9110s 4 channel Motor Driver:

The L9110S is a dual-channel H-bridge motor driver integrated circuit (IC) commonly used for driving small DC motors, stepper motors, and other actuators in electronic projects. It 9 is designed to control the direction and speed of motors, making it a versatile component for robotics, automation, and other applications. Here are the key features and details about the L9110S motor driver:

1. H-Bridge Configuration: The L9110S operates on an H-bridge configuration, providing two output channels 5 (A and B) that can independently control the direction of a motor. This allows the motor to 38 move forward or backward, and the speed can be controlled through pulse-width modulation (PWM).

2. Dual Motor Control: L9110S is capable of driving two motors simultaneously, 8 making it suitable for applications where precise control over multiple motors is required.

3. Voltage Range: The typical 3 operating voltage of the L9110S motor driver is in the range of 2.5V

to 12V, making it compatible with a variety of power sources, including batteries.

4. Output Current: The L9110S can provide a maximum output current of around 800mA per channel, allowing it to drive small to medium-sized motors.

5. Built-in Free-Wheeling Diodes: The IC includes built-in freewheeling diodes, which help protect the circuit from voltage spikes that can occur when a motor is turned off.

6. PWM Speed Control: The L9110S supports PWM input for speed control. By adjusting the duty cycle of the PWM signal, you can control the speed of the connected motor.

7. Simple Control Interface: The control interface for the L9110S is straightforward. Each motor channel (A and B) has two input pins: one for controlling the motor direction (IN1 and IN2) and another for PWM speed control (ENA and ENB).

8. Compact Size: The L9110S motor driver is available in a compact dual-inline package (DIP), making it easy to integrate into various electronic projects.

9. Low Standby Current: In standby mode, the L9110S consumes very low current, which is beneficial for applications where power efficiency is essential.

10. Overcurrent Protection: The L9110S includes overcurrent protection to prevent damage to the motor driver in case of excessive current.

11. Applications: Common applications include small robotics projects, motorized toys, fan speed control, and other projects requiring bi-directional control of DC motors.

12. Wiring and Connection: Typically, users connect the motor terminals to the OUTA and OUTB pins for each channel, and the control signals (IN1, IN2, ENA) are connected to the microcontroller or other control circuit.

13. Ease of Integration: Due to its simplicity and ease of use, the L9110S motor driver is often favoured by hobbyists and beginners for basic motor control application.

Fig: L9110S Motor Driver

Drone Controller Set:

A drone controller set typically refers to the combination of a transmitter (remote controller) and a receiver used to operate and control a drone or unmanned aerial vehicle (UAV). The set is an essential component of the drone system, allowing the operator to send commands to the drone for navigation, stabilization, and other functionalities. Here's an overview of the key components and features of a drone controller set:

1. Transmitter (Remote Controller):

- Radio Frequency (RF) Transmitter: The transmitter generates radio frequency signals that carry control commands from the operator to the drone.
- Frequency Bands: Drone controllers often operate in specific frequency bands, such as 2.4 GHz or 5.8 GHz, to ensure reliable communication and minimize interference.
- Channels: Transmitters come with multiple channels, allowing users to control various functions of the drone independently.

2. Antenna:

- The transmitter is equipped with an antenna that broadcasts the control signals to the drone. Some advanced controllers may have adjustable or detachable antennas for improved signal range and performance.

3. Receiver:

- Drone Receiver: The receiver is installed on the drone and receives the control signals transmitted by the remote controller.
- Decoding and Processing: The receiver decodes and processes the signals, converting them into control commands for the drone's flight controller and other systems.

4. Radio Communication Protocol:

 Drone controllers use specific communication protocols, such as Frequency-Hopping Spread Spectrum (FHSS) or Digital Spread Spectrum (DSS), to ensure secure and interference-resistant communication.

5. Control Sticks and Buttons:

 The remote controller features control sticks (joysticks) and buttons that allow the operator to manipulate the drone's movements, such as throttle, pitch, roll, and yaw.

 Additional buttons may control advanced functions like camera tilt, mode switching, or automated features.

6. Display Screen:

 Some drone controllers come with an integrated display screen that provides real-time telemetry data, battery status, and other relevant information about the drone's performance.

7. Telemetry and Feedback:

 Advanced drone controllers may offer telemetry features, providing the operator with real-time feedback on the drone's altitude, speed, GPS location, and battery status.

8. Modes and Flight Settings:

 Controllers often include different flight modes (e.g., manual, stabilized, GPS-assisted) that cater to various skill levels and specific flight scenarios.

9. Batteries:

 The remote controller is powered by batteries, which may be rechargeable or disposable, depending on the model.

10. Ergonomics and Build Quality:

 Controllers are designed with user comfort in mind, featuring ergonomic grips and a layout that

facilitates intuitive and precise control.

 Build quality is crucial for durability, especially for controllers that may be used in outdoor and challenging conditions.

11. Compatibility:

 Drone controllers are designed to be compatible with specific drone models or systems. It's essential to ensure that the controller matches the drone's communication protocol.

12. Range:

 The effective range of the controller, or the maximum distance at which it can reliably control the drone, is an important consideration for users who require extended flight distances.

Fig: Drone Controller Set

12 Volt Rechargeable Lithium Ion Battery:

A 12-volt rechargeable lithium-ion battery with a capacity of 10,400 mAh (milliampere-hours) is a power storage solution commonly used in various electronic devices and applications. Here's an overview of the key features and characteristics of such a battery:

1. Voltage:

 Voltage Rating: 12 volts - This is the nominal voltage, indicating the average voltage during most of the battery's discharge cycle.

2. Capacity:

 Capacity: 10,400 mAh - This represents the amount of charge the battery can store. In practical terms, it indicates how long the battery can power a device at a specific current draw before needing

recharging.

3. Chemistry:

 Lithium-Ion (Li-Ion): Lithium-ion batteries are known for their high energy density, lightweight design, and relatively low self-discharge rate.

4. Rechargeable:

 The battery is rechargeable, meaning it can be charged and discharged multiple times during its lifespan. This is a significant advantage over non-rechargeable batteries.

5. Form Factor:

 The physical size and form factor of the battery may vary. Common form factors include cylindrical cells, prismatic cells, or pouch cells, depending on the intended application.

6. Energy Density:

 Lithium-ion batteries are known for their high energy density, providing a good balance between capacity and weight.

7. Cycle Life:

 Lithium-ion batteries typically have a high cycle life, allowing them to be charged and discharged hundreds to thousands of times before experiencing a significant reduction in capacity.

8. Applications:

 This type of battery is suitable for a wide range of applications, including:

 Portable electronic devices (e.g., LED lights, portable fans, camping equipment).

 Remote-controlled vehicles (e.g., RC cars, boats).

 Backup power for small electronic systems.

 DIY projects and prototyping.

9. Charging:

 Lithium-ion batteries require specific charging protocols to ensure safe and efficient charging. Overcharging or charging with incorrect voltage can lead to safety issues.

Fig: 12V Rechargeable Battery

REFERENCE

1. Design of Trajectory Generator of a Glass Façade Cleaning Robot Kouki Kanbe; Shunsuke Nansai; Hiroshi Itoh IECON 2021 – 47th Annual Conference of the IEEE Industrial Electronics Society Year: 2021 | Conference Paper | Publisher: IEEE

2. Impact of different brush designs in robotic cleaning on the degradation of anti-soiling coatings Sonali Bhaduri; Makrand Farkade; Rohan Bajhal; Sudhanshu Mallick; Narendra Shiradkar; Anil Kottantharayil 2021 IEEE 48th Photovoltaic Specialists Conference (PVSC)

3. A Survey on Techniques and Applications of Window-Cleaning Robots Zhenjing Li; Qingsong Xu; Lap Mou Tam IEEE Access Year: 2021 | Volume: 9 | Journal Article | Publisher: IEEE

4. A Method for Power Planning to Ensure the Complete Operation of Outdoor Window-Cleaning Robots Jingyi Li; Xiaomin Li 2023 4th International Conference on Computer Vision, Image and Deep Learning (CVIDL)Year: 2023 | Conference Paper | Publisher: IEEE

5. Design & Implementation of Vertical Surface Climbing Cleaner Robot Md Eyasin Rahman; Md Rahat Azad; Md Touhidul Islam; Md Jalal Uddin; Jobayer Inbe Azad2021 International Conference on Intelligent Technologies (CONIT)Year: 2021 | Conference Paper | Publisher: IEEE

6. Force Analysis and Verification of Wall-climbing Robot with Rotor-propellers Mingkang Li; Xueshan Gao; Qingfang Zhang; Peng Liang; Yi Wei; Kejie Li2022 IEEE International Conference on Mechatronics and Automation (ICMA)Year: 2022 | Conference Paper | Publisher: IEEE

7. Analysis on Mechanics and Magnetic Adsorption of Wheeled Wall-Climbing and Obstacle-Jumping Robot Zhanpeng Zhang; Xiaochen Huang; Haoxue Liu; Daofang Zhong; Miao Yuan; Yang Qi; Guangda Lu; Lei Sun2021 China Automation Congress (CAC)

8. Deep Reinforcement Learning-Based 3D Exploration with a Wall Climbing Robot Arya Das; Raju Halder; Atul Thakur TENCON 2021 - 2021 IEEE Region 10 Conference (TENCON)Year: 2021 | Conference Paper | Publisher: IEEE

9. Optimization of Distance Between Magnets for Magnetic Wall Climbing Robots Jaise Jose; R. Sugin Elankavi; D. Dinakaran; RM. Kuppan Chetty; M.M. Ramya 2020 3rd International Conference on Intelligent Sustainable Systems (ICISS)Year: 2020 | Conference Paper | Publisher: IEEE

10. Design and Simulation of Special Hexapod Robot with Vertical Climbing Ability Zihan Zhou; Xiaoqing Zhu2020 IEEE 5th Information Technology and Mechatronics Engineering Conference (ITOEC)Year: 2020 | Conference Paper | Publisher: IEEE

11. Research on Motion Algorithm of glass cleaning robot on regular shaped glass XUE HUI LI; ZHENG YANG; LIANGWEI YAO 2020 International Conference on Computer Science and Management Technology (ICCSMT) Year: 2020 | Conference Paper | Publisher: IEEE

12. Development of Cleaning Module for Wall Climbing Drone with Bio-inspired Watering Mechanism Taewan Kim; Byeongho Yu; Christian Tirtawardhana; I Made Aswin Nahrendra; Hyun Myung 2022 22nd International Conference on Control, Automation and Systems (ICCAS) Year: 2022 | Conference Paper | Publisher: IEEE

13. Design of a cross-frame barrier-crossing and wall-climbing cleaning robot Naigong Yu; Wanhu Feng; Fan Zhang; Hejie Yu 2023 35th Chinese Control and Decision Conference (CCDC) Year: 2023 | Conference Paper | Publisher: IEEE

14. Analysis of the Wheel-wall Gap and Its Influence on Magnetic Force for Wheeled Wall-climbing Robot Adsorbed on the Cylindrical Tank Taoyu Han; Ruiming Qian 2020 IEEE 4th Information Technology, Networking, Electronic and Automation Control Conference (ITNEC)Year: 2020 | Conference Paper | Publisher: IEEE.

15. Research on adsorption reliability of large-load wall-climbing robot for pressure steel pipe work D. Jiang; B. Zhu; D. Hu; X. Fu; Y. Zhao CSAA/IET International Conference on Aircraft Utility Systems (AUS 2020) Year: 2020 | Conference Paper | Publisher: IET

16. Design and Research of a Wall Climbing Robot with Ducted Fan for Aircraft Appearance

Inspection Liutong Qin; Zexi Jin; Shaoxuan Suo; Changlong Zhang; Ke Qiao; Jinxin Liu 2022 International Conference on Sensing, Measurement & Data Analytics in the era of Artificial Intelligence (ICSMD) Year: 2022 | Conference Paper | Publisher: IEEE.

17. Design and Simulation of Special Hexapod Robot with Vertical Climbing Ability Zihan Zhou; Xiaoqing Zhu 2020 IEEE 5th Information Technology and Mechatronics Engineering Conference (ITOEC) Year: 2020 | Conference Paper | Publisher: IEEE.

18. Slip Compensation Fuzzy Control of Double Propeller Wheeled Wall-Climbing Robot for Trajectory Tracking Qingfang Zhang; Mingkang Li; Yi Wei; Xueshan Gao 2022 IEEE International Conference on Robotics and Biomimetics (ROBIO) Year: 2022 | Conference Paper | Publisher: IEEE.

19. Aerodynamic Analysis of a Wall-Climbing Robot with Dual-propeller Yi Wei; Qingfang Zhang; Xueshan Gao; Peng Liang; Mingkang Li; Kejie Li 2022 IEEE International Conference on Mechatronics and Automation (ICMA) Year: 2022 | Conference Paper | Publisher: IEEE

20. Motion Analysis and Trajectory Tracking Control of Propeller-Type Climbing Robot Saif K. Mahmood; Sadeq H. Bakhy; Mouwafak A. Tawfik 2020 2nd Annual International Conference on Information and Sciences (AiCIS) Year: 2020 | Conference Paper | Publisher: IEEE

Sources

1	bing.com/videos INTERNET	6%
2	www.solisplc.com/servo-motor INTERNET	2%
3	www.makerguides.com/choosing-the-best-arduino-board/ INTERNET	2%
4	www.geeksforgeeks.org/embedded-c/ INTERNET	1%
5	www.researchgate.net/publication/352934076_Design_of_... INTERNET	1%
6	robots.net/tech/what-is-flight-controller-in-drone/ INTERNET	1%
7	https://ntpropertycare.com/swing-stage-technique-window-cleaning INTERNET	1%
8	https://docs.arduino.cc/tutorials/nano-esp32/esp-now INTERNET	1%
9	https://www.climateofourfuture.org/exploring-the-sustainable-side-of... INTERNET	<1%
10	www.circuito.io/blog/arduino-code/ INTERNET	<1%
11	https://meganano.uno/arduino-libraries INTERNET	<1%
12	https://www.swellrc.com/understanding-rc-electric-motors INTERNET	<1%
13	https://www.elprocus.com/servo-motor INTERNET	<1%
14	https://www.etechnophiles.com/arduino-mega-pinout-pin-diagram... INTERNET	<1%

15	https://layers.app/blog/cura-vs-prusaslicer-which-3d-printer-slicer-is... INTERNET	<1%
16	https://orcid.org/0000-0001-5998-8277 INTERNET	<1%
17	https://www.aconf.org/contribution/details?filename=slide_125291_R... INTERNET	<1%
18	https://www.geeksforgeeks.org/duty-cycle INTERNET	<1%
19	https://www.scienceopen.com/document?vid=7109b3bd-9266-4430-... INTERNET	<1%
20	psi-info.net/about/high-rise-window-cleaning-faq.php INTERNET	<1%
21	https://www.scihorizon.com/article/optimization-of-distance-betwe... INTERNET	<1%
22	https://robots.net/tech/how-is-a-drone-controlled INTERNET	<1%
23	https://www.semanticscholar.org/paper/Analysis-on-Mechanics-and... INTERNET	<1%
24	ieeexplore.ieee.org/document/9509542 INTERNET	<1%
25	https://docs.arduino.cc/software/ide-v2/tutorials/ide-v2-serial-monitor INTERNET	<1%
26	embeddedcomputing.com/technology/software-and-os/o... INTERNET	<1%
27	arduino.stackexchange.com/questions/893/what-happens ... INTERNET	<1%
28	https://blog.arduino.cc/2021/03/01/announcing INTERNET	<1%
29	seacadtech.com/blog/pdm-in-engineering/ INTERNET	<1%

30	https://www.mroelectric.com/blog/demystifying-the-magic-how-servo... INTERNET <1%
31	https://fpvthrills.com/fpv-drone-radio-protocol INTERNET <1%
32	https://ieeexplore.ieee.org/document/10011910 INTERNET <1%
33	www.electricity-magnetism.org/brushless-dc-motors/ INTERNET <1%
34	https://robu.in/product/sunfun-d2207-2450kv-bldc-motor INTERNET <1%
35	https://robots.net/tech/how-does-a-drone-communicate-with-controller INTERNET <1%
36	https://www.researchgate.net/publication/343002300_Design_and... INTERNET <1%
37	https://windowcleaner.com/pages/understanding-waterfedpoles INTERNET <1%
38	www.linkedin.com/learning/iot-foundations-operating-system-applications/use-p... INTERNET <1%
39	batteryspotlight.com/how-to-recharge-rechargeable-batt... INTERNET <1%
40	https://www.researchgate.net/publication/358661133_Deep_Reinforcem... INTERNET <1%
41	https://medium.com/@henryconochie/as-of-my-last-knowledge-upd... INTERNET <1%
42	www.solar-electric.com/learning-center/shaping-power-ev... INTERNET <1%
43	https://www.researchgate.net/publication/353696442_Design... INTERNET <1%
44	https://www.researchgate.net/publication/362866481_Force_Analysis_... INTERNET <1%

45	https://dr.ntu.edu.sg/handle/10356/65794 INTERNET <1%
46	https://valiantceo.com/maximizing-safety-and-productivity-in... INTERNET <1%
47	https://ijaem.net/issue_dcp/Design and dynamic analysis o... INTERNET <1%
48	https://www.arduino.cc/en/software INTERNET <1%
49	www.arduino.cc/reference/en/ INTERNET <1%
50	https://electricaliq.com/servo-motor-working-principle-and-applicat... INTERNET <1%
51	https://www.mes.com.sg/2019/09/19/overvoltage-undervoltage-all ... INTERNET <1%
52	https://electronics.stackexchange.com/questions/62256 INTERNET <1%
53	https://ieeexplore.ieee.org/xpl/conhome/9315857/proceeding INTERNET <1%
54	carstrucksroads.com/what-is-a-chassis INTERNET <1%
55	https://www.espressif.com/en/products/sdks/esp-idf INTERNET <1%
56	https://www.unrepo.com/embedded/communication-protocols-uart-... INTERNET <1%
57	rcfact.com INTERNET <1%
58	https://www.academia.edu/.../Glass_Cleaning_Robot_For_High_R... INTERNET <1%
59	https://timesofindia.indiatimes.com/city/coimbatore/363-high-rise... INTERNET <1%

60	www.medicalnewstoday.com/articles/160900 INTERNET <1%
61	robocraze.com/products/a2212-2450kv-brushless-outrun... INTERNET <1%
62	www.plasto.in/tips-to-prevent-algae-growth-in-your-wate... INTERNET <1%
63	https://www.onshape.com/en/features/drawings INTERNET <1%
64	docs.arduino.cc/software/ide-v2/tutorials/getting-started-ide-v2 INTERNET <1%
65	https://randomnerdtutorials.com/esp-now-esp8266-nodemcu-arduin... INTERNET <1%
66	www.electronicsforu.com/technology-trends/six-most-imp... INTERNET <1%

EXCLUDE CUSTOM MATCHES	OFF
EXCLUDE QUOTES	OFF
EXCLUDE BIBLIOGRAPHY	OFF