

HP LFP Documentation v1.0

Contents

HP DesignJet Z6/Z9+ Power Options Overview..... 3

HP Latex 2700 Printer Series Overview..... 3

HP DesignJet Z6/Z9+ Power Options Overview..... 4

Configuring Sleep Mode Timers on HP DesignJet Z6/Z9+..... 4

Getting Started with HP Latex 2700 Printer Series..... 5

Configuring Sleep Mode Timers on HP DesignJet Z6/Z9+..... 6

HP DesignJet Z6/Z9+ Power Options Overview

The HP DesignJet Z6/Z9+ printers are designed to optimize energy efficiency while maintaining high performance. This overview provides insights into the power options available for these printers, including sleep mode settings and power management features.

Power Management

The printer can be left powered on without wasting energy, which improves response time and overall system reliability. When not in use for a specified period, the printer enters sleep mode to conserve energy. Interaction with the printer's front-panel display or sending a new print job will wake the printer from sleep mode, allowing it to resume printing immediately.

Important: It is recommended to leave the printer powered on or in sleep mode to avoid wasting ink and time, as the printer performs maintenance on the printheads during sleep mode.

Sleep Mode

Sleep mode reduces the printer's power consumption by turning off certain components while maintaining network connectivity. The printer can be awakened from sleep mode by pressing the power button, opening a door, or sending a print job. The sleep mode wait time can be set from **5 to 240 minutes**. The default is **20 minutes**, which includes 5 minutes in dim mode.

Important: Earlier versions of the User Guide incorrectly stated the timer range as 5–60 minutes with a 10-minute default. The correct values per LFCAS-6510 are: range 5–240 minutes, default 20 minutes.

Changing Power Options

To adjust the sleep mode wait time or other power settings, use the printer's front panel:

- Tap the settings icon, then select **System**.
- Navigate to **Power options** and adjust the **Sleep mode wait time** as needed.

These settings can also be modified through the Embedded Web Server under the Settings pane.

HP Latex 2700 Printer Series Overview

Welcome to the HP Latex 2700 Printer Series, designed to deliver high-quality, durable prints on a wide range of flexible materials. This printer series is equipped with advanced features to enhance your printing experience and ensure exceptional output quality.

The HP Latex 2700 Printer Series utilizes water-based HP Latex inks, providing a strong and vibrant color gamut with a thin ink layer that preserves the gloss and feel of the substrate. With a resolution of 1200 dpi and a 12 picoliter drop size, you can achieve high-quality output with rich colors.

- Print on a variety of substrates, including PVC banners, self-adhesive vinyls, papers, wall coverings, PET films, and textiles.
- Durable prints with outdoor display permanence of up to three years un laminated, and up to five years laminated.
- Automatic color calibration with a built-in spectrophotometer ensures accurate and consistent color reproduction.
- Produce indoor-quality prints at speeds up to 69 m²/h (743 ft²/h).
- Water-based ink provides high adhesion and outstanding scratch resistance with the new HP Latex Overcoat fluid.
- Deliver glossy white on transparent and colored substrates with high-opacity white HP Latex Ink that resists yellowing over time.

The HP Latex 2700 Printer Series is engineered to simplify your workflow and reduce reprints through features like automatic maintenance, assisted loading workflows, automatic print-quality corrections, and unattended flexible printing. Increase your uptime with this smart printer.

Important: Ensure you have the appropriate technical training and experience to operate the printer safely, and always adhere to the safety guidelines provided in the documentation.

For more information, including documentation and useful links, visit the HP support and solutions websites. Access training materials and videos to maximize the potential of your HP Latex 2700 Printer Series.

HP DesignJet Z6/Z9+ Power Options Overview

The HP DesignJet Z6/Z9+ printers are designed to optimize energy efficiency while maintaining high performance. This overview provides insights into the power options available for these printers, including sleep mode settings and power management features.

Power Management

The printer can be left powered on without wasting energy, which improves response time and overall system reliability. When not in use for a specified period, the printer enters sleep mode to conserve energy. Interaction with the printer's front-panel display or sending a new print job will wake the printer from sleep mode, allowing it to resume printing immediately.

Important: It is recommended to leave the printer powered on or in sleep mode to avoid wasting ink and time, as the printer performs maintenance on the printheads during sleep mode.

Sleep Mode

Sleep mode reduces the printer's power consumption by turning off certain components while maintaining network connectivity. The printer can be awakened from sleep mode by pressing the power button, opening a door, or sending a print job. The sleep mode wait time can be set from **5 to 240 minutes**. The default is **20 minutes**, which includes 5 minutes in dim mode.

Important: Earlier versions of the User Guide incorrectly stated the timer range as 5–60 minutes with a 10-minute default. The correct values per LFCAS-6510 are: range 5–240 minutes, default 20 minutes.

Changing Power Options

To adjust the sleep mode wait time or other power settings, use the printer's front panel:

- Tap the settings icon, then select **System**.
- Navigate to **Power options** and adjust the **Sleep mode wait time** as needed.

These settings can also be modified through the Embedded Web Server under the Settings pane.

Configuring Sleep Mode Timers on HP DesignJet Z6/Z9+

This task describes how to configure the sleep mode timers on the HP DesignJet Z6/Z9+ printer series to optimize energy efficiency and ensure quick response times.

1. Access the printer's front panel.

The front panel is a touch-sensitive screen located on the front right of the printer.

2. Tap the **System** icon on the front panel.

This will open the system settings menu where various printer options can be configured.

3. Select **Power options** from the menu.

Here you can adjust settings related to the printer's power management.

4. Choose **Sleep mode wait time**.

You can set the sleep mode timer from 5 to 240 minutes. The default time is 20 minutes, which includes 5 minutes in dim mode.

5. Adjust the timer to your preferred setting.

Use the slider or input field to set the desired time before the printer enters sleep mode.

6. Confirm your selection and exit the menu.

The printer will now enter sleep mode after the specified period of inactivity.

Important: It is recommended to leave the printer powered on or in sleep mode to avoid wasting ink and time due to long preparation times after idle periods.



Warning: Ensure that the printer is not set to power off automatically if you require it to remain connected to the network for remote management tasks.

Getting Started with HP Latex 2700 Printer Series

1. Unpack the printer

Carefully remove the printer from its packaging. Ensure all components are present and undamaged.

2. Set up the printer location

Choose a suitable location for your printer that allows for easy access and ventilation. Ensure the area is free from dust and direct sunlight.

3. Connect the power supply

Connect the printer to a power source using the provided power cord. Ensure the power outlet is grounded and meets the printer's electrical requirements.

4. Install the ink cartridges

Open the ink compartment and insert the HP 883 or HP 893 ink cartridges. Ensure each cartridge is securely placed in its corresponding slot.

5. Load the substrate

Load the desired substrate, such as PVC banners or self-adhesive vinyls, onto the printer. Follow the on-screen instructions for proper alignment and tensioning.

6. Perform initial calibration

Run the automatic color calibration using the built-in spectrophotometer to ensure accurate color reproduction.

7. Print a test page

Print a test page to verify the printer's setup and ensure print quality meets expectations. Adjust settings as necessary.

8. Review safety precautions

Read the safety guidelines provided in the user manual to ensure safe operation of the printer. Pay special attention to warning labels and emergency procedures.

Important:

Ensure that all setup steps are completed before starting regular printing operations to avoid damage to the printer or print quality issues.

Configuring Sleep Mode Timers on HP DesignJet Z6/Z9+

This task describes how to configure the sleep mode timers on the HP DesignJet Z6/Z9+ printer series to optimize energy efficiency and ensure quick response times.

1. Access the printer's front panel.

The front panel is a touch-sensitive screen located on the front right of the printer.

2. Tap the **System** icon on the front panel.

This will open the system settings menu where various printer options can be configured.

3. Select **Power options** from the menu.

Here you can adjust settings related to the printer's power management.

4. Choose **Sleep mode wait time**.

You can set the sleep mode timer from 5 to 240 minutes. The default time is 20 minutes, which includes 5 minutes in dim mode.

5. Adjust the timer to your preferred setting.

Use the slider or input field to set the desired time before the printer enters sleep mode.

6. Confirm your selection and exit the menu.

The printer will now enter sleep mode after the specified period of inactivity.

Important: It is recommended to leave the printer powered on or in sleep mode to avoid wasting ink and time due to long preparation times after idle periods.



Warning: Ensure that the printer is not set to power off automatically if you require it to remain connected to the network for remote management tasks.