

# Infosys

---

## Responsible AI Office

### Infosys Responsible AI Toolkit – Privacy tenet

### API usage Instructions

#### Contents

Introduction.....	2
Analyze.....	2
Anonymize.....	3
Encrypt.....	4
Decrypt .....	5
Image Analyze.....	6
Image Anonymize.....	8
Image Mask .....	9
Image Hashify .....	10
Dicom Anonymize .....	11
Code Anonymize .....	12
Code File Anonymize.....	13
Differential Privacy .....	14

# Introduction

AI systems often rely on vast amounts of personal data. To protect individual privacy, techniques like anonymization, masking, hashing, encryption, and differential privacy are employed to obscure or transform data. This ensures that sensitive information remains confidential while still allowing AI solutions provide valuable insights.

Once API swagger page is populated as per instructions given in the github repository Readme file, click on 'try it out' to use required endpoints. Details of endpoints associated with Privacy tenet are outlined below.

## Analyze


**Endpoint** – /rai/v1/privacy/text/analyze

Using this API, we can check if the input text contains any PII entities or not.

### Input :

Replace the input text with the prompt you want to check for PII entities. In exclusion list mention the PII entities which don't need to be blocked. The fields portfolio and account are optional (we can remove these from the Json if these are not needed), and we can create these from the admin portal. The fields user and lotNumber will be allocated at user login if they are using the application.

With all fields -



**POST** /v1/privacy/text/analyze Analyze

**Parameters**

No parameters

**Request body** required

```
{
  "inputText": "John Smith's SSN is 012884567",
  "portfolio": "string",
  "account": "string",
  "exclusionList": "Karan,Infosys",
  "user": "string",
  "lotNumber": "string"
}
```

**Execute**

Without optional fields -

POST

/rai/v1/privacy/text/analyze Analyze

Parameters

No parameters

Request body required

```
{
  "inputText": "John Smith's SSN is 012884567",
  "exclusionList": "Karan,Infosys",
  "user": "string",
  "lotNumber": "string"
}
```

Execute

## Response :

Server response	
Code	Details
200	<div>Response body</div> <pre>{   "PIIEntities": [     {       "type": "PERSON",       "beginOffset": 0,       "endOffset": 12,       "score": 0.85,       "responseText": "John Smith's"     },     {       "type": "NEW_NPI",       "beginOffset": 20,       "endOffset": 28,       "score": 0.9,       "responseText": "01288456"     },     {       "type": "NEW_GROUP_ID",       "beginOffset": 20,       "endOffset": 25,       "score": 0.9,       "responseText": "01288"     },     {       "type": "my",       "beginOffset": 20,       "endOffset": 21, </pre>

## Anonymize

**Endpoint** – /rai/v1/privacy/text/anonymize

Using this API, we can anonymize all PII entities in the input text.

**Input :** Replace the input text with prompt to be checked, give the PII entities to be redacted in the list. Give fakeData as True if you want to mask the PII detected with fake data. The fields portfolio and account are optional (we can remove these from the Json if these are not needed), and we can create these from the admin portal. The fields user and lotNumber will be allocated at user login if they are using the application. We can give redaction type for the type of anonymization we want

and can give PII entities in the list which we want to be redacted. In exclusion list mention the PII values which don't need to be anonymized and identified.

POST

/rai/v1/privacy/text/anonymize

Anonymize

Parameters

No parameters

Request body required

```

{
  "inputText": "John Smith's SSN is 012884567",
  "portfolio": "string",
  "account": "string",
  "exclusionList": "Karan,Infosys",
  "piiEntitiesToBeRedacted": [
    "US_SSN"
  ],
  "redactionType": "replace",
  "user": "string",
  "lotNumber": "string",
  "fakeData": false
}

```

## Response :

Server response

Code	Details
200	<div>Response body</div> <pre> {   "anonymizedText": "&lt;PERSON&gt; SSN is &lt;US_SSN&gt;" } </pre>

## Encrpyt

**Endpoint** – /rai/v1/privacy/text/encrpyt

Using this API, we can encrypt all PII entities in the input text.

### Input :

Replace the input text with prompt to be checked. Give fakeData as True if you want to mask the PII detected with fake data. The fields portfolio and account are optional (we can remove these from the Json if these are not needed), and we can create these from the admin portal. The fields user and lotNumber will be allocated at user login if they are using the application. We can give

redaction type for the type of anonymization we want and can give PII entities in the list which we want to be identified and encrypted.

POST

/rai/v1/privacy/text/encrypt Encrypt

Parameters

No parameters

Request body required

```

{
  "inputText": "John Smith's SSN is 012884567",
  "exclusionList": "Karan,Infosys",
  "piiEntitiesToBeRedacted": [
    "US_SSN"
  ],
  "redactionType": "replace",
  "user": "string",
  "lotNumber": "string",
  "fakeData": false
}

```

Execute

## Response :

Server response

Code	Details
200	<div>Response body</div> <pre> {   "text": "HXFnt7joMcRIhjW+m3r0+jp56N8YiCNhqjKwVYY7Leg= SSN is L/0KS2Ps/9yihA75Hk6pyzyMLiioZWeqxSse1/tFvrv=",   "items": [     {       "start": 52,       "end": 96,       "entity_type": "US_SSN",       "text": "L/0KS2Ps/9yihA75Hk6pyzyMLiioZWeqxSse1/tFvrv=",       "operator": "encrypt"     },     {       "start": 0,       "end": 44,       "entity_type": "PERSON",       "text": "HXFnt7joMcRIhjW+m3r0+jp56N8YiCNhqjKwVYY7Leg=",       "operator": "encrypt"     }   ] } </pre>

## Decrypt

**Endpoint** – /rai/v1/privacy/text/decrypt

Using this API, we can encrypt PII entities of a specific type at given location in the text.

**Input :** Replace the input text with prompt to be checked, give the PII entities to be encrypted in the list.

POST

/rai/v1/privacy/text/decrpyt Decrypt

Parameters

No parameters

Request body required

```

{
  "text": "John Smith's SSN is 012884567",
  "items": [
    {
      "start": 19,
      "end": 28,
      "entity_type": "US_SSN",
      "text": "John Smith's SSN is 012884567",
      "operator": "encrypt"
    }
  ]
}

```

Execute

**Response :**

```

{
  "decryptedText": "John Smith's SSN is <US_SSN>"
}

```

## Image Analyze

**Endpoint** – /rai/v1/privacy/image/analyze

Using this API, we can analyze the uploaded image for any PII entities.

**Input :**

We can select EasyOcr, tesseract or ComputerVision to analyze the image. Upload the image file, if we want the image to be magnified give 'magnification' as 'true' otherwise give 'false'. If we want to fix the rotation of an unknown image file give 'rotationFlag' as 'true' otherwise 'false'. The fields 'portfolio', 'account' and 'exclusion list' are optional. Portfolio and account can be created from

admin portal and in exclusion list we can mention the PII values which we don't want to be analyzed.

POST

/rai/v1/privacy/image/analyze

Image Analyze

Parameters

Name	Description
OCF string (query)	ComputerVision

Request body required

magnification \* required

string

False

rotationFlag \* required

string

True

image \* required

string(\$binary)

Choose File BCEP\_Level9\_result.jpg

portfolio

string

portfolio

☒

Send empty value

account

string

account

☒

Send empty value

exclusionList

string

exclusionList

☒

Send empty value

Execute

## Response :

Server response

Code	Details
200	<div>Response body</div> <pre>{   "PIIEntities": [     {       "type": "my"     },     {       "type": "DATE_TIME"     },     {       "type": "DATE_TIME"     },     {       "type": "DATE_TIME"     },     {       "type": "my"     },     {       "type": "my"     },     {       "type": "my"     },     {       "type": "my"     },     {       "type": "my"     },     {       "type": "my"     }   ] }</pre> <div>Download</div>

# Image Anonymize

## Endpoint – /rai/v1/privacy/image/anonymize

Using this API, we can anonymize the PII entities present in the uploaded image.

### Input :

We can select EasyOcr, tesseract or ComputerVision to analyze the image. Upload the image file, if we want the image to be magnified give 'magnification' as 'true' otherwise give 'false'. If we want to fix the rotation of an unknown image file give 'rotationFlag' as 'true' otherwise 'false'. The fields 'portfolio', 'account' and 'exclusion list' are optional. Portfolio and account can be created from admin portal and in exclusion list we can mention the PII values which we don't want to be anonymized.

POST /rai/v1/privacy/image/anonymize Image Anonymize

Parameters

Name

Description

OCR

string (query)

ComputerVision

Request body

required

multipart/form-data

magnification

string

required

False

rotationFlag

string

required

True

image

string(\$binary)

required

Choose File BCEP\_Level9\_result.jpg

portfolio

string

portfolio

☒ Send empty value

account

string

account

☒ Send empty value

exclusionList

string

exclusionList

☒ Send empty value

Execute

Clear

### Response :



[illegible]

## Image Mask

**Endpoint** – /rai/v1/privacy/image/masking

Using this API, we can mask the uploaded image with the template we uploaded (section of the image).

**Input :**

Upload the image to be masked and the template( part of the image we want to mask)

POST

/rai/v1/privacy/image/masking Image Mask

Parameters

Cancel

Reset

No parameters

Request body required

multipartform-data

media required  
string(\$binary)

Choose File BCEP\_Level9\_result.jpg


template required  
string(\$binary)

Choose File template1.jpg

Execute

Clear

**Response :**



## Image Hashify

**Endpoint** – /rai/v1/privacy/image

Using this API, we can hash out the PII entities detected in the image we uploaded.

### Input :

We can select EasyOcr, tesseract or ComputerVision to analyze the image. Upload the image file, if we want the image to be magnified give 'magnification' as 'true' otherwise give 'false'. If we want to fix the rotation of an unknown image file give 'rotationFlag' as 'true' otherwise 'false'. The fields 'portfolio', 'account' and 'exclusion list' are optional. Portfolio and account can be created from admin portal and in exclusion list we can mention the PII values which we don't want to be hashed in the image.

POST

/rai/v1/privacy/image/hashify

Image Hashify

Parameters

Cancel

Reset

Name	Description
OCR string (query)	<div>Tesseract</div>

Request body

required

multipart/form-data

magnification \* required

string

True

rotationFlag \* required

string

False

image \* required

string(\$binary)

Choose File

BCEP\_Level9\_result.jpg

portfolio

string

portfolio

☒

Send empty value

account

string

account

☒

Send empty value

exclusionList

string

exclusionList

☒

Send empty value

Execute

Clear

**Response :**

[illegible]

## Dicom Anonymize

**Endpoint** – /rai/v1/privacy/dicom/anonymize

Using this API, we can identify and anonymize the PII entities present in dicom images.

**Input :**

Upload the .dcm image file



POST

/rai/v1/privacy/code/anonymize

Code Redaction

Parameters

No parameters

Request body required

```

class PII
{
    public static void main(String args[])
    {
        name="Raj Kumar";
        System.out.println(name);
    }
}

```

Execute

## Response :

Server response	
Code	Details
200	<div>Response body</div> <pre> class PII {     public static void main(String args[])     {         name="&lt;NAME&gt;";         System.out.println(name);     } } </pre>

## Code File Anonymize

### Endpoint – /rai/v1/privacy/codefile/anonymize

Using this API, we can identify and anonymize the PII entities present in the code file that we uploaded as input

### Input :

Upload the code file in which you want to find and anonymize the PII entities.

**POST** /rai/v1/privacy/codefile/anonymize Code Anonymize

Parameters

No parameters

Request body required

code\_file \* required

string(\$binary)

code.java

Execute

## Response :

Server response	
Code	Details
200	<div>Response body</div> <div><a href="#">Download file</a></div> <div>Response headers</div> <div> <pre> access-control-allow-credentials: true access-control-allow-origin: * access-control-expose-headers: Content-Disposition content-disposition: attachment; filename=code_redacted.java content-type: application/octet-stream date: Mon,05 Aug 2024 16:55:36 GMT strict-transport-security: max-age=31536000; includeSubDomains                     </pre> </div>

Downloaded file –

```

class PII
{
public static void main(String args[])
{
name="<NAME>";
System.out.println(name);
}
}
    
```

## Differential Privacy

**Endpoints** – /rai/v1/privacy/DifferentialPrivacy/file

/rai/v1/privacy/DifferentialPrivacy/anonymize

Using the first API, we can upload the file we want to check for differential privacy and using the second API we can add suppression, noise etc. to the file values.

### Input :

Upload the file you want to check for differential privacy (using /rai/v1/privacy/DifferentialPrivacy/file) . Example – Here uploading a .csv file-

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
1	Employee	Gender	Age	Education	Relationship	Hometown	Unit	Decision_skill_possess	Time_of_service	Time_since_promotion	growth_rate	Travel_Rate	Post_Level	Pay_Scale	Compensation_and_Benefits	Work_Life_balance	
2	EID_2271	F	32	5 Single	Springfield	R&D	Conceptual	7	4	30	1	5	4 type2	1			
3	EID_9658	M	65	2 Single	Lebanon	IT	Directive	41	2	72	1	1	1 type2	1			
4	EID_2220	M	52	3 Married	Springfield	Sales	Directive	21	3	25	0	1	8 type3	1			
5	EID_7652	M	50	5 Single	Washington	Marketing	Analytical	11	4	28	1	1	2 type0	4			
6	EID_6516	F	44	3 Married	Franklin	R&D	Conceptual	12	4	47	1	3	2 type2	4			
7	EID_2028	F	22	4 Married	Franklin	IT	Behavioral	3	1	53	0	3	6 type2	1			
8	EID_2101	M	42	3 Married	Washington	Purchasing	Analytical	6	4	35	1	3	4 type2	1			
9	EID_7693	F	41	2 Married	Springfield	Sales	Conceptual	4	4	35	1	4	8 type2	1			
0	EID_1323	M	31	1 Single	Springfield	IT	Analytical	7	3	73	2	3	8 type2	3			

POST

/v1/privacy/DifferentialPrivacy/file

Diff Privacy File

Parameters

No parameters

Request body required

multipart/form-data

dataset required

string(\$binary)

Choose File

emplist 1.csv

Execute

Clear

Response for file upload:

Server response

Code

Details

200

Response body

```

{
  "allHeaders": [
    "Employee_ID",
    "Gender",
    "Age",
    "Education_Level",
    "Relationship_Status",
    "Hometown",
    "Unit",
    "Decision_skill_possess",
    "Time_of_service",
    "Time_since_promotion",
    "growth_rate",
    "Travel_Rate",
    "Post_Level",
    "Pay_Scale",
    "Compensation_and_Benefits",
    "Work_Life_balance"
  ],
  "numericHeader": [
    "Age",
    "Education_Level",
    "Time_of_service",
    "Time_since_promotion",
    "growth_rate",
    "Travel_Rate",
    "Post_Level",
    "Pay_Scale",
    "Compensation_and_Benefits",
    "Work_Life_balance"
  ]
}

```

Set the column names –

1. In suppression give the column names which you want to remove or suppress
2. In noise list give the column names whose values you want to change by adding some noise or unwanted

3. In binary list give the column names which contain binary values(only two types of values like M or F, T or F) and whose values you want to anonymize by swapping the binary values at all rows. Example: If a column consists of M and F values, then replace M with F and F with M at all places.
4. In range list add the columns whose values you want to anonymize by converting them to a range.

Using the second API, it will do these changes on the file uploaded using the first API –

POST

/v1/privacy/DifferentialPrivacy/anonymize

Diff Privacy Anonymize

Parameters

No parameters

Cancel

Reset

Request body

application/x-www-form-urlencoded

suppression

string

Education\_Level

☐

Send empty value

noiselist

string

Age

☐

Send empty value

binarylist

string

Gender

☐

Send empty value

rangeList

string

Time\_of\_service

☐

Send empty value

## Final Response :

Responses

Curl

```
curl -X 'POST' \
'https://rai-toolkit-dev.az.ad.idemo-ppc.com/v1/privacy/DifferentialPrivacy/anonymize' \
-H 'accept: application/json' \
-H 'Content-Type: application/x-www-form-urlencoded' \
-d 'suppression=Education_Level&noiselist=Age&binarylist=Gender&rangeList=Time_of_service'
```

Request URL

https://rai-toolkit-dev.az.ad.idemo-ppc.com/v1/privacy/DifferentialPrivacy/anonymize

Server response

Code

Details

200

Response body

Employee\_ID,Gender,Age,Relationship\_Status,Hometown,Unit,Decision\_skill\_possess,Time\_of\_service,Time\_since\_promotion,growth\_rate,Travel\_Rate,Post\_Level,Pay\_Scale,Compensation\_and\_Benefits,Work\_Life\_balance  
EID\_22713,F,21,Single,Springfield,R&D,Conceptual,0.0-10.0,0,30,1,5,0,type2,1  
EID\_26559,M,40,Single,Lebanon,IT,Directive,40.0-50.0,772,1,1,1,type2,2  
EID\_22283,M,31,Married,Springfield,Sales,Directive,20.0-30.0,1,25,0,1,0,type3,1  
EID\_7652,M,40,Single,Washington,Marketing,Analytical,10.0-20.0,0,25,1,1,2,type0,0  
EID\_6516,F,44,Married,Franklin,R&D,Conceptual,10.0-20.0,0,47,1,3,2,type2,4  
EID\_28283,F,21,Married,Franklin,IT,Behavioral,0.0-10.0,1,53,0,1,0,type2,1  
EID\_21914,F,41,Married,Washington,Purchasing,Analytical,0.0-10.0,0,0,0,0,0,type2,1  
EID\_7693,F,41,Married,Springfield,Sales,Conceptual,0.0-10.0,0,15,1,0,0,type2,1  
EID\_13232,F,31,Single,Springfield,IT,Analytical,0.0-10.0,0,73,2,0,0,type2,1

Download