

Eshary — Project Summary

Eshary — قةل اءرل اءك رءش

Version 0.1.0+1 · package com.rahala.eshary · default locale ar

1. Overview

name: Eshary — قةل اءرل اءك رءش

purpose: Arabic / RTL financial-operations app for outgoing USD transfers and currency-buy purchases. Flutter + Supabase port of the original single-file project_web.html prototype.

primary_language: Arabic (RTL primary), English secondary

default_locale: ar

platforms: Android (com.rahala.eshary) + Flutter Web. Desktop/iOS scaffolds present but not actively targeted.

version: 0.1.0+1

android_label: قةل اءرل اءك رءش

package: com.rahala.eshary

2. Tech Stack

Package	Version	Purpose
Flutter SDK	>=3.24.0	UI framework, Material 3
Dart SDK	>=3.5.0 <4.0.0	Language
flutter_riverpod	^2.5.1	State management — plain providers, no codegen
supabase_flutter	^2.5.6	Postgres + auth + realtime + session persistence
go_router	^14.2.7	Declarative routing with auth-state refresh
intl	^0.19.0	Number / date formatters (ar + en_US)
share_plus	^10.0.2	Native share sheet
pdf	^3.11.1	PDF document builder
printing	^5.13.2	Share / print PDFs
shared_preferences	^2.3.2	Disk cache + onboarding flag
font_awesome_flutter	^10.7.0	Icon set
google_sign_in	^6.2.1	Google ID-token sign-in
audioplayers	^6.1.0	Asset audio playback
flutter_lints	^4.0.0	Lints — dev_dependency
flutter_localizations	sdk	ar + en localization delegates

3. Architecture

- Feature-folder layout under lib/features/{data,domain,presentation}.
- core/ holds env, supabase client provider, GoRouter, theme tokens.
- shared/ holds glass widgets, formatters, share, JsonCache, PDF export, audio feedback, animated liquid background.

- Repositories live in data/, expose async CRUD against Supabase REST + RPC.
- Domain models are plain immutable classes with fromJson factories (no freezed).
- Riverpod providers expose lists / actions; FutureProviders for queries; Provider Function()> for write actions.
- Routing uses GoRouter with refreshListenable bridging supabase auth stream → router redirect.
- RTL enforced globally via MaterialApp.builder Directionality wrap.
- Read-side offline cache: list responses written into SharedPreferences keyed by user-id, served on network failure.
- Atomic write paths use Supabase RPC functions so insert + balance update happen in one Postgres tx.

4. Features

Folder	Purpose
auth	Email/password + Google sign-in (idToken flow on Android, OAuth redirect on Web). ensureProfile() upsert as belt-and-susp
onboarding	3-page intro carousel; onboarding_completed_v1 flag in SharedPreferences.
splash	Animated logo splash; routes to onboarding / home / sign-in based on flag + auth session.
home	Bottom-nav shell with 4 tabs: جورخ / عارش / فيش رأل / تادادعإل. Glass AppBar with dynamic title.
profile	Profile card (avatar + email + plan badge), change-password form, sign-out with confirm dialog.
settings	Hub with 4 rows: عال معل / ةفارصل الكرش / يتاباسح / ي صخش لل فل مل ا.
companies	User accounts ('ت اباسح') with one nested exchange each. Country picker + exchange-company dropdown sourced from p
exchange_companies	CRUD list of reusable exchange-office company names per user.
countries	Per-user country list, surfaced inline as a glass picker dialog inside AddCompanyDialog.
clients	Counterparty CRUD for the currency-buy flow.
transfers	Outgoing USD transfer composer: 3 collapsible glass sections (ل ي و ح تل ة م ي ق / مال تسال ة ه ج / ة ذفن مل ا ة ه ج ل) + sav
currency_buy	USD purchases from clients with auto LYD computation, pending-state and daily-state RPCs, PDF export, archival blocked w
archive	Per-period archive — sold + bought tables, totals, PDF export per section.

5. Screens

Screen	Title (ar)	Route / location
SplashScreen	—	/splash
OnboardingScreen	معال في ش رأل / تال م عمل اء ارش / تال او حل اء اراد	/onboarding
SignInScreen	ك ت دوع ب اء ج رم	/sign-in
SignUpScreen	دي دج با س ح اء ش ن ا	/sign-up
HomeShell	<dynamic per tab>	/
TransfersScreen	ق دي دج ق ل او ح ذي ف ن ت	/ — tab 0 (جورخ)
CurrencyBuyScreen	ق ل م ع اء ارش	/ — tab 1 (ء ارش)
ArchiveScreen	م ا ع ا ل في ش رأل ا	/ — tab 2 (في ش رأل ا)
SettingsScreen	ت ا د ا د ع ا ل ا	/ — tab 3 (ت ا د ا د ع ا ل ا)
ProfileDetailsScreen	ي ص خ ش ل ا ف ل م ل ا	(pushed from Settings)
CompaniesScreen	ي ت ا ب ا س ح	(pushed from Settings)
AccountDetailsScreen	<company.name>	(pushed from CompaniesScreen)
ExchangeCompaniesScreen	ق ف ا ر ص ل ا ت ا ك ر ش	(pushed from Settings)
ClientsScreen	ء ا ل م ع ل ا	(pushed from Settings)

6. Database — Tables

profiles · migration 0001

Column	Type	Notes
id	uuid	PK, FK auth.users(id) ON DELETE CASCADE
created_at	timestampz	DEFAULT now()

RLS: Self-only: id = auth.uid()

companies · migration 0001

Column	Type	Notes
id	uuid	PK DEFAULT gen_random_uuid()
owner_id	uuid	NOT NULL FK profiles(id) CASCADE
name	text	NOT NULL
start_ref	text	NOT NULL — reference seed for transfers
created_at	timestampz	DEFAULT now()

RLS: Self-only: owner_id = auth.uid()

exchanges · migration 0001 + 0008

Column	Type	Notes
id	uuid	PK
company_id	uuid	NOT NULL FK companies(id) CASCADE
name	text	NOT NULL
balance	numeric(14,2)	NOT NULL DEFAULT 0
our_code	text	nullable
country	text	nullable — added in 0008
created_at	timestampz	DEFAULT now()

RLS: Derived via companies.owner_id (no direct owner_id column — single source of truth)

clients · migration 0001

Column	Type	Notes
id	uuid	PK
owner_id	uuid	NOT NULL FK profiles(id) CASCADE
name	text	NOT NULL
company	text	nullable
code	text	nullable
created_at	timestampz	DEFAULT now()

RLS: Self-only: owner_id = auth.uid()

transfers · migration 0001

Column	Type	Notes
id	uuid	PK
owner_id	uuid	NOT NULL FK profiles(id) CASCADE
company_id	uuid	NOT NULL FK companies(id) RESTRICT
exchange_id	uuid	NOT NULL FK exchanges(id) RESTRICT

Column	Type	Notes
beneficiary_name	text	NOT NULL
beneficiary_account_company	text	nullable
beneficiary_code	text	nullable
amount	numeric(14,2)	NOT NULL CHECK (amount > 0)
reference	text	NOT NULL
status	transfer_status	NOT NULL DEFAULT 'daily' (daily archived)
created_at	timestamptz	DEFAULT now()
archived_at	timestamptz	nullable

RLS: Self-only: owner_id = auth.uid()

currency_buys · migration 0001

Column	Type	Notes
id	uuid	PK
owner_id	uuid	NOT NULL FK profiles(id) CASCADE
my_company_id	uuid	NOT NULL FK companies(id) RESTRICT
exchange_id	uuid	NOT NULL FK exchanges(id) RESTRICT
client_id	uuid	FK clients(id) SET NULL
client_from_account	text	nullable
usd_amount	numeric(14,2)	NOT NULL CHECK (>0)
rate	numeric(10,4)	NOT NULL CHECK (>0)
lyd_amount	numeric(14,2)	NOT NULL CHECK (>=0)
status	currency_buy_status	NOT NULL DEFAULT 'daily' (pending daily archived)
created_at	timestamptz	DEFAULT now()
archived_at	timestamptz	nullable

RLS: Self-only: owner_id = auth.uid()

beneficiaries · migration 0007

Column	Type	Notes
id	uuid	PK
owner_id	uuid	NOT NULL FK profiles(id) CASCADE
name	text	NOT NULL
account	text	nullable
code	text	nullable
created_at	timestamptz	DEFAULT now()

RLS: Self-only: owner_id = auth.uid()

exchange_companies · migration 0009

Column	Type	Notes
id	uuid	PK
owner_id	uuid	NOT NULL FK profiles(id) CASCADE
name	text	NOT NULL

Column	Type	Notes
created_at	timestampz	DEFAULT now()

RLS: Self-only: ec_*_own — owner_id = auth.uid()

countries • migration 0010

Column	Type	Notes
id	uuid	PK
owner_id	uuid	NOT NULL FK profiles(id) CASCADE
name	text	NOT NULL
created_at	timestampz	DEFAULT now()

RLS: Self-only: countries_*_own — owner_id = auth.uid()

Database — RPC functions

Function	Migration	Behavior
archive_daily_transfers(p_owner)	0003	Flips owner's daily transfers to archived, stamps archived_at. Returns row count.
archive_daily_buys(p_owner)	0003	Flips owner's daily buys to archived. Refuses if any pending rows exist (raises check_violation).
next_reference(p_company_id)	0003 + 0006	Returns next transfer reference. 0006 reformat: prefix from start_ref leading non-digits + zero.
record_transfer(...)	0004	Atomic insert into transfers + decrement exchange.balance. Validates company ownership.
record_currency_buy(...)	0004	Atomic insert into currency_buys (status=daily) + increment exchange.balance by usd_amount.
record_pending_buy(...)	0004	Insert pending currency_buy. No balance mutation.
handle_new_user()	0005	AFTER INSERT trigger on auth.users — autocreates profiles row. SECURITY DEFINER.

7. Design System

Colors

Token	Value	Usage
bgDeep	#020617	Background base — slate-950, OLED-friendly
bgPanel	#0B1220	Stacking surface tone — slate-900-ish
glassFill	#FFFFFF @ 8%	Glass surface fill
glassFillStrong	#FFFFFF @ 12%	Stronger glass fill
glassBorder	#FFFFFF @ 12%	Hairline border
glassBorderStrong	#FFFFFF @ 20%	Stronger border
accent	#22D3EE	cyan-400 — primary brand glow
accentDim	#0E7490	cyan-700
positive	#22C55E	green-500 — currency buy / income
negative	#EF4444	red-500 — transfers / outflow
warning	#F59E0B	amber-500 — pending
textHigh	#F8FAFC	slate-50
textMid	#CBD5E1	slate-300
textLow	#94A3B8	slate-400
textDim	#64748B	slate-500

Typography

Family	Weights	Use
Almarai	300 / 400 / 700 / 800	Primary UI font (default in ThemeData)
NotoArabic (Noto Naskh Arabic)	400 / 500 / 600 / 700	Alternate Arabic display font, also bundled for PDF export

Reusable widgets

Widget	Description
GlassCard	Frosted-glass surface — 18px backdrop blur, translucent fill, hairline border, 24px shadow
GlassPanel	Subtle flatter glass section — 12px blur, 14px radius
GlassAppBar	AppBar with backdrop blur 18 + bgDeep @ 35% alpha
showGlassDialog<T>()	Generalized dialog with slide(0.12 0) + scale(0.94 1) + fade entrance over 280ms easeOutCubic
LiquidBackground	Animated 18s loop. Three radial blobs (accent + positive + violet) blurred 80px on a slate-950 base
_CollapsibleSection	Tap-to-expand glass section with chevron + 220ms easeOutCubic AnimatedSize (transfers screen)

8. Recent Changes

— (git log: branch 'main' has no commits yet)