

Level3 Open API

Version

Revision History:

version	date	author	state	description
V1.0.0	2026-09-03	Hedrick Xu	A	1.first draft
V2.0.0	2026-09-10	xrdinary xiao	A	Add passenger flow interface

Correction status: **A** – add **M** – modify **D** – delete **R** – release

1. Authentication

Level3 Open API authentication endpoints

1.1 Authentication Flow

1. Create an application on the platform and obtain `client_id` and `client_secret` .
2. Call the token endpoint with the `client_credentials` flow to obtain `access_token` .
3. When calling business APIs, add `Authorization: Bearer <access_token>` to the request header.
4. When the token is no longer used, call the revoke token endpoint to invalidate it.

1.2 Get Token

Use application credentials to obtain an Open API access token.

Item	Description
URL	<code>/global/open/api/v1/oauth2/token</code>
Method	<code>POST</code>
Content-Type	<code>application/json</code>

Item	Description
Authentication Required	No

Request Parameters

Parameter	Type	Required	Description
<code>client_id</code>	string	Yes	Application client ID
<code>client_secret</code>	string	Yes	Application client secret
<code>grant_type</code>	string	Yes	Grant type, fixed as <code>client_credentials</code>

Request Example

```
{
  "client_id": "your_client_id",
  "client_secret": "your_client_secret",
  "grant_type": "client_credentials"
}
```

Response Parameters

Parameter	Type	Description
<code>code</code>	string	Status code
<code>message</code>	string	Message
<code>data.access_token</code>	string	Access token
<code>data.grant_type</code>	string	Grant type, fixed as <code>client_credentials</code>

Response Example

```
{
  "code": "00000000",
  "message": "success",
  "data": {
    "access_token": "eyJhbGciOiJSUzI1NiIs...\"",
    "grant_type": "client_credentials"
  },
  "timestamp": 1710000000000
}
```

1.3 Revoke Token

Revoke the access token carried in the current `Authorization` request header. After revocation, the token becomes invalid.

Item	Description
URL	<code>/global/open/api/v1/oauth2/revoke</code>
Method	<code>DELETE</code>
Authentication Required	No. The endpoint reads the token to revoke from the <code>Authorization</code> request header

Header Parameters

Parameter	Type	Required	Description
<code>Authorization</code>	string	No	Format: <code>Bearer <access_token></code>

Response Example

```
{
  "code": "00000000",
  "message": "success",
  "timestamp": 1710000000000
}
```

1.4 Notes

- The only supported `grant_type` is `client_credentials`.

- The default token lifetime is 2 hours.
- The token endpoint does not return a `refresh_token`.
- Keep `client_secret` secure. Do not expose it in frontend pages, client packages, or public repositories.

2. Principal

2.1 Query Principal Page

Query principals accessible to the current application with pagination.

Item	Description
URL	<code>/global/open/api/v1/principal/query/page</code>
Method	<code>GET</code>
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
<code>Authorization</code>	string	Yes	Format: <code>Bearer <access_token></code>

Request Parameters

Parameter	Type	Required	Description
<code>page</code>	number	No	Page number. Default value: <code>1</code>
<code>pageSize</code>	number	No	Number of records per page. Default value: <code>10</code>
<code>name</code>	string	No	Principal name. Supports filtering by name

Request Example

```
GET /global/open/api/v1/principal/query/page?
page=1&pageSize=10&name=Example Principal
Authorization: Bearer <access_token>
```

Response Parameters

Parameter	Type	Description
<code>code</code>	string	Status code
<code>message</code>	string	Message
<code>data.total</code>	number	Total number of records
<code>data.page</code>	number	Current page number
<code>data.pageSize</code>	number	Number of records per page
<code>data.exceedTotal</code>	boolean	Whether the actual total exceeds the current counted total
<code>data.data</code>	array	Principal list
<code>data.data[].id</code>	number	Principal ID
<code>data.data[].name</code>	string	Principal name
<code>data.data[].email</code>	string	Email
<code>data.data[].photo</code>	string	Image URL
<code>data.data[].phone</code>	string	Phone number
<code>data.data[].subscribedApps</code>	array	Subscribed application list
<code>data.data[].subscribedApps[].name</code>	string	Application name
<code>data.data[].subscribedApps[].code</code>	string	Application code

Response Example

```
{
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 1,
    "data": [
      {
        "id": 10001,
        "name": "Example Principal",
        "email": "principal@example.com",
        "photo": "https://example.com/principal.png",
        "phone": "+86-13800000000",
        "subscribedApps": [
          {
            "name": "Level3",
            "code": "level3"
          }
        ]
      }
    ],
    "page": 1,
    "pageSize": 10,
    "exceedTotal": false
  },
  "timestamp": 1710000000000
}
```

2.2 Query Principal Details

Query principal details by principal ID.

Item	Description
URL	<code>/global/open/api/v1/principal/query/{id}</code>
Method	GET
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
<code>Authorization</code>	string	Yes	Format: <code>Bearer <access_token></code>

Path Parameters

Parameter	Type	Required	Description
<code>id</code>	number	Yes	Principal ID

Request Example

```
GET /global/open/api/v1/principal/query/10001
Authorization: Bearer <access_token>
```

Response Parameters

Parameter	Type	Description
<code>code</code>	string	Status code
<code>message</code>	string	Message
<code>data.id</code>	number	Principal ID
<code>data.name</code>	string	Principal name
<code>data.email</code>	string	Email
<code>data.photo</code>	string	Image URL
<code>data.phone</code>	string	Phone number
<code>data.areaName</code>	string	Area name
<code>data.address</code>	string	Address

Response Example

```
{
  "code": "00000000",
  "message": "success",
  "data": {
    "id": 10001,
    "name": "Example Principal",
    "email": "principal@example.com",
    "photo": "https://example.com/principal.png",
    "phone": "+86-13800000000",
    "areaName": "South China Area",
    "address": "100 Example Road, Nanshan District, Shenzhen"
  },
  "timestamp": 1710000000000
}
```

2.3 Notes

- Obtain `access_token` from the authentication endpoint before calling these APIs.
- The APIs only return principal data accessible within the current application's authorization scope.

3. Outlet

3.1 Query Outlet Page

Query outlets accessible to the current application with pagination.

Item	Description
URL	<code>/global/open/api/v1/outlet/query/page</code>
Method	GET
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
Authorization	string	Yes	Format: Bearer <access_token>

Request Parameters

Parameter	Type	Required	Description
page	number	No	Page number. Default value: 1
pageSize	number	No	Number of records per page. Default value: 10
name	string	No	Outlet name. Supports filtering by name
parentId	number	No	Principal ID

Request Example

```
GET /global/open/api/v1/outlet/query/page?page=1&pageSize=10&name=Example
Outlet&parentId=10001
Authorization: Bearer <access_token>
```

Response Parameters

Parameter	Type	Description
code	string	Status code
message	string	Message
data.total	number	Total number of records
data.page	number	Current page number
data.pageSize	number	Number of records per page
data.exceedTotal	boolean	Whether the actual total exceeds the current counted total
data.data	array	Outlet list
data.data[].id	string	Outlet ID
data.data[].name	string	Outlet name
data.data[].email	string	Email
data.data[].address	string	Address

Parameter	Type	Description
<code>data.data[].timezoneDictId</code>	number	Time zone dictionary ID
<code>data.data[].areaName</code>	string	Area name
<code>data.data[].outletTag</code>	array	Outlet tags

Response Example

```
{
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 1,
    "data": [
      {
        "id": "20001",
        "name": "Example Outlet",
        "email": "outlet@example.com",
        "address": "100 Example Road, Nanshan District, Shenzhen",
        "timezoneDictId": 30001,
        "areaName": "South China Area",
        "outletTag": ["Direct-operated outlet"]
      }
    ],
    "page": 1,
    "pageSize": 10,
    "exceedTotal": false
  },
  "timestamp": 1710000000000
}
```

3.2 Query Outlet Details

Query outlet details by outlet ID.

Item	Description
URL	<code>/global/open/api/v1/outlet/query/{id}</code>
Method	GET
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
Authorization	string	Yes	Format: Bearer <access_token>

Path Parameters

Parameter	Type	Required	Description
id	number	Yes	Outlet ID

Request Example

```
GET /global/open/api/v1/outlet/query/20001
Authorization: Bearer <access_token>
```

Response Parameters

Parameter	Type	Description
code	string	Status code
message	string	Message
data.id	string	Outlet ID
data.name	string	Outlet name
data.email	string	Email
data.address	string	Address
data.timezoneDictId	number	Time zone dictionary ID
data.areaName	string	Area name
data.phone	string	Phone number

Response Example

```
{
  "code": "00000000",
  "message": "success",
  "data": {
    "id": "20001",
    "name": "Example Outlet",
    "email": "outlet@example.com",
    "address": "100 Example Road, Nanshan District, Shenzhen",
    "timezoneDictId": 30001,
    "areaName": "South China Area",
    "phone": "13800000000"
  },
  "timestamp": 1710000000000
}
```

3.3 Notes

- Obtain `access_token` from the authentication endpoint before calling these APIs.
- The APIs only return or operate on outlet data accessible within the current application's authorization scope.

4. IPVA

4.1 Get In/Out Data By Count Time

Get passenger flow data by time range.

Item	Description
URL	<code>/zt/open/api/v1/ipva/getInOutDataByCountTime</code>
Method	<code>GET</code>
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
<code>Authorization</code>	string	Yes	Format: <code>Bearer <access_token></code>

Parameter	Type	Required	Description
Accept-Language	string	No	Language: zh-CN pt-BR es ja-JP en-US th . Default: zh-CN

Request Parameters

Parameter	Type	Required	Description
outletIds	array	Yes	Outlet IDs (maximum 5)
begCountTime	string	Yes	Start time. Format: yyyy-MM-dd HH:mm:ss .
endCountTime	string	Yes	End time. Format: yyyy-MM-dd HH:mm:ss . Max range: 60 days
interval	string	Yes	Time interval: Hour Day
nextBatchId	integer	Yes	Batch ID. Default: 1 . Always start from 1

Request Example

```
GET /open/api/v1/ipva/getInOutDataByCountTime?
outletIds=1&outletIds=2&begCountTime=2025-01-
01%2000:00:00&endCountTime=2025-01-
31%2023:59:59&interval=Day&nextBatchId=1
Authorization: Bearer <access_token>
Accept-Language: en-US
```

Response Parameters

Parameter	Type	Description
code	string	Status code
message	string	Response message
data	object	Response data
data.total	integer	Total data records
data.count	integer	Current batch record count

Parameter	Type	Description
<code>data.nextBatchId</code>	integer	Next batch ID. When returned value equals requested value, data extraction is complete
<code>data.data</code>	array	Data records
<code>data.data[].outletId</code>	integer	Outlet ID
<code>data.data[].outletName</code>	string	Outlet name
<code>data.data[].countDate</code>	string	Data date. Hour format: <code>yyyy-MM-dd HH:00:00</code> . Day format: <code>yyyy-MM-dd</code>
<code>data.data[].updateTime</code>	string	Update time
<code>data.data[].inSum</code>	integer	Outlet inbound passenger flow
<code>data.data[].outSum</code>	integer	Outlet outbound passenger flow
<code>data.data[].entrance</code>	array	Entrance data
<code>data.data[].entrance[].siteKey</code>	string	Entrance code
<code>data.data[].entrance[].siteName</code>	string	Entrance name
<code>data.data[].entrance[].inSum</code>	integer	Entrance inbound passenger flow
<code>data.data[].entrance[].outSum</code>	integer	Entrance outbound passenger flow
<code>timestamp</code>	integer	Response timestamp

Response Example

```
{
  "requestId": "xxx",
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 10,
    "count": 10,
    "nextBatchId": 1,
    "data": [
      {
        "outletId": 1,
        "outletName": "Outlet A",
        "countDate": "2025-01-01",
        "updateTime": "2025-01-02 10:00:00",
        "inSum": 150,
        "outSum": 120,
        "entrance": [
          {
            "siteKey": "E001",
            "siteName": "Main Entrance",
            "inSum": 80,
            "outSum": 60
          },
          {
            "siteKey": "E002",
            "siteName": "Side Entrance",
            "inSum": 70,
            "outSum": 60
          }
        ]
      }
    ]
  },
  "timestamp": 1710000000000
}
```

4.2 Get Passby Data By Count Time

Get passby passenger flow data by time range.

Item	Description
URL	/zt/open/api/v1/ipva/getPassbyDataByCountTime

Item	Description
Method	GET
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
Authorization	string	Yes	Format: Bearer <access_token>
Accept-Language	string	No	Language: zh-CN pt-BR es ja-JP en-US th . Default: zh-CN

Request Parameters

Parameter	Type	Required	Description
outletIds	array	Yes	Outlet IDs (maximum 5)
begCountTime	string	Yes	Start time. Format: yyyy-MM-dd HH:mm:ss .
endCountTime	string	Yes	End time. Format: yyyy-MM-dd HH:mm:ss . Max range: 60 days
interval	string	Yes	Time interval: Hour Day
nextBatchId	integer	Yes	Batch ID. Default: 1 . Always start from 1

Request Example

```
GET /open/api/v1/ipva/getPassbyDataByCountTime?
outletIds=1&outletIds=2&begCountTime=2025-01-
01%2000:00:00&endCountTime=2025-01-
31%2023:59:59&interval=Day&nextBatchId=1
Authorization: Bearer <access_token>
Accept-Language: en-US
```

Response Parameters

Parameter	Type	Description
<code>code</code>	string	Status code
<code>message</code>	string	Response message
<code>data</code>	object	Response data
<code>data.total</code>	integer	Total data records
<code>data.count</code>	integer	Current batch record count
<code>data.nextBatchId</code>	integer	Next batch ID
<code>data.data</code>	array	Data records
<code>data.data[].outletId</code>	integer	Outlet ID
<code>data.data[].outletName</code>	string	Outlet name
<code>data.data[].countDate</code>	string	Data date
<code>data.data[].updateTime</code>	string	Update time
<code>data.data[].passby</code>	integer	Outlet passby passenger flow
<code>data.data[].entrance</code>	array	Entrance data
<code>data.data[].entrance[].siteKey</code>	string	Entrance code
<code>data.data[].entrance[].siteName</code>	string	Entrance name
<code>data.data[].entrance[].passby</code>	integer	Entrance passby passenger flow
<code>timestamp</code>	integer	Response timestamp

Response Example

```
{
  "requestId": "xxx",
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 10,
    "count": 10,
    "nextBatchId": 1,
    "data": [
      {
        "outletId": 1,
        "outletName": "Outlet A",
        "countDate": "2025-01-01",
        "updateTime": "2025-01-02 10:00:00",
        "passby": 500,
        "entrance": [
          {
            "siteKey": "E001",
            "siteName": "Main Entrance",
            "passby": 300
          },
          {
            "siteKey": "E002",
            "siteName": "Side Entrance",
            "passby": 200
          }
        ]
      }
    ]
  },
  "timestamp": 1710000000000
}
```

4.3 Get Acc Data By Count Time

Get customer count data by time range.

Item	Description
URL	<code>/zt/open/api/v1/ipva/getAccDataByCountTime</code>
Method	GET

Item	Description
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
Authorization	string	Yes	Format: Bearer <access_token>
Accept-Language	string	No	Language: zh-CN pt-BR es ja-JP en-US th . Default: zh-CN

Request Parameters

Parameter	Type	Required	Description
outletIds	array	Yes	Outlet IDs (maximum 5)
begCountTime	string	Yes	Start time. Format: yyyy-MM-dd HH:mm:ss .
endCountTime	string	Yes	End time. Format: yyyy-MM-dd HH:mm:ss . Max range: 60 days
interval	string	Yes	Time interval: Hour Day
nextBatchId	integer	Yes	Batch ID. Default: 1 . Always start from 1

Request Example

```
GET /open/api/v1/ipva/getAccDataByCountTime?
outletIds=1&outletIds=2&begCountTime=2025-01-
01%2000:00:00&endCountTime=2025-01-
31%2023:59:59&interval=Day&nextBatchId=1
Authorization: Bearer <access_token>
Accept-Language: en-US
```

Response Parameters

Parameter	Type	Description
code	string	Status code

Parameter	Type	Description
<code>message</code>	string	Response message
<code>data</code>	object	Response data
<code>data.total</code>	integer	Total data records
<code>data.count</code>	integer	Current batch record count
<code>data.nextBatchId</code>	integer	Next batch ID
<code>data.data</code>	array	Data records
<code>data.data[].outletId</code>	integer	Outlet ID
<code>data.data[].outletName</code>	string	Outlet name
<code>data.data[].countDate</code>	string	Data date
<code>data.data[].accNum</code>	integer	Outlet customer count
<code>data.data[].avgWanderTime</code>	integer	Average dwell time (null for hourly data)
<code>data.data[].updateTime</code>	string	Update time
<code>timestamp</code>	integer	Response timestamp

Response Example

```
{
  "requestId": "xxx",
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 10,
    "count": 10,
    "nextBatchId": 1,
    "data": [
      {
        "outletId": 1,
        "outletName": "Outlet A",
        "countDate": "2025-01-01",
        "accNum": 150,
        "avgWanderTime": 45,
        "updateTime": "2025-01-02 10:00:00"
      }
    ]
  },
  "timestamp": 1710000000000
}
```

4.4 Get Distribute Data By Count Time

Get customer dwell time distribution data by time range.

Item	Description
URL	<code>/zt/open/api/v1/ipva/getDistributeDataByCountTime</code>
Method	GET
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
Authorization	string	Yes	Format: Bearer <access_token>
Accept-Language	string	No	Language: zh-CN pt-BR es ja-JP en-US th . Default: zh-CN

Request Parameters

Parameter	Type	Required	Description
outletIds	array	Yes	Outlet IDs (maximum 5)
begCountTime	string	Yes	Start time. Format: yyyy-MM-dd HH:mm:ss .
endCountTime	string	Yes	End time. Format: yyyy-MM-dd HH:mm:ss . Max range: 60 days
nextBatchId	integer	Yes	Batch ID. Default: 1 . Always start from 1

Request Example

```
GET /open/api/v1/ipva/getDistributeDataByCountTime?
outletIds=1&outletIds=2&begCountTime=2025-01-
01%2000:00:00&endCountTime=2025-01-31%2023:59:59&nextBatchId=1
Authorization: Bearer <access_token>
Accept-Language: en-US
```

Response Parameters

Parameter	Type	Description
code	string	Status code
message	string	Response message
data	object	Response data
data.total	integer	Total data records
data.count	integer	Current batch record count
data.nextBatchId	integer	Next batch ID
data.data	array	Data records
data.data[].outletId	integer	Outlet ID
data.data[].outletName	string	Outlet name
data.data[].countDate	string	Data date

Parameter	Type	Description
<code>data.data[].updateTime</code>	string	Update time
<code>data.data[].distributeData</code>	array	Dwell time distribution data
<code>data.data[].distributeData[].time_TH1</code>	object	distribute percentage
<code>data.data[].distributeData[].time_TH1.name</code>	string	≤30s
<code>data.data[].distributeData[].time_TH1.value</code>	string	percentage
<code>data.data[].distributeData[].time_TH2</code>	object	distribute percentage
<code>data.data[].distributeData[].time_TH3</code>	object	distribute percentage
<code>data.data[].distributeData[].time_TH4</code>	object	distribute percentage
<code>data.data[].distributeData[].time_TH5</code>	object	distribute percentage
<code>data.data[].distributeData[].time_TH6</code>	object	distribute percentage
<code>timestamp</code>	integer	Response timestamp

Response Example

```
{
  "requestId": "xxx",
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 10,
    "count": 10,
    "nextBatchId": 1,
    "data": [
      {
        "outletId": 1,
        "outletName": "Outlet A",
        "countDate": "2025-01-01",
        "updateTime": "2025-01-02 10:00:00",
        "distributeData": [
          {
            "time_TH1": {
              "name": "≤30s",
              "value": "5.39%"
            },
            "time_TH2": {
              "name": "31~60s",
              "value": "13.69%"
            },
            "time_TH3": {
              "name": "1~2min",
              "value": "22.61%"
            },
            "time_TH4": {
              "name": "2~5min",
              "value": "30.08%"
            },
            "time_TH5": {
              "name": "5~10min",
              "value": "15.56%"
            },
            "time_TH6": {
              "name": ">10min",
              "value": "12.66%"
            }
          }
        ]
      }
    ]
  }
},
```

```
"timestamp": 1710000000000
}
```

4.5 Get Customer Portrait By Count Time

Get age and gender data by time range.

Item	Description
URL	<code>/zt/open/api/v1/ipva/getCustomerPortraitByCountTime</code>
Method	GET
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
Authorization	string	Yes	Format: Bearer <access_token>
Accept-Language	string	No	Language: zh-CN pt-BR es ja-JP en-US th . Default: zh-CN

Request Parameters

Parameter	Type	Required	Description
outletIds	array	Yes	Outlet IDs (maximum 5)
begCountTime	string	Yes	Start time. Format: yyyy-MM-dd HH:mm:ss .
endCountTime	string	Yes	End time. Format: yyyy-MM-dd HH:mm:ss . Max range: 60 days
nextBatchId	integer	Yes	Batch ID. Default: 1 . Always start from 1

Request Example

```
GET /open/api/v1/ipva/getCustomerPortraitByCountTime?
outletIds=1&outletIds=2&begCountTime=2025-01-
01%2000:00:00&endCountTime=2025-01-31%2023:59:59&nextBatchId=1
Authorization: Bearer <access_token>
Accept-Language: en-US
```

Response Parameters

Parameter	Type	Description
<code>code</code>	string	Status code
<code>message</code>	string	Response message
<code>data</code>	object	Response data
<code>data.total</code>	integer	Total data records
<code>data.count</code>	integer	Current batch record count
<code>data.nextBatchId</code>	integer	Next batch ID
<code>data.data</code>	array	Data records
<code>data.data[].outletId</code>	integer	Outlet ID
<code>data.data[].outletName</code>	string	Outlet name
<code>data.data[].countDate</code>	string	Data date
<code>data.data[].updateTime</code>	string	Update time
<code>data.data[].spanZeroSix</code>	span object	Age group 0-6
<code>data.data[].spanSevenFifteen</code>	span object	Age group 7-15
<code>data.data[].spanSixteenThirtyFive</code>	span object	Age group 16-35
<code>data.data[].spanThirtySixSixty</code>	span object	Age group 36-60
<code>data.data[].spanSixtyAbove</code>	span object	Age group 60+
<code>data.data[].spanUnknown</code>	span object	Unknown age group

Parameter	Type	Description
Each span object contains:		
customerNum	integer	Customer count
menNum	integer	Male customer count
womenNum	integer	Female customer count
unknownSexNum	integer	Unknown gender customer count
Each span object contains end		
timestamp	integer	Response timestamp

Response Example

```
{
  "requestId": "xxx",
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 10,
    "count": 10,
    "nextBatchId": 1,
    "data": [
      {
        "outletId": 1,
        "outletName": "Outlet A",
        "countDate": "2025-01-01",
        "updateTime": "2025-01-02 10:00:00",
        "spanZeroSix": {
          "customerNum": 10,
          "menNum": 5,
          "womenNum": 5,
          "unknownSexNum": 0
        },
        "spanSevenFifteen": {
          "customerNum": 20,
          "menNum": 10,
          "womenNum": 10,
          "unknownSexNum": 0
        },
        "spanSixteenThirtyFive": {
          "customerNum": 50,
          "menNum": 25,
          "womenNum": 25,
          "unknownSexNum": 0
        },
        "spanThirtySixSixty": {
          "customerNum": 40,
          "menNum": 20,
          "womenNum": 20,
          "unknownSexNum": 0
        },
        "spanSixtyAbove": {
          "customerNum": 15,
          "menNum": 8,
          "womenNum": 7,
          "unknownSexNum": 0
        },
        "spanUnknown": {
          "customerNum": 5,
```

```
        "menNum": 2,
        "womenNum": 3,
        "unknownSexNum": 0
    }
}
],
},
"timestamp": 1710000000000
}
```

4.6 Query Metadata Page

Query metadata events with pagination. Different event types correspond to different event data structures.

Item	Description
URL	/zt/open/api/v1/event/page
Method	GET
Authentication Required	Yes

Header Parameters

Parameter	Type	Required	Description
Authorization	string	Yes	Format: Bearer <access_token>

Request Parameters

Parameter	Type	Required	Description
page	number	No	Page number. Default value: 1
pageSize	number	No	Number of records per page. Default value: 10
deviceId	number	Yes	Device ID
type	number	Yes	Event type: 1 -Body, 2 -Feature, 3 -Cross-line

Request Example

```
GET /zt/open/api/v1/event/page?page=1&pageSize=10&deviceId=10001&type=1
Authorization: Bearer <access_token>
```

Response Parameters (type = 1 Body)

Parameter	Type	Description
code	string	Status code
message	string	Message
data.total	number	Total number of records
data.page	number	Current page number
data.pageSize	number	Number of records per page
data.exceedTotal	boolean	Whether the actual total exceeds the current counted total
data.data	array	Metadata event list
data.data[].id	string	Event ID
data.data[].eventTime	string	Event time
data.data[].eventLogV0	object	Body event data
data.data[].eventLogV0.age	string	Age
data.data[].eventLogV0.bag	string	Bag
data.data[].eventLogV0.channelNum	string	Channel number
data.data[].eventLogV0.gender	string	Gender
data.data[].eventLogV0.glasses	string	Glasses
data.data[].eventLogV0.hat	string	Hat
data.data[].eventLogV0.lowerColor	string	Lower clothing color
data.data[].eventLogV0.rideBike	string	Whether riding a bike

Parameter	Type	Description
<code>data.data[].eventLogV0.trackId</code>	string	User recognition ID
<code>data.data[].eventLogV0.umbrella</code>	string	Whether carrying an umbrella
<code>data.data[].eventLogV0.upperColor</code>	string	Upper clothing color
<code>data.data[].eventLogV0.recognitionTarget</code>	string	Recognition target
<code>data.data[].eventLogV0.scene</code>	string	Scene

Response Example (type = 1 Body)

```
{
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 1,
    "data": [
      {
        "id": "30001",
        "eventTime": "2025-01-22 10:30:00",
        "eventLogV0": {
          "age": "25",
          "bag": "Yes",
          "channelNum": "1",
          "gender": "Male",
          "glasses": "No",
          "hat": "No",
          "lowerColor": "Black",
          "rideBike": "No",
          "trackId": "100001",
          "umbrella": "No",
          "upperColor": "White",
          "recognitionTarget": "Body",
          "scene": "Indoor"
        }
      }
    ],
    "page": 1,
    "pageSize": 10,
    "exceedTotal": false
  },
  "timestamp": 1710000000000
}
```

Response Parameters (type = 2 Feature)

Parameter	Type	Description
code	string	Status code
message	string	Message
data.total	number	Total number of records
data.page	number	Current page number

Parameter	Type	Description
<code>data.pageSize</code>	number	Number of records per page
<code>data.exceedTotal</code>	boolean	Whether the actual total exceeds the current counted total
<code>data.data</code>	array	Metadata event list
<code>data.data[].id</code>	string	Event ID
<code>data.data[].eventTime</code>	string	Event time
<code>data.data[].eventLogV0</code>	object	Feature event data
<code>data.data[].eventLogV0.maskStatus</code>	string	Face status
<code>data.data[].eventLogV0.glasses</code>	string	Glasses
<code>data.data[].eventLogV0.gender</code>	string	Gender
<code>data.data[].eventLogV0.trackId</code>	string	User recognition ID
<code>data.data[].eventLogV0.hat</code>	string	Hat
<code>data.data[].eventLogV0.age</code>	string	Age
<code>data.data[].eventLogV0.recognitionTarget</code>	string	Recognition target
<code>data.data[].eventLogV0.scene</code>	string	Scene

Response Example (type = 2 Feature)

```
{
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 1,
    "data": [
      {
        "id": "30002",
        "eventTime": "2025-01-22 10:35:00",
        "eventLogV0": {
          "maskStatus": "Example Status",
          "glasses": "No",
          "gender": "Female",
          "trackId": "100002",
          "hat": "No",
          "age": "30",
          "recognitionTarget": "Feature",
          "scene": "Indoor"
        }
      }
    ],
    "page": 1,
    "pageSize": 10,
    "exceedTotal": false
  },
  "timestamp": 1710000000000
}
```

Response Parameters (type = 3 Cross-line)

Parameter	Type	Description
code	string	Status code
message	string	Message
data.total	number	Total number of records
data.page	number	Current page number
data.pageSize	number	Number of records per page

Parameter	Type	Description
<code>data.exceedTotal</code>	boolean	Whether the actual total exceeds the current counted total
<code>data.data</code>	array	Metadata event list
<code>data.data[].id</code>	string	Event ID
<code>data.data[].eventTime</code>	string	Event time
<code>data.data[].eventLogV0</code>	object	Cross-line event data
<code>data.data[].eventLogV0.trackId</code>	string	User recognition ID
<code>data.data[].eventLogV0.height</code>	string	Height
<code>data.data[].eventLogV0.eventType</code>	string	Event type
<code>data.data[].eventLogV0.recognitionTarget</code>	string	Recognition target

Response Example (type = 3 Cross-line)

```
{
  "code": "00000000",
  "message": "success",
  "data": {
    "total": 1,
    "data": [
      {
        "id": "30003",
        "eventTime": "2025-01-22 10:40:00",
        "eventLogV0": {
          "trackId": "100003",
          "height": "175",
          "eventType": "Enter",
          "recognitionTarget": "Body"
        }
      }
    ],
    "page": 1,
    "pageSize": 10,
    "exceedTotal": false
  },
  "timestamp": 1710000000000
}
```

4.7 Notes

- Obtain `access_token` from the authentication endpoint before calling these APIs.
- Outlet IDs parameter (`outletIds`) accepts up to 5 IDs per request.
- Time range between `begCountTime` and `endCountTime` cannot exceed 60 days.
- For hourly data, `countDate` format is `yyyy-MM-dd HH:00:00` (e.g., `10:00:00` represents data from `10:00:00` to `10:59:59`).
- For daily data, `countDate` format is `yyyy-MM-dd` .
- The `nextBatchId` parameter must start from `1` for each data pull request. When the returned `nextBatchId` equals the requested value, all data has been retrieved.

Error Codes

All interfaces return the same set of error codes.

Code	Description
00000000	Operation successful
G0000017	Parameter is invalid
ORG200004	Application does not exist
ORG200005	Application has been disabled
ORG200006	Application secret is incorrect
ORG200010	Token is invalid
ORG200011	Token has expired
ORG200012	Failed to parse token
ORG200013	Linked user does not exist
ORG200014	User has been disabled. Please contact the administrator
ZT000007	Time range cannot exceed 60 days
ZT000008	Time conversion error