

Inland Revenue

Build Pack: Account API

Date: 30/09/2020
Version: v1

Contents

1 Overview.....	3
1.1 This solution	3
1.2 Intended audience.....	3
1.3 Prerequisites.....	3
1.3.1 Mutual Transport Layer Security and certificates	3
1.3.2 Authentication options	4
1.3.2.1 OAuth.....	4
1.3.2.2 JWT.....	4
2 Solution design	5
2.1 Architecture.....	5
2.2 Supported HTTP methods	5
2.3 Dependencies between the customer services APIs.....	6
2.4 Account API.....	7
2.4.1 Request payload	7
2.4.2 Response payload	7
2.4.2.1 Address notes.....	9
2.5 Account list	9
2.5.1 Request payload	9
2.5.2 Response payload	10
2.6 Security	10
2.6.1 OAuth.....	11
2.6.2 M2M JWT	12
2.6.2.1 Header	12
2.6.2.2 Payload.....	12
2.6.2.3 startLogon	13
2.6.2.4 sub	13
3 End points and OpenAPI specifications	14
3.1 End points.....	14
3.2 OpenAPI specifications.....	14
4 Glossary.....	15
5 Change log.....	17

1 Overview

1.1 This solution

Inland Revenue has a suite of digital services available for consumption by our service providers that supports efficient, electronic business interactions with Inland Revenue. The application programming interface (API) described in this build pack document provides current account information as held by Inland Revenue.

Before continuing, please consult www.ird.govt.nz/digital-service-providers/services-catalogue for business-level context, use cases and links to relevant policy. The information available here explains how to integrate with Inland Revenue's services.

1.2 Intended audience

Access to the API end point is open to any software provider that has been on-boarded to the API (referred to throughout the remainder of this document as 'Digital Service Providers'). Access to the account data is open to any logon that currently has access to these resources on eServices. This includes tax intermediaries (such as tax agents and bookkeepers) and to customers using software on their own behalf.

1.3 Prerequisites

Party	Requirement	Description
Digital Service Provider	Acquire a X.509 certificate from a competent authority for the Test and Production environments.	This is required when using mutual TLS with cloud-based service providers or financial institutions. Note that the same certificate cannot be used for the Test and Production environments.

1.3.1 Mutual Transport Layer Security and certificates

Mutual Transport Layer Security (TLS) is implemented for this API. This requires the use of a publicly-issued X509 certificate from one of the trusted certificate authorities. Inland Revenue does not issue certificates to external vendors for web service security implementations.

Inland Revenue has the following minimum requirements for accepting public X509 keys:

- Minimum Key Length: 2048
- Signature Algorithm: SHA256[RSA]
- Self-signed certificates are not accepted
- Certificates issued by a private/internal certificate authority are not accepted.

In general, shorter-lived certificates offer a better security posture since the impact of key compromise is less severe but there is no minimum requirement for certificate expiry periods.

Below is a list for examples of certificate authority providers with no recommendations or rankings incorporated. It is recommended that a business researches which certificate authority meets their requirements:

- [Comodo](#)
- [GeoTrust](#)
- [DigiCert](#)
- [GlobalSign](#)
- [Symantec](#)
- [Thawte](#)
- [IdenTrust](#)
- [Entrust](#)
- [Network Solutions](#)
- [RapidSSL](#)
- [Entrust Datacard](#)
- [GoDaddy](#).

1.3.2 Authentication options

1.3.2.1 OAuth

When using OAuth the interaction with IR is transacted under the identity of a myIR user. OAuth requires the presence of a myIR user, as this person must be available to supply their user ID, password and consent at run-time in order to be authenticated. OAuth is especially suited to cloud-based applications where the transacting parties are application users rather than providers.

1.3.2.2 JWT

The alternative to OAuth is JWT, which does not require the presence of a myIR user. Authentication is based on the verification of a digital signature that (provably) belongs to a customer. In order to digitally sign their messages, the customer must acquire a digital certificate from a trusted certificate authority, or generate a self-signed certificate, and supply it to Inland Revenue during the on-boarding process. JWT is therefore appropriate when the following conditions apply:

- The interaction with Inland Revenue is conducted under the identity of an organisation, as opposed to a person AND
- The organisation has the technical and operational capability to securely obtain and manage digital certificates AND
- The organisation's interactions with Inland Revenue can occur in the absence of specific people due to staffing issues such as out-of-hours non-availability, staff turnover and absence from work.


These factors tend to limit the use JWT to larger corporations and public sector organisations. It is not suitable for cloud-based applications as it requires all application users to have their own digital certificates—this is administratively burdensome and requires these users to lodge their private keys with their application provider, which is insecure.

2 Solution design

2.1 Architecture

Inland Revenue is offering a suite of web applications in order to facilitate interactions via software packages. This API will be used by approved organisations to retrieve account information from Inland Revenue.

The diagram below illustrates the flow of data from Inland Revenue to the Digital Service Providers.



2.2 Supported HTTP methods


This service only supports the POST HTTP method and will not allow any updates. This service has two operations that use the POST HTTP method:

- **Retrieve:** Retrieves details about an account
- **List:** Retrieves a list of accounts for the customer.

2.3 Dependencies between the customer services APIs

This API is one of seven 'customer services' APIs designed to be used together—Account, Address, Bank, Contact, Customer, Name and Period. It is important to understand the dependencies between these when deciding which ones to implement, how to correctly sequence their adoption, how authorisation rules impact access, and how to use them in general.

These APIs align to START's data model as depicted below:



2.4 Account API

This operation is used by the consumer to retrieve information about a specific account. This includes information that is unique to certain account types and may not always be present in a response.

2.4.1 Request payload

Field	Requirement	Description
AccountID	Mandatory	Unique ID to identify an account
AccountIDType	Mandatory	Type of ID submitted in Account ID field

2.4.2 Response payload

Note that the requirement status of each field is provided in the accompanying YAML file.

Field	Description
ID	The account ID
IDType	The type of ID submitted in the ID field
Status	Shows the status of the account
AccountType	The type of account
FilingFrequency	The frequency with which the customer can file for this account
FilingChannel	The method with which the customer most recently filed a return for this account
Commence	Commencement day of the account
Cease	Cessation date of the account
BankAccount	The refund bank account for the account
NameOnBankAccount	The name used with the refund bank account
Address.AddressID	Unique ID for address
Address.Type	Type of address (mailing or physical)
Address.Formatted	Formatted, single-line address
Address.Street	Street address line 1
Address.Street2	Street address line 2
Address.Unit	Unit identifier
Address.UnitType	Unit type
Address.City	City name
Address.County	County name
Address.State	State name
Address.PostCode	Postal code

Field	Description
Address.Country	ISO 2 digit standard (New Zealand is NZ)
Address.Attention	The person to whom the correspondence is addressed
Address.Urbanisation	Urbanisation (See address notes below)
Address.District	District type (See address notes below)
Address.SubDistrict	District identifier (See address notes below)
Address.SubProvince	SubProvince name (See address notes below)
Address.Updated	Date on which address was last updated
Contact.ContactID	Unique ID for contact
Contact.ContactType	Contact type (ie primary, secondary)
Contact.Name	Name of contact
Contact.Updated	Date on which contact was last updated
Contact.Phone.PhoneID	Unique ID for phone
Contact.Phone.PhoneType	Mobile, home and/or business phone
Contact.Phone.Country	Country for phone—used to determine country code
Contact.Phone.AreaCode	Area code portion of phone number
Contact.Phone.PhoneNumber	Phone number, without country code
Contact.Phone.Extension	Extension number
INC.BalanceDate	The balance date of an income tax account for a non-individual
INC.ExemptionReason	The reason for an exemption for an income tax account for a non-individual
INC.ProvTaxMethod	The provisional tax method (AIM, Estimation, Ratio, Standard)
INC.ProvTaxRatio	The provisional tax ratio if the method is 'ratio'
INC.GroupMember	Boolean indicating that the income tax account is part of an income group
INC.GroupRepresentative	Boolean indicating that the income tax account is the representative of an income group
INC.ICAGroup	Boolean indicating that the income tax account is a Nominated Company of an ICA group
INC.ICAMember	Boolean indicating that the income tax account is part of an ICA group
INC.TransTasman	Boolean indicating that the customer is a trans-Tasman customer
INC.AgentNonResidentInsurer	Boolean indicating that the customer is an agent non-resident insurer

Field	Description
WFFTC.PaymentFrequency	The frequency with which a Working for Families customer gets paid
WFFTC.CurrentPayer	The agency that pays the Working for Families Tax Credit (MSD or IRD)
GST.AccountingBasis	The accounting basis for a GST account
GST.GroupMember	If the GST account belongs to a GST group as a member
GST.GroupRepresentative	If the GST account belongs to a GST group as a representative

2.4.2.1 Address notes

The following fields contain different data depending on the country of the address:

Field	Region	Data
Urbanisation	New Zealand	Suburb/Rural
	Australia	Suburb/Place
	Europe	Distribution
District	New Zealand	Floor type
	Australia	Floor type
	Finland	Entrance
	Poland	Post Office
SubDistrict	New Zealand	Floor number
	Australia	Floor number
SubProvince	New Zealand	Building
	Australia	Building
Unit	Caribbean	PO Box

2.5 Account list

These are used by the consumer to retrieve a list of accounts associated with a customer ID.

2.5.1 Request payload

Field	Description
CustomerID	ID of the customer for which the account list should be retrieved
CustomerIDType	Type of ID provided

A list of the valid values for **CustomerIDType** can be found in the YAML file.

2.5.2 Response payload

Field	Description
ID	An account identifier for an account belonging to the customer
IDType	An account ID type for an account belonging to the customer

2.6 Security

This API will require a unique identifier in order to establish the calling party's identity and to allow the access model to authenticate.

This design will use JSON Web Tokens (JWT) and OAuth2.0 tokens and protocol to establish the calling party's identity. The OAuth2.0 method requires a user to logon, while JWT is a machine-to-machine credential.

Each HTTPS header contains the authorisation attribute JWT/OAuth:

1. A signed JSON Web Token (JWT) token. This will establish a registered digital services provider identity via the asymmetric public key held in the key store established during onboarding.
2. An OAuth2.0 token that is a customer- or intermediary-level XIAMS user account recognised by START.

This API uses an HTTPS transport layer, with HTTP1.1 transport protocol supported.

Regarding transport layer security (TLS), note that while TLS1.3 is now an industry standard, it is not yet widely adopted, as doing so requires upgrades to perimeter security devices and software. Inland Revenue will upgrade to TLS1.3 once it is adopted widely enough, and where practical, external software partners should also anticipate upgrading to this version. TLS1.0 and TLS1.1 are not supported by myIR or Gateway Services.

Asymmetric keys of approved strength must be used. Inland Revenue requires the following ciphers and key strengths to be used:

Encryption:	Advanced Encryption Standard (AES)	FIPS 197	256-bit key
Hashing:	Elliptic Curve Digital Signature Algorithm (ECDSA) using P-256 or Secure Hash Algorithm (SHA-2) NOTE: ECDSA is preferred but RSA will be supported.	FIPS 180-3	SHA-256 (or greater)

Gateway Services will use this token in the HTTP header of a message in the same manner that an OAuth token has been used, namely:

`"Authorization: {JWTAccessToken}"`

Refer to the Identity and Access Services build pack for more information.

	End point for connections
Purpose	<ul style="list-style-type: none"> End point to which digital service providers will connect
Client application type	<ul style="list-style-type: none"> Cloud applications or in-house servers
Constraints	<ul style="list-style-type: none"> Only for source locations with client-side TLS certificates On the cloud end point Inland Revenue has controls to shield service providers from issues caused by heavy usage from other providers
Mutual TLS	<ul style="list-style-type: none"> Inland Revenue explicitly trusts the certificate the service provider associates with the TLS connection as client for Mutual TLS connections and uses it to identify the web service's sending party
Minimum TLS version	<ul style="list-style-type: none"> 1.2
URL	<ul style="list-style-type: none"> Contains .../gateway/..
Port	<ul style="list-style-type: none"> 4046
Web service consumer identification	<ul style="list-style-type: none"> Machine-to-machine authentication using client-signed JSON web tokens (JWT) OAuth2 authorisation using tokens generated by XIAMS
Firewalling in production	<ul style="list-style-type: none"> No IP address restrictions Access limited by certificate enrolment
Firewalling in non-production environments	<ul style="list-style-type: none"> No IP address restrictions Access limited by certificate enrolment

Delegated permissions: The service will allow for the retrieval of account data for a user (as represented by the JWT or OAuth2 token) who has delegated access. If the user does not have access to the account in the request parameters, an error will be returned.

2.6.1 OAuth

HTTP headers intended for OAuth access services will be have the JWT prefixed with "Bearer ".

HTTP header	Example value
Authorization	Bearer {JWTAccessToken}

Refer to the Identity and Access Services build pack for more information on authorisation flows.

2.6.2 M2M JWT

Authorisation intended for M2M (machine-to-machine) communication will not use "Bearer " flag on the HTTP header and only contain the JWT. The JWT will contain a field "startLogon" which can resolve to a myIR logon. The M2M JWT will be identified by a value of "M2M" in the Key ID ("kid"). The M2M JWT will be signed with a self-signed certificate, for which the public key was provided during onboarding.

HTTP header	Example value
Authorization	{JWTAccessToken}

Example data structure used for M2M authorisation:

```
Base64Url encoded {
  "alg": <algorithm value>,
  "typ": "JWT",
  "kid": "M2M"
}
.
Base64Url encoded {
  "sub": <token subject>,
  "iss": <issuer value>,
  "startLogon": <myIR_user>,
  "iat": <epoch issued value>,
  "exp": <epoch expired value>
}
.
JWS Signature (
  base64UrlEncode(header) + "." + base64UrlEncode(payload)
)
```

2.6.2.1 Header

Field	Requirement	Description	Valid values
alg	Required	Signature or encryption algorithm	RS256, RS384, RS512 ES256, ES384, ES512
typ	Required	Type of token	JWT
kid	Required	Key ID	M2M

2.6.2.2 Payload

Field	Requirement	Description	Valid values
sub	Required	Subject (to whom the token refers)	SHA-1 Thumbprint/fingerprint of signing certificate
iss	Required	Issuer who created this token	eg CompanyNameA
startLogon	Required	The myIR logon of a representative of the token	Valid myIR logon, or null

Field	Requirement	Description	Valid values
		subject. The subject must be the data owner.	
iat	Required	Issued at. The number of seconds since Unix epoch 1 Jan 1970, UTC.	Must not precede the signing certificate issue date Example: 1560144847
exp	Required	Expiration time. The number of seconds since Unix epoch 1 Jan 1970, UTC.	Must not exceed 8 hours from the iat (issued at) time value Example: 1574323940

2.6.2.3 *startLogon*

A myIR logon can be provided in order to use the myIR delegation model for identifying customers for whom account information should be retrieved. If the myIR logon is provided, then account information will only be shown for accounts the logon can access. If a myIR logon is not used, the field should be included with a value of null, and the subject will determine the account information shown.

2.6.2.4 *sub*

A subject must be provided, which is the thumbprint of the signing certificate, and can be used to determine which account information should be retrieved. The subject will always be used to validate the signature of the JWT but will only be used for determining which account information to retrieve when a value for **startLogon** is not provided. The subject can be used for access when the subject is a tax preparer—account information will be returned for accounts currently linked to the tax preparer.

3 End points and OpenAPI specifications

3.1 End points

Current environment information for this service—including the end points for each environment—is available within the relevant Software Development Kit (SDK).

To access the SDK, do one of the following:

- Go to <https://github.com/InlandRevenue> and select this service
- Go to <https://developerportal.ird.govt.nz> and click the link to the SDK within the Gateway Service documentation (please register first).

3.2 OpenAPI specifications

An OpenAPI file allows for the description of the entire API, end points, operations on each end point, and operation parameters. The included .yaml file can be used along with an OpenAPI editor such as editor.swagger.io to view technical specifications for this operation and generate example client code.

To access the latest OpenAPI definition for this service, please do the following:

- Login to the developer portal at <https://developerportal.ird.govt.nz> (register first)
- Download and view the OpenAPI definition within the Gateway Service documentation.

4 Glossary

Acronym/term	Definition
API	Application Programming Interface—set of functions and procedures that allow applications to access the data or features of another application, operating system or other service.
Authentication	The process that verifies the identity of the party attempting to access Inland Revenue
Authorisation	The process of determining whether a party is entitled to perform the function or access a resource
End points	A term used to describe a web service that has been implemented
FIPS	Federal Information Processing Standard—a suite of IT standards from the US Federal Government
Gateway	Inland Revenue’s web services gateway
HTTP, HTTPS	Hyper Text Transmission Protocol (Secure)—the protocol by which web browsers and servers interact with each other. When implemented over TLS1.2 HTTP becomes HTTPS.
IAMS	Identity and Access Management—a logical component that performs authentication and authorisation. Physically it is a set of discrete hardware and software products, plug-ins and protocols. Usually implemented as separate External IAMS (XIAMS) and Internal IAMS.
IAS	Identity and Access Service
IP	Internet Protocol—the principal communication protocol in the Internet protocol suite for relaying datagrams across networks
IRD	Inland Revenue Department (ie IRD number)
OAuth	An HTTPS based protocol for authorising access to a resource, currently at version 2
OpenAPI specifications	Formerly known as Swagger specifications—a specification for machine-readable interface files for describing, producing, consuming and visualising RESTful web services.
Payloads	This refers to the data contained within the messages that are exchanged when a web service is invoked. Messages consist of a header and a payload.
Schemas	An XML schema defines the syntax of an XML document, in particular of a payload. The schema specifies what a valid payload must or can contain, as well as validating the payload.
SHA	Secure Hashing Algorithm. There is a family of them that provide different strengths. SHA-2 is currently favoured over SHA-1, which has been compromised.
SOAP	Simple Object Access Protocol—a set of standards for specifying web services. GWS uses SOAP version 1.2

Acronym/term	Definition
SSL	Secure Sockets Layer certificates—used to establish an encrypted connection between a browser or user’s computer and a service or website
START	Simplified Taxation and Revenue Technology—IR’s new core tax processing application. It is an implementation of the GenTax product from FAST Enterprises.
TLS1.2	Transport Layer Security version 1.2—the protocol that is observed between adjacent servers for encrypting the data that they exchange. Prior versions of TLS and all versions of SSL have been compromised and are superseded by TLS1.2.
URL	Universal Resource Locator—also known as a web address
X.509 certificate	An international standard for encoding and describing a digital certificate. In isolation a public key is just a very large number, the X.509 certificate to which it is bound identifies whose key it is, who issued it, when it expires etc. When a counterparty’s X.509 digital certificate is received, the recipient takes their public key out of it and store the key in their own keystore. The recipient can then use this key to encrypt and sign the messages that they exchange with this counterparty.
XIAMS	External IAMS—an instance of IAMS that authenticates and authorises access by external parties, for example customers, trading partners etc, as opposed to internal parties such as staff
YAML	"YAML Ain't Markup Language"—a human-readable data-serialisation language commonly used for configuration files and in applications where data is stored or transmitted.

5 Change log

This table lists all material changes that have been made to this build pack document since the release of V1 (most recent changes listed first). It does not encompass non-material changes, such as to formatting etc.

Date of change	Document section	Description
30/09/20		V1 released