Correctness Boundaries of Typed Plans for Natural-Language Robot Fleet Control

Artem Tuzov[1*], Dmitrii Vizitei[1], Evgenii Shlomov[1], Senya Belykh[1], Anastasia Malakhova[1], Alexander Maloletov[1]

[1]Innopolis University, Innopolis, Russia.

*Corresponding author(s). E-mail(s): a.tuzov@innopolis.university;
Contributing authors: d.vizitei@innopolis.university;
e.shlomov@innopolis.university; a.malakhova@innopolis.university;
a.maloletov@innopolis.ru;

Abstract

A robot fleet can accept a plan whose assignments, routes, or completion reports still fail to meet the mission requirements. We examine these distinctions in a three-level Robot Operating System 2 implementation with twenty simulated robots. An offline benchmark of 44 cases measures whether generated plans pass checks on representation and selected case-specific requirements. Across five local configurations without constrained decoding, 70.0–87.3% of responses pass. In the selected 18-run simulation series, every run satisfies its pose-based task conditions. The series includes two successful repeats that replaced two incomplete runs after a software change. Separate execution traces document a robot routed to a pickup already assigned to another carrier, rejection of a route for a formation whose offsets did not match the requested column, and an arrival report that omitted a requested robot. A carry task records ordered zone presence for the same robot. The measured outcome therefore covers spatial events; physical cargo transfer is outside the evaluation. The case study identifies which conditions the implemented checks enforce and which require separate evidence.

Keywords: Multi-robot systems, Language models, Fleet coordination, Typed plans, Deterministic guards, ROS 2

1 Introduction

Commanding a fleet of mobile robots that share one workspace is a long-standing problem, and the classical decomposition separates fleet-level decisions — which robot goes where, in what order — from robot-level execution. Large language models make a natural-language front-end to that decomposition newly attractive [1, 2]: a model can reason over compact semantic primitives instead of producing control commands.




Fig. 1 Illustrative duplicate-carrier correction at the language–coordination boundary. An additional robot is routed to the same pickup. The guard retains the robot with the drop-off leg and removes the extra pickup assignment

The difficulty is that a well-formed language response need not describe an executable fleet action. It may refer to unavailable robots, assign conflicting goals, or request a formation whose geometry is incompatible with a corridor. Direct generation of multi-agent path finding (MAPF) solutions by a language model has failed on tested room and maze instances [3]. We therefore separate task interpretation from spatial planning and ask which errors can be handled at their interface.

Hierarchical control, formal intermediate representations, and deterministic validation are established approaches. Our contribution is a case study of their coverage in a mobile fleet. We describe the checks at the interfaces and document execution cases in which a structurally accepted plan still exhibits an assignment error, a route rejection, or a mismatch between a component report and the original request.

Research question 1 (RQ1) asks which checks on generated fleet plans fail under the tested model and serving configurations. To understand what happens after generation, RQ2 asks which observed assignment and spatial conflicts the implemented guards handle and which they leave unchecked. Finally, RQ3 asks why a component can report successful execution without fulfilling the mission's task-evaluator conditions.

We distinguish plan representation, intended task meaning, spatial executability, and evaluator completion. The sources behind these claims have different denominators and provenance; they are not independent replications of one guard-effect experiment. Figure 1 shows a duplicate-carrier correction; the shared-drop-off comparison is a separate case (Sec. 8.1).

2 Related Work

An instruction to a robot fleet leaves two different problems to solve: deciding what the robots should do and finding motions that realize those decisions. Classical multi-agent path finding addresses the latter once starts, goals and movement rules have been specified. Conflict-Based Search [4] resolves path conflicts through constraints, while Priority-Based Search (PBS) [5] and large-neighborhood repair (MAPF-LNS2) [6] offer alternative ways to coordinate paths. The resulting paths coordinate motion under the specified rules, but do not determine whether the supplied assignments and goals express a user's request. A language interface must establish that connection before path planning can serve the intended task. Whether a language model can supply those assignments is a separate question. PlanBench documents plan-generation failures on its tested models and tasks [7].

Grounding language in executable skills is therefore central to early robot planners based on large language models (LLMs). SayCan [1] combines a language model's estimate of a skill's usefulness with an affordance estimate of whether the robot can execute it in the current state. This connects task interpretation to available behavior without asking the language model to generate motor commands. Code as Policies [2] gives the model a more expressive interface: it composes perception and control APIs into programs, including control flow and numerical operations. For fleet control the distinction matters: choosing an available action and assembling a coherent mission require different checks.

Execution can depart from a plan even when its actions are available. Inner Monologue [8] feeds observations and success reports back into language reasoning, allowing subsequent decisions to account for execution. ProgPrompt [9] incorporates this concern into program-like plans through assertions and recovery steps. In its simulated evaluation, assertions are assessed by an LLM using environment-state information, whereas our runtime guards apply explicit predicates. Both approaches make feedback part of planning, and both raise the question our implementation turns on: what does a reported success establish?

For a robot team, grounding individual actions must be combined with allocation and coordination [10]. The task-allocation taxonomy distinguishes single- and multi-task robots, single- and multi-robot tasks, and instantaneous and time-extended assignment [11]. Our duplicate-carrier case concerns the assignment of a single-robot task. SMART-LLM [12] uses prompted task decomposition, coalition formation and allocation to construct a team plan. This makes robot selection part of language-level planning rather than an input assumed to be correct. RoCo [13] instead uses dialogue between robot-specific language agents to develop a joint plan, which is checked before a centralized multi-arm planner generates motion. These designs place coordination at

different points in the pipeline, but both need a connection between the proposed team behavior and its executor's capabilities; our duplicate-carrier and shared-destination cases examine that connection.

Formal planning makes constraints explicit. LaMMA-P [14] uses the Planning Domain Definition Language (PDDL) and heuristic search for heterogeneous teams. HiP-CL [15] translates instructions into a controlled language and then constructs a planning problem with spatial and resource constraints. LLM+P [16] translates a problem into PDDL and delegates search to a classical planner. LLM-Modulo [17] describes a broader pattern in which external verifiers evaluate proposals and provide feedback. Our checks cover a subset of the properties at that boundary. Temporal-logic mission planning can synthesize a controller with guarantees relative to a realizable specification and modeled environment assumptions [18].

CommandSwarm [19] checks generated behavior trees against allowed swarm primitives. Sangchai et al. [20] use structured tools or PDDL and let a person review the intermediate plan. Khatana et al. [21] separately ground candidate multi-robot plans into trajectories and predict inter-robot conflicts to guide replanning. Their geometric verifier checks trajectory conflicts. Our case study follows the mobile-fleet interface through assignment and goal rewrites, a static route rejection, and the evidence used to count mission completion.

Our study follows these architectural choices through execution in one implemented fleet. We examine which malformed plans are rejected, which assignments or destinations are rewritten, and which failures remain after those checks. The formation case shows how an accepted plan can still fail because of route geometry, while the completion cases distinguish component reports from the mission evaluator's ordered spatial conditions. This analysis characterizes the coverage and limits of the implemented checks. It does not compare our system's reliability with that of the approaches reviewed above.

3 System Overview

Figure 2 shows the operator-chat path. Level 1 turns a natural language command into a typed plan and applies interface checks. Level 2 coordinates the resulting fleet actions. Level 3 tracks the scheduled waypoints and executes the control commands.

The interface exposes four distinct correctness questions. Structural validity concerns admissible node types and fields. Task meaning concerns the assignments and goals implied by the operator's command. Geometric feasibility concerns whether robots or formations can traverse the required space. Evaluator completion concerns whether the specified pose-based events occur. No implication between these properties follows from the typed representation alone. Table 1 describes the implemented coverage and its limits; it is not a formal verification of system safety.

Simulation environment

Twenty differential-drive robots operate in Stage [22] on the `amongus` map (66.6×37.75 m, Fig. 3). The world file places five groups of four around their respective home locations. The number deployed is distinct from the number moving in any interval.




Fig. 2 Operator-chat path from a typed fleet plan through interface checks, fleet coordination, and per-robot execution

4 Level 1: Language Orchestration

Plan grammar

In the operator-chat channel, a response contains a natural-language reply and a plan tree in a JavaScript Object Notation (JSON) object. Four leaf types cover fleet actions — `mapf` (move a robot set to a goal set), `formation` (assemble and hold), `disband`, and `idle` (do nothing, with a reason, also the escalation channel) — and two containers, `sequence` and `parallel`, nest recursively. The following example shows the plan subtree:

```
{"type":"sequence","steps":[
 {"type":"mapf","robot_ids":[8,9,10,11],
  "goals":[[-8.7,-5.9],[-9.6,-5.9],
           [-8.7,-6.8],[-9.6,-6.8]]},
 {"type":"formation","formation_id":"column_8",
  "leader_ns":"robot_8",
  "follower_ns":["robot_9",
   "robot_10","robot_11"],
  "offsets_x":[-1.5,-3.0,-4.5],
  "offsets_y":[0,0,0]}]}
```

Table 1 Implemented checks and their observed scope

Property	Check in this implementation	Evidence and limit
Plan representation	Recursive node and field checks, with selected type coercions	E1 also checks case-specific requirements. Acceptance leaves other mission properties open.
Robot assignments	Active-formation membership and single-carrier rules	Single-carrier rule fired in two selected M2 runs.
Occupied goals	Chat-level goal adjustment and planner-level blocked-cell substitution	No chat rewrites in the 13 selected language runs. Both mechanisms appear in the additional M4 records.
Shared drop-off	Spread coincident goals for distinct carry tasks	Logged in three M3 runs. The design does not isolate its effect.
Formation assembly	Stage followers and check pose tolerances	M4 includes an assembled formation and a separate staging failure.
Formation route	Static path check with the planner's footprint approximation	M4 rejected a route at planning time. No pre-assembly check of the full oriented formation route.
Task completion	Pose samples in specified zones at 5 Hz, with pickup before drop-off	All 18 selected M2/M3 runs satisfy this evaluator. Physical transport and intent are outside the metric.
Repair and supervision	Execution remediation, verification repair and bounded mission supervision	One supervision pass per selected language run. No remediation or verification-repair attempts in that series.

The finite set of node types supports recursive validation and a JSON schema. These checks cover the implemented structural rules, not arbitrary task semantics or geometric feasibility.

Three channels and grounding

The reactive channel returns a wait, abort, or replan decision to a behavior-tree node on warning or error. The proactive observer can send a flat mode command to the behavior tree. The operator-chat channel uses the recursive plan grammar and the guards described here. E1 exercises offline generation for that grammar, and the language runs in E2 use the operator-chat path. That path can query live pose and task state and compute room placements through eight allowlisted tools.

Generation and runtime checks

E1 compares text generation with and without a response schema. Both modes parse the returned plan and apply case validators. The E2 operator chat instead enables a tool-calling loop. Enabling that loop allows an auxiliary tool call but does not require one. In both settings the plan is returned as JSON.

The operator-chat path validates node types and fields, coerces selected values, guards active-formation membership, adjusts occupied goals, and stages robots before assembly. The single-carrier rule removes a redundant pickup assignment when it can

identify the robot routed onward to the drop-off. The shared-drop-off rule spreads coincident destinations in eligible cases. Both transformations can change the action requested of a robot. The pose-based evaluator checks the original task zones after execution.

Execution feedback

The operator-chat implementation distinguishes three mechanisms: remediation after an execution error, repair informed by a post-execution state check, and mission supervision that can request additional work within configured limits. State verification reads robot poses and formation status. The results report which mechanisms were invoked in the selected runs.

5 Level 2: Fleet Coordination

MAPF backends

The PBS and LNS2 implementations accept robot identifiers and a goal for each robot through the same action interface. They publish scheduled waypoints to the robots. The simulation runs reported here use LNS2, which checks static reachability with its footprint model before planning.

Supporting components

A formation specification names a leader, followers and per-follower offsets in the leader's frame. The coordination layer excludes active followers from independent MAPF assignment and represents the group through the leader's enlarged planning footprint. This approximation is distinct from planning with the full, orientation-dependent group shape. BehaviorTree.CPP [23] runs the mission tree.

Operational meaning of task completion

The evaluator samples robot positions at 5 Hz. A visit task completes when a robot is observed within 1.5 m of its target. For a carry task, the first robot detected in the pickup zone becomes the evaluator's carrier. The same robot must subsequently be detected in the drop-off zone. One sample inside each zone is sufficient. This procedure can count a robot that passes through without stopping, and the recorded carrier may differ from the one named in the plan.

Pickup and drop-off are logical states. The evaluator checks neither physical load handling nor the full meaning of the operator's command. It continues to use the original zones if a guard rewrites a waypoint. A rewritten goal can therefore receive the same evaluator score while requiring different motion.

6 Level 3: Per-Robot Execution

Each robot runs a Robot Operating System 2 (ROS 2) Humble [24] Nav2 [25] stack with namespace substitution and staggered bring-up. The development record reports discovery and launch difficulties when starting twenty stacks simultaneously. Stage 2D was selected after Gazebo Harmonic did not provide a usable real-time factor in the

development setup. These are engineering observations, not controlled simulator or DDS comparisons.

Localization uses simulator-derived poses. Adaptive Monte Carlo localization (AMCL) is disabled. During development, scans from nearby robots caused difficulties with static-map localization; this motivated removing localization uncertainty from the case study. The experiments therefore do not test peer-aware localization or robustness to pose noise. A tuned CycloneDDS profile and a dynamic-blocker costmap plugin are part of the implementation, but their individual effects are not measured here.

7 Experimental Design

We report two complementary evaluations of the implemented system. The offline benchmark characterizes generated plans; the simulation campaign examines selected execution outcomes. Neither is a component-removal ablation.

E1 — offline plan validation

The benchmark has 44 cases in twelve categories covering navigation, parallel and sequential composition, formation, disbanding, idle, escalation and edge cases. Each reported model and decoding condition contains five scored attempts per case at temperature 0.1. The parser extracts the plan and applies structural checks. Case validators then test selected requirements such as robot identifiers, proximity to a specified destination, and step ordering. A pass means that the response satisfies those checks. No robots are run in E1.

Schema-off requests use unconstrained text generation and parse a JSON plan from the result. Schema-on requests pass the plan schema as the response format. Neither offline condition submits tool definitions. The local sweep used Ollama, a 16 GB RTX 5060 Ti, a 32,768-token context, and a 2,048-token output limit. The local manifest records partial CPU offload for Mistral Small 3.2. Hosted runs used OpenRouter with an 8,192-token output limit. These are comparisons of the logged configurations, which differ in model, serving stack, and sometimes provider or token budget.

Hosted transport errors were handled by rerunning all five attempts of the affected case and replacing that case's original records. The raw records log replacements for 18 schema-off and 44 schema-on Nemotron cases, nine cases in each 397B condition, and 17 schema-on hosted 9B cases. These cells can mix provider routes. Thus 220 is the number of scored records per cell. The harness, its prompt builders, per-case prompts, responses, and scoring scripts support reanalysis of the saved outputs. Exact model snapshots and complete per-request serving configurations are unavailable.

E2 — task-evaluator completion in simulation

M2 consists of four visit tasks and one carry task. M3 consists of six visit tasks and three carry tasks, two of which share a drop-off location (Fig. 3). The selected descriptive series contains five scripted M2 runs with fixed assignments, five M2 runs using hosted Qwen3.5-9B, five M2 runs using hosted Qwen3.5-397B-A17B (cell B), and three M3 runs using the 397B model (cell B-M3). The scripted driver uses the same

coordination and execution layers. Model, routing, allocation and software version vary across the reported cells.

Selection depended on outcome in B/M2. The development record reports that three original runs completed all five tasks, while runs `20260818_085836` and `20260818_090145` each stalled at 4/5. After the single-carrier guard was introduced, those two runs were replaced by `20260818_093216` and `20260818_093704`. The selected B/M2 cell thus combines three original successes and two successful repeats. The bags of the two superseded runs are absent from the public archive, so their scores are taken from the run history. The 18-run analysis estimates neither a campaign-wide completion rate nor a guard effect.

Table 2 Provenance and analysis populations for the simulation evidence

Series	Runs	Inclusion and evidence
Selected M2/M3	18	Four cells. Session IDs and base commits are recorded. All 18 worktrees were dirty. Thirteen runs have a language journal, of which eight have per-phase checkpoints.
Superseded B/M2	2	Two runs at 4/5 tasks replaced after a software change. The three original successes remain in the selected cell.
M3 before/after	2 + 3	Two separate pre-guard runs have bags and logs but no decision journal. The three post-guard runs are the B-M3 cell above.
M4 formation	4 recorded attempts	Two retained qualitative cases (`20260818_140918`, `20260819_073009`). A pilot (`20260818_135527`) stopped early and a 42 s recording (`20260819_072231`) with no motion was discarded. All are outside the selected series.

The archived session files and logs identify the included runs. A recorded base commit does not identify the uncommitted changes present in a run. The comparison uses the task evaluator recorded in `/tasks/state` and the target task list defined for each mission. In completed runs, makespan is the simulation-time interval from the first recorded task-state sample to the first sample at which the last target reaches done.

8 Results

The results are organized around observed boundary failures before the aggregate scores. Assignment and geometric cases address RQ2; qualitative completion-report mismatches address RQ3; the offline results characterize RQ1. Each source retains its own provenance and denominator.




Fig. 3 The `amongus` map (66.6 × 37.75 m, 0.05 m cells) and the eleven distinct 1.5 m zones used by the nine M3 tasks. Circles show the zone boundaries and center markers identify visit, pickup, and drop-off zones. Arrows link pickup and drop-off locations. Stars mark the M2 subset. Squares mark the home locations of the five groups of four robots

8.1 Assignment defects and shared-destination conflicts

The inspectable plans reveal an assignment-level defect relevant to RQ2. All 13 language runs retain a plan and a decision journal, but only eight also retain per-phase checkpoints; the five model-9b runs predate checkpointing and store a single record, so execution order is inspectable only for the later cells. Among the 13 generated plans, 5 carry the same assignment defect: the plan assigns two robots to carry a single item. In three model-9b runs the extra carrier is visible in the stored plan; in two cell-B runs the single-carrier guard had already removed it, and the defect is recorded only by the guard counter. An extra robot sent to the pickup can occupy space needed by the intended carrier. The count describes this inspected set, not the prevalence of defects across unseen missions.

Duplicate-carrier assignments

Three model-9b runs visibly route an extra robot to the pickup and still complete M2. In the two original incomplete B runs, the development record attributes the stall to robot 5 reaching the pickup before robot 1, which was assigned the drop-off leg. The guard later removed an extra pickup assignment in each of the two replacement runs. Both replacements completed M2. The guard counters establish the recorded

intervention. The successful uncorrected runs and the outcome-dependent selection limit what this comparison establishes about completion.

Shared-drop-off execution conflict

M3 assigns two carry tasks to the same drop-off center (Fig. 3). This conflict follows from the mission specification. Both archived pre-guard runs (`20260815_153035` and `20260815_154541`) complete 8/9 tasks. Each of the three B-M3 runs completes 9/9. In run `20260818_111548` the guard changed the common target $(-29.65, -2.85)$ m to $(-28.90, -2.85)$ m for robot 3 and $(-30.40, -2.85)$ m for robot 16. Both goals are 0.75 m from the specified center and inside the original evaluator zone. The logs show spreading in all three post-guard runs. The two series differ in software version and provider routing, and the pre-guard journals are absent. These records document the intervention and outcomes without isolating its effect.

8.2 Case study: an assembled formation with a rejected route

In the interactive M4 session `20260819_073009`, the operator asked for a column. The model returned `offsets_x=[0,0,0]` and `offsets_y=[1.5,-1.5,3.0]`, a line abreast with a 4.5 m span between the outer centers. The formation assembled at the generated offsets and reached stable status after 6.5 s. The logged fraction of broken samples was zero. On a subsequent move request, LNS2 reported that there was no static path for the leader under its enlarged footprint model.

This trace separates three checks. The plan passes structural validation, the generated offsets disagree with the requested geometry, and the planner rejects a route under its footprint approximation. The system does not check an oriented trajectory for the entire formation before assembly. The log therefore establishes rejection by the implemented planner for the requested start and goal. In a separate M4 run (`20260818_140918`), the same column request elicited `offsets_x=[-1.5,-3.0,-4.5]`. These two cases show variation in the generated offsets. They provide no estimate of its frequency.

8.3 Local action reports and mission conditions

The M4 run `20260818_140918` exposes a chain of failures during formation staging. A replan temporarily benched robot 0 and replaced the requested set with the smaller set of planned robots. The action later reported *All agents arrived* although robot 0 was still at its starting position. In a subsequent leg, the planner substituted a free cell for a blocked goal. The formation manager reported that robot 3 was 1.97 m from its required slot, outside its 0.50 m staging tolerance. The executor learned of the refusal only at the step timeout. These observations come from one development trace and are not counted as independent failures.

An arrival report describes the action that the component tracked. The same report can omit a requested robot or concern a substituted goal. The case motivates recording the original request, effective action and completion condition separately.

8.4 Offline plan validation results

Table 3 gives the E1 scores. In the local schema-off runs, the 9B configuration has the highest observed call-level rate (192/220). It leads the 24B and 14B configurations by 8.6 and 12.3 percentage points, respectively, calculated before rounding the displayed rates. Five repeats measure response variation on the same cases. For example, 154/220 responses pass for the local 4B model, while 41/44 cases have at least one pass in five tries.

The published scoring script assigns one diagnostic category per failed response by a fixed priority of error strings. Across the 1,100 local schema-off records, 259 fail. The categories include formation fields or staging (82), structure (81), goals (34), unparseable JSON (34), escalation reason (5), robot identifiers (1), and other validator messages (22). These are script labels: for example, a goal error can concern arity or the requested destination. For Mistral Small 3.2, the same offsets-arity message accounts for 20 of 47 failures, and the most frequent failed response is byte-identical across eight records. This is evidence of a recurring error, not of deterministic generation.

Table 3 Offline validation on 44 cases with five scored responses per case and condition. Call rate is the percentage of 220 responses that passed. Case rate is the percentage of 44 cases with at least one pass in five attempts. Model sizes are nominal; for mixture-of-experts models they are total/active parameters. n/d denotes an undisclosed size. A dash denotes an unreported condition

		Schema off		Schema on	
Model	Size	Call (%)	Case (%)	Call (%)	Case (%)
Local					
Qwen3.5-4B	4B	70.0	93.2	77.7	95.5
Gemma 3 12B	12B	71.4	72.7	—	—
Qwen2.5-14B	14B	75.0	81.8	75.5	81.8
Qwen3.5-9B	9B	87.3	95.5	19.1	22.7
Mistral Small 3.2	24B	78.6	81.8	—	—
Hosted					
Qwen3.5-9B	9B	90.5	97.7	51.4	61.4
Gemini 2.5 Flash	n/d	89.5	90.9	80.9	86.4
Nemotron 3 Ultra	550B/55B	90.5	97.7	88.6	95.5
Qwen3.5-397B-A17B	397B/17B	93.2	100.0	95.0	100.0

8.4.1 Decoding configurations

Call-level scores under schema constraints rise for the local 4B and 14B configurations and fall for the local 9B configuration. Hosted differences also vary in direction. For example, the 397B/17B score rises from 93.2% to 95.0% while Gemini falls from 89.5% to 80.9%. In the hosted comparison, the provider and its support for the response schema can affect both the output and whether a request succeeds. These observations

describe the tested configurations. They do not identify a general decoding or model-size effect.

8.5 Task-evaluator completion in the selected series

Every included run satisfies all of its target task conditions (Table 4). In the original B/M2 series, 3/5 runs completed all tasks according to the run history. The two incomplete runs reached 4/5. After the two replacements, 5/5 runs in the selected B/M2 cell complete all tasks. The table reports the selected runs' outcomes and timing.

Table 4 Selected M2/M3 runs. Task counts are pose-based outcomes per run. Makespan is the mean and sample standard deviation (SD) in simulation seconds. Language-loop time is the mean cumulative wall-clock duration recorded in the decision journals, including any auxiliary calls or retries within the loop

Cell	Mission	Full runs	Tasks per run	Makespan (s) mean ± SD	Language loop (s)
no-LLM	M2	5/5	5/5	203.5 ± 10.6	0
model-9b	M2	5/5	5/5	252.2 ± 26.6	9.5
B	M2	5/5	5/5	260.0 ± 16.5	31.6
B-M3	M3	3/3	9/9	587.7 ± 67.0	51.2

Timing and fleet activity

The M2 mean makespan ranges from 203.5 to 260.0 simulation seconds. The mean language-loop duration ranges from 0 to 31.6 wall-clock seconds. The analysis uses the final cumulative counter for the unique mission record in each language run. The intervals have different clocks and start events, and allocation and software version vary across the cells. We report them separately. Odometry records show that 9–10 distinct robots per selected run traveled at least 0.5 m over the recording. This measures activity over the run, without estimating peak simultaneous motion.

Observed mechanism use

None of the 13 selected language runs invoked remediation or verification repair, and none triggered the active-formation guard or chat-level occupancy rewrites. Each logged one supervision step. Twelve runs made no auxiliary calls. One B-M3 run (`20260818_113030`) called `list_tasks` once and `verify_plan_execution_state` twice. The two additional M4 records contain 10 and 33 auxiliary calls. The available context differs across missions, and the records do not establish why the model chose to call a tool.

9 Discussion

For RQ1, the offline benchmark distinguishes failures to parse a plan from failures on selected requirements for robot selection, goals, and step composition. Differences across decoding settings include both gains and losses. The scored responses describe the tested cases and configurations. They have no paired mission outcomes for estimating the predictive value of structural validity.

For RQ2, the carry cases distinguish a redundant pickup assignment from a shared drop-off requested by the operator. The first can be corrected by removing a pickup assignment. The second can be addressed by adjusting the two destinations within the original zone. A formation can also satisfy the structural and assembly checks while its generated shape differs from the request and the planner rejects the route. These cases show which properties require checks beyond the plan representation.

For RQ3, a component can report success for a reduced robot set or substituted waypoint while the original action remains incomplete. The evaluator provides separate evidence of the specified spatial events. The evidence does not establish physical load transfer, collision safety, or full preservation of intent. The cases motivate logging the original action, its transformed action, the component report, and the evaluator outcome as separate records.

10 Limitations

The study uses one Stage map, simulator-derived poses, two main mission specifications and a small, selected run series. Five language runs have only one journal record each. Dirty worktrees prevent exact reconstruction from the recorded commit IDs, and the superseded B/M2 outcomes come from the development record. The M3 comparison changes software version and provider routing. A controlled guard comparison would require fixed conditions and a prespecified record of all attempts.

E1 repeats 44 case designs. Exact model revisions and complete serving settings are unavailable, and hosted transport replacements can change the provider. E2 uses a task-state interval in simulation time and separately records language-loop duration in wall-clock time. It does not measure operator-to-completion latency or isolate the cost of language orchestration.

The task metric samples zone presence. It does not measure stopping, load handling, or independent collision and intent outcomes. No fleet-size sweep or peak concurrency measurement is available. The observed formation route rejection applies to the planner's footprint model. Inactive repair counters and qualitative development observations do not establish reliability or failure rates.

11 Conclusion

This case study documents how structural validity, task meaning, route feasibility and evaluator completion differ in a typed-plan interface for robot fleets. Offline validation finds recurring errors in formation fields, structure and goals. Simulation traces show how assignment guards, goal transformations and planner checks act on accepted plans, and how a component's report can omit part of the original request. The results

characterize the implemented checks and the cases in which they were exercised. They provide specific conditions to test in future controlled evaluations.

Statements and Declarations

Competing Interests

The authors have no relevant financial or non-financial interests to disclose.

Funding

[Funding statement to be confirmed with the project supervisor before submission. The work was carried out as part of the authors' employment at the Institute of Robotics and Computer Vision, Innopolis University; whether it constitutes external funding is for the institution to state.]

Ethics Approval

Not applicable. This study did not involve human participants or animals.

Consent to Participate

Not applicable.

Consent for Publication

Not applicable.

Data Availability

The benchmark outputs, session metadata, logs, derived metrics, and analysis scripts are in the results directory at the archived repository revision. The recorded bags are available in the public results archive, `llm_swarm_results_2026-11-04.tar.zst` (135 MB). Its SHA-256 checksum is `3866f1fce6254243986b0052e2fc0d6039eadc351e10c460f4ed0feec69f740d`. A per-file manifest accompanies the archive. With the archive unpacked, run the repository's `paper/results/scripts/analyze_sessions.py` with `--sessions` pointing to the unpacked `results/e2_mission_series` and `--json` to export per-run metrics. The two superseded B/M2 bags are absent. Their scores and replacement identifiers are documented in the run history.

Code Availability

The ROS 2 stack, benchmark harness, and analysis scripts are available at repository revision `cab6312`. This revision records the analysis and documentation. It does not capture the uncommitted changes in the historical simulation runs. Licence declarations, where present, are in the individual packages.

Author Contributions

A.T.: Conceptualization, Methodology, Software, Investigation, Data curation, Writing—original draft, Writing—review and editing, Project administration. D.V.: Software, Investigation, Writing—review and editing. E.S.: Conceptualization, Methodology, Software, Investigation, Supervision, Project administration, Writing—review and editing. S.B.: Software, Investigation, Visualization. A.Mal.: Software, Validation. A.Malol.: Supervision, Conceptualization, Writing—review and editing.

References

[1] Ichter, B., Brohan, A., Chebotar, Y., Finn, C., Hausman, K., Herzog, A., Ho, D., Ibarz, J., Irpan, A., Jang, E., Julian, R., Kalashnikov, D., Levine, S., Lu, Y., Parada, C., Rao, K., Sermanet, P., Toshev, A.T., Vanhoucke, V., Xia, F., Xiao, T., Xu, P., Yan, M., Brown, N., Ahn, M., Cortes, O., Sievers, N., Tan, C., Xu, S., Reyes, D., Rettinghouse, J., Quiambao, J., Pastor, P., Luu, L., Lee, K.-H., Kuang, Y., Jesmonth, S., Joshi, N.J., Jeffrey, K., Ruano, R.J., Hsu, J., Gopalakrishnan, K., David, B., Zeng, A., Fu, C.K.: Do as I can, not as I say: Grounding language in robotic affordances. In: Proceedings of the 6th Conference on Robot Learning (CoRL). Proceedings of Machine Learning Research, vol. 205, pp. 287–318 (2023). https://proceedings.mlr.press/v205/ichter23a.html

[2] Liang, J., Huang, W., Xia, F., Xu, P., Hausman, K., Ichter, B., Florence, P., Zeng, A.: Code as policies: Language model programs for embodied control. In: 2023 IEEE International Conference on Robotics and Automation (ICRA), pp. 9493–9500 (2023). https://doi.org/10.1109/ICRA48891.2023.10160591

[3] Chen, W., Koenig, S., Dilkina, B.: Why Solving Multi-agent Path Finding with Large Language Model has not Succeeded Yet. arXiv:2401.03630 (2024). https://doi.org/10.48550/arXiv.2401.03630

[4] Sharon, G., Stern, R., Felner, A., Sturtevant, N.R.: Conflict-based search for optimal multi-agent pathfinding. Artificial Intelligence **219**, 40–66 (2015) https://doi.org/10.1016/j.artint.2014.11.006

[5] Ma, H., Harabor, D., Stuckey, P.J., Li, J., Koenig, S.: Searching with consistent prioritization for multi-agent path finding. In: Proceedings of the AAAI Conference on Artificial Intelligence, vol. 33, pp. 7643–7650 (2019). https://doi.org/10.1609/aaai.v33i01.33017643

[6] Li, J., Chen, Z., Harabor, D., Stuckey, P.J., Koenig, S.: MAPF-LNS2: Fast repairing for multi-agent path finding via large neighborhood search. In: Proceedings of the AAAI Conference on Artificial Intelligence, vol. 36, pp. 10256–10265 (2022). https://doi.org/10.1609/aaai.v36i9.21266

[7] Valmeekam, K., Marquez, M., Olmo, A., Sreedharan, S., Kambhampati, S.: PlanBench: An extensible benchmark for evaluating large language models on planning and reasoning about change. In: Advances in Neural Information Processing Systems 36 (Datasets and Benchmarks Track) (2023). https://papers.neurips.cc/paper_files/paper/2023/hash/7a92bcdede88c7afd108072faf5485c8-Abstract-Datasets_and_Benchmarks.html

[8] Huang, W., Xia, F., Xiao, T., Chan, H., Liang, J., Florence, P., Zeng, A., Tompson, J., Mordatch, I., Chebotar, Y., Sermanet, P., Jackson, T., Brown, N., Luu, L., Levine, S., Hausman, K., Ichter, B.: Inner monologue: Embodied reasoning through planning with language models. In: Proceedings of the 6th Conference on Robot Learning (CoRL). Proceedings of Machine Learning Research, vol. 205, pp. 1769–1782 (2023). https://proceedings.mlr.press/v205/huang23c.html

[9] Singh, I., Blukis, V., Mousavian, A., Goyal, A., Xu, D., Tremblay, J., Fox, D., Thomason, J., Garg, A.: ProgPrompt: Generating situated robot task plans using large language models. In: 2023 IEEE International Conference on Robotics and Automation (ICRA), pp. 11523–11530 (2023). https://doi.org/10.1109/ICRA48891.2023.10161317

[10] Li, P., An, Z., Abrar, S., Zhou, L.: Large language models for multi-robot systems: a survey. Autonomous Robots **50**, 30 (2026) https://doi.org/10.1007/s10514-026-10257-4

[11] Gerkey, B.P., Matarić, M.J.: A formal analysis and taxonomy of task allocation in multi-robot systems. The International Journal of Robotics Research **23**(9), 939–954 (2004) https://doi.org/10.1177/0278364904045564

[12] Kannan, S.S., Venkatesh, V.L.N., Min, B.-C.: SMART-LLM: Smart multi-agent robot task planning using large language models. In: 2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), pp. 12140–12147 (2024). https://doi.org/10.1109/IROS58592.2024.10802322

[13] Mandi, Z., Jain, S., Song, S.: RoCo: Dialectic multi-robot collaboration with large language models. In: 2024 IEEE International Conference on Robotics and Automation (ICRA), pp. 286–299 (2024). https://doi.org/10.1109/ICRA57147.2024.10610855

[14] Zhang, X., Qin, H., Wang, F., Dong, Y., Li, J.: LaMMA-P: Generalizable multi-agent long-horizon task allocation and planning with LM-driven PDDL planner. In: 2025 IEEE International Conference on Robotics and Automation (ICRA), p. 10221 (2025). https://doi.org/10.1109/ICRA55743.2025.11127951 . IEEE

[15] Tran, D., Arefin, M., Ghosh, B., Rahmani, A., He, H.: HiP-CL: High-level planning based on common language for multi-robot teaming. Human-Centric Intelligent Systems **6**, 93–106 (2026) https://doi.org/10.1007/s44230-025-00130-5

[16] Liu, B., Jiang, Y., Zhang, X., Liu, Q., Zhang, S., Biswas, J., Stone, P.: LLM+P: Empowering Large Language Models with Optimal Planning Proficiency. arXiv:2304.11477 (2023). https://doi.org/10.48550/arXiv.2304.11477

[17] Kambhampati, S., Valmeekam, K., Guan, L., Verma, M., Stechly, K., Bhambri, S., Saldyt, L.P., B Murthy, A.: Position: LLMs can't plan, but can help planning in LLM-Modulo frameworks. In: Proceedings of the 41st International Conference on Machine Learning. Proceedings of Machine Learning Research, vol. 235, pp. 22895–22907 (2024). https://proceedings.mlr.press/v235/kambhampati24a.html

[18] Kress-Gazit, H., Fainekos, G.E., Pappas, G.J.: Temporal-logic-based reactive mission and motion planning. IEEE Transactions on Robotics **25**(6), 1370–1381 (2009) https://doi.org/10.1109/TRO.2009.2030225

[19] Majid, M., Majid, A.Y.: CommandSwarm: Safety-Aware Natural Language-to-Behavior-Tree Generation for Robotic Swarms. arXiv:2605.07764 (2026). https://doi.org/10.48550/arXiv.2605.07764

[20] Sangchai, K., Boonpun, M., Kraipetchara, W., Garcia, P.: Symbolic wrappers enable precise human in the loop operation for large action models. Discover Robotics **2**, 8 (2026) https://doi.org/10.1007/s44430-026-00023-7

[21] Khatana, V., Song, Z., Hovakimyan, N., Voulgaris, P.: Verifier-Mediated Multi-LLM Coordination for Multi-Robot Path Planning. arXiv:2610.12761 (2026). https://doi.org/10.48550/arXiv.2610.12761

[22] Vaughan, R.: Massively multi-robot simulation in stage. Swarm Intelligence **2**(2–4), 189–208 (2008) https://doi.org/10.1007/s11721-008-0014-4

[23] Faconti, D.: BehaviorTree.CPP. Open-source library, accessed 2026 (2024). https://www.behaviortree.dev

[24] Macenski, S., Foote, T., Gerkey, B., Lalancette, C., Woodall, W.: Robot operating system 2: Design, architecture, and uses in the wild. Science Robotics **7**(66), 6074 (2022) https://doi.org/10.1126/scirobotics.abm6074

[25] Macenski, S., Martín, F., White, R., Clavero, J.G.: The marathon 2: A navigation system. In: 2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), pp. 2718–2725 (2020). https://doi.org/10.1109/IROS45743.2020.9341207