



SINGLE-PHASE
HYBRID INVERTER

HI-8K-SL

-  Equipped with GEN port, compatible with diesel generators, smart loads, and AC coupling.
-  Color touch screen (4.3"/7" optional).
-  Integrated 0-export function.
-  Compatibility with lead-acid and Li-ion batteries, supports various brands of lithium batteries.
-  Supports PV array input up to 160% of rated inverter power.
-  Low startup voltage threshold, wide operating voltage range.

Technical Data	HI-8K-SL
INPUT DC (PV SIDE)	
Max. PV access power	16kW
Max. PV input power	12.8kW
Max. PV input voltage	600V
Nominal input voltage	360V
MPPT working voltage range	80V-500V
Number of independent MPPT / strings per MPPT	4/1
MPPT max. current	4*20A
Start-up voltage	100V
OUTPUT/INPUT AC (GRID SIDE)	
Nominal apparent power	8kW
Max. apparent power	8.8kVA
Nominal voltage	220V/230V
Nominal frequency	50Hz/60Hz
Rated current	36.4A/34.7A
Max. current	40A
Power factor	-0.8~+0.8 (adjustable)
THDi	<3% (Nominal Output)
Grid system pattern	L+N+PE
Max. AC current from utility grid	100A
OUTPUT AC (BACK-UP)	
Nominal output power	8kW
Max. output apparent power	8.8kVA
Nominal output voltage	220V/230V
Nominal output frequency	50Hz/60Hz
Output THDV	<3%
Automatic switch time	<10ms
BATTERY	
Battery type	Li-ion/Lead-acid
Battery voltage range	40V-60V
Max. charging/discharging current	190A
Charging strategy for Li-ion battery	Self-adaption to BMS
Charging strategy for Lead-acid battery	Three-stage
EFFICIENCY	
Max. MPPT efficiency	99.9%
Europe efficiency	97.5%
Max. battery to load efficiency	94.5%
PROTECTION	
Anti islanding protection	Yes
Insulation impedance protection	Yes
RCD detection	Yes
PV reverse polarity protection	Yes
Output over voltage protection	Yes
Output over current protection	Yes
GENERAL DATA	
Dimensions (L/W/H) in mm	425/290/660
Weight	39kg
Operation temperature range	-25°C~+60°C
Heat dissipation mode	Smart cooling
IP Class	IP 66
Maximum altitude	4000m
Self-Consumption night	<3W
Topology	Trans
FEATURES	
LCD display	Yes
Communication interface	WiFi/4G/USB/CAN/RS485