



Kinetics of thermal degradation of intumescent flame-retardant spirophosphates

N DAVID MATHAN¹, D PONRAJU² and C T VIJAYAKUMAR^{3,*}

¹Department of Chemistry, Nadar Saraswathi College of Engineering and Technology, Theni 625531, India

²Safety Engineering Division, Indira Gandhi Centre for Atomic Research, Kalpakkam 603102, India

³Department of Polymer Technology, Kamaraj College of Engineering and Technology, K. Vellakulam 625701, India

*Author for correspondence (ctvijay22@yahoo.com)

MS received 13 March 2020; accepted 15 September 2020

Abstract. The thermal degradation behaviour of various spirophosphates synthesized using SDP (phenol), SDOC (*o*-cresol), SDMC (*m*-cresol), SDPC (*p*-cresol), SDDMP (2,4-dimethylphenol) and SDTMP (2,4,6-trimethylphenol) with 3,9-dichloro-2,4,8,10-tetraoxa-3,9-diphosphaspiro-[5,5]-undecane-3,9-dioxide (SDCDP) are investigated using thermogravimetric analyzer. The spirophosphates show multistage degradations in the temperature range 180–550°C. The second stage of degradation is more prominent and the substituent effect is clearly reflected at this stage of degradation. The compound SDP showed superior performance since it has the greatest char yield value (44%) and LOI value (27%). The model free kinetic methods of Flynn-Wall-Ozawa and Vyazovkin methods are used to calculate the apparent energy of activation for the thermal degradation (E_a -D) of these spirophosphates. The material SDTMP showed the highest E_a -D values.

Keywords. Spirophosphates; intumescence; thermogravimetric analysis; degradation kinetics; flame retardants.

1. Introduction

Polymeric materials (due to light weight, durability, mechanical performance and resistance towards chemicals, etc.) are advantageously used in many fields (household products, defence materials, aerospace parts and marine parts, etc.). However, the use of polymeric materials is restricted due to its fire risk properties [1,2]. Usually the incorporation of flame-retardant additives or the development of flame-retardant coatings for polymer is the convenient method to impart polymer flame retardancy [3,4]. At present, research has been focused on to develop environmental friendly flame-retardant systems. The patents and literature on environmental friendly flame retardants illustrated the importance of phosphorus-based flame retardants and indicated as very good alternate for halogenated flame retardants. The research on phosphorus-based flame retardants is originated with ammonium polyphosphate (APP) [5].

Phosphorus-based intumescent systems are attracted by many researchers, since it forms nonoxidizable multi-cellular charred layer in the fire condition. The formed char insulate and protect the materials of interest. The acid source, carbonific and spumific agents required to formulate

the intumescent system has more than one functional group. Thus the mechanism of intumescence is complex in nature [6–9].

Previously, the authors synthesized a series of spirophosphates by reacting spirodichlorodiphosphate with phenol, *o*-cresol, *m*-cresol, *p*-cresol, 2,6-dimethylphenol and 2,4,6-trimethylphenol [10,11]. The materials were pyrolysed at 500°C for a constant period (5 s) and the volatile products evolved were analysed using GC-MS. From these results attempts were made to elucidate the degradation mechanism of spirophosphates, which will add to the present understanding of the intumescent behaviour of phosphorus-based compounds. The research carried out on various spirophosphates has been reviewed [12].

It is well known that the flame retardancy of the materials also depends on the thermal stability, degradation rate, char forming rate and char yield. Thermogravimetric (TG) analysis is one among the standard procedures to investigate the thermal stability and the degradation of a material. Getting appropriate data and calculations will provide the kinetic triplets, the apparent activation energy for thermal degradation (E_a -D), the frequency factor (A) and the reaction model $f(\alpha)$. As per the recommendations of Flynn-Wall-Ozawa (FWO) [13,14] and Vyazovkin (VYZ) [15], multiple heating

Electronic supplementary material: The online version of this article (<https://doi.org/10.1007/s12034-020-02317-x>) contains supplementary material, which is available to authorized users.

Published online: 05 February 2021




Dr. C. MATHALAI SUNDARAM, M.E., M.B.A., Ph.D.,
Principal
Nadar Saraswathi College of
Engineering and Technology
Vadapudupatti, Theni-625 531.