

ECAP615

Programming in Java



Harjinder Kaur
Assistant Professor

Learning Outcomes



After this lecture, you will be able to

- Learn the basic concept PreparedStatement and ResultSetMetaData interface.
- Understand the various methods of PreparedStatement and ResultSetMetaData interface.
- Implementation of PreparedStatement and ResultSetMetaData interface.

PreparedStatement interface

- The PreparedStatement interface is a subinterface of Statement.
- It is a pre-compiled SQL statement.
- Prepared Statement objects have some useful additional features than Statement objects.
- Instead of hard coding queries, PreparedStatement object provides a feature to execute a parameterized query.

PreparedStatement interface

Example

- `String sql="insert into tablename values(?,?,?)";`

PreparedStatement Interface

- Why use PreparedStatement?
 - Improves performance
- How to get the instance of PreparedStatement?

Syntax:

- ```
public PreparedStatement prepareStatement(String
query)throws SQLException{
```

# PreparedStatement Interface

The following are the steps to use PreparedStatement :

## 1. Create Connection to Database

Connection Con

```
=DriverManager.getConnection(path,username,password)
```

## 2. Prepare Statement

PreparedStatement Stmt;

```
Stmt = Con.prepareStatement(select * from tablename where
columnname > ?);
```

# PreparedStatement Interface

The following are the steps to use PreparedStatement :

3. Set parameter values for type and position

```
Stmt.setInt(1,20);
```

```
Stmt.setString(2,"ABC");
```

4. Execute the Query

```
ResultSet Rs= Stmt.executeQuery();
```

# Advantages of PreparedStatement

- When PreparedStatement is created, the SQL query is passed as a parameter.
- It contains a pre-compiled SQL query.
- We can use the same PreparedStatement and supply with different parameters at the time of execution.



# Methods of PreparedStatement interface

- `setInt(int, int)`
- `setString(int, string)`
- `setFloat(int, float)`
- `setDouble(int, double)`
- `executeUpdate()`
- `executeQuery()`

# ResultSetMetaData Interface

- If you want to get metadata of a table, ResultSetMetaData interface is useful because it provides methods to get metadata from the ResultSet object.
- The getMetaData() method of ResultSet interface returns the object of ResultSetMetaData.

Syntax:

- `public ResultSetMetaData getMetaData()throws SQLException`

# Methods of ResultSetMetaData Interface

- `getColumnCount()`
- `getColumnLabel()`
- `getColumnName()`
- `getTableName()`

A blue scroll graphic with a black outline, featuring a vertical strip on the left and a small circular detail at the top right corner. The text "That's all for now..." is written in a dark blue, sans-serif font across the center of the scroll.

That's all for now...