

# INTRODUCTION TO BIG DATA

ECAP456

**Dr. Rajni Bhalla**  
Associate Professor


# Learning Outcomes




After this lecture, you will be able to

- learn how to format name node on hadoop master
- learn how to start all hadoop services.

# Introduction



# Multiple Namenodes/Namespaces



# Federation Configuration

Daemon	Configuration Parameter
Namenode	dfs.namenode.rpc-address dfs.namenode.servicerpc-address dfs.namenode.http-address dfs.namenode.https-address dfs.namenode.keytab.file dfs.namenode.name.dir dfs.namenode.edits.dir dfs.namenode.checkpoint.dir dfs.namenode.checkpoint.edits.dir
Secondary Namenode	dfs.namenode.secondary.http-address dfs.secondary.namenode.keytab.file
BackupNode	dfs.namenode.backup.address dfs.secondary.namenode.keytab.file

# Format a namenode

```
hdfs namenode -format [-clusterId <cluster_id>]
```

# Format a namenode

```
# su Hadoop
```

```
$ cd /opt/hadoop/hadoop
```

```
$ bin/hadoop namenode -format
```

# Reason for Hadoop Namenode - Format

- By default the namenode location will be at `"/tmp/hadoop-myuser/dfs/name"`
- While you formatting the namenode, this file location was cleared.



# Reason for Hadoop Namenode - Format

To change the namenode location add the following properties **At hdfs-site.xml**

```
<property>
```

```
<name>dfs.namenode.name.dir</name>
```

```
<value>file:/search/data/dfs/namenode</value>
```

```
</property>
```

```
<property>
```

# Reason for Hadoop Namenode - Format

To change the namenode location add the following

```
<name>dfs.datanode.data.dir</name>
```

```
<value>file:/search/data/dfs/datanode</value>
```

```
</property>
```

# Starting Hadoop Services.

```
cd ~/hadoop/sbin
```

- **start-dfs.sh**
  - stop-dfs.sh
  - start-mapred.sh
  - stop-mapred.sh
  - start-all.sh
  - stop-all.sh

# Starting Hadoop Services.

```
cd ~/hadoop/sbin
```

- **start-dfs.sh**
- **stop-dfs.sh**
- start-mapred.sh
- stop-mapred.sh
- start-all.sh
- stop-all.sh

# Starting Hadoop Services.

```
cd ~/hadoop/sbin
```

- **start-dfs.sh**
- **stop-dfs.sh**
- **start-mapred.sh**
- stop-mapred.sh
- start-all.sh
- stop-all.sh

# Starting Hadoop Services.

```
cd ~/hadoop/sbin
```

- **start-dfs.sh**
- **stop-dfs.sh**
- **start-mapred.sh**
- **stop-mapred.sh**
- start-all.sh
- stop-all.sh

# Starting Hadoop Services.

```
cd ~/hadoop/sbin
```

- start-dfs.sh
- stop-dfs.sh
- start-mapred.sh
- stop-mapred.sh
- start-all.sh
- stop-all.sh

# Starting Hadoop Services.

```
cd ~/hadoop/sbin
```

- `start-dfs.sh`
- `stop-dfs.sh`
- `start-mapred.sh`
- `stop-mapred.sh`
- `start-all.sh`
- `stop-all.sh`





**That's all for now...**