

# INTRODUCTION TO BIG DATA

ECAP456

**Dr. Rajni Bhalla**  
Associate Professor


# Learning Outcomes



After this lecture, you will be able to


- learn anatomy of a MapReduce Job Run

# Introduction



# Introduction

## How MapReduce Works



# Introduction

```
20/24 17:42:42 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
20/24 17:42:42 INFO hdfs.DefaultFileSystemFactory: Ignoring IOException setting permission for path "file:/tmp/hadoop-hvitesh/mapred/staging/Vitesh216083226/.staging/" failed to set permissions of path: \tmp\hadoop-hvitesh\mapred\staging\Vitesh216083226\, staging to 0700
20/24 17:42:42 INFO hdfs.DefaultFileSystemFactory: Ignoring IOException setting permission for path "file:/tmp/hadoop-hvitesh/mapred/staging/Vitesh216083226/.staging/job_local216083226_0000" failed to set permissions of path: \tmp\hadoop-hvitesh\mapred\staging\Vitesh216083226\, staging\job_local216083226_0000 to 0700
20/24 17:42:42 WARN mapred.JobClient: No job for file set. User classes may not be found. See JobConf(Class) or JobConf#setJar(String).
20/24 17:42:42 INFO mapred.LocalJobRunner: Total input paths to process : 1
20/24 17:42:42 WARN mapred.JobClient: Ignoring IOException setting permission for path "file:/tmp/hadoop-hvitesh/mapred/staging/Vitesh216083226/.staging/job_local216083226_0000/job.split": Failed to set permissions of path: \tmp\hadoop-hvitesh\mapred\staging\Vitesh216083226\, staging\job_local216083226_0000\job.split to 0644
20/24 17:42:42 INFO mapred.JobClient: Running Job: job_local216083226_0001
20/24 17:42:42 INFO mapred.LocalJobRunner: Waiting for map tasks
20/24 17:42:42 INFO mapred.LocalJobRunner: Starting task: attempt_local216083226_0001_m_0000000_0
20/24 17:42:42 INFO mapred.Task: Using ResourceCalculatorPlugin: null
20/24 17:42:42 INFO mapred.MapTask: Processing split: file:/C:/Users/Vitesh/workspace/Hadoop Experiments/rmrut.txt:0+368313
20/24 17:42:42 INFO mapred.MapTask: io.sort.mb = 100
20/24 17:42:42 INFO mapred.MapTask: data buffer = 7969176/99612720
20/24 17:42:42 INFO mapred.MapTask: record buffer = 162144/127680
20/24 17:42:42 INFO mapred.MapTask: Starting flush of map output
20/24 17:42:42 INFO mapred.MapTask: Finished split 0
20/24 17:42:42 INFO mapred.Task: Task:attempt_local216083226_0001_m_0000000_0 is done. And is in the process of committing
20/24 17:42:42 INFO mapred.LocalJobRunner:
20/24 17:42:42 INFO mapred.Task: Task 'attempt_local216083226_0001_m_0000000_0' done.
20/24 17:42:42 INFO mapred.LocalJobRunner: Finishing task: attempt_local216083226_0001_m_0000000_0
20/24 17:42:42 INFO mapred.LocalJobRunner: Map task executor complete.
20/24 17:42:42 INFO mapred.Task: Using ResourceCalculatorPlugin: null
20/24 17:42:42 INFO mapred.LocalJobRunner:
20/24 17:42:42 INFO mapred.Reducer: Merging 1 sorted segments
20/24 17:42:42 INFO mapred.Reducer: Down to the last merge-pass, with 1 segments left of total size: 148794 bytes
20/24 17:42:42 INFO mapred.Task: Task:attempt_local216083226_0001_r_0000000_0 is done. And is in the process of committing
20/24 17:42:42 INFO mapred.LocalJobRunner:
20/24 17:42:42 INFO mapred.Task: Task attempt_local216083226_0001_r_0000000_0 is allowed to commit now
20/24 17:42:42 INFO mapred.Task: Saved output of task 'attempt_local216083226_0001_r_0000000_0' to surl
20/24 17:42:42 INFO mapred.LocalJobRunner: reduce > reduce
20/24 17:42:42 INFO mapred.Task: Task 'attempt_local216083226_0001_r_0000000_0' done.
20/24 17:42:42 INFO mapred.JobClient: map 100% reduce 100%
20/24 17:42:42 INFO mapred.JobClient: Job complete: job_local216083226_0001
20/24 17:42:42 INFO mapred.JobClient: Counter: 17
20/24 17:42:42 INFO mapred.JobClient:   File Output Format Counters
20/24 17:42:42 INFO mapred.JobClient:     Bytes Written:109186
20/24 17:42:42 INFO mapred.JobClient:   File Input Format Counters
20/24 17:42:42 INFO mapred.JobClient:     Bytes Read:209311
20/24 17:42:42 INFO mapred.JobClient:   Filesystem Counters
20/24 17:42:42 INFO mapred.JobClient:     FILE_BYTES_READ:950824
20/24 17:42:42 INFO mapred.JobClient:     FILE_BYTES_WRITTEN:509928
20/24 17:42:42 INFO mapred.JobClient:   Map-Reduce Framework
20/24 17:42:42 INFO mapred.JobClient:     Reduce input records:10797
20/24 17:42:42 INFO mapred.JobClient:     Map output materialized bytes:148794
20/24 17:42:42 INFO mapred.JobClient:     Combine output records:10797
20/24 17:42:42 INFO mapred.JobClient:     Map input records:-1163
```

## Job Execution and job Completion

# Introduction

```
wordCountWithCombiner.java 25 wordCount.java
// Learning MapReduce by Nitesh Jain
import org.apache.hadoop.fs.Path;

public class WordCountWithCombiner extends Configured
implements Tool{

    @Override
    public int run(String[] args) throws Exception {
        Configuration conf = getConf();
        Job job = new Job(conf, "MyJob");

        job.setJarByClass(WordCount.class);
        job.setJobName("Word Count With Combiners");

        FileInputFormat.addInputPath(job, new Path(args[0]));
        FileOutputFormat.setOutputPath(job, new Path(args[1]));

        job.setMapperClass(WordCountMapper.class);
        job.setCombinerClass(WordCountReducer.class);
        job.setReducerClass(WordCountReducer.class);

        job.setOutputKeyClass(Text.class);
        job.setOutputValueClass(IntWritable.class);

        return job.waitForCompletion(true) ? 0 : 1;
    }

    public static void main(String[] args) throws Exception {
        int exitCode = ToolRunner.run(new Configuration(), new WordCountWithCombiner(), args);
        System.exit(exitCode);
    }
}
```

Last statement in run method



# Introduction

```
WordCountWithCombiner.java WordCount.java
// Learning MapReduce by Nitesh Jain
import org.apache.hadoop.fs.Path;

public class WordCount {

    public static void main(String[] args) throws Exception {
        if (args.length < 2) {
            System.err.println("Usage: WordCount <input path> <output path>");
            System.exit(-1);
        }

        Job job = new Job();
        job.setJarByClass(WordCount.class);
        job.setJobName("Word Count");

        FileInputFormat.addInputPath(job, new Path(args[0]));
        FileOutputFormat.setOutputPath(job, new Path(args[1]));

        job.setMapperClass(WordCountMapper.class);
        job.setReducerClass(WordCountReducer.class);

        job.setOutputKeyClass(Text.class);
        job.setOutputValueClass(IntWritable.class);

        System.exit(job.waitForCompletion(true) ? 0 : 1);
    }
}
```

Last line in main method

# What happened behind the scene?

- **Jobs gets submitted by WaitforCompletion().**
- Properties that decide the job run:
  - “mapred.job.tracker” (for 0.22 release)
    - This is set in mapred-site.xml
    - Default is local.
    - Set as host:part
  - “mapreduce.framework.name” (for .23 and later(eg 1.X.X)):
    - Can be set to local,classic or yarn



# What happened behind the scene?

- Jobs gets submitted by `WaitforCompletion()`.
- Properties that decide the job run:
  - “`mapred.job.tracker`” (for 0.22 release)
    - This is set in `mapred-site.xml`
    - Default is local.
    - Set as `host:part`
  - “`mapreduce.framework.name`” (for .23 and later(eg 1.X.X)):
    - Can be set to `local,classic` or `yarn`

# What happened behind the scene?

- Jobs gets submitted by `WaitforCompletion()`.
- Properties that decide the job run:
  - “`mapred.job.tracker`” (for 0.22 release)
    - This is set in `mapred-site.xml`
    - Default is local.
    - Set as `host:part`
  - “`mapreduce.framework.name`” (for .23 and later(eg 1.X.X)):
    - Can be set to `local,classic` or `yarn`

# What happened behind the scene?

- Jobs gets submitted by `WaitforCompletion()`.
- Properties that decide the job run:
  - “`mapred.job.tracker`” (for 0.22 release)
    - This is set in `mapred-site.xml`
    - Default is local.
    - Set as `host:part`
  - “`mapreduce.framework.name`” (for .23 and later(eg 1.X.X)):
    - Can be set to `local,classic` or `yarn`

# What happened behind the scene?

- Jobs gets submitted by `WaitforCompletion()`.
- Properties that decide the job run:
  - “`mapred.job.tracker`” (for 0.22 release)
    - This is set in `mapred-site.xml`
    - Default is local.
    - Set as `host:part`
  - “`mapreduce.framework.name`” (for .23 and later(eg 1.X.X)):
    - Can be set to `local,classic` or `yarn`

# What happened behind the scene?

- Jobs gets submitted by `WaitforCompletion()`.
- Properties that decide the job run:
  - “`mapred.job.tracker`” (for 0.22 release)
    - This is set in `mapred-site.xml`
    - Default is local.
    - Set as `host:part`
  - “`mapreduce.framework.name`” (for .23 and later(eg 1.X.X)):
    - Can be set to `local,classic` or `yarn`

# What happened behind the scene?


- Jobs gets submitted by `WaitforCompletion()`.
- Properties that decide the job run:
  - “`mapred.job.tracker`” (for 0.22 release)
    - This is set in `mapred-site.xml`
    - Default is local.
    - Set as `host:part`
  - “`mapreduce.framework.name`” (for .23 and later(eg 1.X.X)):
    - Can be set to `local,classic` or `yarn`

# What happened behind the scene?


- Jobs gets submitted by `WaitforCompletion()`.
- Properties that decide the job run:
  - “`mapred.job.tracker`” (for 0.22 release)
    - This is set in `mapred-site.xml`
    - Default is local.
    - Set as `host:part`
  - “`mapreduce.framework.name`” (for .23 and later(eg 1.X.X)):
    - Can be set to `local`, `classic` or `yarn`




# Classic MapReduce - Overview



# Classic MapReduce - Overview



# Classic MapReduce - Overview




# Classic MapReduce - Overview



1. Client submits the MapReduce job.


# Classic MapReduce - Overview



1. Client submits the MapReduce job.

2. Job tracker co-ordinate the job run

# Classic MapReduce - Overview




1. Client submits the MapReduce job.

2. Job tracker co-ordinate the job run

3. Task tracker run the map and reduce tasks.

# Classic MapReduce - Overview



1. Client submits the MapReduce job.


2. Job tracker co-ordinate the job run

3. Task tracker run the map and reduce tasks.

4. Task tracker sends progress status



# Classic MapReduce - Overview




1. Client submits the MapReduce job.

2. Job tracker co-ordinate the job run

3. Task tracker run the map and reduce tasks.

4. Task tracker sends progress status

5. Job Tracker sends progress status and completion message to client.




# Components of MapReduce

1. Client
2. Yarn node manager
3. Yarn resource manager
4. MapReduce application master
5. Distributed Filesystem

# Components of MapReduce

1. Client
2. Yarn node manager
3. Yarn resource manager
4. MapReduce application master
5. Distributed Filesystem



# How to submit Job?

- use the `submit()`
- `submitJobInternal()`
- `waitForCompletion()`
- reports the progress to the console.
- job counters are displayed

# How to submit Job?

- use the `submit()`
- `submitJobInternal()`
- `waitForCompletion()`
- reports the progress to the console.
- job counters are displayed

# How to submit Job?

- use the `submit()`
- `submitJobInternal()`
- `waitForCompletion()`
- reports the progress to the console.
- job counters are displayed



# How to submit Job?

- use the `submit()`
- `submitJobInternal()`
- `waitForCompletion()`
- reports the progress to the console.
- job counters are displayed

# How to submit Job?

- use the `submit()`
- `submitJobInternal()`
- `waitForCompletion()`
- reports the progress to the console.
- job counters are displayed

# Processes implemented by JobSubmitter for submitting the Job :

Processes implemented by **JobSubmitter** for submitting the Job :

1. The resource manager asks for a new application ID that is used for MapReduce Job ID.
2. Output specification of the job is checked.
3. If the splits cannot be computed, it computes the input splits for the job
4. Resources needed to run the job is copied

# Processes implemented by JobSubmitter for submitting the Job :

Processes implemented by **JobSubmitter** for submitting the Job :

1. The resource manager asks for a new application ID that is used for MapReduce Job ID.
2. Output specification of the job is checked.
3. If the splits cannot be computed, it computes the input splits for the job
4. Resources needed to run the job is copied

# Processes implemented by JobSubmitter for submitting the Job :

Processes implemented by **JobSubmitter** for submitting the Job :

1. The resource manager asks for a new application ID that is used for MapReduce Job ID.
2. Output specification of the job is checked.
3. If the splits cannot be computed, it computes the input splits for the job
4. Resources needed to run the job is copied

# Processes implemented by JobSubmitter for submitting the Job :

Processes implemented by **JobSubmitter** for submitting the Job :

1. The resource manager asks for a new application ID that is used for MapReduce Job ID.
2. Output specification of the job is checked.
3. If the splits cannot be computed, it computes the input splits for the job
4. Resources needed to run the job is copied

# Processes implemented by JobSubmitter for submitting the Job :

Processes implemented by **JobSubmitter** for submitting the Job :

5. It copies job **JAR** with a high replication factor, which is controlled by **mapreduce.client.submit.file.replication** property.
6. By calling `submitApplication()`, submits the job on the resource manager.

# Processes implemented by JobSubmitter for submitting the Job :

Processes implemented by **JobSubmitter** for submitting the Job :

5. It copies job **JAR** with a high replication factor, which is controlled by **mapreduce.client.submit.file.replication** property.
6. By calling **submitApplication()**, submits the job on the resource manager.





**That's all for now...**