

Launchpad (Solana)

Smart Contract Audit Report

Prepared for DAgora



Date Issued:	Aug 21, 2023
Project ID:	AUDIT2022052
Version:	v1.0
Confidentiality Level:	Public



Report Information

Project ID	AUDIT2022052
Version	v1.0
Client	DAgora
Project	Launchpad (Solana)
Auditor(s)	Peeraphut Punsuwan Puttimet Thammasaeng Ronnachai Chaipha
Author(s)	Ronnachai Chaipha
Reviewer	Natsasit Jirathammanuwat
Confidentiality Level	Public

Version History

Version	Date	Description	Author(s)
1.0	Aug 21, 2023	Full report	Ronnachai Chaipha

Contact Information

Company	Inspex
Phone	(+66) 90 888 7186
Telegram	t.me/inspexco
Email	audit@inspex.co

Table of Contents

1. Executive Summary	1
1.1. Audit Result	1
1.2. Disclaimer	1
2. Project Overview	2
2.1. Project Introduction	2
2.2. Scope	3
3. Methodology	4
3.1. Test Categories	4
3.2. Audit Items	5
3.3. Risk Rating	7
4. Summary of Findings	8
5. Detailed Findings Information	10
5.1. Upgradability of Solana Program	10
5.2. Account Collision	11
5.3. Improper Token Withdrawal from Launchpads	19
5.4. Improper Launchpad Setting	23
5.5. Missing of Launchpad Register Validation	30
5.6. Insecure Source of Randomness	37
5.7. Improper Fee Enforcement	44
5.8. Smart Contract with Unpublished Source Code	50
6. Appendix	51
6.1. About Inspex	51

1. Executive Summary

As requested by DAgora, Inspex team conducted an audit to verify the security posture of the Launchpad (Solana) smart contracts between Nov 1, 2022 and Nov 3, 2022. During the audit, Inspex team examined all smart contracts and the overall operation within the scope to understand the overview of Launchpad (Solana) smart contracts. Static code analysis, dynamic analysis, and manual review were done in conjunction to identify smart contract vulnerabilities together with technical & business logic flaws that may be exposed to the potential risk of the platform and the ecosystem. Practical recommendations are provided according to each vulnerability found and should be followed to remediate the issue.

1.1. Audit Result

In the initial audit, Inspex found 2 high, 2 medium, 4 low-severity issues. With the project team's prompt response, 2 high, 2 medium, 2 low-severity issues were resolved or mitigated in the reassessment, while 2 low-severity issues were acknowledged by the team. Therefore, Inspex trusts that Launchpad (Solana) smart contracts have sufficient protections to be safe for public use. However, in the long run, Inspex suggests resolving all issues found in this report.



1.2. Disclaimer

This security audit is not produced to supplant any other type of assessment and does not guarantee the discovery of all security vulnerabilities within the scope of the assessment. However, we warrant that this audit is conducted with goodwill, professional approach, and competence. Since an assessment from one single party cannot be confirmed to cover all possible issues within the smart contract(s), Inspex suggests conducting multiple independent assessments to minimize the risks. Lastly, nothing contained in this audit report should be considered as investment advice.

2. Project Overview

2.1. Project Introduction

DAGora Launchpad is a project that allows the user who wants to have their launchpad contracts created to do so on their own. These launchpads are used to offer NFT redemption to their platforms' users. It also includes all necessary functions to support the business design for the launchpad creators. In exchange, there will be a fee collected for the DAGora.

Scope Information:

Project Name	Launchpad (Solana)
Website	https://dagora.xyz/
Smart Contract Type	Solana Program
Chain	Solana
Programming Language	Rust
Category	NFT, Launchpad

Audit Information:

Audit Method	Whitebox
Audit Date	Nov 1, 2022 - Nov 3, 2022
Reassessment Date	Nov 25, 2022

The audit method can be categorized into two types depending on the assessment targets provided:

1. **Whitebox:** The complete source code of the smart contracts are provided for the assessment.
2. **Blackbox:** Only the bytecodes of the smart contracts are provided for the assessment.

2.2. Scope

The following smart contracts were audited and reassessed by Inspex in detail:

Initial Audit

Contract	Bytecode SHA256 Hash
dagora_launchpad	d34565f92018ef42811bbb3913ee3b4aa4b063a02bf05bba14b00892f55cc1c4

Reassessment


Contract	Bytecode SHA256 Hash
dagora_launchpad	ce3dced175524c4c1730fc65b2148528c7aa8e3e7b96f28a91503319b6d44de3

As the DAgora team has decided not to publish the source code to protect their intellectual property, the users should compare the bytecode hashes with the smart contracts before interacting with them to make sure that they are the same with the contracts audited.

3. Methodology

Inspex conducts the following procedure to enhance the security level of our clients' smart contracts:

1. **Pre-Auditing:** Getting to understand the overall operations of the related smart contracts, checking for readiness, and preparing for the auditing
2. **Auditing:** Inspecting the smart contracts using automated analysis tools and manual analysis by a team of professionals
3. **First Deliverable and Consulting:** Delivering a preliminary report on the findings with suggestions on how to remediate those issues and providing consultation
4. **Reassessment:** Verifying the status of the issues and whether there are any other complications in the fixes applied
5. **Final Deliverable:** Providing a full report with the detailed status of each issue



3.1. Test Categories

Inspex smart contract auditing methodology consists of both automated testing with scanning tools and manual testing by experienced testers. We have categorized the tests into 3 categories as follows:

1. **General Smart Contract Vulnerability (General)** - Smart contracts are analyzed automatically using static code analysis tools for general smart contract coding bugs, which are then verified manually to remove all false positives generated.
2. **Advanced Smart Contract Vulnerability (Advanced)** - The workflow, logic, and the actual behavior of the smart contracts are manually analyzed in-depth to determine any flaws that can cause technical or business damage to the smart contracts or the users of the smart contracts.
3. **Smart Contract Best Practice (Best Practice)** - The code of smart contracts is then analyzed from the development perspective, providing suggestions to improve the overall code quality using standardized best practices.

3.2. Audit Items

The testing items checked are based on our Smart Contract Security Testing Guide (SCSTG) v1.0 (https://github.com/InspexCo/SCSTG/releases/download/v1.0/SCSTG_v1.0.pdf) which covers most prevalent risks in smart contracts. The latest version of the document can also be found at <https://inspex.gitbook.io/testing-guide/>.

The following audit items were checked during the auditing activity:

Testing Category	Testing Items
1. Architecture and Design	1.1. Proper measures should be used to control the modifications of smart contract logic 1.2. The latest stable compiler version should be used 1.3. The circuit breaker mechanism should not prevent users from withdrawing their funds 1.4. The smart contract source code should be publicly available 1.5. State variables should not be unfairly controlled by privileged accounts 1.6. Least privilege principle should be used for the rights of each role
2. Access Control	2.1. Contract self-destruct should not be done by unauthorized actors 2.2. Contract ownership should not be modifiable by unauthorized actors 2.3. Access control should be defined and enforced for each actor roles 2.4. Authentication measures must be able to correctly identify the user 2.5. Smart contract initialization should be done only once by an authorized party 2.6. tx.origin should not be used for authorization
3. Error Handling and Logging	3.1. Function return values should be checked to handle different results 3.2. Privileged functions or modifications of critical states should be logged 3.3. Modifier should not skip function execution without reverting
4. Business Logic	4.1. The business logic implementation should correspond to the business design 4.2. Measures should be implemented to prevent undesired effects from the ordering of transactions 4.3. msg.value should not be used in loop iteration
5. Blockchain Data	5.1. Result from random value generation should not be predictable 5.2. Spot price should not be used as a data source for price oracles 5.3. Timestamp should not be used to execute critical functions 5.4. Plain sensitive data should not be stored on-chain 5.5. Modification of array state should not be done by value 5.6. State variable should not be used without being initialized

Testing Category	Testing Items
6. External Components	<ul style="list-style-type: none">6.1. Unknown external components should not be invoked6.2. Funds should not be approved or transferred to unknown accounts6.3. Reentrant calling should not negatively affect the contract states6.4. Vulnerable or outdated components should not be used in the smart contract6.5. Deprecated components that have no longer been supported should not be used in the smart contract6.6. Delegatecall should not be used on untrusted contracts
7. Arithmetic	<ul style="list-style-type: none">7.1. Values should be checked before performing arithmetic operations to prevent overflows and underflows7.2. Explicit conversion of types should be checked to prevent unexpected results7.3. Integer division should not be done before multiplication to prevent loss of precision
8. Denial of Services	<ul style="list-style-type: none">8.1. State changing functions that loop over unbounded data structures should not be used8.2. Unexpected revert should not make the whole smart contract unusable8.3. Strict equalities should not cause the function to be unusable
9. Best Practices	<ul style="list-style-type: none">9.1. State and function visibility should be explicitly labeled9.2. Token implementation should comply with the standard specification9.3. Floating pragma version should not be used9.4. Builtin symbols should not be shadowed9.5. Functions that are never called internally should not have public visibility9.6. Assert statement should not be used for validating common conditions

3.3. Risk Rating

OWASP Risk Rating Methodology (https://owasp.org/www-community/OWASP_Risk_Rating_Methodology) is used to determine the severity of each issue with the following criteria:

- **Likelihood:** a measure of how likely this vulnerability is to be uncovered and exploited by an attacker
- **Impact:** a measure of the damage caused by a successful attack

Both likelihood and impact can be categorized into three levels: **Low**, **Medium**, and **High**.


Severity is the overall risk of the issue. It can be categorized into five levels: **Very Low**, **Low**, **Medium**, **High**, and **Critical**. It is calculated from the combination of likelihood and impact factors using the matrix below. The severity of findings with no likelihood or impact would be categorized as **Info**.

Likelihood Impact	Likelihood		
	Low	Medium	High
Low	Very Low	Low	Medium
Medium	Low	Medium	High
High	Medium	High	Critical


4. Summary of Findings

The following charts show the number of the issues found during the assessment and the issues acknowledged in the reassessment, categorized into three categories: **General**, **Advanced**, and **Best Practice**.

Assessment:



Reassessment:



The statuses of the issues are defined as follows:

Status	Description
Resolved	The issue has been resolved and has no further complications.
Resolved *	The issue has been resolved with mitigations and clarifications. For the clarification or mitigation detail, please refer to Chapter 5.
Acknowledged	The issue's risk has been acknowledged and accepted.
No Security Impact	The best practice recommendation has been acknowledged.

The information and status of each issue can be found in the following table:

ID	Title	Category	Severity	Status
IDX-001	Upgradability of Solana Program	General	High	Resolved *
IDX-002	Account Collision	Advanced	High	Resolved
IDX-003	Improper Token Withdrawal from Launchpads	Advanced	Medium	Resolved
IDX-004	Improper Launchpad Setting	Advanced	Medium	Resolved
IDX-005	Missing of Launchpad Register Validation	Advanced	Low	Resolved
IDX-006	Insecure Source of Randomness	Advanced	Low	Acknowledged
IDX-007	Improper Fee Enforcement	Advanced	Low	Resolved
IDX-008	Smart Contract with Unpublished Source Code	General	Low	Acknowledged

* The mitigations or clarifications by DAgora can be found in Chapter 5.

5. Detailed Findings Information

5.1. Upgradability of Solana Program

ID	IDX-001
Target	dagora_launchpad
Category	General Smart Contract Vulnerability
CWE	CWE-284: Improper Access Control
Risk	<p>Severity: High</p> <p>Impact: High The logic of the affected programs can be arbitrarily changed. This allows the upgrade authority to change the logic of the program in favor to the platform, e.g., transferring the users' funds to the platform owner's account.</p> <p>Likelihood: Medium Only the program upgrade authority can redeploy the program to the same program address; however, there is no restriction to prevent the authority from inserting malicious logic.</p>
Status	<p>Resolved *</p> <p>The DAGora team has mitigated this issue by confirming that the upgrade authority will be a multisig account controlled by multiple trusted parties.</p>

5.1.1. Description

Programs on Solana can be deployed through the upgradable BPF loader to make them upgradable, allowing the program's upgrade authority to redeploy the program with the new logic, bug fixes, or upgrades to the same program address.

However, there is no restriction on how and when the program will be upgraded. This opens up an attack surface on the program, allowing the upgrade authority to redeploy the program with malicious logic and gain unfair benefits from the users, for example, transferring funds out from the users' accounts.

5.1.2. Remediation

Inspex suggests deploying the program as an immutable program to prevent the program logic from being modified.

However, if the upgradability is needed, Inspex suggests mitigating this issue by the following options:

- Using a multisig account controlled by multiple trusted parties as the upgrade authority
- Implementing a community-run governance to control the redeployment of the program

5.2. Account Collision

ID	IDX-002
Target	dagora_launchpad
Category	Advanced Smart Contract Vulnerability
CWE	CWE-840: Business Logic Errors
Risk	Severity: High Impact: High The whitelisted users will be unable to register on the mintable launchpad. Likelihood: Medium It is likely to happen. Since the attacker can use the users' address as a seed when claiming the NFT from a mintable launchpad to prevent the whitelisted users from the registration process in the launchpad.
Status	Resolved The DAGora team has resolved this issue as suggested by adding the seed constant for each account type.

5.2.1. Description

The `claim_mintable_launchpad()` function can be used to claim the NFT by passing the `nft_mint` account derived by the `seeds` parameter at line 339.

contexts.rs

```
289 #[derive(Accounts)]
290 #[instruction(seeds: Vec<u8>)]
291 pub struct ClaimMintableLaunchpadContext<'info> {
292     #[account(mut)]
293     pub user: Signer<'info>,
294
295     pub mintable_launchpad: Account<'info, MintableLaunchpad>,
296
297     /// CHECK: skip
298     #[account(
299         mut,
300         address = get_launchpad_authority(mintable_launchpad.key()).0
301     )]
302     pub launchpad_authority: AccountInfo<'info>,
303
304     #[account(
305         mut,
306         seeds = [
```

```

307     user.to_account_info().key().as_ref(),
308     mintable_launchpad.key().as_ref()
309 ],
310     bump = user_profile.nonce,
311 )]
312 pub user_profile: Account<'info, UserProfile>,
313
314 /// CHECK: checked by address
315 #[account(
316     mut,
317     address = mintable_launchpad.collection_mint
318 )]
319 pub collection_mint: AccountInfo<'info>,
320
321 /// CHECK: checked by address
322 #[account(
323     mut,
324     address = find_metadata_account(&collection_mint.key()).0
325 )]
326 pub collection_metadata: AccountInfo<'info>,
327
328 /// CHECK: checked by address
329 #[account(
330     mut,
331     address = find_master_edition_account(&collection_mint.key()).0
332 )]
333 pub collection_master_edition: AccountInfo<'info>,
334
335 /// CHECK: checked by seeds
336 #[account(
337     mut,
338     seeds = [
339         seeds.as_ref()
340     ],
341     bump
342 )]
343 pub nft_mint: AccountInfo<'info>,
344 ...

```

The `claim_mintable_launchpad()` function will create the NFT account in the `mintable_launchpad`. `claim_nft()` function and the `nft_mint` account will be passed as the `nft_mint_account` in line 370 as shown below:

lib.rs

```

347 pub fn claim_mintable_launchpad(
348     ctx: Context<ClaimMintableLaunchpadContext>,

```

```

349     seeds: Vec<u8>,
350 ) -> Result<()> {
351     let user = &mut ctx.accounts.user;
352     let mintable_launchpad = &ctx.accounts.mintable_launchpad;
353     let launchpad_authority = &ctx.accounts.launchpad_authority;
354     let user_profile = &mut ctx.accounts.user_profile;
355     let collection_metadata = &ctx.accounts.collection_metadata;
356     let collection_mint = &ctx.accounts.collection_mint;
357     let collection_master_edition = &ctx.accounts.collection_master_edition;
358     let nft_mint = &ctx.accounts.nft_mint;
359     let receipt_account = &ctx.accounts.receipt_account;
360     let token_metadata = &ctx.accounts.token_metadata;
361     let ata_program = &ctx.accounts.ata_program;
362     let token_program = &ctx.accounts.token_program;
363     let system_program = &ctx.accounts.system_program;
364     let sysvar_program = &ctx.accounts.sysvar_program;
365
366     let launchpad_pubkey = &mintable_launchpad.to_account_info().key();
367
368     user_profile.before_claim()?;
369
370     mintable_launchpad.claim_nft(
371         launchpad_pubkey,
372         seeds,
373         user,
374         nft_mint,
375         launchpad_authority,
376         collection_metadata,
377         collection_mint,
378         collection_master_edition,
379         receipt_account,
380         token_metadata,
381         ata_program,
382         token_program,
383         system_program,
384         sysvar_program,
385     )?;
386
387     emit!(ClaimLaunchpadEvent {
388         nft_mint: nft_mint.key()
389     });
390
391     Ok(())
392 }

```

In the `mintable_launchpad.claim_nft()` function, the `nft_mint_account` account is passed to the `create_account()` function as the `to_pubkey` parameter, as shown below in line 192.

states.rs

```
190 create_account(  
191     user,  
192     nft_mint_account,  
193     sysvar_program.minimum_balance(82),  
194     82,  
195     token_program,  
196     &[nft_signer_seeds],  
197 )?;
```

The `create_account()` function is called to create an account for the NFT at the address of the `to_pubkey` account.

utils.rs

```
259 pub fn create_account<'info>(  
260     from_pubkey: &AccountInfo<'info>,  
261     to_pubkey: &AccountInfo<'info>,  
262     lamports: u64,  
263     space: u64,  
264     owner: &AccountInfo<'info>,  
265     signer_seeds: &[&[&[u8]]]  
266 ) -> Result<()> {  
267     let create_account_instruction = system_instruction::create_account(  
268         &from_pubkey.key(),  
269         &to_pubkey.key(),  
270         lamports,  
271         space,  
272         &owner.key(),  
273     );  
274  
275     if signer_seeds.is_empty() {  
276         solana_program::program::invoke(  
277             &create_account_instruction,  
278             &[  
279                 from_pubkey.clone(),  
280                 to_pubkey.clone()  
281             ]  
282         )?;  
283     } else {  
284         solana_program::program::invoke_signed(  
285             &create_account_instruction,  
286             &[  
287                 from_pubkey.clone(),  
288                 to_pubkey.clone()  
289             ],  
290             signer_seeds
```

```

291     }?;
292 }
293
294     Ok(())
295 }

```

After the `claim_mintable_launchpad()` function, the `nft_mint` address will be used for the minted NFT.

When the attacker uses the victim's address combined with the target launchpad's address as a `seeds` parameter of the `claim_mintable_launchpad()` function, the NFT account will be created at the same address as the `user_profile` account which created from the `create_user_profile()` function as shown below in lines 133-140.

contexts.rs

```

122 #[derive(Accounts)]
123 pub struct CreateUserProfileContext<'info> {
124     #[account(mut)]
125     pub user: Signer<'info>,
126
127     /// CHECK: we check later
128     pub launchpad: AccountInfo<'info>,
129
130     #[account(
131         init,
132         seeds = [
133             user.to_account_info().key().as_ref(),
134             launchpad.key().as_ref()
135         ],
136         bump,
137         payer = user,
138         space = 8 + UserProfile::LEN
139     )]
140     pub user_profile: Account<'info, UserProfile>,
141
142     pub system_program: Program<'info, System>
143 }

```

Due to the account collision, the whitelisted users will be unable to register in both mintable and transferable launchpads.

5.2.2. Remediation

Inspex suggests including the seed's prefix in the PDA account creation in order to ensure that each account's address is unique from any other.

For example, adding the `b"USER_PROFILE"` prefix to the seed of the `user_profile` creation as shown in line 133.

contexts.rs

```

122 #[derive(Accounts)]
123 pub struct CreateUserProfileContext<'info> {
124     #[account(mut)]
125     pub user: Signer<'info>,
126
127     /// CHECK: we check later
128     pub launchpad: AccountInfo<'info>,
129
130     #[account(
131         init,
132         seeds = [
133             b"USER_PROFILE",
134             user.to_account_info().key().as_ref(),
135             launchpad.key().as_ref()
136         ],
137         bump,
138         payer = user,
139         space = 8 + UserProfile::LEN
140     )]
141     pub user_profile: Account<'info, UserProfile>,
142
143     pub system_program: Program<'info, System>
144 }

```

Adding the `b"MINTABLE_LAUNCHPAD"` prefix to the seed of the `nft_mint` creation as shown in line 339.

contexts.rs

```

289 #[derive(Accounts)]
290 #[instruction(seeds: Vec<u8>)]
291 pub struct ClaimMintableLaunchpadContext<'info> {
292     #[account(mut)]
293     pub user: Signer<'info>,
294
295     pub mintable_launchpad: Account<'info, MintableLaunchpad>,
296
297     /// CHECK: skip
298     #[account(
299         mut,
300         address = get_launchpad_authority(mintable_launchpad.key()).0
301     )]
302     pub launchpad_authority: AccountInfo<'info>,
303
304     #[account(
305         mut,
306         seeds = [
307             user.to_account_info().key().as_ref(),

```

```
308     mintable_launchpad.key().as_ref()
309 ],
310     bump = user_profile.nonce,
311 )]
312 pub user_profile: Account<'info, UserProfile>,
313
314 /// CHECK: checked by address
315 #[account(
316     mut,
317     address = mintable_launchpad.collection_mint
318 )]
319 pub collection_mint: AccountInfo<'info>,
320
321 /// CHECK: checked by address
322 #[account(
323     mut,
324     address = find_metadata_account(&collection_mint.key()).0
325 )]
326 pub collection_metadata: AccountInfo<'info>,
327
328 /// CHECK: checked by address
329 #[account(
330     mut,
331     address = find_master_edition_account(&collection_mint.key()).0
332 )]
333 pub collection_master_edition: AccountInfo<'info>,
334
335 /// CHECK: checked by seeds
336 #[account(
337     mut,
338     seeds = [
339         b"MINTABLE_LAUNCHPAD",
340         seeds.as_ref()
341     ],
342     bump
343 )]
344 pub nft_mint: AccountInfo<'info>,
345
346 /// CHECK: skip
347 #[account(mut)]
348 pub receipt_account: AccountInfo<'info>,
349
350 /// CHECK: skip
351 #[account(
352     mut,
353     address = find_metadata_account(&nft_mint.key()).0
354 )]
```

Remember to add the seed prefix to every context that uses the `user_profile` account, for example, at line 156.

contexts.rs

```
145 #[derive(Accounts)]
146 pub struct RegisterMintableLaunchpadContext<'info> {
147     #[account(mut)]
148     pub user: Signer<'info>,
149
150     #[account(mut)]
151     pub mintable_launchpad: Account<'info, MintableLaunchpad>,
152
153     #[account(
154         mut,
155         seeds = [
156             b"USER_PROFILE",
157             user.to_account_info().key().as_ref(),
158             mintable_launchpad.to_account_info().key().as_ref()
159         ],
160         bump = user_profile.nonce,
161         constraint = !user_profile.is_registered @ErrorCode::Registered
162     )]
163     pub user_profile: Account<'info, UserProfile>,
164 }
```

5.3. Improper Token Withdrawal from Launchpads

ID	IDX-003
Target	dagora_launchpad
Category	Advanced Smart Contract Vulnerability
CWE	CWE-284: Improper Access Control
Risk	<p>Severity: Medium</p> <p>Impact: High The launchpad's owner can withdraw the NFT from the launchpad at any time. This results in the users not being able to claim the NFT from the launchpad.</p> <p>Likelihood: Low There is nothing to prevent the withdrawal from being done; however, this action can only be done by the launchpad's owner, which is set by the platform's owner.</p>
Status	<p>Resolved</p> <p>The DAGora team has resolved this issue as suggested by adding a mechanism that only allows the launchpad's owner to be able to withdraw before or after redemption time.</p>

5.3.1. Description

In the DAGora launchpad project, both the `withdraw_token_from_mintable_launchpad()` and the `withdraw_token_from_transferable_launchpad()` functions are used by the launchpad's owner to withdraw the leftover tokens from the launchpad.

lib.rs

```

508 pub fn withdraw_token_from_mintable_launchpad(
509     ctx: Context<WithdrawTokenFromMintableLaunchpadContext>,
510     _token_mint: Pubkey,
511     amount: u64,
512 ) -> Result<> {
513     let mintable_launchpad = &ctx.accounts.mintable_launchpad;
514     let launchpad_authority = &ctx.accounts.launchpad_authority;
515     let launchpad_token_account = &ctx.accounts.launchpad_token_account;
516     let owner_token_account = &ctx.accounts.owner_token_account;
517
518     let launchpad_pubkey = &mintable_launchpad.to_account_info().key();
519     let (_, authority_nonce): (Pubkey, u8) =
520     get_launchpad_authority(launchpad_pubkey.clone());
521
522     let seeds: [&[_]] = [&launchpad_pubkey.as_ref(), &authority_nonce];
523     transfer_token(

```

```
524     launchpad_authority,  
525     launchpad_token_account,  
526     owner_token_account,  
527     amount,  
528     &[seeds],  
529     )?;  
530     Ok(())  
531 }  
532  
533 pub fn withdraw_token_from_transferable_launchpad(  
534     ctx: Context<WithdrawTokenFromTransferableLaunchpadContext>,  
535     _nft_mint: Pubkey,  
536     amount: u64,  
537 ) -> Result<()> {  
538     let transferable_launchpad = &ctx.accounts.transferable_launchpad;  
539     let launchpad_authority = &ctx.accounts.launchpad_authority;  
540     let launchpad_token_account = &ctx.accounts.launchpad_token_account;  
541     let owner_token_account = &ctx.accounts.owner_token_account;  
542  
543     let launchpad_pubkey = &transferable_launchpad.to_account_info().key();  
544     let (_, authority_nonce): (Pubkey, u8) =  
545     get_launchpad_authority(launchpad_pubkey.clone());  
546  
547     let seeds: &[&[_]] = &[launchpad_pubkey.as_ref(), &[authority_nonce]];  
548  
549     transfer_token(  
550         launchpad_authority,  
551         launchpad_token_account,  
552         owner_token_account,  
553         amount,  
554         &[seeds],  
555     )?;  
556     Ok(())  
557 }
```

However, there is currently no constraint to prevent the token withdrawal before users claim the token.

5.3.2. Remediation

Inspex suggest adding validation to prevent the launchpad's owner from withdrawing the tokens before the claiming duration has ended, For example as shown below in lines 513-519 and 544-550:

lib.rs

```
508 pub fn withdraw_token_from_mintable_launchpad(  
509     ctx: Context<WithdrawTokenFromMintableLaunchpadContext>,  
510     _token_mint: Pubkey,  
511     amount: u64,
```

```

512 ) -> Result<()> {
513     let mintable_launchpad = &mut ctx.accounts.mintable_launchpad;
514     let current_time = Clock::get().unwrap().unix_timestamp;
515     let duration = 604800; // a week
516     require!(
517         current_time >=
518         mintable_launchpad.redeem_end_timestamp.checked_add(duration).unwrap(),
519         ErrorCode::InvalidWithdrawTime
520     );
521     let launchpad_authority = &ctx.accounts.launchpad_authority;
522     let launchpad_token_account = &ctx.accounts.launchpad_token_account;
523     let owner_token_account = &ctx.accounts.owner_token_account;
524     let launchpad_pubkey = &mintable_launchpad.to_account_info().key();
525     let (_, authority_nonce): (Pubkey, u8) =
526     get_launchpad_authority(launchpad_pubkey.clone());
527     let seeds: [&[_]] = [&launchpad_pubkey.as_ref(), &authority_nonce];
528
529     transfer_token(
530         launchpad_authority,
531         launchpad_token_account,
532         owner_token_account,
533         amount,
534         &seeds,
535     )?;
536     Ok(())
537 }
538
539 pub fn withdraw_token_from_transferable_launchpad(
540     ctx: Context<WithdrawTokenFromTransferableLaunchpadContext>,
541     _nft_mint: Pubkey,
542     amount: u64,
543 ) -> Result<()> {
544     let transferable_launchpad = &mut ctx.accounts.transferable_launchpad;
545     let current_time = Clock::get().unwrap().unix_timestamp;
546     let duration = 604800; // a week
547     require!(
548         current_time >=
549         transferable_launchpad.get_launchpad_core().redeem_end_timestamp.checked_add(du
550         ration).unwrap(),
551         ErrorCode::InvalidWithdrawTime
552     );
553     let launchpad_authority = &ctx.accounts.launchpad_authority;
554     let launchpad_token_account = &ctx.accounts.launchpad_token_account;
555     let owner_token_account = &ctx.accounts.owner_token_account;

```



```
555     let launchpad_pubkey = &transferable_launchpad.to_account_info().key();
556     let (_, authority_nonce): (Pubkey, u8) =
get_launchpad_authority(launchpad_pubkey.clone());
557
558     let seeds: &[&[_]] = &[launchpad_pubkey.as_ref(), &[authority_nonce]];
559
560     transfer_token(
561         launchpad_authority,
562         launchpad_token_account,
563         owner_token_account,
564         amount,
565         &[seeds],
566     )?;
567     Ok(())
568 }
```

5.4. Improper Launchpad Setting

ID	IDX-004
Target	dagora_launchpad
Category	Advanced Smart Contract Vulnerability
CWE	CWE-840: Business Logic Errors
Risk	<p>Severity: Medium</p> <p>Impact: Medium</p> <p>When the duration of the launchpad begins, the launchpad's owner can set the value of the launchpad, such as a minting fee, the maximum number of registered users, whitelisting root, etc. This results in the unreliability of the platform.</p> <p>Likelihood: Medium</p> <p>It is likely that the launchpad's owner will set a new value during the launchpad duration, but the users may observe the setting transaction before buying the token.</p>
Status	<p>Resolved</p> <p>The DAgora team has resolved this issue as suggested by adding the mechanism that prevents the launchpad's owner from updating the launchpad setting after the registration process has started.</p>

5.4.1. Description

The launchpad's state variables can be updated at any time by the launchpad's owner. When the launchpad's owner can update a critical state, that can cause impacts on the users, such as updating the fee mint, setting new whitelisting, or updating the maximum redeem. To be fair to the users, after the launchpad has been started, the launchpad's owner should not be able to update the launchpad's state. The following source code contains the `set_mintable_launchpad()` function logic:

lib.rs

```
79 pub fn set_mintable_launchpad(  
80     ctx: Context<SetMintableLaunchpadContext>,  
81     // launchpad core  
82     is_active: bool,  
83     whitelist_root: Option<[u8; 32]>,  
84     max_register: u64,  
85     max_redeem: u64,  
86     fee_mint: Pubkey,  
87     fee_redeem: u64,  
88     register_start_timestamp: i64,  
89     register_end_timestamp: i64,  
90     redeem_start_timestamp: i64,
```

```
91   redeem_end_timestamp: i64,
92   max_per_user: u64,
93   sharing_fee: u64,
94   protocol_fee: u64,
95   // mintable launchpad
96   collection_mint: Pubkey,
97   name: String,
98   symbol: String,
99   uri: String,
100   seller_fee_basis_points: u16,
101   royalty_fee_for_owner: u8,
102 ) -> Result<()> {
103   let mintable_launchpad = &mut ctx.accounts.mintable_launchpad;
104
105   let launchpad_core: LaunchpadCore = LaunchpadCore {
106     is_active,
107     whitelist_root,
108     max_register,
109     max_redeem,
110     total_register: 0,
111     total_redeem: 0,
112     fee_mint,
113     fee_redeem,
114     sharing_fee,
115     protocol_fee,
116     max_per_user,
117     register_start_timestamp,
118     register_end_timestamp,
119     redeem_start_timestamp,
120     redeem_end_timestamp,
121   };
122   mintable_launchpad.launchpad_core = launchpad_core;
123   mintable_launchpad.total_nft_redeem = 0;
124   mintable_launchpad.collection_mint = collection_mint;
125   mintable_launchpad.name = name.clone();
126   mintable_launchpad.symbol = symbol.clone();
127   mintable_launchpad.uri = uri.clone();
128   mintable_launchpad.seller_fee_basis_points = seller_fee_basis_points;
129   mintable_launchpad.royalty_fee_for_owner = royalty_fee_for_owner;
130
131   emit!(SetMintableLaunchpadEvent {
132     is_active,
133     whitelist_root,
134     fee_mint,
135     fee_redeem,
136     register_start_timestamp,
137     register_end_timestamp,
```

```
138     redeem_start_timestamp,  
139     redeem_end_timestamp,  
140     max_per_user,  
141     collection_mint,  
142     name,  
143     symbol,  
144     uri,  
145     seller_fee_basis_points,  
146     royalty_fee_for_owner  
147 });  
148  
149 Ok::<>()  
150 }
```

According to the above source code, the owner of the launchpad can modify all settings, including **fee_mint**, **fee_redeem**, **fee_redeem**, and **protocol_fee**, to immediately increase or decrease the fee paid by users.

Furthermore, after making changes, the **total_register**, **total_redeem**, and **total_nft_redeem** states will be set to 0, causing the counting state to be invalid when validating in the **validate_max_register()** function.

states.rs

```
103 pub fn validate_max_register(&mut self) -> Result<()> {  
104     if self.max_register > 0 {  
105         require!(self.total_register + 1 <= self.max_register,  
ErrorCodes::ReachMaxRegister);  
106     }  
107  
108     self.total_register = self.total_register.checked_add(1).unwrap();  
109     Ok::<>()  
110 }  
111  
112 pub fn validate_max_redeem(&mut self, amount: u64) -> Result<()> {  
113     if self.max_redeem > 0 {  
114         require!(self.total_redeem.checked_add(amount).unwrap() <= self.max_redeem,  
ErrorCodes::ReachMaxRedeem);  
115     }  
116  
117     self.total_redeem = self.total_redeem.checked_add(amount).unwrap();  
118     Ok::<>()  
119 }
```

It results in other users being able to register or redeem more number than expected.

5.4.2. Remediation

Inspex suggests adding the condition to prevent the launchpad's owner from modifying the state of the launchpad after the registration process is started. In case the launchpad's owner sets the `register_start_timestamp` state to `0` to start the launchpad immediately, the `total_register` state must be checked to ensure that no user has already registered, For example in lines 105-108 and 190-193:

errors.rs

```
71 #[msg("Dagora Launchpad: Cannot update launchpad data at this time.")]
72 CannotUpdateLaunchpad,
```

lib.rs

```
79 pub fn set_mintable_launchpad(
80     ctx: Context<SetMintableLaunchpadContext>,
81     // launchpad core
82     is_active: bool,
83     whitelist_root: Option<[u8; 32]>,
84     max_register: u64,
85     max_redeem: u64,
86     fee_mint: Pubkey,
87     fee_redeem: u64,
88     register_start_timestamp: i64,
89     register_end_timestamp: i64,
90     redeem_start_timestamp: i64,
91     redeem_end_timestamp: i64,
92     max_per_user: u64,
93     sharing_fee: u64,
94     protocol_fee: u64,
95     // mintable launchpad
96     collection_mint: Pubkey,
97     name: String,
98     symbol: String,
99     uri: String,
100     seller_fee_basis_points: u16,
101     royalty_fee_for_owner: u8,
102 ) -> Result<()> {
103     let mintable_launchpad = &mut ctx.accounts.mintable_launchpad;
104
105     let current_time = Clock::get().unwrap().unix_timestamp;
106     let launchpad_core = mintable_launchpad.get_launchpad_core();
107     require!(launchpad_core.total_register == 0,
108         ErrorCode::CannotUpdateLaunchpad);
109     require!(launchpad_core.register_start_timestamp > current_time ||
110         launchpad_core.register_start_timestamp == 0,
111         ErrorCode::CannotUpdateLaunchpad);
```

```
110 let launchpad_core: LaunchpadCore = LaunchpadCore {
111     is_active,
112     whitelist_root,
113     max_register,
114     max_redeem,
115     total_register: 0,
116     total_redeem: 0,
117     fee_mint,
118     fee_redeem,
119     sharing_fee,
120     protocol_fee,
121     max_per_user,
122     register_start_timestamp,
123     register_end_timestamp,
124     redeem_start_timestamp,
125     redeem_end_timestamp,
126 };
127 mintable_launchpad.launchpad_core = launchpad_core;
128 mintable_launchpad.total_nft_redeem = 0;
129 mintable_launchpad.collection_mint = collection_mint;
130 mintable_launchpad.name = name.clone();
131 mintable_launchpad.symbol = symbol.clone();
132 mintable_launchpad.uri = uri.clone();
133 mintable_launchpad.seller_fee_basis_points = seller_fee_basis_points;
134 mintable_launchpad.royalty_fee_for_owner = royalty_fee_for_owner;
135
136 emit!(SetMintableLaunchpadEvent {
137     is_active,
138     whitelist_root,
139     fee_mint,
140     fee_redeem,
141     register_start_timestamp,
142     register_end_timestamp,
143     redeem_start_timestamp,
144     redeem_end_timestamp,
145     max_per_user,
146     collection_mint,
147     name,
148     symbol,
149     uri,
150     seller_fee_basis_points,
151     royalty_fee_for_owner
152 });
153
154 Ok(())
155 }
```

```
170 pub fn set_transferable_launchpad(  
171     ctx: Context<SetTransferableLaunchpadContext>,  
172     // launchpad core  
173     is_active: bool,  
174     whitelist_root: Option<[u8; 32]>,  
175     max_register: u64,  
176     max_redeem: u64,  
177     fee_mint: Pubkey,  
178     fee_redeem: u64,  
179     register_start_timestamp: i64,  
180     register_end_timestamp: i64,  
181     redeem_start_timestamp: i64,  
182     redeem_end_timestamp: i64,  
183     max_per_user: u64,  
184     sharing_fee: u64,  
185     protocol_fee: u64,  
186     // transferable launchpad  
187 ) -> Result<()> {  
188     let transferable_launchpad = &mut ctx.accounts.transferable_launchpad;  
189  
190     let current_time = Clock::get().unwrap().unix_timestamp;  
191     let launchpad_core = transferable_launchpad.get_launchpad_core();  
192     require!(launchpad_core.total_register == 0,  
193         ErrorCode::CannotUpdateLaunchpad);  
194     require!(launchpad_core.register_start_timestamp > current_time ||  
195         launchpad_core.register_start_timestamp == 0,  
196         ErrorCode::CannotUpdateLaunchpad);  
197  
198     let launchpad_core: LaunchpadCore = LaunchpadCore {  
199         is_active,  
200         whitelist_root,  
201         max_register,  
202         max_redeem,  
203         total_register: 0,  
204         total_redeem: 0,  
205         fee_mint,  
206         max_per_user,  
207         fee_redeem,  
208         sharing_fee,  
209         protocol_fee,  
210         register_start_timestamp,  
211         register_end_timestamp,  
212         redeem_start_timestamp,  
213         redeem_end_timestamp,  
214     };  
215  
216     transferable_launchpad.launchpad_core = launchpad_core;
```

```
214  
215     emit!(SetTransferableLaunchpadEvent {  
216         is_active,  
217         whitelist_root,  
218         fee_mint,  
219         fee_redeem,  
220         register_start_timestamp,  
221         register_end_timestamp,  
222         redeem_start_timestamp,  
223         redeem_end_timestamp,  
224         max_per_user,  
225     });  
226  
227     Ok::<(),  
228 }
```


5.5. Missing of Launchpad Register Validation

ID	IDX-005
Target	dagora_launchpad
Category	Advanced Smart Contract Vulnerability
CWE	CWE-20: Improper Input Validation
Risk	Severity: Low Impact: Medium The malicious users can bypass the whitelist checking and create many <code>user_profile</code> accounts in order to register the launchpad before the launchpad start time. Likelihood: Low It will only occur if the launchpad's owner does not bundle the created and set launchpad data instructions into a single transaction.
Status	Resolved The DAGora team has resolved this issue as suggested by validating that the launchpad has already been activated before users register.

5.5.1. Description

In the launchpad creation process, the launchpad's owner will execute the `create_mintable_launchpad()` or the `create_transferable_launchpad()` functions and the `set_mintable_launchpad()` or the `set_transferable_launchpad()` functions respectively.

lib.rs

```
61 pub fn create_mintable_launchpad(  
62     ctx: Context<CreateMintableLaunchpadContext>,  
63     launchpad_path: Vec<u8>,  
64     owner: Pubkey,  
65 ) -> Result<()> {  
66     let mintable_launchpad = &mut ctx.accounts.mintable_launchpad;  
67   
68     mintable_launchpad.nonce = *ctx.bumps.get("mintable_launchpad").unwrap();  
69     mintable_launchpad.owner = owner;  
70   
71     emit!(CreateMintableLaunchpadEvent {  
72         launchpad_path,  
73         owner  
74     });  
75   
76     Ok(())  
77 }
```

lib.rs

```

79 pub fn set_mintable_launchpad(
80     ctx: Context<SetMintableLaunchpadContext>,
81     // launchpad core
82     is_active: bool,
83     whitelist_root: Option<[u8; 32]>,
84     max_register: u64,
85     max_redeem: u64,
86     fee_mint: Pubkey,
87     fee_redeem: u64,
88     register_start_timestamp: i64,
89     register_end_timestamp: i64,
90     redeem_start_timestamp: i64,
91     redeem_end_timestamp: i64,
92     max_per_user: u64,
93     sharing_fee: u64,
94     protocol_fee: u64,
95     // mintable launchpad
96     collection_mint: Pubkey,
97     name: String,
98     symbol: String,
99     uri: String,
100     seller_fee_basis_points: u16,
101     royalty_fee_for_owner: u8,
102 ) -> Result<()> {
103     let mintable_launchpad = &mut ctx.accounts.mintable_launchpad;
104
105     let launchpad_core: LaunchpadCore = LaunchpadCore {
106         is_active,
107         whitelist_root,
108         max_register,
109         max_redeem,
110         total_register: 0,
111         total_redeem: 0,
112         fee_mint,
113         fee_redeem,
114         sharing_fee,
115         protocol_fee,
116         max_per_user,
117         register_start_timestamp,
118         register_end_timestamp,
119         redeem_start_timestamp,
120         redeem_end_timestamp,
121     };
122     mintable_launchpad.launchpad_core = launchpad_core;
123     mintable_launchpad.total_nft_redeem = 0;
124     mintable_launchpad.collection_mint = collection_mint;

```

```

125 mintable_launchpad.name = name.clone();
126 mintable_launchpad.symbol = symbol.clone();
127 mintable_launchpad.uri = uri.clone();
128 mintable_launchpad.seller_fee_basis_points = seller_fee_basis_points;
129 mintable_launchpad.royalty_fee_for_owner = royalty_fee_for_owner;
130
131 emit!(SetMintableLaunchpadEvent {
132     is_active,
133     whitelist_root,
134     fee_mint,
135     fee_redeem,
136     register_start_timestamp,
137     register_end_timestamp,
138     redeem_start_timestamp,
139     redeem_end_timestamp,
140     max_per_user,
141     collection_mint,
142     name,
143     symbol,
144     uri,
145     seller_fee_basis_points,
146     royalty_fee_for_owner
147 });
148
149 Ok(())
150 }

```

After the launchpad is created, if the launchpad data is already set, the users' addresses should be whitelisted in the `launchpad_core.whitelist_root` before registering; the launchpad and the users can only register after the launchpad starts by using the `register_transferable_launchpad()` or the `register_mintable_launchpad()` functions.

lib.rs

```

237 pub fn register_mintable_launchpad(
238     ctx: Context<RegisterMintableLaunchpadContext>,
239     index: u32,
240     proofs: Vec<[u8; 32]>,
241 ) -> Result<()> {
242     let mintable_launchpad = &mut ctx.accounts.mintable_launchpad;
243     let user = &ctx.accounts.user;
244     let user_profile = &mut ctx.accounts.user_profile;
245
246     process_register(
247         mintable_launchpad,
248         user_profile,
249         index,

```

```

250     user.to_account_info().key(),
251     proofs.clone(),
252 )?;
253
254 emit!(RegisterLaunchpadEvent { index, proofs });
255
256 Ok(())
257 }

```

lib.rs

```

259 pub fn register_transferable_launchpad(
260     ctx: Context<RegisterTransferableLaunchpadContext>,
261     index: u32,
262     proofs: Vec<[u8; 32]>,
263 ) -> Result<()> {
264     let transferable_launchpad = &mut ctx.accounts.transferable_launchpad;
265     let user = &ctx.accounts.user;
266     let user_profile = &mut ctx.accounts.user_profile;
267
268     process_register(
269         transferable_launchpad,
270         user_profile,
271         index,
272         user.to_account_info().key(),
273         proofs.clone(),
274     )?;
275
276     emit!(RegisterLaunchpadEvent { index, proofs });
277
278     Ok(())
279 }

```

The `process_register()` function will validate the users by the `validate_register_time()`, the `validate_max_register()` and the `validate_proof()` functions at lines 642-644.

lib.rs

```

631 fn process_register<
632     'info,
633     Launchpad: LaunchpadProcess + AccountSerialize + AccountDeserialize + Owner +
634     Clone,
635 >(
636     launchpad: &mut Account<'info, Launchpad>,
637     user_profile: &mut Account<UserProfile>,
638     index: u32,
639     user_pubkey: Pubkey,
640     proofs: Vec<[u8; 32]>,

```

```

640 ) -> Result<()> {
641     let mut launchpad_core = launchpad.get_launchpad_core();
642     launchpad_core.validate_register_time()?;
643     launchpad_core.validate_max_register()?;
644     launchpad_core.validate_proof(index, user_pubkey, proofs)?;
645
646     launchpad.set_launchpad_core(launchpad_core);
647
648     user_profile.is_registered = true;
649     Ok(())
650 }

```

On the other hand, if the launchpad information is not set, the validation will be skipped because of the default variable value.

The `validate_register_time()` function will be bypassed since the `register_start_timestamp` and `register_end_timestamp` default values are `0`, by the following lines 62-69.

states.rs

```

60 pub fn validate_register_time(&self) -> Result<()> {
61     let current_time = Clock::get().unwrap().unix_timestamp;
62     require!(
63         self.register_start_timestamp == 0 || current_time >=
self.register_start_timestamp,
64         ErrorCode::InvalidRegisterTime
65     );
66     require!(
67         self.register_end_timestamp == 0 || current_time <
self.register_end_timestamp,
68         ErrorCode::InvalidRegisterTime
69     );
70
71     Ok(())
72 }

```

The validation in the `validate_max_register()` function will be skipped because the `max_register` default value is `0`, by the following line 104.

states.rs

```

103 pub fn validate_max_register(&mut self) -> Result<()> {
104     if self.max_register > 0 {
105         require!(self.total_register + 1 <= self.max_register,
ErrorCode::ReachMaxRegister);
106     }
107
108     self.total_register = self.total_register.checked_add(1).unwrap();

```

```

109     Ok(())
110 }

```

Lastly, the `validate_proof()` function will be skipped because the `whitelist_root` value is not set yet, by the following line 89.

states.rs

```

88 pub fn validate_proof(&self, index: u32, address: Pubkey, proofs: Vec<[u8;
    32]>) -> Result<()> {
89     if let Some(root) = self.whitelist_root {
90         let whitelist = WhitelistParams { index, address };
91         let whitelist_data = whitelist.try_to_vec().unwrap();
92         let leaf = hash(&whitelist_data[..]);
93
94         require!(
95             verify_proof(&proofs, &root, &leaf.to_bytes()),
96             ErrorCode::InvalidProofs
97         );
98     }
99
100     Ok(())
101 }

```

In conclusion, in the case that the launchpad's owner does not immediately set up the launchpad information after the launchpad has been created, any user can submit the register launchpad transaction to register, which can bypass all validation such as the starting time and whitelisting validation.

5.5.2. Remediation

Inspex suggests bundling the create and set launchpad instructions into a single transaction to prevent users from registering between the create and set launchpad processes.

Alternatively, implement the mechanism to ensure that no user can register the launchpad before the launchpad data is set (`is_active = true`). For example, lines 152 and 175.

contexts.rs

```

145 #[derive(Accounts)]
146 pub struct RegisterMintableLaunchpadContext<'info> {
147     #[account(mut)]
148     pub user: Signer<'info>,
149
150     #[account(
151         mut,
152         constraint = mintable_launchpad.is_active @ErrorCode::Registered
153     )]
154     pub mintable_launchpad: Account<'info, MintableLaunchpad>,

```

```
155
156   #[account(
157     mut,
158     seeds = [
159       user.to_account_info().key().as_ref(),
160       mintable_launchpad.to_account_info().key().as_ref()
161     ],
162     bump = user_profile.nonce,
163     constraint = !user_profile.is_registered @ErrorCode::Registered
164   )]
165   pub user_profile: Account<'info, UserProfile>,
166 }
167
168 #[derive(Accounts)]
169 pub struct RegisterTransferableLaunchpadContext<'info> {
170   #[account(mut)]
171   pub user: Signer<'info>,
172
173   #[account(
174     mut,
175     constraint = transferable_launchpad.is_active @ErrorCode::Registered
176   )]
177   pub transferable_launchpad: Account<'info, TransferableLaunchpad>,
178
179   #[account(
180     mut,
181     seeds = [
182       user.to_account_info().key().as_ref(),
183       transferable_launchpad.to_account_info().key().as_ref()
184     ],
185     bump = user_profile.nonce,
186     constraint = !user_profile.is_registered @ErrorCode::Registered
187   )]
188   pub user_profile: Account<'info, UserProfile>,
189 }
```

5.6. Insecure Source of Randomness

ID	IDX-006
Target	dagora_launchpad
Category	Advanced Smart Contract Vulnerability
CWE	CWE-330: Use of Insufficiently Random Values
Risk	<p>Severity: Low</p> <p>Impact: Medium</p> <p>A launchpad's owner can control the random result to select a specific NFT. This gives an unfair advantage to the platform users.</p> <p>Likelihood: Low</p> <p>There is nothing to restrict the changes from being done; however, this action can only be done by the launchpad's owner and there is no motivation to specify the NFT that was provided by their own. Furthermore, to get the value from manipulating the randomness, the stored NFT must be revealed beforehand, which is an uncommon strategy for the NFT project.</p>
Status	<p>Acknowledged</p> <p>The DAGora team has acknowledged this issue; the launchpad's owner can only do this action, and the launchpad's owner must be authorized by the DAGora team first.</p>

5.6.1. Description

The `claim_transferable_launchpad()`, the `claim_mintable_launchpad()`, and the `open_mystery_box()` functions are used to claim the NFTs by passing the parameter provided by the launchpad's owner as the random NTF address from the server side.

The `claim_mintable_launchpad()` function will call the `claim_nft()` function and then use `seeds` as the `uri` of NFTs in line 225.

states.rs

```
144 pub fn claim_nft<'info>(  
145     &self,  
146     launchpad_pubkey: &Pubkey,  
147     seeds: Vec<u8>,  
148     user: &AccountInfo<'info>,  
149     nft_mint_account: &AccountInfo<'info>,  
150     launchpad_authority: &AccountInfo<'info>,  
151     collection_metadata: &AccountInfo<'info>,  
152     collection_mint: &AccountInfo<'info>,  
153     collection_master_edition: &AccountInfo<'info>,  

```



```

154     receipt_account: &AccountInfo<'info>,
155     token_metadata: &AccountInfo<'info>,
156     ata_program: &AccountInfo<'info>,
157     token_program: &AccountInfo<'info>,
158     system_program: &AccountInfo<'info>,
159     sysvar_program: &Sysvar<'info, Rent>,
160 ) -> Result<()> {
161     let (nft_mint, nonce): (Pubkey, u8) =
162     Pubkey::find_program_address(&[&seeds], &id());
163     let nft_signer_seeds: &[&[u8]] = &[seeds.as_ref(), &[nonce]];
164
165     let (_, authority_nonce): (Pubkey, u8) =
166     get_launchpad_authority(*launchpad_pubkey);
167
168     let launchpad_seeds: &[&[u8]] = &[launchpad_pubkey.as_ref(),
169     &[authority_nonce]];
170     let mut creators = Vec::new();
171
172     let owner_launchpad = Creator {
173     address: self.owner,
174     verified: false,
175     share: self.royalty_fee_for_owner,
176     };
177     creators.push(owner_launchpad);
178
179     let owner_nft = Creator {
180     address: user.key(),
181     verified: true,
182     share: 100u8.checked_sub(self.royalty_fee_for_owner).unwrap(),
183     };
184     creators.push(owner_nft);
185
186     let collection = Collection {
187     key: collection_mint.key(),
188     verified: false,
189     };
190
191     create_account(
192     user,
193     nft_mint_account,
194     sysvar_program.minimum_balance(82),
195     82,
196     token_program,
197     &[nft_signer_seeds],
198     )?;

```

```
198 create_token_mint(  
199     nft_mint_account,  
200     &sysvar_program.to_account_info(),  
201     0,  
202     launchpad_authority.to_account_info().key(),  
203     COption::None,  
204     &[],  
205 )?;  
206 create_ata(  
207     receipt_account,  
208     user,  
209     nft_mint_account,  
210     user,  
211     ata_program,  
212     token_program,  
213     system_program,  
214     &sysvar_program.to_account_info(),  
215     &[],  
216 )?;  
217 mint_token(  
218     launchpad_authority,  
219     nft_mint_account,  
220     receipt_account,  
221     1,  
222     &[launchpad_seeds],  
223 )?;  
224 let mut uri = self.uri.clone().to_owned();  
225 uri.push_str(&nft_mint.to_string());  
226  
227 let mut name = self.name.clone().to_owned();  
228 name.push_str(&" #".to_string());  
229 name.push_str(&self.total_nft_redeem.to_string());  
230 create_token_metadata(  
231     token_metadata,  
232     nft_mint_account,  
233     launchpad_authority,  
234     user,  
235     user,  
236     name,  
237     self.symbol.clone(),  
238     uri,  
239     Some(creators),  
240     self.seller_fee_basis_points,  
241     true,  
242     false,  
243     Some(collection),  
244     None,
```

```

245     system_program,
246     &sysvar_program.to_account_info(),
247     &[launchpad_seeds],
248 )?;
249 verify_collection_for_token(
250     token_metadata,
251     launchpad_authority,
252     user,
253     collection_mint,
254     collection_metadata,
255     collection_master_edition,
256     None,
257     &[launchpad_seeds],
258 )?;
259
260     Ok(())
261 }

```

This results in some users can specifically choose the NFTs using the **seeds** which generate from the server side.

Moreover, in the `claim_transferable_launchpad()` and the `open_mystery_box()` functions as shown below:

lib.rs

```

394 pub fn claim_transferable_launchpad(
395     ctx: Context<ClaimTransferableLaunchpadContext>,
396     nft_mint: Pubkey,
397     owner_signature: [u8; 64]
398 ) -> Result<()> {
399     let transferable_launchpad = &ctx.accounts.transferable_launchpad;
400     let launchpad_authority = &ctx.accounts.launchpad_authority;
401     let user_profile = &mut ctx.accounts.user_profile;
402     let launchpad_nft_token_account =
403     &ctx.accounts.launchpad_nft_token_account;
404     let user_nft_token_account = &ctx.accounts.user_nft_token_account;
405
406     let ix: Instruction = load_instruction_at_checked(0,
407     &ctx.accounts.sysvar_program)?;
408
409     require!(ix.program_id == ED25519_ID,
410     ErrorCode::InvalidValidateSignInstruction);
411     require!(ix.accounts.len() == 0,
412     ErrorCode::InvalidValidateSignInstruction);
413
414     let message = MessageRandom {

```

```

411     root: user_profile.key(),
412     nft_mint
413 }.try_to_vec().unwrap();
414
415     let hashed_message = hash(&message).to_bytes();
416     require!(ix.data.len() == (16 + 64 + 32 + hashed_message.len()),
417     ErrorCode::InvalidValidateSignInstruction);
418     check_ed25519_data(&ix.data, transferable_launchpad.owner.as_ref(),
419     &hashed_message, &owner_signature)?;
420
421     let launchpad_pubkey = &transferable_launchpad.to_account_info().key();
422
423     user_profile.before_claim()?;
424
425     transferable_launchpad.claim_nft(
426         launchpad_pubkey,
427         launchpad_authority,
428         launchpad_nft_token_account,
429         user_nft_token_account,
430     )?;
431
432     emit!(ClaimLaunchpadEvent { nft_mint });
433
434     Ok(())
435 }
436
437 pub fn open_mystery_box(
438     ctx: Context<OpenMysteryBoxContext>,
439     mystery_nft_mint: Pubkey,
440     owner_signature: [u8; 64]
441 ) -> Result<()> {
442     let user = &ctx.accounts.user;
443     let mintable_launchpad = &mut ctx.accounts.mintable_launchpad;
444     let launchpad_authority = &ctx.accounts.launchpad_authority;
445     let box_mint = &ctx.accounts.box_mint;
446     let box_metadata = &ctx.accounts.box_metadata;
447     let user_box_token_account = &ctx.accounts.user_box_token_account;
448     let launchpad_box_token_account =
449     &ctx.accounts.launchpad_box_token_account;
450     let launchpad_mystery_token_account =
451     &ctx.accounts.launchpad_mystery_token_account;
452     let user_mystery_token_account = &ctx.accounts.user_mystery_token_account;
453
454     let ix: Instruction = load_instruction_at_checked(0,
455     &ctx.accounts.sysvar_program)?;
456
457     require!(ix.program_id == ED25519_ID, ErrorCode::SigVerificationFailed);

```

```

453     require!(ix.accounts.len() == 0, ErrorCode::SigVerificationFailed);
454
455     let message = MessageRandom {
456         root: box_mint.key(),
457         nft_mint: mystery_nft_mint
458     }.try_to_vec().unwrap();
459
460     let hashed_message = hash(&message[..]).to_bytes();
461     // validate message len
462     require!(ix.data.len() == (16 + 64 + 32 + hashed_message.len()),
463         ErrorCode::SigVerificationFailed);
464     check_ed25519_data(&ix.data, mintable_launchpad.owner.as_ref(),
465         &hashed_message, &owner_signature)?;
466
467     let box_metadata: Metadata =
468         Metadata::from_account_info(&box_metadata).unwrap();
469
470     if let Some(collection) = box_metadata.collection {
471         require!(
472             collection.key == mintable_launchpad.collection_mint,
473             ErrorCode::CollectionMismatch
474         );
475     } else {
476         return Err(ErrorCode::CollectionMismatch.into());
477     }
478
479     let launchpad_pubkey = &mintable_launchpad.to_account_info().key();
480     let (_, authority_nonce): (Pubkey, u8) =
481         get_launchpad_authority(launchpad_pubkey.clone());
482     let seeds: [&[_]] = [&launchpad_pubkey.as_ref(), &authority_nonce];
483
484     transfer_token(
485         user,
486         user_box_token_account,
487         launchpad_box_token_account,
488         1,
489         &[],
490     )?;
491     burn_token(
492         launchpad_authority,
493         box_mint,
494         launchpad_box_token_account,
495         1,
496         &seeds,
497     )?;
498     transfer_token(

```

```
496     launchpad_authority,  
497     launchpad_mystery_token_account,  
498     user_mystery_token_account,  
499     1,  
500     &[seeds],  
501 )?;  
502  
503     emit!(OpenMysteryBoxEvent {});  
504  
505     Ok(())  
506 }
```

The `nft_mint` and the `mystery_nft_mint` parameters are validated in lines 417 and 463, which are signed by the owner. The signed message contains both a random NFT index and the user's account. This prevents the signed message from being used by the other users to claim the specific NFT.

However, the random result can be a specific NFT for some users. This is because the `nft_mint` and the `mystery_nft_mint` can be picked and signed by the owner. This results in an unfair advantage for the platform's users.

5.6.2. Remediation

Inspex suggests applying the provably fair and verifiable randomness of the NFT random instead of the centralization random from the off-chain, which the platform can control.

For example, implementing the VRF as the randomness source for the NFT random.

5.7. Improper Fee Enforcement

ID	IDX-007
Target	dagora_launchpad
Category	Advanced Smart Contract Vulnerability
CWE	CWE-840: Business Logic Errors
Risk	<p>Severity: Low</p> <p>Impact: Medium The launchpad's owner will either lose all profits or have to pay an additional fee to the platform.</p> <p>Likelihood: Low It is extremely unlikely that the launchpad's owner or the platform will impose an unreasonable fee that will harm both the launchpad's profitability and the platform's reputation.</p>
Status	<p>Resolved</p> <p>The DAgora team has resolved this issue by ensuring that the <code>total_system_fee</code> is less than the <code>total_redeem_fee</code> and adding the boundary of <code>protocol_fee</code> up to 20%.</p>

5.7.1. Description

During the redemption phase, the registered user could redeem their via the `redeem_mintable_launchpad()` function or the `redeem_transferable_launchpad()` function, which both will call the `process_redeem()` function as shown in lines 296 and 330:

lib.rs

```

281 pub fn redeem_mintable_launchpad<'a>(<
282     ctx: Context<'_, '_, '_, 'a, RedeemMintableLaunchpadContext<'a>>,
283     amount: u64,
284 ) -> Result<()> {
285     let user = &ctx.accounts.user;
286     let mintable_launchpad = &mut ctx.accounts.mintable_launchpad;
287     let launchpad_authority = &ctx.accounts.launchpad_authority;
288     let user_profile = &mut ctx.accounts.user_profile;
289
290     let user_fee_token_account = &ctx.accounts.user_fee_token_account;
291     let launchpad_fee_token_account = &ctx.accounts.launchpad_fee_token_account;
292     let protocol_fee_token_account = &ctx.accounts.protocol_fee_token_account;
293
294     let launchpad_key = &mintable_launchpad.to_account_info().key();
295

```

```
296 process_redeem(  
297     mintable_launchpad,  
298     &launchpad_key,  
299     user_profile,  
300     &user.to_account_info(),  
301     launchpad_authority,  
302     user_fee_token_account,  
303     launchpad_fee_token_account,  
304     protocol_fee_token_account,  
305     amount,  
306 )?;  
307  
308 emit!(RedeemLaunchpadEvent { amount });  
309  
310 Ok(())  
311 }
```

lib.rs

```
313 pub fn redeem_transferable_launchpad(  
314     ctx: Context<RedeemTransferableLaunchpadContext>,  
315     amount: u64,  
316 ) -> Result<()> {  
317     let user = &ctx.accounts.user;  
318     let transferable_launchpad = &mut ctx.accounts.transferable_launchpad;  
319     let launchpad_authority = &ctx.accounts.launchpad_authority;  
320     let user_profile = &mut ctx.accounts.user_profile;  
321  
322     let user_fee_token_account = &ctx.accounts.user_fee_token_account;  
323     let launchpad_fee_token_account = &ctx.accounts.launchpad_fee_token_account;  
324     let protocol_fee_token_account = &ctx.accounts.protocol_fee_token_account;  
325  
326     let launchpad_key = &transferable_launchpad.to_account_info().key();  
327  
328     // we cover limit by total nft in launchpad  
329  
330     process_redeem(  
331         transferable_launchpad,  
332         &launchpad_key,  
333         user_profile,  
334         &user.to_account_info(),  
335         launchpad_authority,  
336         user_fee_token_account,  
337         launchpad_fee_token_account,  
338         protocol_fee_token_account,  
339         amount,  
340     )?;  
341 }
```



```

342     emit!(RedeemLaunchpadEvent { amount });
343
344     Ok(())
345 }

```

The `process_redeem()` function is used to process the fee that the registered user must pay to redeem the NFT.

The `total_fee` state is the total fee that the user must pay, which is calculated by multiplying the amount by the `launchpad_core.fee_redeem` state as shown in line 595.

lib.rs

```

569 fn process_redeem<
570     'info,
571     Launchpad: LaunchpadProcess + AccountSerialize + AccountDeserialize + Owner +
Clone,
572 >(<
573     launchpad: &mut Account<Launchpad>,
574     launchpad_key: &Pubkey,
575     user_profile: &mut Account<UserProfile>,
576     user: &AccountInfo<'info>,
577     launchpad_authority: &AccountInfo<'info>,
578     user_fee_token_account: &AccountInfo<'info>,
579     launchpad_fee_token_account: &AccountInfo<'info>,
580     protocol_fee_token_account: &AccountInfo<'info>,
581     amount: u64,
582 ) -> Result<> {
583     let mut launchpad_core: LaunchpadCore = launchpad.get_launchpad_core();
584     launchpad_core.validate_redeem_time()?;
585     launchpad_core.validate_max_redeem(amount)?;
586
587     if launchpad_core.max_per_user > 0 {
588         require!(
589             user_profile.total_nft_redeem.checked_add(amount).unwrap() <=
launchpad_core.max_per_user,
590             ErrorCode::ReachMaximumPerUser
591         );
592     }
593     launchpad.set_launchpad_core(launchpad_core);
594
595     let total_fee = amount.checked_mul(launchpad_core.fee_redeem).unwrap();
596

```

When the `total_fee` state is greater than zero, the `protocol_fee` is calculated by multiplying the `total_fee` state with the `launchpad_core.protocol_fee` state as shown below in line 598.

Moreover, the `protocol_fee` is added by the `launchpad_core.sharing_fee` state and transferred to

the `launchpad_fee_token_account` account as shown below in line 603.

lib.rs

```

597 if total_fee > 0 {
598     let mut protocol_fee = total_fee
599         .checked_mul(launchpad_core.protocol_fee)
600         .unwrap()
601         .checked_div(10000)
602         .unwrap();
603     protocol_fee = protocol_fee.checked_add(launchpad_core.sharing_fee).unwrap();
604     transfer_token(
605         user,
606         &user_fee_token_account,
607         &launchpad_fee_token_account,
608         total_fee,
609         &[],
610     )?;
611
612     if protocol_fee > 0 {
613         let (_, authority_nonce): (Pubkey, u8) =
614             get_launchpad_authority(*launchpad_key);
615         let seeds: &[&[_]] = &[launchpad_key.as_ref(), &[authority_nonce]];
616
617         transfer_token(
618             launchpad_authority,
619             launchpad_fee_token_account,
620             protocol_fee_token_account,
621             protocol_fee,
622             &[seeds],
623         )?;
624     }
625 }

```

If the `protocol_fee` is greater than zero, it will transfer the fee from the `launchpad_fee_token_account` account to the `protocol_fee_token_account` account.

In some cases, the `protocol_fee` that transfers from the `launchpad_fee_token_account` account to the `protocol_fee_token_account` account could be greater than the `total_fee` that the registered user transfers to the `launchpad_fee_token_account`, for example:

The registered user transfers to the `total_fee` only 300.

Variable	Value
<code>launchpad_core.fee_redeem</code>	100
<code>amount</code>	3

total_fee	$3 * 100 = 300$
-----------	-----------------

The program transfers 450 (**protocol_fee**) from the **launchpad_fee_token_account** account to the **protocol_fee_token_account** account, which is greater than the registered user transfer to the **launchpad_fee_token_account** account which is just 300(**total_fee**).

Variable	Value
protocol_fee	50%
sharing_fee	300
protocol_fee	$(50\% \text{ of } 300) + 300 = 450$

This results in the exceeded fee being drained from the **launchpad_fee_token_account** account instead.

5.7.2. Remediation

Inspex suggests insisting the user pay the extra fee as the most valuable of the **total_fee** and the **protocol_fee** to prevent the launchpad from losing its profits, For example in lines 607-609:

lib.rs

```

595 let total_fee = amount.checked_mul(launchpad_core.fee_redeem).unwrap();
596
597 if total_fee > 0 {
598     let mut protocol_fee = total_fee
599         .checked_mul(launchpad_core.protocol_fee)
600         .unwrap()
601         .checked_div(10000)
602         .unwrap();
603     protocol_fee = protocol_fee.checked_add(launchpad_core.sharing_fee).unwrap();
604
605     let mut fee_to_pay = total_fee;
606
607     if (protocol_fee > total_fee){
608         fee_to_pay = protocol_fee;
609     }
610
611     transfer_token(
612         user,
613         &user_fee_token_account,
614         &launchpad_fee_token_account,
615         fee_to_pay,
616         &[],
617     )?;
618
619     if protocol_fee > 0 {
620         let (_, authority_nonce): (Pubkey, u8) =

```

```
621 get_launchpad_authority(*launchpad_key);
622     let seeds: &&[_] = &[launchpad_key.as_ref(), &[authority_nonce]];
623     transfer_token(
624         launchpad_authority,
625         launchpad_fee_token_account,
626         protocol_fee_token_account,
627         fee_to_pay,
628         &[seeds],
629     )?;
630 }
631 }
```

5.8. Smart Contract with Unpublished Source Code

ID	IDX-008
Target	dagora_solana
Category	General Smart Contract Vulnerability
CWE	CWE-1006: Bad Coding Practices
Risk	Severity: Low Impact: Medium The logic of the smart contract may not align with the user's understanding, causing undesired actions to be taken when the user interacts with the smart contract. Likelihood: Low The possibility for the users to misunderstand the functionalities of the contract is not very high with the help of the documentation and user interface.
Status	Acknowledged The Coin98 team has acknowledged this issue and decided not to publish the source code because the team wants to protect their intellectual property.

5.8.1. Description

The smart contract source code is not publicly published, so the users will not be able to easily verify the correctness of the functionalities and the logic of the smart contract by themselves. Therefore, it is possible that the user's understanding of the smart contract does not align with the actual implementation, leading to undesired actions on interacting with the smart contract.

5.8.2. Remediation

Inspex suggests publishing the contract source code through a public code repository or verifying the smart contract source code on the blockchain explorer so that the users can easily read and understand the logic of the smart contract by themselves.

6. Appendix

6.1. About Inspex



CYBERSECURITY PROFESSIONAL SERVICE

Inspex is formed by a team of cybersecurity experts highly experienced in various fields of cybersecurity. We provide blockchain and smart contract professional services at the highest quality to enhance the security of our clients and the overall blockchain ecosystem.

Follow Us On:

Website	https://inspex.co
Twitter	@InspexCo
Facebook	https://www.facebook.com/InspexCo
Telegram	@inspex_announcement



inspex
CYBERSECURITY PROFESSIONAL SERVICE