

## Linux kernel v.5.15.32

```
struct super_block {
    struct list_heads_list;          /* Keep this first */
    dev_t                            s_dev;          /* search index; _not_ kdev_t */
    unsigned char                    s_blocksize_bits;
    unsigned long                    s_blocksize;
    loff_t                           s_maxbytes;     /* Max file size */
    struct file_system_type *s_type;
    const struct super_operations *s_op;
    const struct dqquot_operations *dq_op;
    const struct quotactl_ops *s_qcop;
    const struct export_operations *s_export_op;
    unsigned long                    s_flags;
    unsigned long                    s_iflags;        /* internal SB_I_* flags */
    unsigned long                    s_magic;
    struct dentry *s_root;
    struct rw_semaphore s_umount;
    int s_count;
    atomic_t s_active;
#ifdef CONFIG_SECURITY
    void *s_security;
#endif
    const struct xattr_handler **s_xattr;
#ifdef CONFIG_FS_ENCRYPTION
    const struct fscrypt_operations *s_cop;
    struct key *s_master_keys; /* master crypto keys in use */
#endif
#ifdef CONFIG_FS_VERITY
    const struct fsverity_operations *s_vop;
#endif
#ifdef CONFIG_UNICODE
    struct unicode_map *s_encoding;
    __ul6 s_encoding_flags;
#endif
    struct hlist_bl_head s_roots; /* alternate root dentries for NFS */
    struct list_heads_mounts; /* list of mounts; _not_ for fs use */
    struct block_device *s_bdev;
    struct backing_dev_info *s_bdi;
    struct mtd_info *s_mtd;
    struct hlist_node s_instances;
    unsigned int s_quota_types; /* Bitmask of supported quota
types */
    struct quota_info s_dquot; /* Diskquota specific options */
    struct sb_writers s_writers;
    /*
     * Keep s_fs_info, s_time_gran, s_fsnotify_mask, and
     * s_fsnotify_marks together for cache efficiency. They are frequently
     * accessed and rarely modified.
     */
    void *s_fs_info; /* Filesystem private info */
    /* Granularity of c/m/atime in ns (cannot be worse than a second) */
    u32 s_time_gran;
    /* Time limits for c/m/atime in seconds */
    time64_t s_time_min;
    time64_t s_time_max;
#ifdef CONFIG_FSNOTIFY
    __u32 s_fsnotify_mask;
    struct fsnotify_mark_connector __rcu *s_fsnotify_marks;
#endif
    char s_id[32]; /* Informational name */
    uuid_t s_uuid; /* UUID */
    unsigned int s_max_links;
    fmode_t s_mode;
    /*
     * The next field is for VFS *only*. No filesystems have any business
```

```

    * even looking at it. You had been warned.
    */
    struct mutex s_vfs_rename_mutex; /* Kludge */
    /*
     * Filesystem subtype.  If non-empty the filesystem type field
     * in /proc/mounts will be "type.subtype"
     */
    const char *s_subtype;
    const struct dentry_operations *s_d_op; /* default d_op for dentries */
    /*
     * Saved pool identifier for cleancache (-1 means none)
     */
    int cleancache_poolid;
    struct shrinker s_shrink; /* per-sb shrinker handle */
    /* Number of inodes with nlink == 0 but still referenced */
    atomic_long_t s_remove_count;
    /*
     * Number of inode/mount/sb objects that are being watched, note that
     * inodes objects are currently double-accounted.
     */
    atomic_long_t s_fsnotify_connectors;
    /* Being remounted read-only */
    int s_readonly_remount;
    /* per-sb errseq_t for reporting writeback errors via syncfs */
    errseq_t s_wb_err;
    /* AIO completions deferred from interrupt context */
    struct workqueue_struct *s_dio_done_wq;
    struct hlist_head s_pins;
    /*
     * Owning user namespace and default context in which to
     * interpret filesystem uids, gids, quotas, device nodes,
     * xattrs and security labels.
     */
    struct user_namespace *s_user_ns;
    /*
     * The list_lru structure is essentially just a pointer to a table
     * of per-node lru lists, each of which has its own spinlock.
     * There is no need to put them into separate cachelines.
     */
    struct list_lru s_dentry_lru;
    struct list_lru s_inode_lru;
    struct rcu_head rcu;
    struct work_struct destroy_work;
    struct mutex s_sync_lock; /* sync serialisation lock */
    /*
     * Indicates how deep in a filesystem stack this SB is
     */
    int s_stack_depth;
    /* s_inode_list_lock protects s_inodes */
    spinlock_t s_inode_list_lock ____cacheline_aligned_in_smp;
    struct list_heads_inodes; /* all inodes */

    spinlock_t s_inode_wblist_lock;
    struct list_heads_inodes_wb; /* writeback inodes */
} __randomize_layout;

struct super_operations {
    struct inode *(*alloc_inode)(struct super_block *sb);
    void (*destroy_inode)(struct inode *);
    void (*free_inode)(struct inode *);

    void (*dirty_inode)(struct inode *, int flags);
    int (*write_inode)(struct inode *, struct writeback_control *wbc);
    int (*drop_inode)(struct inode *);
    void (*evict_inode)(struct inode *);
    void (*put_super)(struct super_block *);
    int (*sync_fs)(struct super_block *sb, int wait);

```

```

int (*freeze_super) (struct super_block *);
int (*freeze_fs) (struct super_block *);
int (*thaw_super) (struct super_block *);
int (*unfreeze_fs) (struct super_block *);
int (*statfs) (struct dentry *, struct kstatfs *);
int (*remount_fs) (struct super_block *, int *, char *);
void (*umount_begin) (struct super_block *);

int (*show_options) (struct seq_file *, struct dentry *);
int (*show_devname) (struct seq_file *, struct dentry *);
int (*show_path) (struct seq_file *, struct dentry *);
int (*show_stats) (struct seq_file *, struct dentry *);
#ifdef CONFIG_QUOTA
    ssize_t (*quota_read) (struct super_block *, int, char *, size_t, loff_t);
    ssize_t (*quota_write) (struct super_block *, int, const char *, size_t,
loff_t);
    struct dqquot ** (*get_dquots) (struct inode *);
#endif
long (*nr_cached_objects) (struct super_block *,
                           struct shrink_control *);
long (*free_cached_objects) (struct super_block *,
                             struct shrink_control *);
};

struct file_system_type {
    const char *name;
    int fs_flags;
#define FS_REQUIRES_DEV 1
#define FS_BINARY_MOUNTDATA 2
#define FS_HAS_SUBTYPE 4
#define FS_USERNS_MOUNT 8 /* Can be mounted by userns root */
#define FS_DISALLOW_NOTIFY_PERM 16 /* Disable fanotify permission events */
#define FS_ALLOW_IDMAP 32 /* FS has been updated to handle vfs
idmappings. */
#define FS_THP_SUPPORT 8192 /* Remove once all fs converted */
#define FS_RENAME_DOES_D_MOVE 32768 /* FS will handle d_move() during
rename() internally. */
    int (*init_fs_context) (struct fs_context *);
    const struct fs_parameter_spec *parameters;
    struct dentry * (*mount) (struct file_system_type *, int,
                             const char *, void *);
    void (*kill_sb) (struct super_block *);
    struct module *owner;
    struct file_system_type * next;
    struct hlist_head fs_supers;
    struct lock_class_key s_lock_key;
    struct lock_class_key s_umount_key;
    struct lock_class_key s_vfs_rename_key;
    struct lock_class_key s_writers_key[SB_FREEZE_LEVELS];

    struct lock_class_key i_lock_key;
    struct lock_class_key i_mutex_key;
    struct lock_class_key invalidate_lock_key;
    struct lock_class_key i_mutex_dir_key;
};

struct vfsmount {
    struct dentry *mnt_root; /* root of the mounted tree */
    struct super_block *mnt_sb; /* pointer to superblock */
    int mnt_flags;
    struct user_namespace *mnt_userns;
} __randomize_layout;

```

```

struct dentry {
    /* RCU lookup touched fields */
    unsigned int d_flags; /* protected by d_lock */
    seqcount_spinlock_t d_seq; /* per dentry seqlock */
    struct hlist_bl_node d_hash; /* lookup hash list */
    struct dentry *d_parent; /* parent directory */
    struct qstr d_name;
    struct inode *d_inode; /* Where the name belongs to - NULL is
                           * negative */
    unsigned char d_iname[DNAME_INLINE_LEN]; /* small names */
    /* Ref lookup also touches following */
    struct lockref d_lockref; /* per-dentry lock and refcount */
    const struct dentry_operations *d_op;
    struct super_block *d_sb; /* The root of the dentry tree */
    unsigned long d_time; /* used by d_revalidate */
    void *d_fsdata; /* fs-specific data */
    union {
        struct list_head d_lru; /* LRU list */
        wait_queue_head_t *d_wait; /* in-lookup ones only */
    };
    struct list_head d_child; /* child of parent list */
    struct list_head d_subdirs; /* our children */
    /*
     * d_alias and d_rcu can share memory
     */
    union {
        struct hlist_node d_alias; /* inode alias list */
        struct hlist_bl_node d_in_lookup_hash; /* only for in-lookup
ones */
        struct rcu_head d_rcu;
    } d_u;
} __randomize_layout;

struct dentry_operations {
    int (*d_revalidate)(struct dentry *, unsigned int);
    int (*d_weak_revalidate)(struct dentry *, unsigned int);
    int (*d_hash)(const struct dentry *, struct qstr *);
    int (*d_compare)(const struct dentry *,
                     unsigned int, const char *, const struct qstr *);
    int (*d_delete)(const struct dentry *);
    int (*d_init)(struct dentry *);
    void (*d_release)(struct dentry *);
    void (*d_prune)(struct dentry *);
    void (*d_iput)(struct dentry *, struct inode *);
    char *(*d_dname)(struct dentry *, char *, int);
    struct vfsmount *(*d_automount)(struct path *);
    int (*d_manage)(const struct path *, bool);
    struct dentry *(*d_real)(struct dentry *, const struct inode *);
} __cacheline_aligned;

struct dentry_stat_t {
    long nr_dentry;
    long nr_unused;
    long age_limit; /* age in seconds */
    long want_pages; /* pages requested by system */
    long nr_negative; /* # of unused negative dentries */
    long dummy; /* Reserved for future use */
};

extern struct dentry_stat_t dentry_stat;

```

```

/*
 * Keep mostly read-only and often accessed (especially for
 * the RCU path lookup and 'stat' data) fields at the beginning
 * of the 'struct inode'
 */
struct inode {
    umode_t            i_mode;
    unsigned short     i_opflags;
    kuid_t             i_uid;
    kgid_t             i_gid;
    unsigned int       i_flags;
#ifdef CONFIG_FS_POSIX_ACL
    struct posix_acl *i_acl;
    struct posix_acl *i_default_acl;
#endif
    const struct inode_operations *i_op;
    struct super_block *i_sb;
    struct address_space *i_mapping;
#ifdef CONFIG_SECURITY
    void               *i_security;
#endif
    /* Stat data, not accessed from path walking */
    unsigned long      i_ino;
    /*
     * Filesystems may only read i_nlink directly.  They shall use the
     * following functions for modification:
     *
     * (set|clear|inc|drop)_nlink
     * inode_(inc|dec)_link_count
     */
    union {
        const unsigned int i_nlink;
        unsigned int __i_nlink;
    };
    dev_t             i_rdev;
    loff_t            i_size;
    struct timespec64 i_atime;
    struct timespec64 i_mtime;
    struct timespec64 i_ctime;
    spinlock_t        i_lock; /* i_blocks, i_bytes, maybe i_size */
    unsigned short    i_bytes;
    u8                i_blkbits;
    u8                i_write_hint;
    blkcnt_t          i_blocks;
#ifdef __NEED_I_SIZE_ORDERED
    seqcount_t         i_size_seqcount;
#endif
    /* Misc */
    unsigned long      i_state;
    struct rw_semaphore i_rwsem;
    unsigned long      dirtied_when; /* jiffies of first dirtying */
    unsigned long      dirtied_time_when;
    struct hlist_node  i_hash;
    struct list_head i_io_list; /* backing dev IO list */
#ifdef CONFIG_CGROUP_WRITEBACK
    struct bdi_writeback *i_wb; /* the associated cgroup wb */
    /* foreign inode detection, see wbc_detach_inode() */
    int                i_wb_frn_winner;
    u16                i_wb_frn_avg_time;
    u16                i_wb_frn_history;
#endif
    struct list_head i_lru; /* inode LRU list */
    struct list_head i_sb_list;
    struct list_head i_wb_list; /* backing dev writeback list */
    union {
        struct hlist_head i_dentry;
        struct rcu_head i_rcu;
    };
};

```

```

};
atomic64_t          i_version;
atomic64_t          i_sequence; /* see futex */
atomic_t            i_count;
atomic_t            i_dio_count;
atomic_t            i_writecount;
#ifdef CONFIG_IMA || defined(CONFIG_FILE_LOCKING)
atomic_t            i_readcount; /* struct files open RO */
#endif

union {
    const struct file_operations *i_fop; /* former ->i_op-
>default_file_ops */
    void (*free_inode)(struct inode *);
};
struct file_lock_context*i_flctx;
struct address_space i_data;
struct list_head i_devices;
union {
    struct pipe_inode_info *i_pipe;
    struct cdev *i_cdev;
    char *i_link;
    unsigned i_dir_seq;
};
__u32 i_generation;
#ifdef CONFIG_FSNOTIFY
__u32 i_fsnotify_mask; /* all events this inode cares
about */
struct fsnotify_mark_connector __rcu *i_fsnotify_marks;
#endif

#ifdef CONFIG_FS_ENCRYPTION
struct fscrypt_info *i_crypt_info;
#endif

#ifdef CONFIG_FS_VERITY
struct fsverity_info *i_verity_info;
#endif

void *i_private; /* fs or device private pointer */
} __randomize_layout;

struct inode_operations {
    struct dentry * (*lookup) (struct inode *, struct dentry *, unsigned int);
    const char * (*get_link) (struct dentry *, struct inode *, struct
delayed_call *);
    int (*permission) (struct user_namespace *, struct inode *, int);
    struct posix_acl * (*get_acl) (struct inode *, int, bool);
    int (*readlink) (struct dentry *, char __user *, int);
    int (*create) (struct user_namespace *, struct inode *, struct dentry *,
umode_t, bool);
    int (*link) (struct dentry *, struct inode *, struct dentry *);
    int (*unlink) (struct inode *, struct dentry *);
    int (*symlink) (struct user_namespace *, struct inode *, struct dentry *,
const char *);
    int (*mkdir) (struct user_namespace *, struct inode *, struct dentry *,
umode_t);
    int (*rmdir) (struct inode *, struct dentry *);
    int (*mknod) (struct user_namespace *, struct inode *, struct dentry *,
umode_t, dev_t);
    int (*rename) (struct user_namespace *, struct inode *, struct dentry *,
struct inode *, struct dentry *, unsigned int);
    int (*setattr) (struct user_namespace *, struct dentry *,
struct iattr *);
    int (*getattr) (struct user_namespace *, const struct path *,
struct kstat *, u32, unsigned int);
    ssize_t (*listxattr) (struct dentry *, char *, size_t);
    int (*fiemap) (struct inode *, struct fiemap_extent_info *, u64 start,
u64 len);

```

```

int (*update_time)(struct inode *, struct timespec64 *, int);
int (*atomic_open)(struct inode *, struct dentry *,
                   struct file *, unsigned open_flag,
                   umode_t create_mode);
int (*tmpfile)(struct user_namespace *, struct inode *,
               struct dentry *, umode_t);
int (*set_acl)(struct user_namespace *, struct inode *,
               struct posix_acl *, int);
int (*fileattr_set)(struct user_namespace *mnt_userns,
                   struct dentry *dentry, struct fileattr *fa);
int (*fileattr_get)(struct dentry *dentry, struct fileattr *fa);
} cacheline_aligned;

/*
 * Inode flags - they have no relation to superblock flags now
 */
#define S_SYNC (1 << 0) /* Writes are synced at once */
#define S_NOATIME (1 << 1) /* Do not update access times */
#define S_APPEND (1 << 2) /* Append-only file */
#define S_IMMUTABLE (1 << 3) /* Immutable file */
#define S_DEAD (1 << 4) /* removed, but still open directory */
#define S_NOQUOTA (1 << 5) /* Inode is not counted to quota */
#define S_DIRSYNC (1 << 6) /* Directory modifications are synchronous */
#define S_NOCMTIME (1 << 7) /* Do not update file c/mtime */
#define S_SWAPFILE (1 << 8) /* Do not truncate: swapon got its bmaps */
#define S_PRIVATE (1 << 9) /* Inode is fs-internal */
#define S_IMA (1 << 10) /* Inode has an associated IMA struct */
#define S_AUTOMOUNT (1 << 11) /* Automount/referral quasi-directory */
#define S_NOSEC (1 << 12) /* no suid or xattr security attributes */
#ifdef CONFIG_FS_DAX
#define S_DAX (1 << 13) /* Direct Access, avoiding the page cache */
#else
#define S_DAX 0 /* Make all the DAX code disappear */
#endif
#define S_ENCRYPTED (1 << 14) /* Encrypted file (using fs/crypto/) */
#define S_CASEFOLD (1 << 15) /* Casefolded file */
#define S_VERITY (1 << 16) /* Verity file (using fs/verity/) */

/**
 * struct address_space - Contents of a cacheable, mappable object.
 * @host: Owner, either the inode or the block_device.
 * @i_pages: Cached pages.
 * @invalidate_lock: Guards coherency between page cache contents and
 * file offset->disk block mappings in the filesystem during invalidates.
 * It is also used to block modification of page cache contents through
 * memory mappings.
 * @gfp_mask: Memory allocation flags to use for allocating pages.
 * @i_mmap_writable: Number of VM_SHARED mappings.
 * @nr_thps: Number of THPs in the pagecache (non-shmem only).
 * @i_mmap: Tree of private and shared mappings.
 * @i_mmap_rwsem: Protects @i_mmap and @i_mmap_writable.
 * @nrpages: Number of page entries, protected by the i_pages lock.
 * @writeback_index: Writeback starts here.
 * @a_ops: Methods.
 * @flags: Error bits and flags (AS_*).
 * @wb_err: The most recent error which has occurred.
 * @private_lock: For use by the owner of the address_space.
 * @private_list: For use by the owner of the address_space.
 * @private_data: For use by the owner of the address_space.
 */
struct address_space {
    struct inode *host;
    struct xarray i_pages;
    struct rw_semaphore invalidate_lock;
    gfp_t gfp_mask;
    atomic_t i_mmap_writable;

```

```

#ifdef CONFIG_READ_ONLY_THP_FOR_FS
    /* number of thp, only for non-shmem files */
    atomic_t      nr_thps;
#endif

struct rb root cached    i mmap;
struct rw semaphore    i mmap rwsem;
unsigned long          nrpages;
pgoff_t                writeback_index;
const struct address_space_operations *a_ops;
unsigned long          flags;
errseq_t              wb_err;
spinlock_t            private_lock;
struct list_head private_list;
void                  *private_data;
} attribute ((aligned(sizeof(long)))) randomize layout;
/*
 * On most architectures that alignment is already the case; but
 * must be enforced here for CRIS, to let the least significant bit
 * of struct page's "mapping" pointer be used for PAGE_MAPPING_ANON.
 */

struct file {
    union {
        struct llist_node    fu_llist;
        struct rcu_head fu_rcuhead;
    } f_u;
    struct path                f_path;
    struct inode              *f_inode;          /* cached value */
    const struct file_operations *f_op;
    /*
     * Protects f_ep, f_flags.
     * Must not be taken from IRQ context.
     */
    spinlock_t                f_lock;
    enum rw_hint              f_write_hint;
    atomic_long_t             f_count;
    unsigned int              f_flags;
    fmode_t                   f_mode;
    struct mutex              f_pos_lock;
    loff_t                    f_pos;
    struct fown_struct        f_owner;
    const struct cred         *f_cred;
    struct file_ra_state      f_ra;
    u64                       f_version;
#ifdef CONFIG_SECURITY
    void                      *f_security;
#endif
    /* needed for tty driver, and maybe others */
    void                      *private_data;

#ifdef CONFIG_EPOLL
    /* Used by fs/eventpoll.c to link all the hooks to this file */
    struct hlist_head        *f_ep;
#endif
} /* #ifdef CONFIG_EPOLL */
    struct address_space      *f_mapping;
    errseq_t                  f_wb_err;
    errseq_t                  f_sb_err; /* for syncfs */
} randomize layout
attribute ((aligned(4))); /* lest something weird decides that 2 is OK */

struct file_operations {
    struct module *owner;
    loff_t (*llseek) (struct file *, loff_t, int);
    ssize_t (*read) (struct file *, char __user *, size_t, loff_t *);
    ssize_t (*write) (struct file *, const char __user *, size_t, loff_t *);

```



```

    ssize_t (*read_iter) (struct kiocb *, struct iov_iter *);
    ssize_t (*write_iter) (struct kiocb *, struct iov_iter *);
    int (*iopoll) (struct kiocb *kiocb, bool spin);
    int (*iterate) (struct file *, struct dir_context *);
    int (*iterate_shared) (struct file *, struct dir_context *);
    __poll_t (*poll) (struct file *, struct poll_table_struct *);
    long (*unlocked_ioctl) (struct file *, unsigned int, unsigned long);
    long (*compat_ioctl) (struct file *, unsigned int, unsigned long);
    int (*mmap) (struct file *, struct vm_area_struct *);
    unsigned long mmap_supported_flags;
    int (*open) (struct inode *, struct file *);
    int (*flush) (struct file *, fl_owner_t id);
    int (*release) (struct inode *, struct file *);
    int (*fsync) (struct file *, loff_t, loff_t, int datasync);
    int (*fasync) (int, struct file *, int);
    int (*lock) (struct file *, int, struct file_lock *);
    ssize_t (*sendpage) (struct file *, struct page *, int, size_t, loff_t *,
int);
    unsigned long (*get_unmapped_area) (struct file *, unsigned long, unsigned
long, unsigned long, unsigned long);
    int (*check_flags) (int);
    int (*flock) (struct file *, int, struct file_lock *);
    ssize_t (*splice_write) (struct pipe_inode_info *, struct file *, loff_t *,
size_t,
unsigned int);
    ssize_t (*splice_read) (struct file *, loff_t *, struct pipe_inode_info *,
size_t,
unsigned int);
    int (*setlease) (struct file *, long, struct file_lock **, void **);
    long (*fallocate) (struct file *file, int mode, loff_t offset,
loff_t len);
    void (*show_fdinfo) (struct seq_file *m, struct file *f);
#ifdef CONFIG_MMU
    unsigned (*mmap_capabilities) (struct file *);
#endif
    ssize_t (*copy_file_range) (struct file *, loff_t, struct file *,
loff_t, size_t, unsigned int);
    loff_t (*remap_file_range) (struct file *file_in, loff_t pos_in,
struct file *file_out, loff_t pos_out,
loff_t len, unsigned int remap_flags);
    int (*fadvise) (struct file *, loff_t, loff_t, int);
} __randomize_layout;

struct path {
    struct vfsmount *mnt;
    struct dentry *dentry;
} __randomize_layout;

```