






Application type Web application Android Learn more Chrome App Learn more iOS Learn more PlayStation 4 Other Name Web client 1 Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/					
Android Learn more Chrome App Learn more iOS Learn more PlayStation 4 Other Name Web client 1 Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Application type				
Chrome App Learn more iOS Learn more PlayStation 4 Other Name Web client 1 Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Web application				
iOS Learn more PlayStation 4 Other Name Web client 1 Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Android Learn more				
PlayStation 4 Other Name Web client 1 Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Chrome App Learn more				
Name Web client 1 Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	iOS Learn more				
Web client 1 Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	PlayStation 4				
Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*e.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	· ·				
Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*e.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/					
Restrictions Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://e.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Name ②				
Enter JavaScript origins, redirect URIs, or both Learn More Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It o (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Web client 1				
Origins and redirect domains must be added to the list of Authorized Domains in the OAuth Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It of (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Restrictions				
Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It o (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Enter JavaScript origins, redirect URIs, or both Learn More				
Authorized JavaScript origins For use with requests from a browser. This is the origin URI of the client application. It o (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Origins and redirect domains must be added to the list of Authorized Domains in the OAuth				
For use with requests from a browser. This is the origin URI of the client application. It o (https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	origina and redirect domains must be duded to the list of Addionaged bornains in the order				
(https://*.example.com) or a path (https://example.com/subdir). If you're using a nonst in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/					
in the origin URI. https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/					
https://www.example.com Authorized redirect URIs For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a cannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	(https://*.example.com) or a path (https://example.com/subdir). If you're using a nons				
Authorized redirect URIs For use with requests from a web server. This is the path in your application that users authenticated with Google. The path will be appended with the authorization code for a sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	in the origin URI.				
For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a cannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	https://www.example.com				
For use with requests from a web server. This is the path in your application that users a authenticated with Google. The path will be appended with the authorization code for a cannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	Authorized redirect LIDIs				
authenticated with Google. The path will be appended with the authorization code for a Sannot contain URL fragments or relative paths. Cannot be a public IP address. https://sfdcintegration.wordpress.com/	7141101120110110110110110110110110110110110				
https://sfdcintegration.wordpress.com/ https://www.example.com					
https://sfdcintegration.wordpress.com/ https://www.example.com					
https://www.example.com	abiliot contain one magnitude of relative patris. Calmot be a public in address.				
	https://sfdcintegration.wordpress.com/				
	https://www.example.com				
Create Cancel	Create Cancel				
Sansar Sansar	Salise!				
















This app isn't verified

This app hasn't been verified by Google yet. Only proceed if you know and trust the developer.

If you're the developer, submit a verification request to remove this screen. Learn more


Hide Advanced

BACK TO SAFETY

Google hasn't reviewed this app yet and can't confirm it's authentic. Unverified apps may pose a threat to your personal data. <u>Learn more</u>


Go to wordpress.com (unsafe) -










Remote Site Edit Enter the URL for the remote site. All s-controls, JavaScript OnClick commands in custom buttons, Apex, and AJAX pro Remote Site Edit Save Save & New Cancel Remote Site Name | Gmail_API_Settings | https://www.googleapis.com Disable Protocol Security | i





















Gmail_Custom_Setting Edit Provide values for the fields you created. This data is cached with the application. Edit Gmail_Custom_Setting Save Save & New Cancel Gmail_Custom_Setting Information Name Gmail Endpoint Value https://www.googleapis.com/gmail/v1/users/me/messages









Timestamp Event Details 21:06:30:706 USER_DEBUG [21] DEBUG resp	Execution Log		
21:06:30:000 USER_DEBUG "messages": [21:06:30:000 USER_DEBUG { 21:06:30:000 USER_DEBUG "id": "1663a8c43838d96c", 21:06:30:000 USER_DEBUG "threadId": "1663a8c43838d96c" 21:06:30:000 USER_DEBUG }, 21:06:30:000 USER_DEBUG { 21:06:30:000 USER_DEBUG "id": "1663a57778bd2504", 21:06:30:000 USER_DEBUG "threadId": "1663a57778bd2504" 21:06:30:000 USER_DEBUG "threadId": "1663a57778bd2504"	Timestamp	Event	Details
21:06:30:000	21:06:30:706	USER_DEBUG	[21] DEBUG resp {
21:06:30:000	21:06:30:000	USER_DEBUG	"messages": [
21:06:30:000	21:06:30:000	USER_DEBUG	{
21:06:30:000	21:06:30:000	USER_DEBUG	"id": "1663a8c43838d96c",
21:06:30:000	21:06:30:000	USER_DEBUG	"threadId": "1663a8c43838d96c"
21:06:30:000	21:06:30:000	USER_DEBUG	},
21:06:30:000	21:06:30:000	USER_DEBUG	{
21:06:30:000 USER_DEBUG },	21:06:30:000	USER_DEBUG	"id": "1663a57778bd2504",
	21:06:30:000	USER_DEBUG	"threadId": "1663a57778bd2504"
21:06:30:000 USER_DEBUG {	21:06:30:000	USER_DEBUG	},
	21:06:30:000	USER_DEBUG	{

