Learning to Probe Before Acting: Critic-Free RL for Multi-Turn Code Agents

Abstract

Outcome-reward RL for LLMs often treats a sampled completion as one trajectory and broadcasts a single scalar advantage to every generated token. For a one-turn completion this is a crude but coherent approximation: the model state evolves by appending tokens to the context. In tool-using or multi-turn agents, the trajectory includes decisions whose effects pass through external state, tool outputs, and later prompts. An early probe or draft is not just a prefix of the final answer; it changes the information available to later turns. Uniformly assigning the final reward to all generated tokens can therefore give the wrong credit signal.

We study this issue in code-policy generation, a minimal setting where the final artifact is executable and objectively scored. The model interacts with a task for two chat turns. In the first turn it may run scratchpad or probe code, or submit a draft policy and observe feedback. In the second turn it must commit a Python `policy(state)` function. Only this final policy is executed for reward, so useful first-turn behavior receives credit only through its effect on later continuations.

We propose a critic-free estimator that branches rollouts at turn boundaries. For each prompt, the model samples several first-turn variants and several final continuations under each variant. Leaf rewards define a root Monte Carlo baseline for the prompt and a conditional baseline for each first-turn prefix. First-turn tokens are credited when their prefix improves the expected reward of downstream continuations; final-turn tokens are compared only against continuations from the same prefix.

The estimator is paired with a simple implementation for token-summed clipped policy-gradient objectives. Because the objective is additive over disjoint sets of model tokens when all pieces share the same global token normalizer, the loss can be evaluated one turn at a time while accumulating the exact full-trajectory gradient.

We evaluate on a custom slosh-tank control task. The policy observes cart and slosh state but not actuator gain. A first-turn probe can estimate the gain from the response to a commanded pulse; the final policy can then adapt its controller. Frozen two-turn prompting follows the probe format but does not compute or use the gain estimate, leaving a concrete target for RL training.

1 Introduction

Reinforcement learning is, in part, the problem of assigning credit across decisions. Modern outcome-reward RL for LLMs usually simplifies this problem: sample a completion, score the completed answer, and broadcast a single advantage to all generated tokens. For a one-turn completion this approximation is often serviceable because the dynamics are just autoregressive context growth. Each token influences later tokens by becoming part of the prefix.

That simplification becomes less well matched to tool-using and multi-turn agents. A trajectory may contain natural-language reasoning, tool calls, scratchpad programs, environment probes, candidate solutions, and final answers. These are not merely contiguous pieces of one answer. A tool call can change the external state or reveal information; a scratchpad program can produce

observations that later code uses; a draft can shape the next prompt through tool feedback. Treating all generated tokens as equally responsible for the final reward ignores this structure.

This paper studies a small, verifiable instance of that broader problem. The agent must write executable policy code. It is given an environment interface, interacts for two chat turns, and finally emits a Python `policy(state)` function. The final policy is executed across scenarios and receives a scalar reward. The deployed object is therefore a program, not an LLM queried during control.

This setting connects multi-turn agent RL with recent work on executable discovery. Systems such as FunSearch and AlphaEvolve search over programs using automated evaluation, and AI-Scientist-style systems place code execution inside larger research loops [10, 11, 12]. Our focus is narrower: rather than building a full discovery system, we isolate one learning problem that such systems face when useful work happens before the final executable artifact is scored.

The key example in this paper is probe-and-adapt control. The environment hides an actuator gain from the policy state. A first-turn program can command a short pulse, observe the velocity change, and infer the gain. A second-turn policy can then rescale its controller. If the final policy succeeds, however, a flat reward does not say whether the first-turn probe was informative or whether the second-turn code happened to work despite it.

We propose a critic-free Monte Carlo estimator for this situation. For each prompt, we sample a small tree: multiple first-turn variants, and multiple second-turn continuations below each variant. The average reward over the whole tree estimates the root value. The average reward below one first-turn branch estimates the value of that prefix. The difference gives a first-turn advantage. The difference between a leaf reward and its prefix value gives a second-turn advantage. Thus, early turns are trained according to the downstream contexts they create, while final turns are trained relative to alternatives from the same context.

This estimator is related to recent multi-turn agent-RL and credit-assignment work. ArCHer learns turn-level values; RAGEN/StarPO studies flat trajectory-level optimization for interactive agents; Agent Lightning frames agent executions as MDP trajectories; and turn-level reward-design methods add intermediate rewards to PPO or GRPO [6, 4, 13, 14]. Our setting keeps the sparse final-reward assumption: no learned value head and no hand-designed turn reward. It also follows the spirit of VinePPO, but branches at tool-turn boundaries rather than inside a single completion [3].

The implementation uses a standard token-summed clipped surrogate. The useful property is additivity: if all partial losses share the same global token normalizer, the loss can be split across turns. We therefore compute one forward/backward pass per turn and accumulate the exact full-trajectory gradient. This is an implementation device, not the main conceptual contribution.

The contributions are:

1. a critic-free turn-level Monte Carlo baseline for sparse-reward multi-turn RL;
2. an application of this baseline to code-policy generation, where an early turn may gather information used by the final executable policy;
3. an exact turn-wise implementation of the token-summed clipped objective;
4. a probe-and-adapt benchmark with a measured blind-vs-oracle gap, plus an ablation design comparing flat multi-turn, branched flat, and hierarchical per-turn baselines.

2 Related work

Sparse-reward multi-turn LLM agents. Recent work treats LLM agents as sequential decision-makers rather than single completions. ArCHer uses learned turn-level values for language agents [6]. RAGEN/StarPO studies trajectory-level reinforcement learning for interactive agents [4]. Agent Lightning casts arbitrary agent executions as MDP trajectories with a credit-assignment module [13]. Other work adds explicit turn-level rewards to multi-turn PPO or GRPO [14]. These approaches address the same failure mode: a final reward alone is too coarse to say which turn mattered. Our method differs by estimating turn-level baselines from final rewards alone, without a learned critic or manually designed intermediate reward.

Monte Carlo credit assignment without critics. GRPO replaces PPO's learned critic with group-relative Monte Carlo baselines [1]. Token-summed variants such as DAPO modify the normalization for long language-model completions [2]. These methods are critic-free, but a flat group baseline still assigns the same advantage to every token in a trajectory. VinePPO addresses a related issue by re-branching from intermediate reasoning states and estimating values with Monte Carlo continuations [3]. Our estimator is the turn-level analogue: the branch points are chat/tool boundaries, and the resulting scalar advantage is broadcast to the tokens of the corresponding turn.

Executable discovery and code generation. FunSearch, AlphaEvolve, and related systems show that LLMs can search over executable programs using automated evaluators [10, 11]. Work on automatic discovery of RL algorithms broadens this view to machine-designed update rules [15]. CodeRL, RLTF, and SWE-RL use execution or rule-based feedback to train code generators [16, 17, 18]. ReVeal is closer to our setting because it uses multi-turn code generation with tool feedback and dense per-turn rewards [19]. Our setting is different in that the first turn is valuable primarily as information gathering: it may reveal a hidden environment parameter that the final policy should exploit.

Scientific agents. AI-Scientist-style systems use LLMs to generate hypotheses, write and run code, analyze results, and draft papers [12]. These systems motivate our setting, but they operate at a higher level of abstraction. We study a smaller trainable component: how to assign credit inside a multi-turn, tool-mediated interaction when only the final executable artifact receives a reward.

3 Method

3.1 Setup

The agent is a language model π_θ over chat-template trajectories. The base is `Qwen3-4B-Instruct-2507` with frozen weights W; θ parameterizes a LoRA adapter $W' = W + AB^\top$. A task $\mathcal{T}$ specifies environment source code, S scenarios $\{\sigma_i\}$ that vary the seed and hidden parameters, and a per-scenario reward. The scoring oracle runs a candidate policy body in a sandboxed subprocess against each scenario and returns $R(\text{code}; \mathcal{T}) = \sum_i r_i(\text{code}; \sigma_i)$. Validation failures, errors, and timeouts on σ_i score the *error floor* $r_i = -200$, calibrated below any running-but-failing trajectory — otherwise errored rollouts ($r = 0$) outrank running-but-poor rollouts and the gradient rewards crashing.

3.2 Chat-template protocol

Each turn the model emits one fenced code block tagged `policy` or `main`. `policy` defines `def policy(state)`, which the tool executes across all scenarios and reports the summed reward

as a user-role message. `main` is scratchpad or probe code run in a rehearsal sandbox; the tool returns truncated stdout but no final policy reward. The final turn must be `policy`; `main` or untagged final turns are floored. Malformed intermediate turns are likewise floored and surfaced as a textual rejection. A length-N trajectory is $\tau = (s, y^{(1)}, m^{(1)}, \ldots, y^{(N-1)}, m^{(N-1)}, y^{(N)})$, with completions $y^{(n)}$ alternating with tool messages $m^{(n)}$, and $R(\tau) = R(\text{code in } y^{(N)})$ the only scalar reward. The remainder of the paper specializes to N=2: a single intermediate turn (draft policy or scratchpad) followed by a committed `policy`. Generalizing the rollout, advantages, and loss decomposition below to N>2 is straightforward (see §6).

3.3 Token-summed clipped surrogate

For trajectory b at position t, with importance ratio $\rho_t^b = \pi_\theta/q$ and per-token advantage A_t^b,

$$\mathcal{L}(\theta) = -\frac{1}{N_{\text{tok}}} \sum_{b,t} \mathbf{1}\{\text{model token}\} \cdot \min\big(\rho_t^b A_t^b,\ \text{clip}(\rho_t^b,\ 1-\epsilon_{\text{lo}},\ 1+\epsilon_{\text{hi}}) A_t^b\big), \tag{1}$$

with N_{tok} the count of model tokens in the global batch.[1] (1) is *additive over disjoint token subsets*: for any partition of model-token positions, the loss equals the sum of partial losses computed with the same N_{tok}. This is the property the per-turn decomposition (§3.6) exploits.

3.4 Branched rollout

For each prompt s, sample G_1 turn-1 variants in one `model.generate` call: $y_i^{(1)} \sim q(\cdot \mid s)$, $i = 1, \ldots, G_1$. For each $y_i^{(1)}$ execute the tool to obtain m_i, then sample G_2 continuations $y_{i,j}^{(2)} \sim q(\cdot \mid s, y_i^{(1)}, m_i)$ in one call. Score each leaf to obtain $\{R_{i,j}\}$. Generate-call cost per prompt is $1 + G_1$, versus $2G_1G_2$ for an unbranched rollout with the same number of leaves.

3.5 Per-turn MC value estimates and advantages

Two empirical values, both pure averages over the tree:

$$\widehat{V}_0 = \frac{1}{G_1 G_2} \sum_{i,j} R_{i,j}, \qquad \widehat{V}_1^{(i)} = \frac{1}{G_2} \sum_{j} R_{i,j}. \tag{2}$$

$\widehat{V}_0$ estimates the initial-state value; $\widehat{V}_1^{(i)}$ the value after committing to turn-1 variant $y_i^{(1)}$. Per-turn advantages, broadcast to every token of the corresponding turn:

$$A_i^{(1)} = \widehat{V}_1^{(i)} - \widehat{V}_0 \qquad \text{(over } y_i^{(1)}\text{)}, \tag{3}$$

$$A_{i,j}^{(2)} = R_{i,j} - \widehat{V}_1^{(i)} \qquad \text{(over } y_{i,j}^{(2)}\text{)}. \tag{4}$$

The turn-2 advantage uses the conditional mean given the turn-1 prefix rather than the global per-prompt mean: a poor turn-2 sample drawn from a strong turn-1 is recognized as poor instead of inheriting its prefix's above-average outcome. Tool-message tokens are masked via `tool_mask`; their advantage is zero. Figure 1 contrasts this scheme with the two closest critic-free / per-turn-credit baselines for multi-turn LLM RL.

3.6 Per-turn loss decomposition

The token-summed clipped surrogate (1) factors over any partition of the model-token positions into disjoint subsets that share the same global normalizer N_{tok}. Letting $\mathcal{I}_n$ index the model

[1] This matches the DAPO and CISPO recipes; per-row averaging variants (original GRPO, BNPO, Dr.GRPO) divide by per-row token counts.




Figure 1: Comparison of credit-assignment mechanisms on a 2-turn branched rollout from prompt s with G_1=G_2=2. All three panels show the same rollout structure — turn-1 fan-out $\{y_i^{(1)}\}$, tool message m_i, turn-2 fan-out $\{y_{i,j}^{(2)}\}$, leaf rewards $R_{i,j}$ — and differ only in how the per-token baseline is computed. **(a) Flat baseline** (StarPO / RAGEN [4], the N=2 generalization of RLOO/GRPO [1] from Figure 2 of [3]): one mean $\widehat{V}_0$ over all G_1G_2 leaves, broadcast to every model token of both turns. A poor turn-2 from a strong turn-1 inherits its prefix's above-average outcome. **(b) Per-turn critic** (ArCHer [6]): a learned value head $\widehat{V}_\phi(s_n)$ provides per-state baselines at each turn boundary, with the moving-target bias issues typical of bootstrapped value learning. **(c) Per-turn MC** (ours, Arm F): the conditional mean $\widehat{V}_1^{(i)} = \frac{1}{G_2}\sum_j R_{i,j}$ over the G_2 continuations of turn-1 variant i baselines that variant's turn-1 tokens; $\widehat{V}_0$ baselines the root. Turn-2 tokens are scored against their own prefix's $\widehat{V}_1^{(i)}$, not the global mean. Group-relative within a turn, VinePPO-like across turns — i.e., VinePPO's intra-completion MC re-branching [3], applied at turn boundaries.

tokens of turn n,

$$\mathcal{L} = \sum_{n=1}^{N} \mathcal{L}_{\mathcal{I}_n}, \qquad N_{\text{tok}} = \sum_{n=1}^{N} |\mathcal{I}_n|. \tag{5}$$

Per-row averaged variants (original GRPO, BNPO, Dr.GRPO) do *not* factor this way: each row carries its own denominator, so the partial sums do not combine into the single-row loss. The token-summed form is what makes the decomposition exact.

(5) is exploited to compute $\mathcal{L}$ in N forward/backward passes rather than one. Pass n forwards $[s \,|\, y^{(1)} \,|\, m^{(1)} \,|\, \ldots \,|\, y^{(n)}]$, computes $\mathcal{L}_{\mathcal{I}_n}$, backwards, and frees. By (5) the parameter gradients accumulated across the N passes equal the single-pass gradient exactly.

Why this saves memory. The dominant activation cost is the LM-head logit tensor ($|V|$ = 151,936). A single forward+backward over the full trajectory holds the saved-for-backward LM-head tensors at all $\sum_n T_n$ model-token positions simultaneously; doing one forward+backward per turn holds at most $\max_n T_n$ positions at peak, and (5) guarantees the accumulated gradient is identical. This is gradient accumulation at the turn level within a trajectory — the saving is a factor of roughly N for equal-length turns, $\approx 2\times$ at our N=2 settings. Appendix A works through the accounting.

Restrictions. The decomposition's exactness has one *conceptual* requirement and two *implementation* requirements. Conceptual: the token-summed normalizer of (1) — per-row averaged variants do not factor across token-position partitions, as discussed above. Implementation: $\beta = 0$ (a KL term to π_{ref} would require per-segment slicing of reference log-probabilities) and `num_iterations`$= 1$ (so cached `old_per_token_logps` need no re-segmenting). The two implementation requirements can be lifted with extra bookkeeping at no theoretical cost (§6).

4 Experimental setup

Environment. We use a custom slosh-tank control task rather than a standard benchmark whose solution may already be familiar to the base model. A cart carries liquid represented by a damped pendulum mode. The policy observes $\{t, x, v, \theta, \omega, g, \text{steps_left}\}$ and outputs acceleration clipped to $[-1, 1]$ m/s^2. Success requires reaching the goal while also settling velocity, slosh angle, and slosh velocity. In the V1 task, the only hidden parameter is actuator gain $\kappa \in \{0.65, 0.80, 1.00\}$; all other parameters are fixed. Full dynamics and the gain sweep are in Appendix B.

Why it tests turn-level credit. A first-turn probe can estimate κ by commanding a short pulse and measuring $\Delta v/(a_{\text{cmd}}\Delta t)$. The final policy can then rescale its controller. This makes the first turn useful only through its effect on the final policy. Blind nominal PD has a large gap to an oracle that divides actions by κ: at the V1 levels the blind-vs-oracle success gaps are 100, 49.5, and 0 percentage points. Thus the task has one stress level, one transitional level, and one nominal level.

Model and training. We train LoRA rank $r = 16$ on attention projections of `Qwen3-4B-Instruct-2507`; base weights are frozen, bf16 is used, and gradient checkpointing is enabled. Unless stated otherwise, $G_1 = G_2 = 4$ and each turn is capped at 400 tokens. The loss is the token-summed clipped surrogate (1) with $\epsilon_{\text{lo}} = 0.2$, asymmetric upper clipping, $\beta = 0$, no critic, no GAE, and no context truncation across turns.

Diagnostics. We log $\widehat{V}_0$, the between-prefix and within-prefix reward standard deviations, their ratio, per-turn advantage scales, error-floor rate, and generate calls per prompt. The between/within ratio is also used diagnostically: values above one indicate that first-turn choice dominates continuation noise, where per-turn credit should help most.

5 Evaluating the per-turn credit assignment

The substantive empirical claim is the credit-assignment contribution: hierarchical per-turn advantages (3)–(4) should outperform a flat trajectory-level advantage broadcast across both turns. Table 1 defines the six-arm ablation. The key comparisons are E vs. D for the rollout tree and F vs. E for the per-turn baseline.

Primary metric. Held-out four-condition success rate on a stress distribution (more extreme actuator-gain values than train, i.e. κ further from 1) at the best checkpoint, reported as median and IQR over ≥ 3 seeds per arm, plotted against gradient steps and against wall-clock. Statistical test: paired Wilcoxon over per-seed best-checkpoint goal rates; report effect size, not just p. The minimum convincing comparison is F > D at matched leaves.

Diagnostic checks. We track two mechanism checks. First, when turn 1 emits a `policy`, its reward should improve faster under F than under flat multi-turn training. Second, prompts with high iteration-0 signal ratio $\widehat{\sigma}(\widehat{V}_1^{(i)})/\overline{\widehat{\sigma}(R_{i,\cdot})}$ should show the largest F–D gain; otherwise the proposed credit-assignment explanation is weak.

Arm	Rollout structure	Advantage	What it isolates over the previous arm
A — Frozen, one-shot	N=1 inference, no training	—	Base model's prior on the code-policy interface
B — Frozen, multi-turn prompted	N=2 inference, no training	—	Does the two-turn protocol help at inference time? (Voyager-/FunSearch-style frozen-LLM use)
C — Single-turn GRPO	G flat N=1 rollouts, trained	Standard GRPO advantage	Does RL fine-tuning help at all?
D — Flat StarPO	G independent N=2 trajectories, trained	$A(\tau) = R(\tau) - \bar{R}$, broadcast to all tokens	Does multi-turn training help over single-turn? (RAGEN-style)
E — Branched, flat	$G_1 \times G_2$ tree, trained	$A_{i,j} = R_{i,j} - \bar{R}$ on all tokens	Does the tree alone help (more leaves per generate call), independent of credit?
F — Branched, hierarchical (ours)	$G_1 \times G_2$ tree, trained	$A_i^{(1)} = \widehat{V}_1^{(i)} - \widehat{V}_0$ on $y_i^{(1)}$; $A_{i,j}^{(2)} = R_{i,j} - \widehat{V}_1^{(i)}$ on $y_{i,j}^{(2)}$	The per-turn baseline contribution

Table 1: Ablation arms, ordered from weakest baseline (top) to ours (bottom). Trained arms (C–F) match leaf count $G = G_1 G_2 = 16$ so they see the same number of scored trajectories per step. D uses $2G$ `generate` calls per prompt; F uses $1 + G_1$. Report both equal-rollouts and equal-wall-clock comparisons. Frozen arms (A, B) use `Qwen3-4B-Instruct-2507` (§3.1) with no gradient updates, and serve as training-free references analogous to Voyager- or FunSearch-style frozen-LLM uses of the code-policy interface. (Table 2's Qwen2.5-Coder-3B numbers are preserved as the historical Arm A record from the prior base model; the current 1-turn re-run on Qwen3-4B is in Table 3's third column.)

Arm A: frozen one-shot baseline (preliminary). Table 2 reports the first completed arm. Qwen2.5-Coder-3B-Instruct (no LoRA, N=1, temperature 0.8) achieves **0% success** at all three gain values $\kappa \in \{0.65, 0.80, 1.00\}$ over 20 sampled policies $\times$ 50 seeds each. The mean reward ≈ -112 is well below both the blind PD (-10 to $+112$ depending on κ) and the oracle ($+111$), a gap of $\approx$223 points. Even the single best generated policy scores -12.1 at every κ, confirming the base model cannot write a working controller zero-shot. Two failure modes account for the result: $\approx$40% of policies crash at runtime (hallucinated state keys; penalised at -200), and the rest produce control-theoretically wrong code (reversed-sign bang-bang, pendulum dynamics mis-applied as a control law). The flat reward across all three κ values confirms the model has no awareness of the hidden gain. This large gap to both reference curves establishes that RL fine-tuning has a clear training signal, validating the benchmark difficulty.

κ	Qwen 1-shot (mean)	Qwen 1-shot (max)	Blind PD	Oracle PD
0.65	-112.0	-12.1	-9.6	$+111.2$
0.80	-111.9	-12.1	$+45.9$	$+111.4$
1.00	-111.9	-12.1	$+111.5$	$+111.5$

Table 2: Arm A: frozen one-shot Qwen2.5-Coder-3B-Instruct vs. reference policies on the slosh-tank task ($\kappa \in \{0.65, 0.80, 1.00\}$, 20 policy samples, 50 seeds each, κ fixed per episode). Mean reward averages over all samples; max is the best mean achieved by any single generated policy. Crashed policies scored at -200 (matching the GRPO training signal). Oracle scales PD gains by $1/\kappa$; blind uses nominal gains.

Arm B: frozen two-turn baseline (preliminary). Table 3 reports the second completed arm: the same model in the two-turn probe-then-adapt prompt (N=2, temperature 0.8, 20 sampled policies × 50 seeds per κ). Arm B was run after adopting `Qwen3-4B-Instruct-2507` as the study's base model; for direct comparability, the 1-turn run was repeated on the same base and is included as the third column of Table 3. Table 2's Qwen2.5-Coder-3B numbers remain as the original Arm A record.

The format gate fires, the value transfer does not. 60/60 samples open turn 1 with `# MODE: main` and call `env.reset()` — vs. 27% `main`-mode usage on the earlier 3B baseline; 21/60 also step the env at least once with a known commanded acceleration. Yet **0/60 samples compute a κ estimate** from the probe data: the arithmetic that would turn the printed Δv into a gain estimate — $\kappa \approx \Delta v/(a_{\text{cmd}}\,\Delta t)$ at $\theta \approx \omega \approx 0$ on a single step — is never written, even when all of a_{cmd}, Δv, and Δt are on screen. The protocol's intent appears in 60/60 turn-1 comments ("probing the environment to gain insights about the hidden actuator gain κ"); the corresponding code appears zero times.

Mean reward improves modestly; success rate does not. The 2-turn per-sample median mean-reward exceeds the 1-turn median by 12–18 points at every κ (-57.7 vs. -76.3 at $\kappa = 0.65$; -74.2 vs. -86.8 at $\kappa = 0.80$; -68.2 vs. -86.5 at $\kappa = 1.00$), consistent with the model writing slightly better controllers in turn 2 after seeing the state shape printed in turn 1 — a weak format-side effect, not information gathering. Success rate stays $\leq 0.7\%$ across all κ, driven by a single $\kappa = 0.65$ sample whose Pattern-D (reset-only) probe transferred no information and whose turn-2 body is a clean four-state PD controller earning +5.7 mean reward and 14% per-seed success rate — the first positive frozen-baseline reward on the slosh task, and an instance of *control reasoning* improving rather than probe-then-adapt operating.

The probe-then-adapt protocol is therefore *nominal but not operative*: every sample passes the format gate, the prompt's instruction to probe is followed, but the value the protocol is supposed to deliver — a κ estimate that conditions the turn-2 controller — never materialises. The headline gap RL fine-tuning has to close is exactly to make κ-estimation arithmetic appear in turn-1 probe code and be *read* by the turn-2 policy. The signal the trainer needs is supplied by the G_2 branched continuations of §3.6: a turn-1 probe that contains the information turn-2 needs should produce, on average, higher-reward G_2 leaves, and the per-turn baseline $\widehat{V}_1^{(i)}$ of Figure 1 (c) is what propagates that signal back to turn-1 tokens.

κ	Naive PD	Oracle PD	Qwen3-4B 1-turn	Qwen3-4B 2-turn
0.65	0%	100%	0%	**0.7**%†
0.80	46%	100%	0.5%	0%
1.00	100%	100%	0.7%	0%

Table 3: Arms A and B on `Qwen3-4B-Instruct-2507` vs. reference controllers on the slosh-tank task. Success rate is the fraction of 50 episodes simultaneously meeting all four settling conditions ($|x-g|, |v|, |\theta|, |\omega|$), averaged over 20 generated policies. Naive uses nominal PD gains; oracle scales gains by $1/\kappa$. †The $\kappa = 0.65$ Arm B aggregate is driven by a single outlier sample with 14% per-seed success; the per-sample distribution is otherwise within sampling noise of the 1-turn column at n=20 (median rewards -57.7 vs. -76.3). The best Arm B sample is the first positive frozen-baseline mean reward observed on this task.

Failure modes. If F does not beat D, the hierarchical baseline is not useful in this domain. If F ≈ E while both beat D, the benefit comes from branching rather than turn-level credit. If C–F do not beat A/B, the protocol is better framed as prompting rather than RL training.

6 Limitations and future work

The implementation and experiments use $N = 2$. Extending to more turns is conceptually direct: each boundary value becomes the conditional Monte Carlo mean over the subtree below it, and the loss decomposition applies one partial loss per turn. The cost is bookkeeping and additional forward/backward passes, not a new estimator.

The method also assumes deterministic rewards given the seed. In stochastic environments, the same estimator applies but G_2 must grow to separate prefix quality from environment noise. The current implementation uses $\beta = 0$ and `num_iterations`= 1; KL penalties and cached old log-probabilities can be supported by storing the same quantities per turn segment.

A natural memory/variance extension is token subsampling within a turn. Since each turn uses one scalar advantage broadcast across its tokens, subsampling tokens is an unbiased estimator of the same token-summed gradient when N_{tok} counts only kept positions. We leave uniform and asymmetric subsampling variants to future work.

7 Conclusion

We present a critic-free approach to turn-level credit assignment in sparse-reward multi-turn RL. The method branches rollouts at chat-turn boundaries and uses the resulting Monte Carlo conditional means as per-turn baselines. We apply it to code-policy generation, where the first turn can gather information and the final turn emits the executable policy that receives reward. The token-summed objective also gives an exact turn-wise implementation, but the main goal is credit assignment: giving useful early turns a learning signal when only the final artifact is scored.

A Memory accounting and the trailing-window LM-head

The loss only needs logits whose successor token was emitted by the model; prompt and tool-message logits do not contribute. HF `transformers` exposes this through `logits_to_keep`: an integer keeps the last K positions, while an index tensor selects arbitrary positions.

This reduces unnecessary logits, but a single forward/backward still holds all selected LM-head outputs until backward completes. With gradient checkpointing, transformer-body activations are comparatively small; the expensive saved tensor is the LM-head output of shape $(B, K, |V|)$. Therefore, a full multi-turn backward over all model tokens scales with $K = \sum_n T_n$.

The per-turn decomposition serializes these positions. Turn n forwards the prefix through $y^{(n)}$, computes the partial token-summed loss for that turn using the global N_{tok}, backpropagates, and frees the graph. By additivity of (1), the accumulated gradient equals the single-pass gradient, while the peak LM-head tensor scales with $\max_n T_n$.

Regime	Positions through LM head	Logit tensor
Single pass, no `logits_to_keep`	$T_{\text{full}} = 1350$	$\approx 13.1\,\text{GB}$
Single pass, selected model tokens	$\sum_n T_n = 800$	$\approx 7.8\,\text{GB}$
Two turn-wise passes	400 per pass, freed between	$\approx 3.9\,\text{GB}$

Table 4: Arithmetic LM-head logit sizes for $B = 16$, $|V| \approx 152{,}000$, and 4-byte logits. Total GPU memory also includes weights, optimizer state, body activations, KV cache, and allocator overhead.

The decomposition is not a new `logits_to_keep` trick; all regimes use the same primitive. The non-trivial point is that token-summed normalization makes the per-turn gradients sum exactly to

the full-trajectory gradient. Per-row-averaged variants would require either a different normalizer or an approximation.

B Slosh-tank environment

A one-dimensional cart carries liquid represented by one damped pendulum mode. The policy commands horizontal acceleration clipped to $[-1, 1]$ m/s^2 and observes $\{t, x, v, \theta, \omega, g, \text{steps_left}\}$. Hidden parameters can include actuator gain κ, delay D, deadband b, slosh length L, and damping c; V1 varies only κ.

The semi-implicit dynamics use $\Delta t = 0.06$ s:

$$\begin{aligned} a_{\text{true}} &= \kappa \,\text{deadband}(a_{\text{cmd}[t-D]}), \\ v \mathrel{+}= \Delta t\, a_{\text{true}}, &\qquad x \mathrel{+}= \Delta t\, v, \\ \dot{\omega} = -\frac{g}{L}\theta - c\omega - a_{\text{true}}, &\qquad \dot{\theta} = \omega. \end{aligned} \tag{6}$$

Success requires $|x-g| < \epsilon_x$, $|v| < \epsilon_v$, $|\theta| < \epsilon_\theta$, and $|\omega| < \epsilon_\omega$ simultaneously, preventing controllers that reach the goal without settling the liquid.

Why actuator gain is the V1 unknown. With goal distance $D_g \approx 1.8$ m and $a_{\max} = 1$ m/s^2, the minimum bang-bang transit time is $T_{\text{tr}} = 2\sqrt{D_g/a_{\max}} = 2.68$ s. The episode time gives slack $\tau = T_{\text{ep}}/T_{\text{tr}} = 2.35$. Thus low κ does not mainly cause transit failure; it slows near-goal settling because all corrective actions are attenuated. This creates a smooth blind-vs-oracle gap while keeping the probe interpretable: for a short pulse near $\theta \approx \omega \approx 0$, $\kappa \approx \Delta v/(a_{\text{cmd}}\Delta t)$.

Confirmed V1 configuration.

Parameter	Symbol	V1 value	Status
Episode steps	N_{steps}	105 ($\tau = 2.35$)	fixed
Actuator gain	κ	$\{0.65, 0.80, 1.00\}$	varied
Action delay	D	0	fixed
Deadband	b	0	fixed
Slosh length	L	0.70 m	fixed
Damping	c	0.06 s^{-1}	fixed

Empirical blind-vs-oracle gap

Table 5 and Figure 2 show the reference sweep over 200 seeds per gain. Blind nominal PD transitions from 0% to 100% success across $\kappa \in [0.65, 0.90]$, while the oracle controller remains at 100%. The V1 levels therefore give one stress case, one transitional case, and one nominal case.

κ	Blind PD success	Oracle PD success
0.65	0%	100%
0.70	0%	100%
0.75	25.5%	100%
0.80	50.5%	100%
0.85	85%	100%
0.90	100%	100%

Table 5: Blind nominal PD vs. oracle PD with actions divided by κ.

The two-turn protocol is useful only if a probe-aware controller can close some of this gap. The blind controller sets the no-probe baseline, the oracle sets the upper bound, and a hand-written pulse-probe controller is the achievable probe-aware reference.




Figure 2: Blind and oracle success vs. actuator gain over 200 seeds per level.

References

[1] Z. Shao et al. *DeepSeekMath*. arXiv:2402.03300, 2024.

[2] Q. Yu et al. *DAPO: An Open-Source LLM Reinforcement Learning System at Scale*. arXiv:2503.14476, 2025.

[3] A. Kazemnejad et al. *VinePPO: Unlocking RL Potential For LLM Reasoning Through Refined Credit Assignment*. arXiv:2410.01679, 2024.

[4] Z. Wang et al. *RAGEN: Training Agents by Reinforcing Reasoning*. 2025.

[5] Z. Liu et al. *GEM: Reinforcement Learning for Generalist Models*. 2025.

[6] Y. Zhou et al. *ArCHer: Training Language Model Agents via Hierarchical Multi-Turn RL*. ICML, 2024.

[7] P. Wang et al. *Math-Shepherd*. ACL, 2024.

[8] L. Luo et al. *Improve Mathematical Reasoning in Language Models by Automated Process Supervision*. arXiv:2406.06592, 2024.

[9] G. Wang et al. *Voyager*. TMLR, 2024.

[10] B. Romera-Paredes et al. *Mathematical discoveries from program search with large language models*. Nature, 2024.

[11] A. Novikov et al. *AlphaEvolve: A coding agent for scientific and algorithmic discovery*. 2025.

[12] C. Lu et al. *The AI Scientist: Towards Fully Automated Open-Ended Scientific Discovery*. arXiv:2408.06292, 2024.

[13] X. Luo et al. *Agent Lightning: Train ANY AI Agents with Reinforcement Learning*. arXiv:2508.03680, 2025.

[14] W. Zeng et al. *Reinforcing Multi-Turn Reasoning in LLM Agents via Turn-Level Reward Design*. arXiv:2505.11821, 2025.

[15] J. Oh et al. *Discovering State-of-the-art Reinforcement Learning Algorithms*. Nature, 2025.

[16] H. Le et al. *CodeRL: Mastering Code Generation through Pretrained Models and Deep Reinforcement Learning*. NeurIPS, 2022.

[17] J. Liu et al. *RLTF: Reinforcement Learning from Unit Test Feedback*. 2023.

[18] Y. Wei et al. *SWE-RL: Advancing LLM Reasoning via Reinforcement Learning on Open Software Evolution*. 2025.

[19] M. Jin et al. *ReVeal: Reinforcement Learning for Verifiable Multi-Turn Code Generation*. 2025.