ls
1
grep
2
nl
3
nl
4
python
5
python
6
python
7
8
nl
9
python
10
python
11
grep
12
echo
12
git
12
git
localization
patch
validation
general

```
.../n")if old in s:    s = s.replace(old, new)    p.write_text(s)    print('patched')else:    print('pattern not found')
```

```
.../from django.http import httpresponse# memoryview contentr = httpresponse(memoryview(b"my content"))print(repr(r.content))print(type(r.content))# bytearray contentr2 = httpresponse(bytearray(b"bytearr"))print(repr(r2.content))print(type(r2.content))# string and bytes to ensure no regressionsr3 = httpresponse("text")r4 = httpresponse(b"bytes")print(repr(r3.content), type(r3.content))print(repr(r4.content), type(r4.content))
```

```
.../from django.conf import settingsif not settings.configured:    settings.configure(default_charset='utf-8')from django.http import httpresponse# memoryview contentr = httpresponse(memoryview(b"my content"))print(repr(r.content))print(type(r.content))# bytearray contentr2 = httpresponse(bytearray(b"bytearr"))print(repr(r2.content))print(type(r2.content))# string and bytes to ensure no regressionsr3 = httpresponse("text")r4 = httpresponse(b"bytes")print(repr(r3.content), type(r3.content))print(repr(r4.content), type(r4.content))
```

```
.../n"if old in s:    s = s.replace(old, new)    p.write_text(s)    print('patched iterable check')else:    print('pattern not found')
```

```
.../from django.conf import settingsif not settings.configured:    settings.configure(default_charset='utf-8')from django.http import httpresponsetests = [    ('memoryview', httpresponse(memoryview(b"my content"))),    ('bytearray', httpresponse(bytearray(b"bytearr"))),    ('str', httpresponse("text")),    ('bytes', httpresponse(b"bytes")),    ('iterable_chunks', httpresponse([b'hello ', b'world'])),]for name, resp in tests:    print(name, '->', repr(resp.content), type(resp.content))# also verify write() and writelines() behaviorr = httpresponse()r.write(memoryview(b'xyz'))r.write(bytearray(b'123'))r.writelines([b'aa', b'bb'])print('write+writelines ->', repr(r.content))
```