ls
1
grep
1
true
2
nl
3
nl
4
nl
5
grep
5
6
nl
7
python3
8
python3
django
9
pytest
10
python3
11
python3
12
echo
12
git
12
git
localization
patch
validation
general

```
.../n                    user = none',    s,    flags=re.m)p.write_text(s)print("patched", p)
```

```
.../fallback secret (what would have been generated before rotation)key_salt = "django.contrib.auth.models.abstractbaseuser.get_session_auth_hash"old_hash = salted_hmac(key_salt, user.password, secret=settings.secret_key_fallbacks[0], algorithm="sha256").hexdigest()# some invalid hashinvalid_hash = "0"*64print("current_hash matches helper:", auth._session_hash_matches(user, current_hash))print("old_hash matches helper (fallback):", auth._session_hash_matches(user, old_hash))print("invalid_hash matches helper:", auth._session_hash_matches(user, invalid_hash))
```

```
.../from django.conf import settings# minimal settings needed for our testsettings.configure(    secret_key="new_secret_key_123",    secret_key_fallbacks=["old_secret_key_abc"],    installed_apps=[],)import djangodjango.setup()from django.contrib import authfrom django.utils.crypto import salted_hmacclass dummyuser:    def __init__(self, password):        self.password = password    def get_session_auth_hash(self):        key_salt = "django.contrib.auth.models.abstractbaseuser.get_session_auth_hash"        return salted_hmac(key_salt, self.password, algorithm="sha256").hexdigest()user = dummyuser("pbkdf2_password_hash_example")current_hash = user.get_session_auth_hash()key_salt = "django.contrib.auth.models.abstractbaseuser.get_session_auth_hash"old_hash = salted_hmac(key_salt, user.password, secret=settings.secret_key_fallbacks[0], algorithm="sha256").hexdigest()invalid_hash = "0"*64print("current_hash matches helper:", auth._session_hash_matches(user, current_hash))print("old_hash matches helper (fallback):", auth._session_hash_matches(user, old_hash))print("invalid_hash matches helper:", auth._session_hash_matches(user, invalid_hash))
```