Прогнозирование намерений. Исследование свойств локальных моделей при пространственном декодировании сигналов головного мозга

 Φ илатов A.B., Mаркин~B.O. filatov.av@phystech.edu; markin.vo@phystech.edu ${
m M}\Phi{
m T}{
m H}$

В данной работе рассматривается проблема создания нейрокомпьютерного интерфейса. Особенностью этой проблемы является требование стабильности у моделей. Поэтому при построении таких систем используются простые модели. Важным аспектом создания таких моделей является построение надежного признакового пространства. В данной статье рассматривается построение признакового пространства на данных электрокортикограммы для метода частичной регрессии наименьших квадратов

Основной вклад данной работы заключается в учете пространственной зависимости в модели. В нашем подходе используется пространственная аппроксимация искомого сигнала с помощью нормального распределения и полиномов. Информация об аппроксимации учитывается при создании признакового пространства. В статье приведены результаты численных экспериментов на данных электрокортикограмм головного мозга обезъян.

Ключевые слова: отбор признаков; нейрокомпьютерный интерфейс; электрокортикограмма; локальные модели

1 Введение

Нейрокомпьютерный интерфейс (BCI) [1] позволяет считывать сигналы нейронов головного мозга, анализировать их и переводить в команды исполняющей системы. Исследования в данной области позволяют людям с нарушениями двигательных функций организма заменить или восстановить их. Примером такой системы является система управления роботизированным протезом посредством мозговых импульсов.

Мозговая активность представляет собой совокупность электрических импульсов различной амплитуды и частоты, возникающих в коре головного мозга. Исследование мозговой активности может производиться при помощи электрокортикографии [2] или [3] электроэнцефалографии. На выходе этих процедур мы получаем временной ряд напряжений сигнала, который используется как сырые данные для задачи. В нашей задаче используется данные из [4].

Стандартные подходы к решению задачи состоят в извлечении информативных признаков из пространственных, частотных и временных характеристик сигнала [5,6]. Большинство методов в смежных работах исследуют частотные характеристики [7–9]. Наиболее распространёнными моделями являются алгоритмы PLS [8, 10, 11], PCA [10, 11]. В работе [12] используются алгоритмы, построенные на скрытых марковских моделях. В работах [9, 13] авторы рассматривают различные участки сигнала в виде слов. В работе [14] задача отбора признаков сводится к задаче квадратичного программирования (QuadraticProgramming Feature Selection [15]). Также для решения задачи используются нейросетевые модели [16].

Литература

- [1] Jerry J Shih, Dean J Krusienski, and Jonathan R Wolpaw. Brain-computer interfaces in medicine. In *Mayo Clinic Proceedings*, volume 87, pages 268–279. Elsevier, 2012.
- [2] N Jeremy Hill, Disha Gupta, Peter Brunner, Aysegul Gunduz, Matthew A Adamo, Anthony Ritaccio, and Gerwin Schalk. Recording human electrocorticographic (ecog) signals for neuroscientific research and real-time functional cortical mapping. *JoVE (Journal of Visualized Experiments)*, (64):e3993, 2012.
- [3] Michael J Aminoff. Electroencephalography: general principles and clinical applications. Electrodiagnosis in Clinical Neurology, 6th ed.; Aminoff, MJ, Ed, pages 37–84, 2012.
- [4] Zenas C Chao, Yasuo Nagasaka, and Naotaka Fujii. Long-term asynchronous decoding of arm motion using electrocorticographic signals in monkey. Frontiers in neuroengineering, 3:3, 2010.
- [5] Soichiro Morishita, Keita Sato, Hidenori Watanabe, Yukio Nishimura, Tadashi Isa, Ryu Kato, Tatsuhiro Nakamura, and Hiroshi Yokoi. Brain-machine interface to control a prosthetic arm with monkey ecogs during periodic movements. *Frontiers in neuroscience*, 8:417, 2014.
- [6] David M Alexander, Peter Jurica, Chris Trengove, Andrey R Nikolaev, Sergei Gepshtein, Mikhail Zvyagintsev, Klaus Mathiak, Andreas Schulze-Bonhage, Johanna Ruescher, Tonio Ball, et al. Traveling waves and trial averaging: the nature of single-trial and averaged brain responses in large-scale cortical signals. Neuroimage, 73:95–112, 2013.
- [7] César Márquez Chin, Milos R Popovic, Adam Thrasher, Tracy Cameron, Andres Lozano, and Robert Chen. Identification of arm movements using correlation of electrocorticographic spectral components and kinematic recordings. *Journal of neural engineering*, 4(2):146, 2007.
- [8] Andrey Eliseyev and Tatiana Aksenova. Stable and artifact-resistant decoding of 3d hand trajectories from ecog signals using the generalized additive model. *Journal of neural engineering*, 11(6):066005, 2014.
- [9] Carlos A Loza and Jose C Principe. Unsupervised robust detection of behavioral correlates in ecog. In 2017 8th International IEEE/EMBS Conference on Neural Engineering (NER), pages 509–512. IEEE, 2017.
- [10] Andrey Eliseyev and Tetiana Aksenova. Penalized multi-way partial least squares for smooth trajectory decoding from electrocorticographic (ecog) recording. *PloS one*, 11(5), 2016.
- [11] Roman Rosipal and Nicole Kramer. Overview and recent advances in partial least squares. In International Statistical and Optimization Perspectives Workshop Subspace, Latent Structure and Feature Selection, pages 34–51. Springer, 2005.
- [12] Rui Zhao, Gerwin Schalk, and Qiang Ji. Coupled hidden markov model for electrocorticographic signal classification. In 2014 22nd International Conference on Pattern Recognition, pages 1858– 1862. IEEE, 2014.
- [13] Hai-bin Zhao, Chun-yang Yu, Chong Liu, and Hong Wang. Ecog-based brain-computer interface using relative wavelet energy and probabilistic neural network. In 2010 3rd International Conference on Biomedical Engineering and Informatics, volume 2, pages 873–877. IEEE, 2010.
- [14] Anastasia Motrenko and Vadim Strijov. Multi-way feature selection for ecog-based brain-computer interface. Expert Systems with Applications, 114:402–413, 2018.
- [15] Irene Rodriguez-Lujan, Ramon Huerta, Charles Elkan, and Carlos Santa Cruz. Quadratic programming feature selection. *Journal of Machine Learning Research*, 11(Apr):1491–1516, 2010.
- [16] Ziqian Xie. Deep learning approach for brain machine interface. 2018.