



Toolforge webservices are in the final stages of [migrating to the toolforge.org domain](#).
Please help us clean up older documentation referring to tools.wmflabs.org!

Incident documentation/20150914-extension1

[< Incident documentation](#)

Contents [\[hide\]](#)

- [1 Summary](#)
- [2 Timeline](#)
- [3 Conclusions](#)
- [4 Actionables](#)

Summary

On 2015-09-14 from about 09:47 UTC until 09:59 UTC, the x1 master was saturated with slow queries caused by a missing index. This caused all Flow boards to be inaccessible: trying to view a Flow board displayed a database error message.

Timeline

- 09:43 Jaime runs [the last ALTER statements](#) for a complex schema change for Flow
- 09:47 Matthias notices that every Flow page view dies with `(Cannot access the database: Too many connections (10.64.16.18))`
- 09:51 Jaime figures out this is because all queries are now unindexed: the ALTERs dropped the indexes that were being used
- 09:56 Roan retrieves the old index definitions from git history
- 09:59 Jaime recreates the old indexes; Flow comes back up immediately

Conclusions

The [commit message](#) of the change contained detailed instructions about how to carry out the migration. It instructed that `patch3.sql` (setting the field to NOT NULL and dropping the old indexes) be run before turning off `$wgFlowMigrateReferenceWiki`. However, this was incorrect: as long as `$wgFlowMigrateReferenceWiki` was turned on, the old indexes would be used, so the correct order was to create the new indexes, turn off the setting, then remove the old indexes. This mistake was missed in code review and missed again by the Flow devs who were present when the schema change was executed. The other statements in `phase3.sql` (setting the fields to NOT NULL, and DROP INDEX statements for temporary indexes that were added later) were appropriate to run at that stage, further hiding the incorrectly placed DROP INDEX statements.

Actionables

- Do we have (or should we develop) something that tells us which indexes are used and which aren't? That would have allowed us to verify each index was unused before dropping it.

Create a debug mode for MW that blows in your face when an unindexed query is run and enable it by default in Vagrant and betalabs? [maxsem](#) ([talk](#)) 20:06, 18 September 2015 (UTC)
- ...?
- Better monitoring for connections reaching `max_connections` and query performance: [bug T112473](#) [bug T99485](#)

Category: [Incident documentation](#)

This page was last edited on 1 July 2016, at 18:01.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. See [Terms of Use](#) for details.

[Main page](#)
[Recent changes](#)
[Server admin log \(Prod\)](#)
[Server admin log \(RelEng\)](#)
[Deployments](#)
[SRE/Operations Help](#)
[Incident status](#)

[Cloud VPS & Toolforge](#)

[Cloud VPS documentation](#)

[Toolforge documentation](#)

[Request Cloud VPS project](#)

[Server admin log \(Cloud VPS\)](#)

[Tools](#)

[What links here](#)

[Related changes](#)

[Special pages](#)

[Permanent link](#)

[Page information](#)

[Cite this page](#)

[Print/export](#)

[Create a book](#)

[Download as PDF](#)

[Printable version](#)

