
REMOTEPSW

By: Christopher Lane (Lane@Sumex-Aim.Stanford.Edu)

Uses: COURIERSERVE, COURIERDEFS

REMOTEPSW defines a *remote* process status window facility that runs on top of Courier. The remote process status window is identical to the local one except that it contains **UPDATE** (to get the current process status) instead of **BREAK**, and **INFO** is not implemented. Both the client and server code are contained in the module which must be loaded on both hosts. The Courier server must be running on the host you wish to monitor.

The only user function is:

(REMOTE.PROCESS.STATUS.WINDOW *HOST*)

[Function]

which opens a remote process status window onto *HOST*, where *HOST* is any NS host specification that COURIER.OPEN accepts.

```

221 # 0.52612.100127 # 0
COURIER221#0.52612.100127#137624
COURIER.LISTENER+124745
SPP#221#0.52612.100127#5
COURIER.LISTENER
LAFITEMAILWATCH
ERIS#LEAF
\3MBWATCHER
MOUSE
TEdit#2
TEdit
EXEC
\NSGATELISTENER
\PUPGATELISTENER
\TIMER.PROCESS
BACKGROUND

```

BT	WHO?	KILL
BTV	KBD←	RESTART
BTV*	INFO	WAKE
BTV!	UPDATE	SUSPEND