

File created: 12-Jun-90 16:10:42 {DSK}<usr>local>lde>lispcore>library>TCPCHAT.;3

changes to: (FILES TCP)  
(VARS TCPCHATCOMS)

previous date: 15-Feb-90 13:09:03 {DSK}<usr>local>lde>lispcore>library>TCPCHAT.;2

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

;;  
;; Copyright (c) 1985, 1986, 1987, 1988, 1990 by Venue & Xerox Corporation. All rights reserved.

(RPAQQ TCPCHATCOMS

```
[ (FNS TCPCHAT.BIN TCPCHAT.HOST.FILTER TCPCHAT.NEGOTIATE TCPCHAT.OPEN TCPCHAT.OPTION.COMMAND
  TCPCHAT.OPTION.INPUT TCPCHAT.OPTION.OUTPUT TCPCHAT.OPTION.TRACE TCPCHAT.TERMINAL.TYPE)
  (VARS TCPCHAT.TELNET.TTY.TYPES TELNET.OPTIONS)
  (INITVARS (TCPCHAT.TRACEFLG)
    (TCPCHAT.TRACEFILE))
  (FILES (SYSLOAD)
    TCP CHAT)
  (DECLARE%: EVAL@COMPILE DONTCOPY (FILES CHATDECLS)
    (COMS (CONSTANTS * TELNET.COMMANDS)
      (CONSTANTS * TELNET.MARKS))
    (RECORDS TELNET.OPTION TELNET.OPTIONSTATE)
    (GLOBALVARS TCPCHAT.TELNET.TTY.TYPES TELNET.OPTIONS TELNET.MARKS))
  (DECLARE%: DONTVAL@LOAD DOCOPY
    ;; Tell Chat we exist
    (ADDVARS (CHAT.PROTOCOLTYPES (TCP . TCPCHAT.HOST.FILTER))
      (CHAT.PROTOCOL.ABBREVS (N . TCP)
        (T . TCP]))
```

(DEFINEQ

(TCPCHAT.BIN

```
[LAMBDA (STREAM) ; Edited 7-Jul-88 18:03 by atm
  (bind CHAR while (AND (EQ (SETQ CHAR (\BUFFERED.BIN STREAM))
    TELNET.IAC)
    (NEQ (SETQ CHAR (\BUFFERED.BIN STREAM))
    TELNET.IAC))
  do (TCPCHAT.NEGOTIATE CHAR STREAM) finally (RETURN CHAR]))
```

(TCPCHAT.HOST.FILTER

```
[LAMBDA (HOST) ; Edited 12-Apr-88 17:14 by bvm
  (COND
    ((AND \IPFLG (DODIP.HOSTP HOST))
    (LIST HOST (FUNCTION TCPCHAT.OPEN]))
```

(TCPCHAT.NEGOTIATE

```
[LAMBDA (COMMAND STREAM) ; Edited 7-Jul-88 18:03 by atm
  (TCPCHAT.OPTION.INPUT (TCP.OTHER.STREAM STREAM)
    COMMAND
    (\BUFFERED.BIN STREAM]))
```

(TCPCHAT.OPEN

```
[LAMBDA (HOST) ; Edited 17-Apr-87 10:06 by jrb:
  (PROG ((STREAM (TCP.OPEN (DODIP.HOSTP HOST)
    \TCP.TELNET.PORT NIL 'ACTIVE 'INPUT))
    [OSTYPE (OR (AND (GETHASH (U-CASE HOST)
    \IP.HOSTNAMES)
    (fetch (HOSTS.TXT.ENTRY HTE.OS.TYPE) of (GETHASH (U-CASE HOST)
    \IP.HOSTNAMES)))
    (GETHOSTINFO HOST 'OSTYPE)]
    OUTPUTSTREAM)
    (COND
      (STREAM (replace (STREAM BINABLE) of STREAM with NIL) ; Can't run microcoded
        (replace (STREAM STRMBINFN) of STREAM with (FUNCTION TCPCHAT.BIN))
        (STREAMPROP STREAM 'SETDISPLAYTYPE (FUNCTION NIL))
        [COND
          ((EQ OSTYPE 'INTERLISP)
            (RETURN (CONS STREAM (TCP.OTHER.STREAM STREAM)
              ; (STREAMPROP STREAM (QUOTE SETDISPLAYTYPE)
              ; (FUNCTION TCPCHAT.TERMINAL.TYPE))
            (SETQ OUTPUTSTREAM (TCP.OTHER.STREAM STREAM))
            [STREAMPROP OUTPUTSTREAM 'OPTIONSTATES (for OPTION in TELNET.OPTIONS
              collect (create TELNET.OPTIONSTATE
                OPTION _ (fetch (TELNET.OPTION OPTION)
                  of OPTION])
            (TCPCHAT.OPTION.COMMAND OUTPUTSTREAM TELNET.DO TELNET.ECHO)
```

```
[LAMBDA (OUTPUTSTREAM COMMAND OPTION) ; Edited 17-Apr-87 16:34 by jrb:
  (LET (CMDNUM)
    (COND
      ((NULL COMMAND))
      ([SETQ CMDNUM (CDR (FASSOC COMMAND '( (WILL \, TELNET.WILL)
                                              (WONT \, TELNET.WONT)
                                              (DO \, TELNET.DO)
                                              (DONT \, TELNET.DONT]
                                              (TCPCHAT.OPTION.COMMAND OUTPUTSTREAM CMDNUM OPTION 'SENDERBACK))
      (T (APPLY* COMMAND (TCP.OTHER.STREAM OUTPUTSTREAM]))
```

**(TCPCHAT.OPTION.TRACE**

```

[LAMBDA (COMMAND OPTION PREFIX)
  (DECLARE (GLOBALVARS TCPCHAT.TRACEFLG TCPCHAT.TRACEFILE))
  (COND
    (TCPCHAT.TRACEFLG [COND
      ((SMALLP COMMAND)
        (SETQ COMMAND (SELECTC COMMAND
          (TELNET.DO 'DO)
          (TELNET.DONT 'DONT)
          (TELNET.WILL 'WILL)
          (TELNET.WONT 'WONT)
          COMMAND])
        (printout TCPCHAT.TRACEFILE PREFIX ": " COMMAND " ")
        (PRINTCONSTANT OPTION TELNET.MARKS TCPCHAT.TRACEFILE)
        (TERPRI TCPCHAT.TRACEFILE]))
    (* ejs%: "22-Apr-85 16:41")
  )

```

**(TCPCHAT.TERMINAL.TYPE**

```

[LAMBDA (INPUTSTREAM)
  (LET ((COMMAND))
    (SELECTC (\BUFFERED.BIN INPUTSTREAM)
      (TELNET.SEND
        (IF TCPCHAT.TRACEFLG
          THEN (printout TCPCHAT.TRACEFILE "REQUEST IS SEND"))
        (IF (EQ (SETQ COMMAND (\BUFFERED.BIN INPUTSTREAM))
          TELNET.IAC)
          THEN (IF TCPCHAT.TRACEFLG
            THEN (printout TCPCHAT.TRACEFILE " IAC"))
          ELSE (IF TCPCHAT.TRACEFLG
            THEN (printout " EXPECTED IAC, GOT " COMMAND)))
        (IF (EQ (SETQ COMMAND (\BUFFERED.BIN INPUTSTREAM))
          TELNET.SE)
          THEN (IF TCPCHAT.TRACEFLG
            THEN (printout TCPCHAT.TRACEFILE " SE"))
          ELSE (IF TCPCHAT.TRACEFLG
            THEN (printout " EXPECTED SE, GOT " COMMAND)))
        (IF TCPCHAT.TRACEFLG
          THEN (TERPRI TCPCHAT.TRACEFILE))
        [LET* [(OUTPUTSTREAM (TCP.OTHER.STREAM INPUTSTREAM))
          (DISPLAYTYPE (OR (CDR (FASSOC (fetch (CHATDISPLAYTYPE DPYNAME)
            of (STREAMPROP INPUTSTREAM 'DISPLAYTYPE))
            TCPCHAT.TELNET.TTY.TYPES))
          (CDR (FASSOC (fetch (CHATDISPLAYTYPE DPYNAME)
            of (STREAMPROP OUTPUTSTREAM 'DISPLAYTYPE))
            TCPCHAT.TELNET.TTY.TYPES))
          (BOUT OUTPUTSTREAM TELNET.IAC)
          (BOUT OUTPUTSTREAM TELNET.SB)
          (BOUT OUTPUTSTREAM TELNET.TERMINAL.TYPE)
          (BOUT OUTPUTSTREAM TELNET.IS)
          (PRIN1 DISPLAYTYPE OUTPUTSTREAM)
          (BOUT OUTPUTSTREAM TELNET.IAC)
          (BOUT OUTPUTSTREAM TELNET.SE)
          (FORCEOUTPUT OUTPUTSTREAM)
          (COND
            (TCPCHAT.TRACEFLG (printout TCPCHAT.TRACEFILE "SEND(BACK) IAC SB
              TERMINAL-TYPE IS " DISPLAYTYPE " IAC SE" T))
            (TELNET.IS
              ; We told them we couldn't handle this - or would have had they
              ; asked...
            )
          (IF TCPCHAT.TRACEFLG
            THEN (printout TCPCHAT.TRACEFILE "REQUEST IS IS, which is an error: rest of command
              is:" T))
          (WHILE (NEQ (SETQ COMMAND (\BUFFERED.BIN INPUTSTREAM))
            TELNET.SE)
            DO (IF TCPCHAT.TRACEFLG
              THEN (PRIN1 (CHARACTER COMMAND)
                TCPCHAT.TRACEFILE)))
          (IF TCPCHAT.TRACEFLG
            THEN (printout TCPCHAT.TRACEFILE " SE" T))
          (IF TCPCHAT.TRACEFLG
            THEN (printout TCPCHAT.TRACEFILE "REQUEST IS " COMMAND ", which is an error" T))
        )
      )
    )
  )
(RPAQQ TCPCHAT.TELNET.TTY.TYPES ((DM2500 . DATAMEDIA-2500)
  (VT100 . DEC-VT100)))
(RPAQQ TELNET.OPTIONS
  ((94 WONT WONT DONT DONT)
  (0 WILL WONT NIL DONT)
  (1 WONT WONT DO DO)
  (3 WILL WILL NIL NIL)
  (5 WONT WONT DONT DONT)
  (6 WILL NIL NIL NIL)
  (24 WILL NIL DONT NIL TCPCHAT.TERMINAL.TYPE)))

```

```

{MEDLEY}<obsolete>tcp>TCPCHAT.;1

(RPAQQ TCPCHAT.TRACEFLG )

(RPAQQ TCPCHAT.TRACEFILE )

(FILESLoad (SYSLOAD)
  TCP CHAT)

(DECLARE%: EVAL@COMPILE DONTCOPY

(FILESLoad CHATDECLS)

(RPAQQ TELNET.COMMANDS ( (TELNET.SE 240)
  (TELNET.SB 250)
  (TELNET.WILL 251)
  (TELNET.WONT 252)
  (TELNET.DO 253)
  (TELNET.DONT 254)
  (TELNET.IAC 255)
  (TELNET.SEND 1)
  (TELNET.IS 0)))

(DECLARE%: EVAL@COMPILE

(RPAQQ TELNET.SE 240)

(RPAQQ TELNET.SB 250)

(RPAQQ TELNET.WILL 251)

(RPAQQ TELNET.WONT 252)

(RPAQQ TELNET.DO 253)

(RPAQQ TELNET.DONT 254)

(RPAQQ TELNET.IAC 255)

(RPAQQ TELNET.SEND 1)

(RPAQQ TELNET.IS 0)

(CONSTANTS (TELNET.SE 240)
  (TELNET.SB 250)
  (TELNET.WILL 251)
  (TELNET.WONT 252)
  (TELNET.DO 253)
  (TELNET.DONT 254)
  (TELNET.IAC 255)
  (TELNET.SEND 1)
  (TELNET.IS 0)
)

(RPAQQ TELNET.MARKS ( (TELNET.BINARY 0)
  (TELNET.ECHO 1)
  (TELNET.SUPPRESS.GOAHEAD 3)
  (TELNET.STATUS 5)
  (TELNET.TIMING.MARK 6)
  (TELNET.TERMINAL.TYPE 24)))

(DECLARE%: EVAL@COMPILE

(RPAQQ TELNET.BINARY 0)

(RPAQQ TELNET.ECHO 1)

(RPAQQ TELNET.SUPPRESS.GOAHEAD 3)

(RPAQQ TELNET.STATUS 5)

(RPAQQ TELNET.TIMING.MARK 6)

(RPAQQ TELNET.TERMINAL.TYPE 24)

(CONSTANTS (TELNET.BINARY 0)
  (TELNET.ECHO 1)
  (TELNET.SUPPRESS.GOAHEAD 3)
  (TELNET.STATUS 5)
  (TELNET.TIMING.MARK 6)
  (TELNET.TERMINAL.TYPE 24)
)

(DECLARE%: EVAL@COMPILE

(RECORD TELNET.OPTION (OPTION ON.DO ON.DONT ON.WILL ON.WONT ON.SB))

(RECORD TELNET.OPTIONSTATE (OPTION WILLING DOING))
)

```

```
{MEDLEY}<obsolete>tcp>TCPCHAT.;1
```

Page 5

```
(DECLARE%: DOEVAL@COMPILE DONTCOPY  
(GLOBALVARS TCPCHAT.TELNET.TTY.TYPES TELNET.OPTIONS TELNET.MARKS)  
)  
(DECLARE%: DONTEVAL@LOAD DOCOPY  
(ADDTOVAR CHAT.PROTOCOLTYPES (TCP . TCPCHAT.HOST.FILTER))  
(ADDTOVAR CHAT.PROTOCOL.ABBREVS (N . TCP)  
                                     (T . TCP))  
)  
(PUTPROPS TCPCHAT COPYRIGHT ("Venue & Xerox Corporation" 1985 1986 1987 1988 1990))
```

---

FUNCTION INDEX

TCPCHAT.BIN .....	1	TCPCHAT.OPEN .....	1	TCPCHAT.OPTION.OUTPUT .....	2
TCPCHAT.HOST.FILTER .....	1	TCPCHAT.OPTION.COMMAND .....	2	TCPCHAT.OPTION.TRACE .....	3
TCPCHAT.NEGOTIATE .....	1	TCPCHAT.OPTION.INPUT .....	2	TCPCHAT.TERMINAL.TYPE .....	3

---

CONSTANT INDEX

TELNET.BINARY .....	4	TELNET.IAC .....	4	TELNET.SEND .....	4	TELNET.TIMING.MARK .....	4
TELNET.DO .....	4	TELNET.IS .....	4	TELNET.STATUS .....	4	TELNET.WILL .....	4
TELNET.DONT .....	4	TELNET.SB .....	4	TELNET.SUPPRESS.GOAHEAD ..	4	TELNET.WONT .....	4
TELNET.ECHO .....	4	TELNET.SE .....	4	TELNET.TERMINAL.TYPE .....	4		

---

VARIABLE INDEX

CHAT.PROTOCOL.ABBREVS ...	5	TCPCHAT.TELNET.TTY.TYPES ..	3	TCPCHAT.TRACEFLG .....	4	TELNET.MARKS .....	4
CHAT.PROTOCOLTYPES .....	5	TCPCHAT.TRACEFILE .....	4	TELNET.COMMANDS .....	4	TELNET.OPTIONS .....	3

---

RECORD INDEX

TELNET.OPTION .....	4	TELNET.OPTIONSTATE .....	4
---------------------	---	--------------------------	---

---