

File created: 16-May-90 11:55:52 {DSK}<usr>local>lde>lispcore>sources>ADVISE.;2

changes to: (IL:VARS IL:ADVISECOMS)

previous date: 15-Aug-88 12:29:50 {DSK}<usr>local>lde>lispcore>sources>ADVISE.;1

Read Table: XCL

Package: SYSTEM

Format: XCCS

; Copyright (c) 1978, 1984, 1986, 1987, 1988, 1990 by Venue & Xerox Corporation. All rights reserved.  
; The following program was created in 1978 but has not been published  
; within the meaning of the copyright law, is furnished under license,  
; and may not be used, copied and/or disclosed except in accordance  
; with the terms of said license.

```
(IL:RPAQQ IL:ADVISECOMS
  ((IL:STRUCTURES ADVICE)
   (IL:VARIABLES IL:ADVISEDFNS *UNADVISED-FNS*)
   ;;
   ;; Interlisp entry points.
   (IL:FNS IL:ADVISE IL:UNADVISE IL:READADVISE)
   (IL:PROP IL:ARGNAMES IL:ADVISE)
   ;;
   ;; XCL entry points.
   (IL:FUNCTIONS XCL:ADVISE-FUNCTION XCL:UNADVISE-FUNCTION XCL:READADVISE-FUNCTION)
   (IL:FUNCTIONS UNADVISE-FROM-RESTORE-CALLS FINISH-ADVISING FINISH-UNADVISING)
   ;;
   ;; The advice database.
   (IL:VARIABLES *ADVICE-HASH-TABLE*)
   (IL:FUNCTIONS ADD-ADVICE DELETE-ADVICE GET-ADVICE-MIDDLE-MAN SET-ADVICE-MIDDLE-MAN INSERT-ADVICE-FORM
    )
   (IL:SETFS GET-ADVICE-MIDDLE-MAN)
   ;;
   ;; Hacking the actual advice forms.
   (IL:FUNCTIONS CREATE-ADVISED-DEFINITION MAKE-AROUND-BODY)
   ;;
   ;; Dealing with the File Manager
   (IL:FILEPKGCOMS IL:ADVISE IL:ADVISE)
   (IL:FUNCTIONS XCL:REINSTALL-ADVICE)
   (IL:FUNCTIONS ADVICE-GETDEF ADVICE-PUTDEF ADVICE-DELDEF ADVICE-HASDEF ADVICE-NEWCOM
    ADVICE-FILE-DEFINITIONS ADVICE-CONTENTS ADVICE-ADDTOCOM)
   (IL:PROP IL:PROPTYPE IL:ADVISED)
   ;;
   ;; Dealing with old-style advice
   (IL:FUNCTIONS IL:READADVISE1 ADD-OLD-STYLE-ADVICE CANONICALIZE-ADVICE-SYMBOL
    CANONICALIZE-ADVICE-WHEN-SPEC CANONICALIZE-ADVICE-WHERE-SPEC)
   (IL:DEFINE-TYPES XCL:ADVISED-FUNCTIONS)
   (IL:FUNCTIONS XCL:DEFADVISE)
   ;; Arrange for the proper package. Because of the DEFSTRUCT above, we must have the file dumped in the SYSTEM package.
   (IL:PROP (IL:MAKEFILE-ENVIRONMENT IL:FILETYPE)
    IL:ADVISE)
   (IL:DECLARE\ IL:DONTEVAL@LOAD IL:DOEVAL@COMPILE IL:DONTCOPY IL:COMPILEVARS (IL:ADDVARS (IL:NLAMA
    IL:READADVISE
    IL:UNADVISE
    )
    (IL:NLAML)
    (IL:LAMA
    IL:ADVISE)
    )))

(DEFSTRUCT (ADVICE (:TYPE LIST))
  BEFORE
  AFTER
  AROUND)

(DEFVAR IL:ADVISEDFNS NIL)

(DEFVAR *UNADVISED-FNS* NIL)

;;
;; Interlisp entry points.
```

(IL:DEFINEQ

**(IL:ADVISE**

(IL:LAMBDA IL:ARGS

; Edited 6-Apr-87 18:00 by Pavel

;;; ADVISE the FN given. ADVISE1 is for advice of the type (foo IN bar)

(LET (IL:FN IL:WHEN IL:WHERE IL:WHAT)

;; First we straighten out the arguments given to us

(IL:SETQ IL:FN (IL:ARG IL:ARGS 1))

(CASE IL:ARGS

(2 (IL:SETQ IL:WHAT (IL:ARG IL:ARGS 2)))

(3 (IL:SETQ IL:WHEN (IL:ARG IL:ARGS 2))

(IL:SETQ IL:WHAT (IL:ARG IL:ARGS 3)))

(4 (IL:SETQ IL:WHEN (IL:ARG IL:ARGS 2))

(IL:SETQ IL:WHERE (IL:ARG IL:ARGS 3))

(IL:SETQ IL:WHAT (IL:ARG IL:ARGS 4)))

(T (IL:IF (&lt; IL:ARGS 2)

IL:THEN (ERROR 'IL:TOO-FEW-ARGUMENTS :CALLEE 'IL:ADVISE :ACTUAL IL:ARGS :MINIMUM 2)

IL:ELSE (ERROR 'IL:TOO-MANY-ARGUMENTS :CALLEE 'IL:ADVISE :ACTUAL IL:ARGS :MAXIMUM 4))))

(IL:SETQ IL:WHEN (CANONICALIZE-ADVICE-WHEN-SPEC IL:WHEN))

(IL:SETQ IL:WHERE (CANONICALIZE-ADVICE-WHERE-SPEC IL:WHERE))

(IL:IF (IL:NLISTP IL:FN)

IL:THEN (XCL:ADVISE-FUNCTION IL:FN IL:WHAT :WHEN IL:WHEN :PRIORITY IL:WHERE)

IL:ELSEIF (IL:STRING-EQUAL (CADR IL:FN)

"IN")

IL:THEN (XCL:ADVISE-FUNCTION (FIRST IL:FN)

IL:WHAT :IN (THIRD IL:FN)

:WHEN IL:WHEN :PRIORITY IL:WHERE)

IL:ELSE (IL:FOR IL:X IL:IN IL:FN IL:JOIN (IL:IF (IL:NLISTP IL:X)

IL:THEN (XCL:ADVISE-FUNCTION IL:X IL:WHAT :WHEN IL:WHEN

:PRIORITY IL:WHERE)

IL:ELSE (XCL:ADVISE-FUNCTION (FIRST IL:X)

IL:WHAT :IN (THIRD IL:X)

:WHEN IL:WHEN :PRIORITY IL:WHERE))))))

**(IL:UNADVISE**

(IL:NLAMBDA IL:FNS

; Edited 6-Apr-87 16:21 by Pavel

(IL:SETQ IL:FNS (IL:NLAMBDA.ARGs IL:FNS))

(FLET ((IL:UNADVISE-ENTRY (IL:ENTRY)

(IL:IF (IL:LISTP IL:ENTRY)

IL:THEN (XCL:UNADVISE-FUNCTION (FIRST IL:ENTRY)

:IN

(THIRD IL:ENTRY))

IL:ELSE (XCL:UNADVISE-FUNCTION IL:ENTRY))))

(COND

((NULL IL:FNS)

(IL:FOR IL:ENTRY IL:IN (IL:REVERSE IL:ADVISED-FNS) IL:JOIN (IL:UNADVISE-ENTRY IL:ENTRY)))

((IL:EQUAL IL:FNS '(T))

(AND (NOT (NULL IL:ADVISED-FNS))

(IL:UNADVISE-ENTRY (CAR IL:ADVISED-FNS))))

(T (IL:FOR IL:ENTRY IL:IN IL:FNS IL:JOIN (IL:UNADVISE-ENTRY IL:ENTRY))))))

**(IL:READVISE**

(IL:NLAMBDA IL:FNS

; Edited 6-Apr-87 16:52 by Pavel

(IL:SETQ IL:FNS (IL:NLAMBDA.ARGs IL:FNS))

(FLET ((IL:READVISE-ENTRY (IL:ENTRY)

(IL:IF (IL:LISTP IL:ENTRY)

IL:THEN (XCL:READVISE-FUNCTION (FIRST IL:ENTRY)

:IN

(THIRD IL:ENTRY))

IL:ELSE (XCL:READVISE-FUNCTION IL:ENTRY))))

(COND

((NULL IL:FNS)

(IL:FOR IL:ENTRY IL:IN (IL:REVERSE \*UNADVISED-FNS\*) IL:JOIN (IL:READVISE-ENTRY IL:ENTRY)))

((IL:EQUAL IL:FNS '(T))

(AND (NOT (NULL \*UNADVISED-FNS\*))

(IL:READVISE-ENTRY (CAR \*UNADVISED-FNS))))

(T

; advise them all, in reverse order.

; IL:JOIN (IL:READVISE-ENTRY IL:ENTRY)))

; simple case, readvise just the last one that was unadvised.

; they gave us some functions, so readvise THEM. We can't use

; READVISE-ENTRY here, because we may have to deal with

; old-style advice.

(IL:FOR IL:ENTRY IL:IN IL:FNS IL:JOIN (IL:READVISE1 IL:ENTRY))))))

)

(IL:PUTPROPS IL:ADVISE IL:ARGNAMES (IL:WHO IL:WHEN IL:WHERE IL:WHAT))

;;

;; XCL entry points.

(DEFUN XCL:ADVISE-FUNCTION (XCL::FN-TO-ADVISE XCL::FORM &amp;KEY (:IN XCL::IN-FN))

```

(WHEN :BEFORE)
(XCL::PRIORITY :LAST))

(COND
  ((CONSP XCL::FN-TO-ADVISE)
    (IL:FOR XCL::FN IL:IN XCL::FN-TO-ADVISE IL:JOIN (XCL:ADVISE-FUNCTION XCL::FN XCL::FORM :IN XCL::IN-FN :WHEN
      WHEN :PRIORITY XCL::PRIORITY)))
  ((CONSP XCL::IN-FN)
    (IL:FOR XCL::FN IL:IN XCL::IN-FN IL:JOIN (XCL:ADVISE-FUNCTION XCL::FN-TO-ADVISE XCL::FORM :IN XCL::FN :WHEN
      WHEN :PRIORITY XCL::PRIORITY)))
  ((NULL XCL::FORM)
    (FORMAT *ERROR-OUTPUT* "No advice given, so nothing done.")
    NIL)
  ((IL:UNSAFE.TO.MODIFY XCL::FN-TO-ADVISE "advise")
    (FORMAT *ERROR-OUTPUT* "~S not advised.~%" XCL::FN-TO-ADVISE)
    NIL)
  (T (COND
    (XCL::IN-FN (IF (NOT (HAS-CALLS XCL::IN-FN XCL::FN-TO-ADVISE))
      (ERROR "~S is not called from ~S." XCL::FN-TO-ADVISE XCL::IN-FN)))
    (T (IF (NULL (IL:GETD XCL::FN-TO-ADVISE))
      (ERROR 'XCL:UNDEFINED-FUNCTION :NAME XCL::FN-TO-ADVISE))))
    (XCL:UNBREAK-FUNCTION XCL::FN-TO-ADVISE :IN XCL::IN-FN :NO-ERROR T)
    (COND
      ((NULL XCL::IN-FN)
        ;; Adjust the database of advice for this function.
        (WHEN (NOT (MEMBER XCL::FN-TO-ADVISE IL:ADVISEDFNS :TEST 'EQ))
          ; If FN-TO-ADVISE is not currently advised, the new advice
          ; replaces any that may have been given before.
          (DELETE-ADVICE XCL::FN-TO-ADVISE))
        (ADD-ADVICE XCL::FN-TO-ADVISE WHEN XCL::PRIORITY XCL::FORM)
        ;; Finish off the process. This part is shared with READWISE-FUNCTION.
        (FINISH-ADVISING XCL::FN-TO-ADVISE NIL))
      (T (LET* ((XCL::ADVICE-NAME `(,XCL::FN-TO-ADVISE :IN ,XCL::IN-FN))
        (XCL::ALREADY-ADVISED? (MEMBER XCL::ADVICE-NAME IL:ADVISEDFNS :TEST 'EQUAL)))
        ;; Adjust the database of advice for this request.
        (WHEN (NOT XCL::ALREADY-ADVISED?)
          ; If not currently advised, the new advice replaces any that may
          ; have been given before.
          (DELETE-ADVICE XCL::ADVICE-NAME))
        (ADD-ADVICE XCL::ADVICE-NAME WHEN XCL::PRIORITY XCL::FORM)
        ;; Finish off the process. This part is shared with READWISE-FUNCTION.
        (FINISH-ADVISING XCL::FN-TO-ADVISE XCL::IN-FN))))))

(DEFUN XCL:UNADVISE-FUNCTION (XCL::FN-TO-UNADVISE &KEY ((:IN XCL::IN-FN))
  XCL::NO-ERROR)
  (COND
    ((CONSP XCL::FN-TO-UNADVISE)
      (IL:FOR XCL::FN IL:IN XCL::FN-TO-UNADVISE IL:JOIN (XCL:UNADVISE-FUNCTION XCL::FN :IN XCL::IN-FN)))
    ((CONSP XCL::IN-FN)
      (IL:FOR XCL::FN IL:IN XCL::IN-FN IL:JOIN (XCL:UNADVISE-FUNCTION XCL::FN-TO-UNADVISE :IN XCL::FN)))
    (T (XCL:UNBREAK-FUNCTION XCL::FN-TO-UNADVISE :IN XCL::IN-FN :NO-ERROR T)
      (IF (NULL XCL::IN-FN)
        (LET ((XCL::ORIGINAL (GET XCL::FN-TO-UNADVISE 'IL:ADVISED)))
          (COND
            ((NULL XCL::ORIGINAL)
              (UNLESS XCL::NO-ERROR (FORMAT *ERROR-OUTPUT* "~S is not advised.~%" XCL::FN-TO-UNADVISE))
              NIL)
            (T (IL:PUTD XCL::FN-TO-UNADVISE (IL:GETD XCL::ORIGINAL)
              T)
              (REMPROP XCL::FN-TO-UNADVISE 'IL:ADVISED)
              (PUSH XCL::FN-TO-UNADVISE *UNADVISED-FNS*)
              (SETQ IL:ADVISEDFNS (DELETE XCL::FN-TO-UNADVISE IL:ADVISEDFNS))
              (LIST XCL::FN-TO-UNADVISE))))
        (LET* ((XCL::ADVICE-NAME `(,XCL::FN-TO-UNADVISE :IN ,XCL::IN-FN))
          (XCL::MIDDLE-MAN (GET-ADVICE-MIDDLE-MAN XCL::ADVICE-NAME)))
          (COND
            ((NULL XCL::MIDDLE-MAN)
              (UNLESS XCL::NO-ERROR (FORMAT *ERROR-OUTPUT* "~S is not advised.~%" XCL::ADVICE-NAME))
              NIL)
            (T (CHANGE-CALLS XCL::MIDDLE-MAN XCL::FN-TO-UNADVISE XCL::IN-FN)
              (FINISH-UNADVISING XCL::ADVICE-NAME XCL::MIDDLE-MAN)
              (LIST XCL::ADVICE-NAME))))))

(DEFUN XCL:READWISE-FUNCTION (XCL::FN-TO-READWISE &KEY ((:IN XCL::IN-FN))
  (COND
    ((CONSP XCL::FN-TO-READWISE)
      (IL:FOR XCL::FN IL:IN XCL::FN-TO-READWISE IL:JOIN (XCL:READWISE-FUNCTION XCL::FN :IN XCL::IN-FN)))
    ((CONSP XCL::IN-FN)
      (IL:FOR XCL::FN IL:IN XCL::IN-FN IL:JOIN (XCL:READWISE-FUNCTION XCL::FN-TO-READWISE :IN XCL::FN)))
    (T (XCL:UNBREAK-FUNCTION XCL::FN-TO-READWISE :IN XCL::IN-FN :NO-ERROR T)
      (FINISH-ADVISING XCL::FN-TO-READWISE XCL::IN-FN)))

```

```

(DEFUN UNADVISE-FROM-RESTORE-CALLS (FROM TO FN)
  (LET ((ENTRY (FIND-IF #'(LAMBDA (ENTRY)
    (AND (CONSP ENTRY)
      (EQ (FIRST ENTRY)
        FROM)
      (EQ (THIRD ENTRY)
        FN))))
    (IL:ADVISED FNS)))
  (ASSERT (NOT (NULL ENTRY))
    NIL "BUG: Inconsistency in SI::UNADVISE-FROM-RESTORE-CALLS")
  (FINISH-UNADVISING ENTRY TO)
  (FORMAT *TERMINAL-IO* "~S unadvised.~%" ENTRY)))

(DEFUN FINISH-ADVISING (FN-TO-ADVISE IN-FN)
  (COND
    ((NULL IN-FN)
      (LET* ((ALREADY-ADVISED? (MEMBER FN-TO-ADVISE IL:ADVISED FNS :TEST 'EQ))
        (ORIGINAL (IF ALREADY-ADVISED?
          (GET FN-TO-ADVISE 'IL:ADVISED)
          (LET ((*PRINT-CASE* :UPCASE))
            (MAKE-SYMBOL (FORMAT NIL "Original ~A" FN-TO-ADVISE))))))
        ;; Adjust the database of advice for this function.
        (WHEN (NOT ALREADY-ADVISED?)
          (IL:PUTD ORIGINAL (IL:GETD FN-TO-ADVISE)
            T))
          (IL:PUTD FN-TO-ADVISE (COMPILE NIL (CREATE-ADVISED-DEFINITION FN-TO-ADVISE ORIGINAL FN-TO-ADVISE)))
          (WHEN (NOT ALREADY-ADVISED?)
            (SETF (GET FN-TO-ADVISE 'IL:ADVISED)
              ORIGINAL)))
        ;; These are outside the WHEN because COMPILE calls VIRGINFN, which may unadvise the function.
        (SETQ *UNADVISED-FNS* (DELETE FN-TO-ADVISE *UNADVISED-FNS* :TEST 'EQ))
        (SETQ IL:ADVISED FNS
          ; Move FN-TO-ADVISE to the front of IL:ADVISED FNS if there
          ; already, else just add to front.
          (CONS FN-TO-ADVISE (DELETE FN-TO-ADVISE IL:ADVISED FNS :TEST 'EQ)))
        (IL:MARKASCHANGED FN-TO-ADVISE 'IL:ADVICE)
        (LIST FN-TO-ADVISE)))
      (T (LET* ((ADVICE-NAME `((,FN-TO-ADVISE ,IN ,IN-FN))
        (ALREADY-ADVISED? (MEMBER ADVICE-NAME IL:ADVISED FNS :TEST 'EQUAL))
        MIDDLE-MAN)
        ;; Create a middle-man for this request. If one has already been created, use it.
        (SETQ MIDDLE-MAN (OR (GET-ADVICE-MIDDLE-MAN ADVICE-NAME)
          (SETF (GET-ADVICE-MIDDLE-MAN ADVICE-NAME)
            (CONSTRUCT-MIDDLE-MAN FN-TO-ADVISE IN-FN))))
        ;; Give the middle-man the new advised definition.
        (IL:PUTD MIDDLE-MAN (COMPILE NIL (CREATE-ADVISED-DEFINITION FN-TO-ADVISE FN-TO-ADVISE ADVICE-NAME
          )))
        (WHEN (NOT ALREADY-ADVISED?)
          ;; Redirect any calls to FN-TO-ADVISE in IN-FN to call the middle-man.
          (CHANGE-CALLS FN-TO-ADVISE MIDDLE-MAN IN-FN 'UNADVISE-FROM-RESTORE-CALLS))
        ;; Save a trail of information. These are outside the WHEN because COMPILE calls VIRGINFN, which may unadvise the function.
        (SETQ *UNADVISED-FNS* (DELETE ADVICE-NAME *UNADVISED-FNS* :TEST 'EQUAL))
        (SETQ IL:ADVISED FNS
          ; Move ADVICE-NAME to the front of IL:ADVISED FNS if there
          ; already, else just add to front.
          (CONS ADVICE-NAME (DELETE ADVICE-NAME IL:ADVISED FNS :TEST 'EQUAL)))
        (IL:MARKASCHANGED ADVICE-NAME 'IL:ADVICE)
        (LIST ADVICE-NAME))))))

(DEFUN FINISH-UNADVISING (ADVICE-NAME MIDDLE-MAN)
  (SETQ IL:ADVISED FNS (DELETE ADVICE-NAME IL:ADVISED FNS :TEST 'EQUAL))
  (PUSH ADVICE-NAME *UNADVISED-FNS*))

;;
;; The advice database.

(DEFVAR *ADVICE-HASH-TABLE* (MAKE-HASH-TABLE :TEST 'EQUAL))

;;; Hash-table mapping either a function name or a list in the form (FOO :IN BAR) to a pair (advice . middle-man).

)

(DEFUN ADD-ADVICE (NAME WHEN PRIORITY FORM)

;;; Advice is stored on the hash table SI::*ADVICE-HASH-TABLE*. It is actually stored as a cons whose CAR is the advice and CDR is the middle-man
;;; name (for advice of the type (FOO :IN BAR)).

  (LET* ((OLD-ADVICE (GETHASH NAME *ADVICE-HASH-TABLE*))

```

```

(ADVICE (IF (NULL OLD-ADVICE)
            (MAKE-ADVICE)
            (CAR OLD-ADVICE))))
(ECASE WHEN
  (:BEFORE (SETF (ADVICE-BEFORE ADVICE)
                 (INSERT-ADVICE-FORM FORM PRIORITY (ADVICE-BEFORE ADVICE))))
  (:AFTER (SETF (ADVICE-AFTER ADVICE)
                 (INSERT-ADVICE-FORM FORM PRIORITY (ADVICE-AFTER ADVICE))))
  (:AROUND (SETF (ADVICE-AROUND ADVICE)
                  (INSERT-ADVICE-FORM FORM PRIORITY (ADVICE-AROUND ADVICE)))))
(WHEN (NULL OLD-ADVICE)
  (SETF (GETHASH NAME *ADVICE-HASH-TABLE*)
        (CONS ADVICE NIL))))

```

```

(DEFUN DELETE-ADVICE (NAME)
  (REMHASH NAME *ADVICE-HASH-TABLE*))

```

```

(DEFUN GET-ADVICE-MIDDLE-MAN (NAME)
  (CDR (GETHASH NAME *ADVICE-HASH-TABLE*)))

```

```

(DEFUN SET-ADVICE-MIDDLE-MAN (NAME MIDDLE-MAN)
  (SETF (CDR (GETHASH NAME *ADVICE-HASH-TABLE*))
        MIDDLE-MAN))

```

```

(DEFUN INSERT-ADVICE-FORM (FORM PRIORITY ENTRY-LIST)

```

;; Insert the new advice FORM into ENTRY-LIST using PRIORITY as a specification of where in that list to put it. If an equalish piece of advice already exists, remove it first.

```

(LET ((ENTRY (LIST PRIORITY FORM)))
  (SETF ENTRY-LIST
        (LABELS ((EQUALISH
                   (X Y)
                   ;; EQUALP, but don't ignore case in strings.
                   (TYPECASE X
                     (SYMBOL (EQ X Y))
                     (CONS (AND (CONSP Y)
                                (EQUALISH (CAR X)
                                           (CAR Y))
                                (EQUALISH (CDR X)
                                           (CDR Y))))
                     (NUMBER (AND (NUMBERP Y)
                                   (= X Y)))
                     (CHARACTER (AND (CHARACTERP Y)
                                       (CHAR= X Y)))
                     (STRING (AND (STRINGP Y)
                                   (STRING= X Y)))
                     (PATHNAME (AND (PATHNAMEP Y)
                                     (IL:%PATHNAME-EQUAL X Y)))
                     (VECTOR (AND (VECTORP Y)
                                   (LET ((SX (LENGTH X)))
                                     (AND (EQL SX (LENGTH Y))
                                           (DOTIMES (I SX T)
                                             (IF (NOT (EQUALISH (AREF X I)
                                                                (AREF Y I)))
                                                (RETURN NIL))))))
                     (ARRAY (AND (ARRAYP Y)
                                   (EQUAL (ARRAY-DIMENSIONS X)
                                           (ARRAY-DIMENSIONS Y))
                                   (LET ((FX (IL:%FLATTEN-ARRAY X))
                                         (FY (IL:%FLATTEN-ARRAY Y)))
                                     (DOTIMES (I (ARRAY-TOTAL-SIZE X)
                                               T)
                                       (IF (NOT (EQUALISH (AREF FX I)
                                                            (AREF FY I)))
                                           (RETURN NIL))))))
                   (T ;; so that datatypes will be properly compared
                     (OR (EQ X Y)
                         (LET ((TYPENAME (IL:TYPENAME X)))
                           (AND (EQ TYPENAME (IL:TYPENAME Y))
                                (LET ((DESCRIPTORS (IL:GETDESCRIPTORS TYPENAME)))
                                  (IF DESCRIPTORS
                                     (IL:FOR FIELD IL:IN DESCRIPTORS
                                       IL:ALWAYS (EQUALISH (IL:FFETCHFIELD FIELD X)
                                                            (IL:FFETCHFIELD FIELD Y))))))))))
                   (DELETE-IF #'(LAMBDA (OLD-ENTRY)
                                (XCL:DESTRUCTURING-BIND (OLD-PRIORITY OLD-FORM)
                                                          OLD-ENTRY
                                                          (AND (EQUAL PRIORITY OLD-PRIORITY)
                                                                (EQUALISH FORM OLD-FORM))))
                             ENTRY-LIST)))

```

```

(COND
  ((NULL ENTRY-LIST)
   (LIST ENTRY))
  ((EQ PRIORITY :FIRST)
   (CONS ENTRY ENTRY-LIST))
  ((EQ PRIORITY :LAST)
   (NCONC ENTRY-LIST (LIST ENTRY))))
(T
  (UNLESS (AND (CONSP PRIORITY)
               (MEMBER (CAR PRIORITY)
                       ' (IL:BEFORE IL:AFTER))))
    (ERROR "Malformed priority argument to ADVISE: ~S" PRIORITY))
  (XCL:CONDITION-CASE (IL:EDITE ENTRY-LIST `((IL:LC ,@(CDR PRIORITY))
                                             (IL:BELOW IL:^)
                                             (, (CAR PRIORITY)
                                              ,ENTRY))))
  (ERROR (C)
    (ERROR "Error from EDITE during insertion of new advice:~% ~A~%" C)))
  ENTRY-LIST))))

```

; PRIORITY is a command to the old TTY Editor.

```
(DEFSETF GET-ADVICE-MIDDLE-MAN SET-ADVICE-MIDDLE-MAN)
```

```

;;
;; Hacking the actual advice forms.

```

```

(DEFUN CREATE-ADVISED-DEFINITION (ADVISED-FN FN-TO-CALL ADVICE-NAME)
  (MULTIPLE-VALUE-BIND (LAMBDA-CAR ARG-LIST CALLING-FORM)
    (FUNCTION-WRAPPER-INFO ADVISED-FN FN-TO-CALL)
    (LET* ((ADVICE (CAR (GETHASH ADVICE-NAME *ADVICE-HASH-TABLE*)))
           (BEFORE-FORMS (MAPCAR 'SECOND (ADVICE-BEFORE ADVICE)))
           (AFTER-FORMS (MAPCAR 'SECOND (ADVICE-AFTER ADVICE)))
           (AROUND-FORMS (MAPCAR 'SECOND (ADVICE-AROUND ADVICE)))
           (BODY-FORM (MAKE-AROUND-BODY CALLING-FORM AROUND-FORMS)))
      ` (,LAMBDA-CAR , (IF (EQ LAMBDA-CAR 'LAMBDA)
                          ' (&REST XCL:ARGLIST)
                          ARG-LIST)
        ,@(AND ARG-LIST (MEMBER LAMBDA-CAR ' (IL:LAMBDA IL:NLAMBDA))
              ` ((DECLARE (SPECIAL ,@(IF (SYMBOLP ARG-LIST)
                                          (LIST ARG-LIST)
                                          ARG-LIST))))))
        (IL:\\CALLME ' (:ADVISED ,ADVICE-NAME))
        (BLOCK NIL
          (XCL:DESTRUCTURING-BIND (IL:!VALUE . IL:!OTHER-VALUES)
            (MULTIPLE-VALUE-LIST (PROGN ,@BEFORE-FORMS ,BODY-FORM)
              ,@AFTER-FORMS
              (APPLY 'VALUES IL:!VALUE IL:!OTHER-VALUES)))))))

```

```

(DEFUN MAKE-AROUND-BODY (CALLING-FORM AROUND-FORMS)
  (REDUCE #' (LAMBDA (CURRENT-BODY NEXT-AROUND-FORM)
    (LET ((CANONICALIZED-AROUND-FORM (SUBST ' (XCL:INNER)
                                           ' IL:* NEXT-AROUND-FORM)))
      ` (MACROLET ((XCL:INNER NIL ' ,CURRENT-BODY)
                  ,CANONICALIZED-AROUND-FORM))
        AROUND-FORMS :INITIAL-VALUE CALLING-FORM))
    AROUND-FORMS :INITIAL-VALUE CALLING-FORM))

```

```

;;
;; Dealing with the File Manager

```

```

(IL:PUTDEF 'IL:ADVICE 'IL:FILEPKGCOMS
  ' ((IL:COM IL:MACRO (IL:X (IL:P IL:* (ADVICE-FILE-DEFINITIONS 'IL:X NIL)))
     IL:CONTENTS IL:NILL IL:ADD ADVICE-ADDTOCOM)
    (TYPE IL:DESCRIPTION "advice" IL:NEWCOM ADVICE-NEWCOM IL:GETDEF ADVICE-GETDEF IL:DELDEF ADVICE-DELDEF
     IL:PUTDEF ADVICE-PUTDEF IL:HASDEF ADVICE-HASDEF)))

```

```

(IL:PUTDEF 'IL:ADVICE 'IL:FILEPKGCOMS ' ((IL:COM IL:MACRO (IL:X (IL:P IL:* (ADVICE-FILE-DEFINITIONS 'IL:X T)))
                                           IL:CONTENTS ADVICE-CONTENTS IL:ADD ADVICE-ADDTOCOM)))

```

```

(DEFUN XCL:REINSTALL-ADVICE (XCL::NAME &KEY XCL::BEFORE XCL::AFTER XCL::AROUND)
  (IL:FOR XCL::ADVICE IL:IN XCL::BEFORE IL:DO (XCL:DESTRUCTURING-BIND (XCL::PRIORITY XCL::FORM)
    XCL::ADVICE
    (ADD-ADVICE XCL::NAME :BEFORE XCL::PRIORITY XCL::FORM)))
  (IL:FOR XCL::ADVICE IL:IN XCL::AFTER IL:DO (XCL:DESTRUCTURING-BIND (XCL::PRIORITY XCL::FORM)
    XCL::ADVICE
    (ADD-ADVICE XCL::NAME :AFTER XCL::PRIORITY XCL::FORM)))
  (IL:FOR XCL::ADVICE IL:IN XCL::AROUND IL:DO (XCL:DESTRUCTURING-BIND (XCL::PRIORITY XCL::FORM)
    XCL::ADVICE
    (ADD-ADVICE XCL::NAME :AROUND XCL::PRIORITY XCL::FORM))))

```

```

(DEFUN ADVICE-GETDEF (NAME TYPE OPTIONS)
  (LET ((ADVICE (CAR (GETHASH NAME *ADVICE-HASH-TABLE*))))

```

```

(AND ADVICE (APPEND (IL:FOR ENTRY IL:IN (ADVICE-BEFORE ADVICE) IL:COLLECT (CONS ' :BEFORE (COPY-TREE ENTRY)
))
              (IL:FOR ENTRY IL:IN (ADVICE-AFTER ADVICE) IL:COLLECT (CONS ' :AFTER (COPY-TREE ENTRY)))
              (IL:FOR ENTRY IL:IN (ADVICE-AROUND ADVICE) IL:COLLECT (CONS ' :AROUND (COPY-TREE ENTRY)
              )))))

```

```

(DEFUN ADVISE-PUTDEF (NAME TYPE DEFINITION)
  (LET ((CANONICAL-DEFN (IL:FOR ENTRY IL:IN DEFINITION IL:COLLECT (LIST (CANONICALIZE-ADVICE-WHEN-SPEC
                                                                           (CAR ENTRY))
                                                                           (CANONICALIZE-ADVICE-WHERE-SPEC
                                                                           (COPY-TREE (CADR ENTRY)))
                                                                           (COPY-TREE (CADDR ENTRY))))))
    (CURRENT-ADVICE (OR (CAR (GETHASH NAME *ADVICE-HASH-TABLE*))
                        (CAR (SETF (GETHASH NAME *ADVICE-HASH-TABLE*)
                                (CONS (MAKE-ADVICE)
                                      NIL))))))
    (SETF (ADVICE-BEFORE CURRENT-ADVICE)
      (MAPCAR #'REST (IL:FOR ENTRY IL:IN CANONICAL-DEFN IL:WHEN (EQ (CAR ENTRY)
                                                                    :BEFORE)
                        IL:COLLECT ENTRY)))
    (SETF (ADVICE-AFTER CURRENT-ADVICE)
      (MAPCAR #'REST (IL:FOR ENTRY IL:IN CANONICAL-DEFN IL:WHEN (EQ (CAR ENTRY)
                                                                    :AFTER)
                        IL:COLLECT ENTRY)))
    (SETF (ADVICE-AROUND CURRENT-ADVICE)
      (MAPCAR #'REST (IL:FOR ENTRY IL:IN CANONICAL-DEFN IL:WHEN (EQ (CAR ENTRY)
                                                                    :AROUND)
                        IL:COLLECT ENTRY)))
    (IF (CONSP NAME)
        (XCL:READWISE-FUNCTION (FIRST NAME)
                              :IN
                              (THIRD NAME))
        (XCL:READWISE-FUNCTION NAME))))

```

```

(DEFUN ADVISE-DELDEF (NAME TYPE)
  (DECLARE (IGNORE TYPE))
  (WHEN (MEMBER NAME IL:ADVISEDfNS :TEST 'EQUAL)
    (IF (CONSP NAME)
        (XCL:UNADVISE-FUNCTION (FIRST NAME)
                              :IN
                              (THIRD NAME))
        (XCL:UNADVISE-FUNCTION NAME))
    (FORMAT *TERMINAL-IO* "~S unadvised." NAME))
  (REHASH NAME *ADVICE-HASH-TABLE*))

```

```

(DEFUN ADVISE-HASDEF (NAME TYPE SOURCE)
  (AND (GETHASH NAME *ADVICE-HASH-TABLE*)
       (OR NAME T)))

```

```

(DEFUN ADVISE-NEWCOM (NAME TYPE LISTNAME FILE)

```

;; If you make a new com for ADVISE, you should make an ADVISE command.

```

(IL:DEFAULTMAKENEWCOM NAME 'IL:ADVISE LISTNAME FILE))

```

```

(DEFUN ADVISE-FILE-DEFINITIONS (NAMES READWISE?)

```

;; READWISE? is true for the File Manager command ADVISE and false for the command ADVICE. For ADVISE, we want to emit a form to readwise the  
 ;; named functions after reinstalling the advice.

```

(LET ((REAL-NAMES NIL))
  ` (, @ (IL:FOR FN IL:IN NAMES
    IL:COLLECT (LET* ((NAME (IL:IF (CONSP FN)
                                  IL:THEN (ASSERT (AND (EQ (SECOND FN)
                                                            :IN)
                                                            (= 3 (LENGTH FN)))
                                  NIL "~S should be of the form (FOO :IN BAR)" FN)
                                FN
                                IL:ELSE (LET ((NAME (CANONICALIZE-ADVICE-SYMBOL FN))
                                              (OLD-ADVICE (GET FN 'IL:READWISE)))
                                          (WHEN OLD-ADVICE
                                            (ADD-OLD-STYLE-ADVICE NAME OLD-ADVICE)
                                            (REMPROP FN 'IL:READWISE))
                                          NAME))))
      (ADVICE (CAR (GETHASH NAME *ADVICE-HASH-TABLE*)))))
    (ASSERT (NOT (NULL ADVICE))
      NIL "Can't find advice for ~S" NAME)
    (PUSH NAME REAL-NAMES)
    ` (XCL:REINSTALL-ADVICE ',NAME
      , @ (AND (ADVICE-BEFORE ADVICE)
        ` (:BEFORE ', (ADVICE-BEFORE ADVICE)))
      , @ (AND (ADVICE-AFTER ADVICE)

```

```

      \(:AFTER ', (ADVICE-AFTER ADVICE)))
      ,@ (AND (ADVICE-AROUND ADVICE)
      \(:AROUND ', (ADVICE-AROUND ADVICE))))))
, @ (AND READVICE? \(:IL:READVICE ,@ (REVERSE REAL-NAMES))))))

```

```

(DEFUN ADVICE-CONTENTS (COM NAME TYPE)
  (AND (EQ TYPE 'IL:ADVICE)
    (COND
      ((NULL NAME) ; Return a list of the ADVICE's in the given COM.
       (CDR COM))
      ((EQ NAME 'T) ; Return T if there are ANY ADVICE's in the given COM.
       (NOT (NULL (CDR COM))))
      ((OR (SYMBOLP NAME)
            (= (LENGTH NAME)
               3)
            (EQ (SECOND NAME)
                 :IN)) ; Return T iff an ADVICE named NAME in the given COM.
       (AND (MEMBER NAME (CDR COM)
                       :TEST
                       'EQUAL)
            T))
      (T ; NAME is a list of names. Return the intersection of that list with
          ; the ADVICE's in the given COM.
          (INTERSECTION NAME (CDR COM)
                        :TEST
                        'EQUAL))))))

```

```

(DEFUN ADVICE-ADDTOCOM (COM NAME TYPE NEAR)

```

```

;; This is the ADD method for both of the ADVICE and ADVISE commands.

```

```

;; Add the given name only if the type is ADVICE. Also, add it to ADVICE commands only if a NEAR was specified. We want to normally create only
;; ADVISE commands. If the user really wants an ADVICE command, they'll have to create it themselves.

```

```

  (AND (EQ TYPE 'IL:ADVICE)
        (OR (EQ (CAR COM)
                 'IL:ADVISE)
            (NOT (NULL NEAR))))
  (IL:ADDTOCOM1 COM NAME NEAR NIL))

```

```

(IL:PUTPROPS IL:ADVISED IL:PROPTYPE IGNORE)

```

```

;;

```

```

;; Dealing with old-style advice

```

```

(DEFUN IL:READVICE1 (IL:FN)
  (FLET ((IL:READVICE-ENTRY (IL:ENTRY)
    (IL:IF (IL:LISTP IL:ENTRY)
      IL:THEN (XCL:READVICE-FUNCTION (FIRST IL:ENTRY)
                                      :IN
                                      (THIRD IL:ENTRY))
      IL:ELSE (XCL:READVICE-FUNCTION IL:ENTRY))))
    (IL:IF (IL:LISTP IL:FN)
      IL:THEN (ASSERT (IL:STRING.EQUAL (SECOND IL:FN)
                                         "IN")
                     NIL "~S should be in the form (FOO IN BAR).~%" IL:FN)
      (IL:READVICE-ENTRY IL:FN))
    (IL:ELSE (LET ((IL:NAME (CANONICALIZE-ADVICE-SYMBOL IL:FN))
                  (IL:OLD-ADVICE (GET IL:FN 'IL:READVICE)))
      (IL:IF IL:OLD-ADVICE
        IL:THEN (ADD-OLD-STYLE-ADVICE IL:NAME IL:OLD-ADVICE)
        (REMPROP IL:FN 'IL:READVICE))
      (IL:READVICE-ENTRY IL:NAME))))))

```

```

(DEFUN ADD-OLD-STYLE-ADVICE (NAME OLD-ADVICE)

```

```

;; OLD-ADVICE should be the value of the READVICE property of some symbol. Note that the CAR of that value is the old middle-man used for -IN-
;; advice. Thus, we take the CDR below.

```

```

  (WHEN (NOT (MEMBER NAME IL:ADVISED FNS :TEST 'EQUAL))
    (DELETE-ADVICE NAME))
  (IL:FOR ADVICE IL:IN (CDR OLD-ADVICE) IL:DO (XCL:DESTRUCTURING-BIND (WHEN WHERE WHAT)
    ADVICE
    ;; Translate Interlisp names to the new standard.
    (ADD-ADVICE NAME (CANONICALIZE-ADVICE-WHEN-SPEC WHEN)
                  (CANONICALIZE-ADVICE-WHERE-SPEC WHERE)
                  WHAT))))

```

```

(DEFUN CANONICALIZE-ADVICE-SYMBOL (SYMBOL)
  (LET ((IN-POS (IL:STRPOS "-IN-" SYMBOL)))

```



```

(IF (NULL IN-POS)
  SYMBOL
  (LIST (IL:SUBATOM SYMBOL 1 (1- IN-POS))
    :IN
    (IL:SUBATOM SYMBOL (+ IN-POS 4)
      NIL))))))

```

```

(DEFUN CANONICALIZE-ADVICE-WHEN-SPEC (SPEC)
  (IF (NULL SPEC)
    ' :BEFORE
    (INTERN (STRING SPEC)
      "KEYWORD"))))

```

```

(DEFUN CANONICALIZE-ADVICE-WHERE-SPEC (SPEC)
  (CASE SPEC
    ((NIL LAST IL:BOTTOM IL:END :LAST) ' :LAST)
    ((IL:TOP IL:FIRST :FIRST) ' :FIRST)
    (T (IF (CONSP SPEC)
      SPEC
      (ERROR "Illegal WHERE specification to ADVISE: ~S" SPEC)))))

```

```

(XCL:DEF-DEFINE-TYPE XCL:ADVISED-FUNCTIONS "Advised function definitions")

```

```

(XCL:DEFDEFINER (XCL:DEFADVICE (:PROTOTYPE (LAMBDA (XCL::NAME)
  \ (XCL:DEFADVICE ,XCL::NAME
    "advice"))))
  XCL:ADVISED-FUNCTIONS (XCL::NAME &BODY XCL::ADVICE-FORMS)
  \ (PROGN ,. (XCL:WITH-COLLECTION
    (DOLIST (XCL::ADVICE XCL::ADVICE-FORMS)
      (XCL:COLLECT (XCL:DESTRUCTURING-BIND
        (XCL::FN-TO-ADVISE XCL::FORM &KEY XCL::IN WHEN XCL::PRIORITY)
        XCL::ADVICE
        \ (XCL:ADVISE-FUNCTION ',XCL::FN-TO-ADVISE ',XCL::FORM
          ,@ (AND XCL::IN `(:IN ',XCL::IN))
          ,@ (AND WHEN `(:WHEN ,WHEN))
          ,@ (AND XCL::PRIORITY `(:PRIORITY ,XCL::PRIORITY))))))))))

```

:: Arrange for the proper package. Because of the DEFSTRUCT above, we must have the file dumped in the SYSTEM package.

```

(IL:PUTPROPS IL:ADVISE IL:MAKEFILE-ENVIRONMENT (:READTABLE "XCL" :PACKAGE "SYSTEM"))
(IL:PUTPROPS IL:ADVISE IL:FILETYPE :COMPILE-FILE)
(IL:DECLARE\ : IL:DONTEVAL@LOAD IL:DOEVAL@COMPILE IL:DONTCOPY IL:COMPILERVERS
(IL:ADDTOVAR IL:NLAMA IL:READADVISE IL:UNADVISE)
(IL:ADDTOVAR IL:NLAML )
(IL:ADDTOVAR IL:LAMA IL:ADVISE)
)
(IL:PUTPROPS IL:ADVISE IL:COPYRIGHT ("Venue & Xerox Corporation" T 1978 1984 1986 1987 1988 1990))

```

FUNCTION INDEX

ADD-ADVICE .....	4	ADVISE-CONTENTS .....	8	INSERT-ADVICE-FORM .....	5
ADD-OLD-STYLE-ADVICE .....	8	XCL:ADVISE-FUNCTION .....	2	MAKE-AROUND-BODY .....	6
ADVICE-ADDTOCOM .....	8	CANONICALIZE-ADVICE-SYMBOL .....	8	IL:READVICE .....	2
ADVICE-DELDEF .....	7	CANONICALIZE-ADVICE-WHEN-SPEC ...	9	XCL:READVICE-FUNCTION .....	3
ADVICE-FILE-DEFINITIONS .....	7	CANONICALIZE-ADVICE-WHERE-SPEC ...	9	IL:READVICE1 .....	8
ADVICE-GETDEF .....	6	CREATE-ADVISED-DEFINITION .....	6	XCL:REINSTALL-ADVICE .....	6
ADVICE-HASDEF .....	7	DELETE-ADVICE .....	5	SET-ADVICE-MIDDLE-MAN .....	5
ADVICE-NEWCOM .....	7	FINISH-ADVISING .....	4	IL:UNADVISE .....	2
ADVICE-PUTDEF .....	7	FINISH-UNADVISING .....	4	UNADVISE-FROM-RESTORE-CALLS .....	4
IL:ADVISE .....	2	GET-ADVICE-MIDDLE-MAN .....	5	XCL:UNADVISE-FUNCTION .....	3

VARIABLE INDEX

*ADVISE-HASH-TABLE* .....	4	*UNADVISED-FNS* .....	1	IL:ADVISEDFNS .....	1
---------------------------	---	-----------------------	---	---------------------	---

PROPERTY INDEX

IL:ADVISE .....	2, 9	IL:ADVISED .....	8
-----------------	------	------------------	---

DEFINER INDEX

XCL:DEFADVISE .....	9
---------------------	---

DEFINE-TYPE INDEX

XCL:ADVISED-FUNCTIONS .....	9
-----------------------------	---

SETF INDEX

GET-ADVICE-MIDDLE-MAN .....	6
-----------------------------	---

STRUCTURE INDEX

ADVISE .....	1
--------------	---