



```

(COND
  ((IGREATERP BYTES 0)
   (SETQ LEN (ARG BYTES 2]))
  (LONGSEQUENCE)
  (SHOULDNT])

```

**(FINDNONPRIMNAME**

```

[LAMBDA (CODE)
  (SEARCHIPLIST CODE (CONSTANT NONPRIMS])]

```

(\* rmk%: "15-Mar-84 09:07")

**(FINDOPNAME**

```

[LAMBDA (CODE)
  (SEARCHIPLIST CODE (CONSTANT (for OP DOTLOC in OPERATORS collect

```

(\* rmk%: "16-Jun-84 15:24")

(\* Strip off extension)

```

(COND
  ((SETQ DOTLOC (STRPOS "." (CAR OP)))
   (LIST (SUBATOM (CAR OP)
             1
             (SUB1 DOTLOC))
          (CADR OP)))
  (T OP])

```

**(SHORTINT**

```

[LAMBDA BYTES
  (for I (RESULT _ 0) from 1 to BYTES do (SETQ RESULT (LOGOR (LLSH RESULT 8)
                                                                (ARG BYTES I)))
  finally (RETURN (IDIFFERENCE RESULT 4000]))

```

(\* rmk%: "19-APR-83 17:34")

(ARG BYTES I)))

**(TOKENFORMAT**

```

[LAMBDA (BYTE)
  (SELECTQ (LRSH BYTE 7)
    (0 'SHORTINT)
    (SELECT (LOGAND (LRSH BYTE 5)
      3)
      (0 'SHORTOP)
      (1 'LONGOP)
      (2 'SHORTSEQUENCE)
      (3 'LONGSEQUENCE)
      (SHOULDNT])

```

(\* rmk%: "19-APR-83 17:41")

**(FINDSEQUENCETYPE**

```

[LAMBDA (CODE)
  (for X in (CONSTANT SEQUENCETYPES) when (EQ CODE (CADR X)) do (RETURN (CAR X))
  finally (RETURN (LIST CODE 'NOT-A-SEQUENCE-TYPE]))

```

(\* rmk%: "15-Mar-84 09:04")

**(PRINTTOKEN**

```

[LAMBDA (ISTREAM OSTREAM)
  (PROG (CODE BYTE2 (BYTE1 (BIN.RIP ISTREAM OSTREAM)))
    (SELECTQ (TOKENFORMAT BYTE1)
      (SHORTINT (SETQ BYTE2 (BIN.RIP ISTREAM OSTREAM))
        (printout OSTREAM .TAB 20)
        (PRINT (SHORTINT BYTE1 BYTE2)
          OSTREAM))
      (SHORTOP (SETQ CODE (LOGAND BYTE1 31))
        (printout OSTREAM .TAB 20)
        (printout OSTREAM (OR (FINDOPNAME CODE)
                              (FINDNONPRIMNAME CODE)
                              (CONCAT CODE "not an opcode"))
          T))
      (LONGOP (SETQ CODE (IPLUS (LLSH (LOGAND BYTE1 31)
        8)
        (BIN.RIP ISTREAM OSTREAM)))
        (printout OSTREAM .TAB 20)
        (printout OSTREAM (OR (FINDOPNAME CODE)
                              (FINDNONPRIMNAME CODE)
                              (CONCAT CODE "not an opcode"))
          T))
      (SHORTSEQUENCE
        (PRINTSEQUENCE ISTREAM OSTREAM (FINDSEQUENCETYPE (LOGAND BYTE1 31))
          (BIN.RIP ISTREAM OSTREAM)))
      (LONGSEQUENCE (PRINTSEQUENCE ISTREAM OSTREAM (FINDSEQUENCETYPE (LOGAND BYTE1 31))
        (LOGOR (LLSH (BIN.RIP ISTREAM OSTREAM)
          16)
          (LLSH (BIN.RIP ISTREAM OSTREAM)
            8)
          (BIN.RIP ISTREAM OSTREAM))))
      (SHOULDNT])

```

(\* hdj "15-Jul-86 21:55")

**(PRINTSEQUENCE**

```

[LAMBDA (ISTREAM OUTSTREAM TYPE LENGTH)

```

; Edited 22-Jun-2021 10:52 by rmk:

```

(DECLARE (SPECVARS LENGTH)) ; For byte counting
(SELECTQ TYPE
  (SEQIDENTIFIER
    (printout OUTSTREAM 20 "ID: ")
    (until (EQ LENGTH 0) do (PRINTCCODE (\INCCODE ISTREAM 'LENGTH LENGTH)
                                   OUTSTREAM)))
  (SEQINTEGER (printout OUTSTREAM 20
    (for I from 1 to LENGTH do (PRINTTOKEN ISTREAM OUTSTREAM)))
  (SEQRATIONAL (PROG [(NUM (READINT.IP ISTREAM (LRSH LENGTH 1)))
    (DENOM (READINT.IP ISTREAM (LRSH LENGTH 1)
    (printout OUTSTREAM 20 NUM "/" DENOM " = " (FQUOTIENT NUM DENOM)))]
  (SEQSTRING (printout OUTSTREAM 20 "STR[" LENGTH "] = %")
    (until (EQ LENGTH 0) do (PRINTCCODE (\INCCODE ISTREAM 'LENGTH LENGTH)
                                   OUTSTREAM))
    (printout OUTSTREAM '%'))
  (SEQCOMMENT (for I from 1 to LENGTH first (printout OUTSTREAM 20 "Comment vector of " LENGTH " bytes" 22)
    do (printout OUTSTREAM .I4 (BIN ISTREAM))))
  (SEQPACKEDPIXELVECTOR
    (bind YBYTES (I _ 5)
      (XBITS _ (READINT.IP ISTREAM 2))
      (YBITS _ (READINT.IP ISTREAM 2))
      first (printout OUTSTREAM 20 "Packed pixel" " vector of " LENGTH " bytes [" XBITS "X" YBITS "J")
        (SETQ YBYTES (UNFOLD (FOLDHI YBITS BITSPERWORD)
          BYTESPERWORD))) (* "The number of bytes on a line is always even--gets to a word
                           boundary")
    while (ILEQ I LENGTH) do (printout OUTSTREAM T 10)
      (for J from 1 to YBYTES do (printout OUTSTREAM .I8.-2.T (BIN ISTREAM)
        (add I 1))))
  (SEQLARGEVECTOR
    (for I VAL (BYTESPERELT _ (BIN ISTREAM)) from 2 to LENGTH
      first (printout OUTSTREAM 20 "Large vector of " BYTESPERELT " bytes per element")
      do (SETQ VAL (READINT.IP ISTREAM BYTESPERELT))
        (printout OUTSTREAM 22 .I5 I ": " VAL)))
  (SEQCONTINUED (HELP "Can't handle SEQCONTINUED yet"))
  (SEQINSERTFILE
    (HELP "Can't handle SEQINSERTFILE yet"))
  (SEQCOMPRESSPIXELVECTOR
    (HELP "Can't handle SEQCOMPRESSPIXELVECTOR yet"))
  (SHOULDNT))
(TERPRI OUTSTREAM)]

```

**(SEARCHLIST**

```

[LAMBDA (CODE IPLIST) ; (* rmk%: "15-Mar-84 09:15")
  (for X in IPLIST when (EQ CODE (CADR X)) do (RETURN (CAR X))

```

**(READINT.IP**

```

[LAMBDA (ISTREAM NBYTES) ; Edited 25-Mar-88 17:50 by bvm
  (for I (RESULT _ 0) from 1 to NBYTES do (SETQ RESULT (LOGOR (LLSH RESULT 8)
    (BIN.RIP ISTREAM)))
  finally (RETURN (SIGNED RESULT (UNFOLD NBYTES BITSPERBYTE]))

```

**(SHOWFILE**

```

[LAMBDA (IPFILE OUTPUTFILE MAXZEROLINES) ; Edited 24-Sep-2023 13:52 by rmk
  (* rmk%: "16-Jun-84 15:29")
  (OR MAXZEROLINES (SETQ MAXZEROLINES 5))
  (RESETLST
    [PROG (STREAM)
      [RESETSAVE (SETQ STREAM (OPENSTREAM IPFILE 'INPUT))
        ' (PROGN (CLOSEF? OLDVALUE) (* Don't do an OPENSTREAM until
        (OPENP stream) is NIL if stream is closed.)
      (RESETSAVE (OUTPUT))
      [RESETSAVE (SETQ OUTPUTFILE (OPENSTREAM OUTPUTFILE 'OUTPUT))
        ' (PROGN (CLOSEF? OLDVALUE)
          (AND RESETSTATE (DELFILE OLDVALUE)
        (OUTPUT OUTPUTFILE)
        (printout NIL .FONT DEFAULTFONT (OPENP STREAM 'INPUT)
          T T)
        [for I B1 B2 B3 B4 B5 B6 B7 B8 (NZEROLINES _ 0) from 1 by 8 until (\EOFP STREAM)
          do (printout NIL .I5 I %,,)
            (SETQ B1 (SHOWBYTE STREAM))
            (SETQ B2 (SHOWBYTE STREAM))
            (SETQ B3 (SHOWBYTE STREAM))
            (SETQ B4 (SHOWBYTE STREAM))
            (printout NIL %,,)
            (SETQ B5 (SHOWBYTE STREAM))
            (SETQ B6 (SHOWBYTE STREAM))
            (SETQ B7 (SHOWBYTE STREAM))
            (SETQ B8 (SHOWBYTE STREAM))
            (TAB 23)
            (COND
              (B1 (printout NIL .I4 B1)))
            (COND
              (B2 (printout NIL .I4 B2)))

```

```

(COND
  (B3 (printout NIL .I4 B3)))
(COND
  (B4 (printout NIL .I4 B4)))
(printout NIL %, ,)
(COND
  (B5 (printout NIL .I4 B5)))
(COND
  (B6 (printout NIL .I4 B6)))
(COND
  (B7 (printout NIL .I4 B7)))
(COND
  (B8 (printout NIL .I4 B8 T]
(RETURN (LIST (CLOSEF IPFILE)
              (CLOSEF OUTPUTFILE]))))

```

**(SHOWBYTE**

(\* rmk%: "13-JUL-82 18:01")

```

[LAMBDA (STREAM)
  (PROG [(BYTE (COND
    ((NOT (\EOFP STREAM))
     (\BIN STREAM]
    [COND
      (BYTE (PRIN1 (COND
        ((AND (IGEQ BYTE (CHARCODE SPACE))
              (ILESSP BYTE (CHARCODE DEL))
              (NEQ BYTE 96))
        (CHARACTER BYTE))
        (T '%.]
      (RETURN BYTE])
    )
  (DECLARE%: EVAL@COMPILE
  (PUTPROPS BIN.RIP MACRO [ARGS (LET ((ISTREAM (CAR ARGS))
                                         (OSTREAM (CADR ARGS)))
                                   `(LET [(C (BIN ,ISTREAM]
                                         (COND
                                           ((IGREATERP (POSITION ,OSTREAM)
                                                         15)
                                            (printout ,OSTREAM 5 " | " 8)))
                                           (printout ,OSTREAM .I3 C " ")
                                          C])
    )
  (DECLARE%: EVAL@COMPILE DONTCOPY
  (FILESLOAD (LOADCOMP)
    INTERPRESS)
  )
  (DECLARE%: DONTVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILERVERS
  (ADDTOVAR NLAMA )
  (ADDTOVAR NLAML )
  (ADDTOVAR LAMA SHORTINT TOKEN)
  )
  (PUTPROPS READINTERPRESS COPYRIGHT ("Xerox Corporation" 1983 1984 1985 1986 1988 2021))

```

FUNCTION INDEX

FINDNONPRIMNAME ..2	OPCODE .....1	PRINTTOKEN .....2	SHORTINT .....2	TOKEN .....1
FINDOPNAME .....2	PRINTMASTER .....1	READINT.IP .....3	SHOWBYTE .....4	TOKENFORMAT .....2
FINDSEQUENCETYPE ..2	PRINTSEQUENCE .....2	SEARCHIPLIST .....3	SHOWFILE .....3	

MACRO INDEX

BIN.RIP .....4
----------------