File created: 19-Dec-88 15:40:33 **{DSK}<LISPFILES>LOGIC>MEDLEY>LOGIC-DEVEL.;7**

changes to: (IL:VARS IL:LOGIC-DEVELCOMS)
(IL:FUNCTIONS EDIT-AXIOM EDIT-SA PROMPTREAD)

previous date: 19-Dec-88 14:47:38 {DSK}<LISPFILES>LOGIC>MEDLEY>LOGIC-DEVEL.;6

Read Table: INTERLISP

Package: USER

Format: XCCS

```
;;
;; Copyright (c) 1987, 1988 by ROBERTO GHISLANZONI.  All rights reserved.

(IL:RPAQQ IL:LOGIC-DEVELCOMS
          ((IL:* IL:NOW IL:THESE IL:ARE IL:MACROS)
           (IL:FUNCTIONS DRIBBLEP SEE-ENV-P SET-MENU TRACINGP)
           (IL:* IL:THESE IL:ARE IL:FUNCTIONS)
           (IL:FUNCTIONS CREATE-DEVEL-THEORY CREATE-THEORY-MENU EDIT-AXIOM EDIT-SA GET-LIST-PROP GET-TB-PROPERTY
                  GET-THEORY-INTERNAL LIST-ALL-THEORIES-INTERNAL LOAD-DEVEL-THEORY LOGIC-BUTTONFN
                  LOGIC-DEVELOPER LOGIC-MENU-FUNCTION MERGE-THEORIES-DEVEL MY-CREATE-TBRECORD PRINT-TB-ITEMS
                  PROMPTREAD SAVE-DEVEL-THEORY SHOW-PROFILE SOLVE-DEBUGGER START-PROVING UNIFY-DEBUGGER)
           (IL:ADDVARS (IL:BackgroundMenuCommands ("Logic" '(IL:ADD.PROCESS '(LOGIC-DEVELOPER))
                                                  "Open a window on logic programming environment")))
           (IL:VARS *LOGIC-MENU-ITEMS* *LOGIC-RELEASE-NUMBER* *LOGIC-CLOSE-ON-COMPLETION-FLG* (IL:BackgroundMenu
                                                                                               NIL)
                  (IL:LogicMiddleMenu NIL)
                  IL:LogicMiddleMenuCommands)
           (IL:P (IL:FILESLOAD IL:TABLEBROWSER))
           (IL:RECORDS IL:TABLEBROWSER IL:TABLEITEM)
           (IL:CONSTANTS IL:TB.LEFT.MARGIN)))


          (IL:* IL:* IL:NOW IL:THESE IL:ARE IL:MACROS)

(DEFMACRO DRIBBLEP (WINDOW TYPE)
   `[COND
       ((EQ ,TYPE 'SOLVE)
        (IL:GETWINDOWPROP (IL:GETWINDOWPROP ,WINDOW 'IL:SOLVE-WINDOW)
               'IL:TYPESCRIPTSTREAM))
       ((EQ ,TYPE 'UNIFY)
        (IL:GETWINDOWPROP (IL:GETWINDOWPROP ,WINDOW 'IL:UNIFY-WINDOW)
               'IL:TYPESCRIPTSTREAM])


(DEFMACRO SEE-ENV-P (WINDOW)
   `(IL:GETWINDOWPROP WINDOW 'IL:SEE))


(DEFMACRO SET-MENU (MENU FIELD VALUE)
   `(SETF (IL:FETCH ,FIELD IL:OF ,MENU)
          ,VALUE))


(DEFMACRO TRACINGP (WINDOW TYPE)
   `[COND
       ((EQ ,TYPE 'SOLVE)
        (EQ (IL:GETWINDOWPROP ,WINDOW 'IL:SOLVE)
            'TRACE))
       ((EQ ,TYPE 'UNIFY)
        (EQ (IL:GETWINDOWPROP ,WINDOW 'IL:UNIFY)
            'TRACE])


          (IL:* IL:* IL:THESE IL:ARE IL:FUNCTIONS)

(DEFUN CREATE-DEVEL-THEORY (MAIN-WINDOW)
   [PROG* [(PW (IL:GETPROMPTWINDOW MAIN-WINDOW))
           (THEORY-NAME (PROGN (IL:CLEARW PW)
                               (PROMPTREAD "Theory name" PW T]
     ;; Every theory is stored in a tablebrowser as a tableitem
          (AND THEORY-NAME (LET* [(ACTUAL-THEORY (MAKE-HASH-TABLE))
                                  (TB-ITEM (MY-CREATE-TBRECORD (ACONS 'THEORY ACTUAL-THEORY
                                                                      (ACONS 'THEORY-NAME THEORY-NAME NIL]
                                 (IL:CLEARW PW)
                                 (IL:TB.INSERT.ITEM (IL:GETWINDOWPROP MAIN-WINDOW 'IL:TABLEBROWSER)
                                        TB-ITEM)
                                 (IL:CLEARW PW)
                                 (FORMAT PW "~%%Theory created"])
```

```
(DEFUN CREATE-THEORY-MENU (MAINW)
    ;; For speed improving, the list of all theories are kept in a menu; this menu is updated every time the user makes a change
    (IL:PUTWINDOWPROP MAINW 'IL:THEORIES-MENU (PROG ((MENU (IL:CREATE IL:MENU)))
                                                    (SET-MENU MENU IL:TITLE "Which theory?")
                                                    (SET-MENU MENU IL:ITEMS (IL:SORT (LIST-ALL-THEORIES MAINW)
                                                                                     #'IL:ALPHORDER))
                                                    (RETURN MENU))))


(DEFUN EDIT-AXIOM (WINDOW)
   [LET [(CHOOSEN-THEORY-NAME (IL:MENU (IL:GETWINDOWPROP WINDOW 'IL:THEORIES-MENU]
        (AND CHOOSEN-THEORY-NAME (LET* ((THEORY (GET-THEORY CHOOSEN-THEORY-NAME WINDOW))
                                        [CHOOSEN-AXIOM (PROG ((MENU (IL:CREATE IL:MENU)))
                                                             (SET-MENU MENU IL:TITLE "Which axiom?")
                                                             [SET-MENU MENU IL:ITEMS (APPEND
                                                                                      (LIST '--NEW--)
                                                                                      (IL:SORT (ALL-PREDS
                                                                                                THEORY]
                                                             (RETURN (IL:MENU MENU]
                                        *AXIOM-TEMPLATE*)
                                       (AND CHOOSEN-AXIOM
                                            (COND
                                               [(EQ CHOOSEN-AXIOM '--NEW--)
                                                (LET* ((PW (IL:GETPROMPTWINDOW WINDOW))
                                                       (NEWNAME (PROGN (IL:CLEARW PW)
                                                                       (PROMPTREAD "Axiom name" PW T)))
                                                       PROC-NAME)
                                                      (PROG NIL
                                                            [SETF *AXIOM-TEMPLATE*
                                                                  (LIST (LIST (LIST 'PREDICATE]
                                                        LP  (IL:SPAWN.MOUSE)
                                                            [SETF *AXIOM-TEMPLATE*
                                                                  (IL:EDITE (IL:COPYALL *AXIOM-TEMPLATE*)
                                                                            NIL
                                                                            (FORMAT NIL "New Predicate: ~A in ~A
                                                                                   theory " NEWNAME
                                                                                   CHOOSEN-THEORY-NAME)
                                                                            NIL NIL (AND
                                                                                     *LOGIC-CLOSE-ON-COMPLETION-FLG*
                                                                                         '(:CLOSE-ON-COMPLETION]
                                                            [PROG ((CLAUSE-NUMBER 1)
                                                                   (AXS *AXIOM-TEMPLATE*))
                                                              LP1 (COND
                                                                     ((NULL AXS)
                                                                      (RETURN))
                                                                     ((NOT (EQ NEWNAME (CAAAR AXS)))
                                                                      (IL:CLEARW PW)
                                                                      (FORMAT PW "Clause number ~D: incorrect
                                                                             predicate name: ~A" CLAUSE-NUMBER
                                                                             (CAAAR AXS))
                                                                      (GO LP))
                                                                     (T (SETF AXS (CDR AXS))
                                                                        (INCF CLAUSE-NUMBER)
                                                                        (GO LP1]
                                                            (SETF (GETHASH NEWNAME THEORY)
                                                                  *AXIOM-TEMPLATE*]
                                                  (T (PROG NIL
                                                           (IL:TTYDISPLAYSTREAM (IL:GETPROMPTWINDOW WINDOW))
                                                           (SETF *AXIOM-TEMPLATE* (GETHASH CHOOSEN-AXIOM THEORY))
                                                       LP  (IL:SPAWN.MOUSE)
                                                           [SETF *AXIOM-TEMPLATE* (IL:EDITE (IL:COPYALL
                                                                                             *AXIOM-TEMPLATE*
                                                                                             )
                                                                                            NIL
                                                                                            (FORMAT NIL "Predicate: ~A
                                                                                                   in ~A theory "
                                                                                                   CHOOSEN-AXIOM
                                                                                                   CHOOSEN-THEORY-NAME
                                                                                                   )
                                                                                            NIL NIL
                                                                                            (AND
                                                                                        *LOGIC-CLOSE-ON-COMPLETION-FLG*
                                                                                                 '(
                                                                                                   :CLOSE-ON-COMPLETION
                                                                                                   ]
                                                           [PROG ((CLAUSE-NUMBER 1)
                                                                  (AXS *AXIOM-TEMPLATE*))
                                                             LP1 (COND
                                                                    ((NULL AXS)
                                                                     (RETURN))
                                                                    ((NOT (EQ CHOOSEN-AXIOM (CAAAR AXS)))
                                                                     (IL:CLEARW (IL:GETPROMPTWINDOW WINDOW))
                                                                     (FORMAT (IL:GETPROMPTWINDOW WINDOW)
                                                                            "Clause number ~D: incorrect predicate
                                                                            name: ~A" CLAUSE-NUMBER (CAAAR AXS))
                                                                     (GO LP))
```

```
                                                        (T (SETF AXS (CDR AXS))
                                                           (INCF CLAUSE-NUMBER)
                                                           (GO LP1]
                                                  (SETF (GETHASH CHOOSEN-AXIOM THEORY)
                                                        *AXIOM-TEMPLATE*])


(DEFUN EDIT-SA (WINDOW)
   [LET* [(CHOOSEN-THEORY-NAME (IL:MENU (IL:GETWINDOWPROP WINDOW 'IL:THEORIES-MENU]
         (AND CHOOSEN-THEORY-NAME (LET* ((THEORY (GET-THEORY CHOOSEN-THEORY-NAME WINDOW))
                                         [CHOOSEN-SA (PROG ((MENU (IL:CREATE IL:MENU)))
                                                           (SET-MENU MENU IL:TITLE "Which sa?")
                                                           [SET-MENU MENU IL:ITEMS (APPEND (LIST '--NEW--)
                                                                                           (IL:SORT (ALL-SAS
                                                                                                    THEORY]
                                                           (RETURN (IL:MENU MENU]
                                         *SA-TEMPLATE*)
                                        (AND CHOOSEN-SA
                                             (COND
                                                [(EQ CHOOSEN-SA '--NEW--)
                                                 (LET* [(PW (IL:GETPROMPTWINDOW WINDOW))
                                                        (NEWNAME (PROGN (IL:CLEARW PW)
                                                                        (PROMPTREAD "SA name" PW T]
                                                       (PROGN (SETF *SA-TEMPLATE* (LIST 'LAMBDA
                                                                                        (LIST 'ARGS)
                                                                                        '<BODY>))
                                                              (IL:SPAWN.MOUSE)
                                                              (SETF *SA-TEMPLATE*
                                                                    (IL:EDITE (IL:COPYALL *SA-TEMPLATE*)
                                                                              NIL
                                                                              (FORMAT NIL "New SA: ~A in ~A theory
" NEWNAME CHOOSEN-THEORY-NAME)))
                                                              (SETF (GETHASH NEWNAME THEORY)
                                                                    (CONS 'SA *SA-TEMPLATE*]
                                                (T (PROGN (IL:TTYDISPLAYSTREAM (IL:GETPROMPTWINDOW WINDOW))
                                                          (SETF *SA-TEMPLATE* (CDR (GETHASH CHOOSEN-SA THEORY)))
                                                          (IL:SPAWN.MOUSE)
                                                          (SETF *SA-TEMPLATE* (IL:EDITE (IL:COPYALL
                                                                                              *SA-TEMPLATE*)
                                                                                        NIL
                                                                                        (FORMAT NIL "SA: ~A in ~A
                                                                                               theory " CHOOSEN-SA
                                                                                               CHOOSEN-THEORY-NAME)
                                                                                        ))
                                                          (SETF (GETHASH CHOOSEN-SA THEORY)
                                                                (CONS 'SA *SA-TEMPLATE*])


(DEFUN GET-LIST-PROP (TI-LIST PROPERTY)
   [PROG (RES)
     LABEL
         (COND
            ((NULL TI-LIST)
             (RETURN RES))
            (T [SETF RES (APPEND RES (LIST (GET-TB-PROPERTY (CAR TI-LIST)
                                                            PROPERTY]
               (SETF TI-LIST (CDR TI-LIST))
               (GO LABEL])


(DEFUN GET-TB-PROPERTY (ITEM PROP)
   (IL:LISTGET (IL:FETCH IL:TIDATA IL:OF ITEM)
          PROP))


(DEFUN GET-THEORY-INTERNAL (THEORY-NAME &OPTIONAL WINDOW)
   [LET* ((TB (IL:GETWINDOWPROP WINDOW 'IL:TABLEBROWSER))
          (ITEMS (IL:FETCH IL:TBITEMS IL:OF TB)))
         (PROG NIL
           LABEL
               (COND
                  ((NULL ITEMS))
                  [(STRING-EQUAL (SYMBOL-NAME (GET-TB-PROPERTY (CAR ITEMS)
                                                               'THEORY-NAME))
                                 (SYMBOL-NAME THEORY-NAME))
                   (RETURN (GET-TB-PROPERTY (CAR ITEMS)
                                            'THEORY]
                  (T (SETF ITEMS (CDR ITEMS))
                     (GO LABEL])


(DEFUN LIST-ALL-THEORIES-INTERNAL (WINDOW)
   (GET-LIST-PROP (IL:TB.COLLECT.ITEMS (IL:GETWINDOWPROP WINDOW 'IL:TABLEBROWSER))
          'THEORY-NAME))


(DEFUN LOAD-DEVEL-THEORY (MAINW &OPTIONAL NAME-OF-THEORY)
```

```
   (LET* [(PW (IL:GETPROMPTWINDOW MAINW))
          [THEORY-NAME (OR NAME-OF-THEORY (PROGN (IL:CLEARW PW)
                                                 (PROMPTREAD "Theory name" PW T]
          [THEORY-FILE-NAME (MERGE-PATHNAMES (MAKE-PATHNAME :NAME THEORY-NAME :TYPE 'LGC]
          (ACTUAL-THEORY (MAKE-HASH-TABLE))
          (TB-ITEM (MY-CREATE-TBRECORD (ACONS 'THEORY ACTUAL-THEORY (ACONS 'THEORY-NAME THEORY-NAME NIL]
         (IL:CLEARW PW)
         (OR (AND (PROBE-FILE THEORY-FILE-NAME)
                  (PROGN [WITH-OPEN-FILE (FILE THEORY-FILE-NAME :DIRECTION :INPUT)
                                 (FORMAT PW "Loading theory ")
                                 (PROG (THEORY-NAME PRED-NUMBER SAS-NUMBER)
                                       (READ FILE)
                                 ;; skip on the theory name
                                       (SETF SAS-NUMBER (READ FILE))
                                       (DO ((SAS SAS-NUMBER (DECF SAS)))
                                           ((EQ SAS 0)
                                            NIL)
                                         (PROGN (FORMAT PW ".")
                                                (SETF (GETHASH (READ FILE)
                                                               ACTUAL-THEORY)
                                                      (READ FILE))))
                                       (SETF PRED-NUMBER (READ FILE))
                                       (DO ((PREDS PRED-NUMBER (DECF PREDS)))
                                           ((= PREDS 0)
                                            NIL)
                                         (PROGN (FORMAT PW ".")
                                                (SETF (GETHASH (READ FILE)
                                                               ACTUAL-THEORY)
                                                      (READ FILE))))]
                           (IL:TB.INSERT.ITEM (IL:GETWINDOWPROP MAINW 'IL:TABLEBROWSER)
                                  TB-ITEM)
                           (IL:CLEARW PW)
                           (FORMAT PW "~%%Theory loaded")
                           T))
             (FORMAT PW "~%%Theory not found"))))

(DEFUN LOGIC-BUTTONFN (WINDOW)
   [COND
      ((IL:LASTMOUSESTATE IL:LEFT)
       T)
      ((IL:LASTMOUSESTATE IL:MIDDLE)
       (CASE (IL:MENU (OR IL:LogicMiddleMenu (PROGN (SETF IL:LogicMiddleMenu (IL:CREATE IL:MENU))
                                                    (SET-MENU IL:LogicMiddleMenu IL:ITEMS
                                                              IL:LogicMiddleMenuCommands)
                                                    (SET-MENU IL:LogicMiddleMenu IL:ITEMWIDTH 60)
                                                    (SET-MENU IL:LogicMiddleMenu IL:ITEMHEIGHT 14)
                                                    IL:LogicMiddleMenu)))
             (Dribble [LET ((PW (IL:GETPROMPTWINDOW WINDOW))
                            (STREAM NIL)
                            (FILENAME NIL))
                       (IL:CLEARW PW)
                       (SETF FILENAME (IL:PROMPTFORWORD "Typescript to file: " NIL NIL PW))
                       (IL:CLEARW PW)
                       (COND
                          ((NULL FILENAME)
                           (CLOSE (IL:GETWINDOWPROP WINDOW 'IL:TYPESCRIPTSTREAM))
                           (IL:CLEARW PW)
                           (IL:PUTWINDOWPROP WINDOW 'IL:TYPESCRIPTSTREAM NIL)
                           (FORMAT PW "File closed"))
                          (T (SETF STREAM (OPEN (MERGE-PATHNAMES (MAKE-PATHNAME :NAME FILENAME :TYPE
                                                                                'TRC))
                                                :DIRECTION :OUTPUT :IF-EXISTS :NEW-VERSION :IF-DOES-NOT-EXIST
                                                :CREATE))
                             (IL:CLEARW PW)
                             (FORMAT PW "~S opened" (NAMESTRING STREAM))
                             (IL:PUTWINDOWPROP WINDOW 'IL:TYPESCRIPTSTREAM STREAM)))])

(DEFUN LOGIC-DEVELOPER ()
   (IN-PACKAGE 'USER)
   (LET* ((LOGIC-WINDOW (IL:CREATEW NIL (FORMAT NIL "Logic ~D -- Horn clauses programming environment"
                                                *LOGIC-RELEASE-NUMBER*)
                                    6 T))                                    ; the main window
          (UNIFY-WINDOW (IL:CREATEW '(10 10 400 400)
                                    "Logic unifier Trace Window" 4 T))
          (SOLVE-WINDOW (IL:CREATEW '(410 10 400 400)
                                    "Logic solver Trace Window" 4 T))
          (REGION (IL:GETWINDOWPROP LOGIC-WINDOW 'IL:REGION))
          (THEORIES-WINDOW (IL:CREATEW (IL:CREATEREGION (- (FIRST REGION)
                                                           120)
                                                        (SECOND REGION)
                                                        120
                                                        (FOURTH REGION))
                                       "Theories window" 4 T))
          [TABLE-BROWSER (IL:TB.MAKE.BROWSER NIL THEORIES-WINDOW '(IL:FONT (HELVETICA 12 BRR)
```

```
                                                                IL:PRINTFN PRINT-TB-ITEMS]
          (LOGIC-CONTROL-MENU (IL:CREATE IL:MENU))
          (PROC (IL:THIS.PROCESS))
          LOGIC-CONTROL-MENU-WINDOW)
         (DECLARE (SPECIAL LOGIC-WINDOW))
         (IL:CLEARW THEORIES-WINDOW)
         (IL:DSPSCROLL 'IL:ON UNIFY-WINDOW)
         (IL:DSPSCROLL 'IL:ON SOLVE-WINDOW)
         (IL:DSPSCROLL 'IL:ON THEORIES-WINDOW)
         (IL:PUTWINDOWPROP UNIFY-WINDOW 'IL:BUTTONEVENTFN 'LOGIC-BUTTONFN)
         (IL:PUTWINDOWPROP SOLVE-WINDOW 'IL:BUTTONEVENTFN 'LOGIC-BUTTONFN)
         (IL:PUTWINDOWPROP LOGIC-WINDOW 'IL:MODE 'IL:FIRST)
         (IL:PUTWINDOWPROP LOGIC-WINDOW 'IL:TRUTH-VALUE-ONLY T)
         (IL:PUTWINDOWPROP LOGIC-WINDOW 'IL:WINDOWENTRYFN 'IL:GIVE.TTY.PROCESS)
         (IL:PUTWINDOWPROP LOGIC-WINDOW 'IL:UNIFY-WINDOW UNIFY-WINDOW)
         (IL:PUTWINDOWPROP LOGIC-WINDOW 'IL:SOLVE-WINDOW SOLVE-WINDOW)
         (IL:PUTWINDOWPROP LOGIC-WINDOW 'IL:TABLEBROWSER TABLE-BROWSER)
         (IL:PUTWINDOWPROP LOGIC-WINDOW 'IL:SOLVE 'NOTRACE)
         (IL:PUTWINDOWPROP LOGIC-WINDOW 'IL:UNIFY 'NOTRACE)
         (SET-MENU LOGIC-CONTROL-MENU IL:TITLE "Control menu")
         (SET-MENU LOGIC-CONTROL-MENU IL:MENUCOLUMNS 1)
         (SET-MENU LOGIC-CONTROL-MENU IL:ITEMS *LOGIC-MENU-ITEMS*)
         (SET-MENU LOGIC-CONTROL-MENU IL:WHENSELECTEDFN #'LOGIC-MENU-FUNCTION)
         (SET-MENU LOGIC-CONTROL-MENU IL:CENTERFLG T)
         (SET-MENU LOGIC-CONTROL-MENU IL:ITEMWIDTH 105)
         (SET-MENU LOGIC-CONTROL-MENU IL:ITEMHEIGHT 14)
         (IL:ATTACHWINDOW (IL:MENUWINDOW LOGIC-CONTROL-MENU)
                LOGIC-WINDOW
                'IL:RIGHT
                'IL:TOP)
         (IL:ATTACHWINDOW THEORIES-WINDOW LOGIC-WINDOW 'IL:LEFT 'IL:TOP)
         (IL:OPENW LOGIC-WINDOW)
         (IL:TTYDISPLAYSTREAM LOGIC-WINDOW)
         (IL:USEREXEC " Logic>" NIL #'START-PROVING)
         (IL:DEL.PROCESS PROC)
         (IL:CLOSEW LOGIC-WINDOW)
         T))

(DEFUN LOGIC-MENU-FUNCTION (ITEM MENU BUTTON)
   [LET [(ACTION (SECOND ITEM))
         (MAINW (IL:MAINWINDOW (IL:WFROMMENU MENU]
        (CASE ACTION
            (EXIT
               (MAPCAR #'IL:CLOSEW (IL:ATTACHEDWINDOWS MAINW))
               (IL:DEL.PROCESS (IL:GETWINDOWPROP MAINW 'IL:PROCESS))
               [AND (STREAMP (IL:GETWINDOWPROP (IL:GETWINDOWPROP MAINW 'IL:SOLVE-WINDOW)
                                 'IL:TYPESCRIPTSTREAM))
                    (CLOSE (IL:GETWINDOWPROP (IL:GETWINDOWPROP MAINW 'IL:SOLVE-WINDOW)
                                 'IL:TYPESCRIPTSTREAM]
               [AND (STREAMP (IL:GETWINDOWPROP (IL:GETWINDOWPROP MAINW 'IL:UNIFY-WINDOW)
                                 'IL:TYPESCRIPTSTREAM))
                    (CLOSE (IL:GETWINDOWPROP (IL:GETWINDOWPROP MAINW 'IL:UNIFY-WINDOW)
                                 'IL:TYPESCRIPTSTREAM]
               (IL:CLOSEW MAINW))
            (TRUTH-VALUE (IL:PUTWINDOWPROP MAINW 'IL:TRUTH-VALUE-ONLY T))
            (ALL-VALUES (IL:PUTWINDOWPROP MAINW 'IL:TRUTH-VALUE-ONLY NIL))
            (LOAD-THEORY
               (LOAD-DEVEL-THEORY MAINW)
               (CREATE-THEORY-MENU MAINW))
            (SAVE-THEORY (SAVE-DEVEL-THEORY MAINW))
            (CREATE-THEORY
               (CREATE-DEVEL-THEORY MAINW)
               (CREATE-THEORY-MENU MAINW))
            (MERGE-THEORIES (MERGE-THEORIES-DEVEL MAINW))
            (EDIT-SA [IL:ADD.PROCESS `(EDIT-SA ,MAINW])
            (EDIT-AXIOM [IL:ADD.PROCESS `(EDIT-AXIOM ,MAINW])
            (NO-SHOW-ENV (IL:PUTWINDOWPROP MAINW 'IL:SEE NIL))
            (DELETE-AXIOM [LET [(CHOOSEN-THEORY-NAME (IL:MENU (IL:GETWINDOWPROP MAINW 'IL:THEORIES-MENU]
                               (AND CHOOSEN-THEORY-NAME
                                    (LET [(CHOOSEN-AXIOM (PROG ((MENU (IL:CREATE IL:MENU)))
                                                               (SET-MENU MENU IL:TITLE "Which axiom?")
                                                               (SET-MENU MENU IL:ITEMS
                                                                      (IL:SORT (ALL-PREDS (GET-THEORY
                                                                                             CHOOSEN-THEORY-NAME
                                                                                                MAINW))
                                                                               #'IL:ALPHORDER))
                                                               (RETURN (IL:MENU MENU]
                                         (AND CHOOSEN-AXIOM (LOGIC-DELETE CHOOSEN-AXIOM CHOOSEN-THEORY-NAME
                                                                   MAINW])
            (DELETE-SA [LET [(CHOOSEN-THEORY-NAME (IL:MENU (IL:GETWINDOWPROP MAINW 'IL:THEORIES-MENU]
                            (AND CHOOSEN-THEORY-NAME
                                 (LET [(CHOOSEN-SA (PROG ((MENU (IL:CREATE IL:MENU)))
                                                         (SET-MENU MENU IL:TITLE "Which SA?")
                                                         (SET-MENU MENU IL:ITEMS (IL:SORT (ALL-SAS (GET-THEORY

                                                                                                CHOOSEN-THEORY-NAME
```

```
                                                                                                MAINW))
                                                                                    #'IL:ALPHORDER))
                                                                (RETURN (IL:MENU MENU]
                                                        (AND CHOOSEN-SA (LOGIC-DELETE CHOOSEN-SA CHOOSEN-THEORY-NAME MAINW])
                (SHOW-AXIOM [LET [(CHOOSEN-THEORY-NAME (IL:MENU (IL:GETWINDOWPROP MAINW 'IL:THEORIES-MENU]
                                 (AND CHOOSEN-THEORY-NAME (PROG [(MENU (IL:CREATE IL:MENU))
                                                                 CHOOSEN-AXIOM
                                                                 (ALL-ITEMS (IL:SORT (ALL-PREDS (GET-THEORY
                                                                                                 CHOOSEN-THEORY-NAME
                                                                                                 MAINW]
                                                                 (IL:SET-MENU MENU IL:TITLE "Which axiom?")
                                                                 (IL:SET-MENU MENU IL:ITEMS ALL-ITEMS)
                                                            JUMP
                                                                 (AND (NULL ALL-ITEMS)
                                                                      (RETURN))
                                                                 (SETF CHOOSEN-AXIOM (IL:MENU MENU))
                                                                 (AND CHOOSEN-AXIOM (PROGN (SHOW-DEFINITION
                                                                                            CHOOSEN-AXIOM
                                                                                            CHOOSEN-THEORY-NAME
                                                                                            MAINW)
                                                                                   (GO JUMP])
                (SHOW-SA [LET [(CHOOSEN-THEORY-NAME (IL:MENU (IL:GETWINDOWPROP MAINW 'IL:THEORIES-MENU]
                               (AND CHOOSEN-THEORY-NAME (PROG [(MENU (IL:CREATE IL:MENU))
                                                               CHOOSEN-SA
                                                               (ALL-ITEMS (IL:SORT (ALL-SAS (GET-THEORY
                                                                                             CHOOSEN-THEORY-NAME
                                                                                             MAINW))
                                                                                           #'IL:ALPHORDER]
                                                               (IL:SET-MENU MENU IL:TITLE "Which SA?")
                                                               (IL:SET-MENU MENU IL:ITEMS ALL-ITEMS)
                                                          JUMP
                                                               (AND (NULL ALL-ITEMS)
                                                                    (RETURN))
                                                               (SETF CHOOSEN-SA (IL:MENU MENU))
                                                               (AND CHOOSEN-SA (PROGN (SHOW-DEFINITION CHOOSEN-SA
                                                                                       CHOOSEN-THEORY-NAME MAINW
                                                                                       )
                                                                                 (GO JUMP])
                (FIRST (IL:PUTWINDOWPROP MAINW 'IL:MODE 'IL:FIRST))
                (SET-MODE (IL:PUTWINDOWPROP MAINW 'IL:MODE 'IL:FIRST))
                (ALL (IL:PUTWINDOWPROP MAINW 'IL:MODE 'IL:ALL))
                (INTERACTIVE (IL:PUTWINDOWPROP MAINW 'IL:MODE 'IL:INTERACTIVE))
                (TRACE-UNIFIER (IL:PUTWINDOWPROP MAINW 'IL:UNIFY 'TRACE))
                (TRACE-SOLVER (IL:PUTWINDOWPROP MAINW 'IL:SOLVE 'TRACE))
                (NOTRACE-SOLVER [PROGN (IL:PUTWINDOWPROP MAINW 'IL:SOLVE 'NOTRACE)
                                       (AND (STREAMP (IL:GETWINDOWPROP (IL:GETWINDOWPROP MAINW 'IL:SOLVE-WINDOW)
                                                                       'IL:TYPESCRIPTSTREAM))
                                            (CLOSE (IL:GETWINDOWPROP (IL:GETWINDOWPROP MAINW 'IL:SOLVE-WINDOW)
                                                                     'IL:TYPESCRIPTSTREAM])
                (NOTRACE-UNIFIER [PROGN (IL:PUTWINDOWPROP MAINW 'IL:UNIFY 'NOTRACE)
                                        (AND (STREAMP (IL:GETWINDOWPROP (IL:GETWINDOWPROP MAINW 'IL:UNIFY-WINDOW)
                                                                        'IL:TYPESCRIPTSTREAM))
                                             (CLOSE (IL:GETWINDOWPROP (IL:GETWINDOWPROP MAINW 'IL:UNIFY-WINDOW)
                                                                      'IL:TYPESCRIPTSTREAM])
                (DELETE-THEORY [LET [(TB (IL:GETWINDOWPROP MAINW 'IL:TABLEBROWSER]
                                    (DO ((ITEMS (IL:TB.COLLECT.ITEMS TB 'IL:SELECTED)
                                                (CDR ITEMS)))
                                        ((NULL ITEMS))
                                      (IL:TB.DELETE.ITEM TB (CAR ITEMS)))])
                (UNDELETE [LET [(TB (IL:GETWINDOWPROP MAINW 'IL:TABLEBROWSER]
                               (DO ((ITEMS (IL:TB.COLLECT.ITEMS TB 'IL:SELECTED)
                                           (CDR ITEMS)))
                                   ((NULL ITEMS))
                                 (IL:TB.UNDELETE.ITEM TB (CAR ITEMS)))])
                (EXPUNGE (LET [(TB (IL:GETWINDOWPROP MAINW 'IL:TABLEBROWSER]
                              (DO ((ITEMS (IL:TB.COLLECT.ITEMS TB 'IL:DELETED)
                                          (CDR ITEMS)))
                                  ((NULL ITEMS))
                                (IL:TB.REMOVE.ITEM TB (CAR ITEMS)))
                              (CREATE-THEORY-MENU MAINW)))
                (ERASE (LET [(TB (IL:GETWINDOWPROP MAINW 'IL:TABLEBROWSER]
                            (DO ((ITEMS (IL:TB.COLLECT.ITEMS TB)
                                        (CDR ITEMS)))
                                ((NULL ITEMS))
                              (IL:TB.REMOVE.ITEM TB (CAR ITEMS)))
                            (CREATE-THEORY-MENU MAINW)))
                (SHOW-PROFILE (SHOW-PROFILE MAINW)))])

(DEFUN MERGE-THEORIES-DEVEL (MAINW &OPTIONAL NEW-THEORY LIST-OF-THEORIES)
   [LET* [(PW (IL:GETPROMPTWINDOW MAINW))
          (THEORY-NAME (OR NEW-THEORY (PROGN (IL:CLEARW PW)
                                             (PROMPTREAD "New theory name" PW T]
         (AND THEORY-NAME (LET* [(ACTUAL-THEORY (MAKE-HASH-TABLE))
                                 [TB-ITEM (MY-CREATE-TBRECORD (ACONS 'THEORY ACTUAL-THEORY (ACONS
                                                                                            'THEORY-NAME
                                                                                            THEORY-NAME
```

```
                                                                                                NIL]
                                    [SELECTED-THEORIES (OR LIST-OF-THEORIES (IL:TB.COLLECT.ITEMS
                                                                              (IL:GETWINDOWPROP MAINW
                                                                                    'IL:TABLEBROWSER)
                                                                              'IL:SELECTED]
                                    (SELECTED-THEORY-NAMES (OR LIST-OF-THEORIES
                                                               (DO ((THS SELECTED-THEORIES (CDR THS))
                                                                    (RESULT NIL))
                                                                   ((NULL THS)
                                                                    RESULT)
                                                                 [SETQ RESULT (APPEND RESULT
                                                                                      (LIST (GET-TB-PROPERTY
                                                                                             (CAR THS)
                                                                                             'THEORY-NAME])]
                                   (IL:CLEARW PW)
                                   (IL:TB.INSERT.ITEM (IL:GETWINDOWPROP MAINW 'IL:TABLEBROWSER)
                                         TB-ITEM)
                                   (IL:CLEARW PW)
                                   (MERGE-INTERNAL THEORY-NAME SELECTED-THEORY-NAMES MAINW)
                                   (CREATE-THEORY-MENU MAINW)
                                   (FORMAT PW "Theories merged"])

(DEFUN MY-CREATE-TBRECORD (ALIST)
   [PROG ((ELTS ALIST)
          (TI (IL:CREATE IL:TABLEITEM)))
     LABEL
         (COND
            ((NULL ELTS)
             (RETURN TI))
            (T (LET* ((PAIR (CAR ELTS))
                      (PROP (CAR PAIR))
                      (VALUE (CDR PAIR)))
                     (CASE PROP
                         (SELECTED (SET-MENU TI IL:TISELECTED VALUE))
                         (DELETED (SET-MENU TI IL:TIDELETED VALUE))
                         (UNDELETABLE (SET-MENU TI IL:TIUNDELETABLE VALUE))
                         (UNSELECTABLE (SET-MENU TI IL:TIUNSELECTABLE VALUE))
                         (DATA (SET-MENU TI IL:TIDATA VALUE))
                         (T (SET-MENU TI IL:TIDATA (APPEND (IL:FETCH IL:TIDATA IL:OF TI)
                                                           (LIST PROP VALUE)))))
                     (SETF ELTS (CDR ELTS))
                     (GO LABEL]))

(DEFUN PRINT-TB-ITEMS (BROWSER ITEM WINDOW)
   (IL:DSPXPOSITION 10 WINDOW)
   (SETF *PRINT-PRETTY* NIL)
   (FORMAT WINDOW "~S~%" (GET-TB-PROPERTY ITEM 'THEORY-NAME))
   (SETF *PRINT-PRETTY* T))

(DEFUN PROMPTREAD (PROMPTSTRING WINDOW SAMELINE?)
   (PROG [NEWVALUE (MAINWINDOW (IL:WINDOWPROP WINDOW 'IL:MAINWINDOW]
         (IL:RESETLST
             (IL:RESETSAVE (IL:TTYDISPLAYSTREAM (OR WINDOW IL:PROMPTWINDOW)))
             (IL:RESETSAVE (IL:TTY.PROCESS (IL:THIS.PROCESS)))
             (IL:CLRPROMPT)
             (IL:RESETSAVE (IL:PRINTLEVEL 4 3))
             (FORMAT T "~A: " PROMPTSTRING)
             (IL:CLEARBUF T T)                                  ; clear tty buffer because it sometimes has stuff left.
             (IL:ALLOW.BUTTON.EVENTS)
             (UNWIND-PROTECT
                 [SETF NEWVALUE (CAR (IL:ERSETQ (IL:TTYINREAD T T]))
         (RETURN NEWVALUE)))

(DEFUN SAVE-DEVEL-THEORY (MAINWINDOW)
   [LET [(PW (OR (CAR (IL:GETWINDOWPROP MAINWINDOW 'IL:PROMPTWINDOW))
                 (IL:GETPROMPTWINDOW MAINWINDOW]
        (DO ((TI-SELECTED (PROGN (IL:CLEARW PW)
                                 (IL:TB.COLLECT.ITEMS (IL:GETWINDOWPROP MAINWINDOW 'IL:TABLEBROWSER)
                                                      'IL:SELECTED))
                          (CDR TI-SELECTED)))
            ((NULL TI-SELECTED)
             (FORMAT PW "done"))
          [PROG [(THEORY-NAME (GET-TB-PROPERTY (CAR TI-SELECTED)
                                               'THEORY-NAME))
                 (THEORY (GET-TB-PROPERTY (CAR TI-SELECTED)
                                          'THEORY]
                (WITH-OPEN-FILE (FILE (MERGE-PATHNAMES (MAKE-PATHNAME :NAME THEORY-NAME :TYPE 'LGC))
                                      :DIRECTION :OUTPUT :IF-EXISTS :NEW-VERSION :IF-DOES-NOT-EXIST :CREATE)
                       (LET [(PREDS (IL:SORT (ALL-PREDS THEORY)))
                             (SAS (IL:SORT (ALL-SAS THEORY]
                            (PROGN (IL:CLEARW PW)
                                   (FORMAT PW "Saving ~A" THEORY-NAME)
                                   (FORMAT FILE "~S~%" THEORY-NAME)
```

```
                                    (FORMAT FILE "~D~%" (LENGTH SAS))
                                    (DO ((SA-NAME SAS (CDR SA-NAME)))
                                        ((NULL SA-NAME)
                                         NIL)
                                       (PROGN (FORMAT PW ".")
                                              (FORMAT FILE "~S ~S ~%" (CAR SA-NAME)
                                                     (GETHASH (CAR SA-NAME)
                                                            THEORY))))
                                    (FORMAT FILE "~D~%" (LENGTH PREDS))
                                    (DO ((PRED-NAME PREDS (CDR PRED-NAME)))
                                        ((NULL PRED-NAME)
                                         NIL)
                                       (PROGN (FORMAT PW ".")
                                              (FORMAT FILE "~S ~S ~%" (CAR PRED-NAME)
                                                     (GETHASH (CAR PRED-NAME)
                                                            THEORY))))]))]

(DEFUN SHOW-PROFILE (WINDOW)
   [LET ((PW (IL:GETPROMPTWINDOW WINDOW)))
        (IL:CLEARW PW)
        (FORMAT PW "~%Mode: ~A /Unifier: ~A /Solver: ~A /Values: ~A" (IL:GETWINDOWPROP WINDOW 'IL:MODE)
               (IL:GETWINDOWPROP WINDOW 'IL:UNIFY)
               (IL:GETWINDOWPROP WINDOW 'IL:SOLVE)
               (NOT (IL:GETWINDOWPROP WINDOW 'IL:TRUTH-VALUE-ONLY])

(DEFUN SOLVE-DEBUGGER (TREE FORMULA CLAUSES WINDOW)
   [COND
      ((TRACINGP WINDOW 'SOLVE)
       ;; This is the part for debugging:  the main features of the language are shown to the user  in specified windows
       (FORMAT (IL:GETWINDOWPROP WINDOW 'IL:SOLVE-WINDOW)
              "Formula is ~A,~%clauses are ~A,~%conjs are ~A~%~%" FORMULA CLAUSES (CONJ (AND-LEVEL TREE)))
       (AND (DRIBBLEP WINDOW 'SOLVE)
            (FORMAT (IL:GETWINDOWPROP (IL:GETWINDOWPROP WINDOW 'IL:SOLVE-WINDOW)
                           'IL:TYPESCRIPTSTREAM)
                   "Formula is ~A,~%clauses are ~A,~%conjs are ~A~%~%" FORMULA CLAUSES (CONJ (AND-LEVEL
                                                                                              TREE])

(DEFUN START-PROVING (CONJS LINE)
   (IN-PACKAGE 'USER)
   [LET* ((*VARIABLES-COUNTER* 0)
          (SELECTED-TIS (IL:TB.COLLECT.ITEMS (IL:GETWINDOWPROP LOGIC-WINDOW 'IL:TABLEBROWSER)
                               'IL:SELECTED))
          [THEORIES (APPEND (LIST '*BACKGROUND-THEORY*)
                            (GET-LIST-PROP SELECTED-TIS 'THEORY-NAME]
          (TREE (MAKE-TREE (MAKE-AND-NODE CONJS NIL THEORIES)
                           NIL))
          (TRUTH-VALUE-ONLY (IL:GETWINDOWPROP LOGIC-WINDOW 'IL:TRUTH-VALUE-ONLY))
          RESULT NEXT-OR)
         (DECLARE (SPECIAL *VARIABLES-COUNTER*))
         (PROG NIL
           JUMP
               (SETF RESULT (LOGIC-PROVE TREE LOGIC-WINDOW))
               (COND
                  ((NULL RESULT)                                    ; The proof is failed

                   )
                  (T (CASE (IL:GETWINDOWPROP LOGIC-WINDOW 'IL:MODE)
                           (IL:FIRST [OR (AND TRUTH-VALUE-ONLY (PROGN (FORMAT T "~A~%" T)
                                                                      T))
                                         (FORMAT T "~S~%" (LOOKUP CONJS (UNIFICATION-ENV (AND-LEVEL RESULT])
                           (IL:ALL
                              (OR (AND TRUTH-VALUE-ONLY (PROGN (FORMAT T "~A~%" T)
                                                               T))
                                       (PROGN [FORMAT T "~S~%" (LOOKUP CONJS (UNIFICATION-ENV (AND-LEVEL RESULT]
                                              T))
                              (SETF NEXT-OR (FIRST (OR-LEVELS RESULT)))
                              (SETF TREE (SOLVE (NEW-TREE RESULT NEXT-OR)
                                                (FORMULA-OR NEXT-OR)
                                                (CLAUSES-OR NEXT-OR)))
                              (GO JUMP))
                           (IL:INTERACTIVE
                              (OR (AND TRUTH-VALUE-ONLY (PROGN (FORMAT T "~A~%" T)
                                                               T))
                                       (PROGN [FORMAT T "~S~%" (LOOKUP CONJS (UNIFICATION-ENV (AND-LEVEL RESULT]
                                              T))
                              (FORMAT T "More? ")
                              (AND (Y-OR-N-P)
                                   (PROGN (SETF NEXT-OR (FIRST (OR-LEVELS RESULT)))
                                          (SETF TREE (SOLVE (NEW-TREE RESULT NEXT-OR)
                                                            (FORMULA-OR NEXT-OR)
                                                            (CLAUSES-OR NEXT-OR)))
                                          (GO JUMP)))))]
   T)
```

```
(DEFUN UNIFY-DEBUGGER (PATT DAT ENV WINDOW)
   ;; This part is devoted to debugging, on the window and on the file
   (LET* [(TRACE-WINDOW (IL:GETWINDOWPROP WINDOW 'IL:UNIFY-WINDOW))
          (DRIBBLE? (DRIBBLEP WINDOW 'UNIFY))
          (STREAM (AND DRIBBLE? (IL:GETWINDOWPROP TRACE-WINDOW 'IL:TYPESCRIPTSTREAM]
         (FORMAT TRACE-WINDOW "~%%Unifying ~A ~%%with ~A~%%in ~A~%%" PATT DAT ENV)
         (AND DRIBBLE? (FORMAT STREAM "~%%Unifying ~A ~%%with ~A~%%in ~A~%% " PATT DAT ENV))))

(IL:ADDTOVAR IL:BackgroundMenuCommands ("Logic" '(IL:ADD.PROCESS '(LOGIC-DEVELOPER))
                                        "Open a window on logic programming environment"))

(IL:RPAQQ *LOGIC-MENU-ITEMS*
          (("Show profile" SHOW-PROFILE "Show the profile on env")
           ("Truth value only" TRUTH-VALUE "The proof returns only T or NIL" (IL:SUBITEMS ("All values "
                                                                                            ALL-VALUES
                                                                                            "Returns the
                                                                                            goal with all
                                                                                            the variables")
                                                                                    ))
           ("Show(Axiom)" SHOW-AXIOM "Shows definition of an axiom" (IL:SUBITEMS ("Show SA" SHOW-SA "Shows
                                                                                  definition of a semantic
                                                                                  attachment")))
           ("Edit(Axiom)" EDIT-AXIOM "Edits the specified axiom" (IL:SUBITEMS ("Edit SA" EDIT-SA "Edits the
                                                                               specified SA")))
           ("Delete(Axiom)" DELETE-AXIOM "Deletes the specified axiom" (IL:SUBITEMS ("Delete SA" DELETE-SA
                                                                                     "Deletes the
                                                                                     specified semantic
                                                                                     attachment")))
           ("Set Mode(First)" SET-MODE "Set mode of demonstration" (IL:SUBITEMS ("First" FIRST "Stops at first
                                                                                 solution reached")
                                                                               ("All" ALL "Finds out all solutions")
                                                                               ("Interactive" INTERACTIVE "Ask user
                                                                                 to continue")))
           ("Trace unifier" TRACE-UNIFIER "Trace the unifier" (IL:SUBITEMS ("No trace" NOTRACE-UNIFIER "Do not
                                                                            trace unifier")))
           ("Trace solver" TRACE-SOLVER "Trace the solver" (IL:SUBITEMS ("No trace" NOTRACE-SOLVER "Do not trace
                                                                         solver")))
           ("Create theory" CREATE-THEORY "Creates new theory")
           ("Delete theory" DELETE-THEORY "Deletes the labelled theories" (IL:SUBITEMS ("Expunge deleted
                                                                                        theories" EXPUNGE
                                                                                              "Expunged deleted
                                                                                              theories")
                                                                                      ("Undelete theories" UNDELETE
                                                                                              "Undelete theories")))
           ("Merge theories" MERGE-THEORIES "Merges the selected theories")
           ("Load theory" LOAD-THEORY "Prompts user for theory to load")
           ("Save theory" SAVE-THEORY "Saves selected theories")
           ("Erase env" ERASE "Erases all the environment")
           ("Exit" EXIT "Closes development window")))

(IL:RPAQQ *LOGIC-RELEASE-NUMBER* "1.3")

(IL:RPAQQ *LOGIC-CLOSE-ON-COMPLETION-FLG* T)

(IL:RPAQQ IL:BackgroundMenu NIL)

(IL:RPAQQ IL:LogicMiddleMenu NIL)

(IL:RPAQQ IL:LogicMiddleMenuCommands ((DRIBBLE 'Dribble "Dribbles on file")))

(IL:FILESLOAD IL:TABLEBROWSER)

(IL:DECLARE%: IL:EVAL@COMPILE

(IL:DATATYPE IL:TABLEBROWSER ((IL:TBREADY IL:FLAG)
                              (NIL 7 IL:FLAG)
                              (IL:TBITEMS IL:POINTER)
                              (IL:TB#ITEMS IL:WORD)
                              (IL:TB#DELETED IL:WORD)
                              (IL:TB#LINESPERITEM IL:WORD)
                              (IL:TBFIRSTSELECTEDITEM IL:WORD)
                              (IL:TBLASTSELECTEDITEM IL:WORD)
                              (NIL IL:WORD)
                              (IL:TBMAXXPOS IL:WORD)
                              (IL:TBFONTHEIGHT IL:WORD)
                              (IL:TBFONTASCENT IL:WORD)
                              (IL:TBFONTDESCENT IL:WORD)
                              (IL:TBWINDOW IL:POINTER)
                              (IL:TBLOCK IL:POINTER)
                              (IL:TBUSERDATA IL:POINTER)
                              (IL:TBFONT IL:POINTER)
                              (IL:TBEXTENT IL:POINTER)
                              (IL:TBUPDATEFROMHERE IL:POINTER)
                              (IL:TBCOLUMNS IL:POINTER)
```

```
                                (IL:TBPRINTFN IL:POINTER)
                                (IL:TBCOPYFN IL:POINTER)
                                (IL:TBFONTCHANGEFN IL:POINTER)
                                (IL:TBCLOSEFN IL:POINTER)
                                (IL:TBAFTERCLOSEFN IL:POINTER)
                                (IL:TBTITLEEVENTFN IL:POINTER)
                                (IL:TBAFTEREXPUNGEFN IL:POINTER)
                                (IL:TBORIGIN IL:POINTER)
                                (NIL IL:POINTER)
                                (NIL IL:POINTER)
                                (NIL IL:POINTER)))

(IL:DATATYPE IL:TABLEITEM ((IL:TISELECTED IL:FLAG)
                           (IL:TIDELETED IL:FLAG)
                           (IL:TIUNDELETABLE IL:FLAG)
                           (IL:TIUNSELECTABLE IL:FLAG)
                           (IL:TIUNCOPYSELECTABLE IL:FLAG)
                           (NIL 3 IL:FLAG)
                           (IL:TIDATA IL:POINTER)
                           (IL:TI# IL:WORD)
                           (NIL IL:WORD)))
)

(IL:/DECLAREDATATYPE 'IL:TABLEBROWSER
       '(IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:POINTER IL:WORD IL:WORD IL:WORD
                IL:WORD IL:WORD IL:WORD IL:WORD IL:WORD IL:WORD IL:WORD IL:POINTER IL:POINTER IL:POINTER
                IL:POINTER IL:POINTER IL:POINTER IL:POINTER IL:POINTER IL:POINTER IL:POINTER IL:POINTER
                IL:POINTER IL:POINTER IL:POINTER IL:POINTER IL:POINTER IL:POINTER IL:POINTER)
       ;; ---field descriptor list elided by lister---
       '48)

(IL:/DECLAREDATATYPE 'IL:TABLEITEM '(IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:FLAG IL:POINTER
                                     IL:WORD IL:WORD)
       ;; ---field descriptor list elided by lister---
       '4)

(IL:DECLARE%: IL:EVAL@COMPILE

(IL:RPAQQ IL:TB.LEFT.MARGIN 8)

(IL:CONSTANTS IL:TB.LEFT.MARGIN)
)

(IL:PUTPROPS IL:LOGIC-DEVEL IL:COPYRIGHT ("ROBERTO GHISLANZONI" 1987 1988))
```

FUNCTION INDEX

VARIABLE INDEX

MACRO INDEX

RECORD INDEX

CONSTANT INDEX