```
18-May-90 01:15:40 {DSK}<usr>local>lde>lispcore>sources>XCL-EXTRAS.;2
 File created:
  changes to:
               (IL: VARS IL: XCL-EXTRASCOMS)
previous date:
               11-Jan-88 16:59:17 {DSK}<usr>local>lde>lispcore>sources>XCL-EXTRAS.;1
 Read Table:
               XCL
    Package:
               XEROX-COMMON-LISP
      Format:
                XCCS
; Copyright (c) 1987, 1988, 1990 by Venue & Xerox Corporation. All rights reserved.
(IL:RPAQQ IL:XCL-EXTRASCOMS
           :: Finess the define-file-info problem
            (IL:DEFINE-TYPES FILE-ENVIRONMENTS)
            (IL:FUNCTIONS DEFINE-FILE-ENVIRONMENT)
            ;; Macro for writing macros
            (IL:FUNCTIONS ONCE-ONLY)
            ;; CL veneer on IL record module
            (IL:FUNCTIONS RECORD-FETCH SETF-FETCH RECORD-FFETCH SETF-FFETCH RECORD-CREATE)
            (IL:SETFS RECORD-FETCH RECORD-FFETCH)
            :: An alternate version of the above
            (IL:FUNCTIONS DEFINE-RECORD)
            (IL:FUNCTIONS RECORD-ACCESS-MACRO SETF-RECORD-ACCESS-MACRO RECORD-PREDICATE-MACRO
                   RECORD-CONSTRUCTOR-MACRO)
            (IL:PROP (IL:FILETYPE IL:MAKEFILE-ENVIRONMENT)
                    IL:XCL-EXTRAS)))
;; Finess the define-file-info problem
(DEF-DEFINE-TYPE FILE-ENVIRONMENTS "File info")
(DEFDEFINER DEFINE-FILE-ENVIRONMENT FILE-ENVIRONMENTS (FILE &KEY READTABLE PACKAGE BASE COMPILER)
   (LET ((ROOTNAME (INTERN (STRING FILE)
                             (FIND-PACKAGE "INTERLISP")))))
         '(EVAL-WHEN (EVAL LOAD)
                 ,@(IF (OR READTABLE PACKAGE BASE)
                         ((SETF (GET ', ROOTNAME 'IL: MAKEFILE-ENVIRONMENT)
                                  (,@(IF READTABLE
                                          `(:READTABLE ,READTABLE))
                                   ,@(IF PACKAGE
                                          `(:PACKAGE , PACKAGE))
                                   ,@(IF BASE
                                          `(:BASE ,BASE))))))
                 ,@(IF COMPILER
                         ((SETF (GET ', ROOTNAME 'IL:FILETYPE)
                                  ,COMPILER))))))
;; Macro for writing macros
(DEFMACRO ONCE-ONLY (VARS &BODY BODY)
  ONCE-ONLY assures that the forms given as vars are evaluated in the proper order, once only. Used in the body of macro definitions. Taken from
::: Zeta Lisp.
   (LET* ((GENSYM-VAR (GENSYM))
           (RUN-TIME-VARS (GENSYM))
           (RUN-TIME-VALS (GENSYM))
           (EXPAND-TIME-VAL-FORMS (MAPCAR #'(LAMBDA (VAR)
                                                        (IF (OR (SYMBOLP , VAR)
                                                                 (CONSTANTP , VAR))
                                                             .VAR
                                                                  ((,GENSYM-VAR (GENSYM)))
(PUSH ,GENSYM-VAR ,RUN-TIME-VARS)
                                                             (LET
                                                                  (PUSH , VAR , RUN-TIME-VALS)
                                                                  ,GENSYM-VAR)))
                                            VARS)))
          '(,'LET* (,RUN-TIME-VARS ,RUN-TIME-VALS (WRAPPED-BODY (,'LET
                                                                      , (WITH-COLLECTION
                                                                         (DO ((VAR VARS (CDR VAR))
                                                                              (EXPAND-TIME-VAL-FORM
                                                                                      EXPAND-TIME-VAL-FORMS (CDR
                                                                                                      EXPAND-TIME-VAL-FORM
                                                                             ((NULL VAR))
                                                                            (COLLECT (LIST (CAR VAR)
                                                                                            (CAR EXPAND-TIME-VAL-FORM)))
))
                                                                      ,@BODY)))
```

```
'(,'LET , (WITH-COLLECTION (DO ((RUN-TIME-VAR (REVERSE , RUN-TIME-VARS)
                                                         (CDR RUN-TIME-VAR))
                                                  (RUN-TIME-VAL (REVERSE , RUN-TIME-VALS)
                                                         (CDR RUN-TIME-VAL)))
                                                 ((NULL RUN-TIME-VAR))
                                               (COLLECT (LIST (CAR RUN-TIME-VAR)
                                                              (CAR RUN-TIME-VAL)))))
                          ,WRAPPED-BODY))))
;; CL veneer on IL record module
(DEFMACRO {f RECORD\text{-}FETCH} (RECORD FIELD OBJECT)
   (LET ((IL-RECORD (INTERN (STRING RECORD)
                           IL:*INTERLISP-PACKAGE*))
         (IL-FIELD (INTERN (STRING FIELD)
                          IL:*INTERLISP-PACKAGE*)))
        `(IL:|fetch| (,IL-RECORD ,IL-FIELD) |L:|of| ,OBJECT)))
(DEFMACRO SETF-FETCH (RECORD FIELD OBJECT NEW-VALUE)
   (LET ((IL-RECORD (INTERN (STRING RECORD)
                           IL: *INTERLISP-PACKAGE*))
         (IL-FIELD (INTERN (STRING FIELD)
                          IL:*INTERLISP-PACKAGE*)))
        `(IL:|replace| (, IL-RECORD , IL-FIELD) | IL:|of| , OBJECT | IL:|with| , NEW-VALUE)))
(DEFMACRO RECORD-FFETCH (RECORD FIELD OBJECT)
   (LET ((IL-RECORD (INTERN (STRING RECORD)
                           IL:*INTERLISP-PACKAGE*))
         (IL-FIELD (INTERN (STRING FIELD)
                          IL:*INTERLISP-PACKAGE*)))
        `(IL:|ffetch| (,IL-RECORD ,IL-FIELD) | IL:|of| ,OBJECT)))
(DEFMACRO SETF-FFETCH (RECORD FIELD OBJECT NEW-VALUE)
   (IL-FIELD (INTERN (STRING FIELD)
                          IL:*INTERLISP-PACKAGE*)))
        `(IL:|freplace| (,IL-RECORD ,IL-FIELD) | IL:|of| ,OBJECT | IL:|with| ,NEW-VALUE)))
(DEFMACRO RECORD-CREATE (RECORD & REST KEYWORD-PAIRS)
   (LET ((IL-RECORD (INTERN (STRING RECORD)
                           IL:*INTERLISP-PACKAGE*)))
        '(IL:|create| ,IL-RECORD ,@(WITH-COLLECTION (DO ((KEYWORD KEYWORD-PAIRS (CDDR KEYWORD))
                                                       (VALUE (CDR KEYWORD-PAIRS)
                                                               (CDDR VALUE))
                                                       KEYWORD-SYMBOL)
                                                       ((NULL KEYWORD))
                                                     (SETQ KEYWORD-SYMBOL (INTERN (STRING (CAR KEYWORD))
                                                                                 IL:*INTERLISP-PACKAGE*))
                                                     (COLLECT KEYWORD-SYMBOL)
                                                     (IF (NOT (MEMBER KEYWORD-SYMBOL '(IL:USING IL:COPYING
                                                                                          IL:REUSING IL:SMASHING)
                                                                     #'EO))
                                                         (COLLECT 'IL:_))
                                                     (COLLECT (CAR VALUE)))))))
(DEFSETF RECORD-FETCH SETF-FETCH)
(DEFSETF RECORD-FFETCH SETF-FFETCH)
;; An alternate version of the above
(DEFDEFINER DEFINE-RECORD IL:STRUCTURES (RECORD-NAME INTERLISP-RECORD-NAME &KEY (CONC-NAME NIL CONC-NAME-P)
                                                     (CONSTRUCTOR NIL CONSTRUCTOR-P)
                                                     (PREDICATE NIL PREDICATE-P)
                                                     (FAST-ACCESSORS NIL)
                                                     (PACKAGE *PACKAGE*))
   (IF (NOT (PACKAGEP PACKAGE))
       (SETQ PACKAGE (FIND-PACKAGE PACKAGE)))
   (SETO CONC-NAME (IF CONC-NAME-P
                        (IF CONC-NAME
                            (STRING CONC-NAME)
                        (CONCATENATE 'STRING (STRING RECORD-NAME)
                               "-")))
   (LET
    ((DECLARATION (IL: RECLOOK INTERLISP-RECORD-NAME))
     (FIELD-NAMES (IL:RECORDFIELDNAMES INTERLISP-RECORD-NAME)))
```

```
(IF (NULL DECLARATION)
    (ERROR "Record ~s not yet defined." INTERLISP-RECORD-NAME))
'(EVAL-WHEN (COMPILE LOAD EVAL)
             ,@(MAPCAN #'(LAMBDA (FIELD-NAME)
                                  (WHEN FIELD-NAME
                                       (LET ((NEW-NAME (INTERN (CONCATENATE 'STRING CONC-NAME (STRING FIELD-NAME))
                                                               PACKAGE)))
                                            '((SETF (MACRO-FUNCTION ', NEW-NAME)
                                                    'RECORD-ACCESS-MACRO)
                                              (CL::SET-SHARED-SETF-INVERSE ', NEW-NAME 'SETF-RECORD-ACCESS-MACRO)
                                              (SETF (GET ', NEW-NAME :SLOT-INFO)
                                                      , '((, INTERLISP-RECORD-NAME , FIELD-NAME)
                                                         ,FAST-ACCESSORS))))))
                      FIELD-NAMES)
             ,@(LET ((NEW-NAME (IF PREDICATE-P
                                     PREDICATE
                                     (INTERN (CONCATENATE 'STRING (STRING RECORD-NAME)
                                                      "-P")
                                             PACKAGE))))
                     (WHEN (AND NEW-NAME (OR (EQ (CAR DECLARATION) 'IL:DATATYPE)
                                               (FIND-IF #'(LAMBDA (CLAUSE)
                                                                   (AND (CONSP CLAUSE)
                                                                         (OR (EQ (CAR CLAUSE)
'IL:TYPE?)
                                                                              (EQ (CAR CLAUSE)
'IL: |type?|))))
                                                       DECLARATION)))
                         '((SETF (MACRO-FUNCTION ', NEW-NAME)
                                  'RECORD-PREDICATE-MACRO)
                           (SETF (GET ', NEW-NAME : TYPE-INFO)
                                   ,INTERLISP-RECORD-NAME))))
             ,@(LET ((NEW-NAME (IF CONSTRUCTOR-P
                                     CONSTRUCTOR
                                     (INTERN (CONCATENATE 'STRING "MAKE-" (STRING RECORD-NAME))
                                             PACKAGE))))
                     (WHEN (AND NEW-NAME (OR (NOT (MEMBER (CAR DECLARATION)
                                                             '(IL:BLOCKRECORD IL:ACCESSFNS IL:ATOMRECORD)
                                                             :TEST
                                                             #'EO))
                                               (FIND-IF #'(LAMBDA (CLAUSE)
                                                                   (IF (CONSP CLAUSE)
                                                                        (OR (EQ (CAR CLAUSE)
                                                                                  IL: CREATE)
                                                                            (EQ (CAR CLAUSE)
'IL: create))
                                                                        (EQ CLAUSE INTERLISP-RECORD-NAME)))
                                                       (CDDR DECLARATION))))
                         '((SETF (MACRO-FUNCTION ', NEW-NAME)
                                   RECORD-CONSTRUCTOR-MACRO)
                                  (GET ', NEW-NAME :FIELD-INFO)
                           (SETF
                                   (,INTERLISP-RECORD-NAME ,FIELD-NAMES))))))))
(DEFUN RECORD-ACCESS-MACRO (FORM &OPTIONAL ENV)
   (DECLARE (IGNORE ENV))
   (DESTRUCTURING-BIND (SPECIFIER FAST-ACCESSOR-P)
           (OR (GET (CAR FORM)
                    :SLOT-INFO)
               (ERROR "No slot information cached."))
           (IF FAST-ACCESSOR-P
                '(|L:|ffetch| , SPECIFIER |L:|of| , (SECOND FORM))
               `(IL:|fetch| ,SPECIFIER IL:|of| ,(SECOND FORM)))))
(CL::DEFINE-SHARED-SETF-MACRO SETF-RECORD-ACCESS-MACRO ACCESSOR (DATUM) (NEW-VALUE)
   (DESTRUCTURING-BIND (SPECIFIER FAST-ACCESSOR-P)
           (OR (GET ACCESSOR :SLOT-INFO)
               (ERROR "No slot information cached."))
           (IF FAST-ACCESSOR-P
               `(IL:|freplace| ,SPECIFIER | IL:|of| ,DATUM | IL:|with| ,NEW-VALUE)
`(IL:|replace| ,SPECIFIER | IL:|of| ,DATUM | IL:|with| ,NEW-VALUE))))
(DEFUN RECORD-PREDICATE-MACRO (FORM &OPTIONAL ENV)
   (DECLARE (IGNORE ENV))
'(IL:|type?| , (OR (GET (CAR FORM)
                         :TYPE-INFO)
                    (ERROR "No type information cached."))
            , (SECOND FORM)))
(DEFUN RECORD-CONSTRUCTOR-MACRO (FORM &OPTIONAL ENV)
   (DECLARE (IGNORE ENV))
   (DESTRUCTURING-BIND (TYPE FIELD-NAMES)
           (OR (GET (CAR FORM)
                    :FIELD-INFO)
```

```
(ERROR "No field information cached.")) `(IL:|create| , TYPE ,@(WITH-COLLECTION (DO* ((KEYWORD (CDR FORM)
                                                                 (CDDR KEYWORD))
                                                          (KEYWORD-SYMBOL (CAR KEYWORD)
                                                                 (CAR KEYWORD))
                                                          (VALUE (CADR KEYWORD)
                                                                 (CADR KEYWORD))
                                                         RESERVED-WORD)
                                                        ((NULL KEYWORD))
                                                      (SETQ RESERVED-WORD (CAR (MEMBER KEYWORD-SYMBOL
                                                                                          ' (IL:USING IL:COPYING
                                                                                              IL:REUSING IL:SMASHING)
                                                                                          :TEST
                                                                                          'STRING=)))
                                                      (COLLECT (OR RESERVED-WORD (CAR (MEMBER KEYWORD-SYMBOL
                                                                                                 FIELD-NAMES :TEST
'STRING=))))
                                                      (IF (NOT RESERVED-WORD)
                                                           (COLLECT 'IL:_))
                                                      (COLLECT VALUE))))))
(IL:PUTPROPS IL:XCL-EXTRAS IL:FILETYPE :COMPILE-FILE)
(IL:PUTPROPS IL:XCL-EXTRAS IL:MAKEFILE-ENVIRONMENT (:READTABLE "XCL" :PACKAGE "XCL"))
(IL:PUTPROPS IL:XCL-EXTRAS IL:COPYRIGHT ("Venue & Xerox Corporation" 1987 1988 1990))
```


FUNCTION INDEX
RECORD-ACCESS-MACRO3 RECORD-CONSTRUCTOR-MACRO 3 RECORD-PREDICATE-MACRO SETF-RECORD-ACCESS-MACRO 3
MACRO INDEX
ONCE-ONLY1 RECORD-CREATE .2 RECORD-FETCH2 RECORD-FFETCH2 SETF-FETCH2 SETF-FETCH2
DEFINER INDEX
DEFINE-FILE-ENVIRONMENT
SETF INDEX
RECORD-FETCH
PROPERTY INDEX
IL:XCL-EXTRAS4
DEFINE-TYPE INDEX
FILE-ENVIRONMENTS