

File created: 6-Jul-2022 22:31:49 {DSK}<home>larry>loops>users>rules>RULESP.;3

changes to: (VARS RULESPCOMS)  
(FNS FlushRule LetterP Next?CompoundSeparator ParseAtom ParseBackSlash ParseColon  
ParseCompoundSeparator ParseDot ParseEqSign ParseGreaterSign ParseLeftArrow ParseLessSign  
ParseLiteral ParseMinus ParseNotSign ParseNumber ParseOneCharToken ParsePlus ParseString  
ParseTokens ScanFor SkipRule UnParseTerm)

previous date: 11-May-93 13:01:29 {DSK}<home>larry>loops>users>rules>RULESP.;1

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

::  
:: Copyright (c) 1993 by Venue.

(RPAQQ **RULESPCOMS**

[(DECLARE%: DONTCOPY (PROP MAKEFILE-ENVIRONMENT RULESP))

; Copyright (c) 1982 by Xerox Corporation  
; Written in August 1982 by Mark Stefik, Alan Bell, and Danny  
; Bobrow.  
; Fns for Parsing RuleSets.

(FNS \* RULEPARSEFNS)

; Vars and constants for RuleSet parsing.

(E (for VAR in RULEVARS do (SET VAR NIL)))  
(VARS \* RULEVARS)  
(GLOBALVARS \* RULEVARS)  
(CONSTANTS \* RULECONSTANTS)

; Globals for the RuleSet compiler.

(P (SETQ GLOBALVARS (APPEND GLOBALVARS RULEVARS)))

(DECLARE%: DONTCOPY

(PUTPROPS **RULESP MAKEFILE-ENVIRONMENT** (:PACKAGE "INTERLISP" :READTABLE "INTERLISP" :BASE 10))  
)

:: Copyright (c) 1982 by Xerox Corporation  
:: Written in August 1982 by Mark Stefik, Alan Bell, and Danny Bobrow.  
:: Fns for Parsing RuleSets.

(RPAQQ **RULEPARSEFNS** (FlushRule LetterP Next?CompoundSeparator ParseAtom ParseBackSlash ParseColon  
ParseCompoundSeparator ParseDot ParseEqSign ParseGreaterSign ParseLeftArrow  
ParseLessSign ParseLiteral ParseMinus ParseNotSign ParseNumber ParseOneCharToken  
ParsePlus ParseString ParseTokens ScanFor SkipRule UnParseTerm))

(DEFINEQ

(**FlushRule**

[LAMBDA (errorMsg boldToken moreMsg)

(\* mjs%: "14-FEB-83 12:00")

(\* Error Routine activated during RuleSet Parsing. Prints error message and then discards ruleSetTokens remaining in this rule.)

(PROG (token)  
(SETQ parseErrorFlg T)  
(printout NIL T errorMsg)  
(COND  
(boldToken (printout NIL " " .FONT BOLDFONT boldToken .FONT DEFAULTFONT)))  
(COND  
(moreMsg (printout NIL " " moreMsg)))  
(COND  
(ruleSetTokens (printout T " error near: ")  
(for I from 1 to 5 as token in ruleSetTokens when token do (PRIN1 (UnParseTerm token))  
(SPACES 1))  
(TERPRI)))  
(COND  
(rsCompilerDebugFlg (PAUSE "Push RETURN to continue.")))  
(CLEARBUF)  
(SkipRule]))

(**LetterP**

[LAMBDA (character)

(\* mjs%: "16-AUG-82 11:42")

(\* Returns T if the character is an alphabetic letter and NIL otherwise.)

(PROG (code flg)  
(SETQ code (CHCON1 character))  
[SETQ flg (OR (AND (IGREATERP code 64)  
(ILESSP code 91))  
(AND (IGREATERP code 96)  
(ILESSP code 123])

(RETURN flg)]

**(Next?CompoundSeparator**

[LAMBDA NIL

(\* mjs%: "9-FEB-83 11:22")

(\* Subroutine of ParseLiteral. Looks ahead in ruleParseSource to see whether a compound separator follows. Returns T if yes, and NIL otherwise. Does not change ruleParseSource or char.)

```
(PROG [nextChar (oneCharSeprs (CONSTANT (LIST dot colon comma)))
      (afterDot (CONSTANT (LIST dot comma bang)))
      (afterComma (CONSTANT (LIST bang)))
      (afterColon (CONSTANT (LIST colon comma bang))
      (SETQ nextChar (SUBATOM ruleParseSource 1 1))
      (RETURN (OR (AND (FMEMB ruleParseChar oneCharSeprs)
                        (OR (LetterP nextChar)
                            (EQ nextChar upArrow)))
                  (AND (EQ ruleParseChar dot)
                        (FMEMB nextChar afterDot))
                  (AND (EQ ruleParseChar colon)
                        (FMEMB nextChar afterColon))
                  (AND (EQ ruleParseChar comma)
                        (FMEMB nextChar afterComma))
```

**(ParseAtom**

[LAMBDA NIL

(\* mjs%: "9-FEB-83 12:07")

(\* Subroutine of ParseLiteral. Recognizes atoms. Input string is in global variable ruleSetSource. Returns parsed atom.)

```
(PACK (CONS ruleParseChar (while (AND (SETQ ruleParseChar (GNC ruleParseSource))
                                       (OR (LetterP ruleParseChar)
                                           (NUMBERP ruleParseChar)))
      collect ruleParseChar])
```

**(ParseBackSlash**

[LAMBDA NIL

(\* mjs%: "8-JUN-83 10:41")

(\* Subroutine of ParseTokens. Recognizes ruleSetTokens starting with a backSlash. Input string is in global variable ruleSetSource. Returns parsed token.)

```
(PROG (nextChar)
      (SETQ nextChar (SUBATOM ruleParseSource 1 1))
      (RETURN (COND
                ((LetterP nextChar) (* Here for / lisp variables.)
                 (SETQ ruleParseChar (GNC ruleParseSource))
                 (ParseLiteral 'LispVar backSlash))
                (T (SETQ parseErrorFlg nextChar)
                   (SETQ ruleParseChar (GNC ruleParseSource))
```

**(ParseColon**

[LAMBDA NIL

(\* mjs%: "11-FEB-83 14:37")

(\* Subroutine of ParseTokens. Recognizes ruleSetTokens starting with a colon. Input string is in global variable ruleSetSource. Returns parsed token.)

```
(PROG (nextChar)
      (SETQ nextChar (SUBATOM ruleParseSource 1 1))
      (RETURN (COND
                ((AND (EQ bang nextChar)
                      (LetterP (SUBSTRING ruleParseSource 2 2)))
                 (* here for %:! to self.)
                 (SETQ ruleParseChar (GNC ruleParseSource))
                 (SETQ ruleParseChar (GNC ruleParseSource))
                 (ParseLiteral 'self colonBang))
                ((LetterP nextChar) (* Here for %: to self.)
                 (SETQ ruleParseChar (GNC ruleParseSource))
                 (ParseLiteral 'self colon))
                [(EQ colon nextChar) (* Here for ::| constructs.)
                 (SETQ ruleParseChar (GNC ruleParseSource))
                 (SETQ nextChar (SUBATOM ruleParseSource 1 1))
                 (COND
                  ((LetterP nextChar) (* here for ::| to self.)
                   (SETQ ruleParseChar (GNC ruleParseSource))
                   (ParseLiteral 'self coloncolon))
                  ((AND (EQ bang nextChar)
                        (LetterP (SUBSTRING ruleParseSource 2 2)))
                   (* here for ::|| to self.)
                   (SETQ ruleParseChar (GNC ruleParseSource))
                   (SETQ ruleParseChar (GNC ruleParseSource))
                   (ParseLiteral 'self colonColonBang))
                  (T (SETQ parseErrorFlg nextChar)
                     (SETQ ruleParseChar (GNC ruleParseSource))
                     (* Here for %: all by itself.)
```

```
(SETQ ruleParseChar (GNC ruleParseSource))
colon])
```

**(ParseCompoundSeparator**

[LAMBDA NIL

; Edited 14-Dec-87 21:34 by jrb:

(\* \* Subroutine of ParseLiteral. Recognizes compoundSeparators.  
Input string is in global variable ruleSetSource. Returns parsed separator.)

```
(PROG (separator)
  (SETQ separator ruleParseChar)
  (SETQ ruleParseChar (GNC ruleParseSource))
  (RETURN (COND
    ((OR (LetterP ruleParseChar)
      (EQ ruleParseChar upArrow))
      (* Here for %: or %. or (\, compound.))
      separator)
    ((AND (EQ separator colon)
      (EQ ruleParseChar bang))
      (* Here for %:! compound.)
      (SETQ ruleParseChar (GNC ruleParseSource))
      colonBang)
    ((AND (EQ separator comma)
      (EQ ruleParseChar bang))
      (* Here for %,! compound.)
      (SETQ ruleParseChar (GNC ruleParseSource))
      commaBang)
    ((AND (EQ separator colon)
      (EQ ruleParseChar colon))
      (SETQ ruleParseChar (GNC ruleParseSource))
      (COND
        ((EQ ruleParseChar bang)
          (* Here for |::| compound.)
          (SETQ ruleParseChar (GNC ruleParseSource))
          colonColonBang)
        (T
          (* Here for |::| compound.)
          coloncolon)))
    ((AND (EQ separator colon)
      (EQ ruleParseChar comma))
      (SETQ ruleParseChar (GNC ruleParseSource))
      (COND
        ((EQ ruleParseChar bang)
          (* Here for %:,! compound.)
          (SETQ ruleParseChar (GNC ruleParseSource))
          colonCommaBang)
        (T
          (* Here for %:, compound.)
          colonComma)))
    ((EQ separator dot)
      (COND
        ((EQ ruleParseChar bang)
          (* Here for .! compound.)
          (SETQ ruleParseChar (GNC ruleParseSource))
          dotBang)
        ((EQ ruleParseChar dot)
          (SETQ ruleParseChar (GNC ruleParseSource))
          (COND
            ((EQ ruleParseChar star)
              (SETQ ruleParseChar (GNC ruleParseSource))
              dotDotStar)
            (T
              (* Here for |..| compound.)
              dotdot)))
        ((EQ ruleParseChar comma)
          (* Here for ., compound.)
          (SETQ ruleParseChar (GNC ruleParseSource))
          dotcomma)))
    (T
      (* Invalid compound separator.)
      (SETQ parseErrorFlg ruleParseChar]))
```

**(ParseDot**

[LAMBDA NIL

(\* mjs%: "11-FEB-83 11:48")

(\* \* Subroutine of ParseTokens. Recognizes ruleSetTokens starting with a period.  
Input string is in global variable ruleSetSource. Returns parsed token.)

```
(PROG (nextChar)
  (SETQ nextChar (SUBATOM ruleParseSource 1 1))
  (RETURN (COND
    ((NUMBERP nextChar)
      (* Here for floating point numbers.)
      (ParseNumber))
    ((AND (EQ bang nextChar)
      (LetterP (SUBSTRING ruleParseSource 2 2)))
      (* here for .! msgs to self.)
      (SETQ ruleParseChar (GNC ruleParseSource))
      (SETQ ruleParseChar (GNC ruleParseSource))
      (ParseLiteral 'self dotBang))
    ((LetterP nextChar)
      (* Here for %. messages to self.)
      (SETQ ruleParseChar (GNC ruleParseSource))
      (ParseLiteral 'self dot))
    (T (SETQ parseErrorFlg nextChar)
      (SETQ ruleParseChar (GNC ruleParseSource))
```

**(ParseEqSign**

[LAMBDA NIL

(\* mjs%: "22-JAN-83 09:26")

(\*\* Subroutine of ParseTokens. Recognizes ruleSetTokens starting with eqSign --  
either = or ==. Input string is in global variable ruleSetSource. Returns parsed token.)

```
(SETQ ruleParseChar (GNC ruleParseSource))
(COND
  ((EQ ruleParseChar eqSign) (* Here for ==)
   (SETQ ruleParseChar (GNC ruleParseSource))
   eqeqSign)
  (T (* Here for =)
   eqSign))
```

**(ParseGreaterSign**

[LAMBDA NIL

(\* mjs%: "22-JAN-83 09:26")

(\*\* Subroutine of ParseTokens. Recognizes ruleSetTokens starting with greaterSign either > or >=.  
Input string is in global variable ruleSetSource. Returns parsed token.)

```
(SETQ ruleParseChar (GNC ruleParseSource))
(COND
  ((EQ ruleParseChar eqSign) (* Here for >=)
   (SETQ ruleParseChar (GNC ruleParseSource))
   greaterEqSign)
  (T (* Here for >)
   greaterSign))
```

**(ParseLeftArrow**

[LAMBDA NIL

(\* mjs%: "22-JAN-83 09:26")

(\*\* Subroutine of ParseTokens. Recognizes ruleSetTokens starting with leftArrow --  
either \_ or \_+ or \_-. Input string is in global variable ruleSetSource.  
Returns parsed token.)

```
(SETQ ruleParseChar (GNC ruleParseSource))
(COND
  ((EQ ruleParseChar plus) (* Here for _+)
   (SETQ ruleParseChar (GNC ruleParseSource))
   push)
  ((EQ ruleParseChar minus) (* Here for _-)
   (SETQ ruleParseChar (GNC ruleParseSource))
   pop)
  ((EQ ruleParseChar bang) (* Here for _!)
   (SETQ ruleParseChar (GNC ruleParseSource))
   leftArrowBang)
  (T (* Here for _)
   leftArrow))
```

**(ParseLessSign**

[LAMBDA NIL

(\* mjs%: "22-JAN-83 09:27")

(\*\* Subroutine of ParseTokens. Recognizes ruleSetTokens starting with lessSign either < or <=.  
Input string is in global variable ruleSetSource. Returns parsed token.)

```
(SETQ ruleParseChar (GNC ruleParseSource))
(COND
  ((EQ ruleParseChar eqSign) (* Here for <=)
   (SETQ ruleParseChar (GNC ruleParseSource))
   lessEqSign)
  ((EQ ruleParseChar lessSign) (* Here for <<)
   (SETQ ruleParseChar (GNC ruleParseSource))
   membSign)
  (T (* Here for <)
   lessSign))
```

**(ParseLiteral**

[LAMBDA (leftLiteral separator)

(\* mjs%: " 8-JUN-83 10:45")

(\*\* Subroutine of ParseTokens. Recognizes literals. Input string is in global variable ruleSetSource.  
Returns parsed literal. If literal is compound, returns a list of the separator followed by the two parts of the compound.  
For example, RS..ws parses to ([..] RS ws)%. ParseLiteral recurs to handle nested compound literals, such as obj.sel%:var  
which parses to (%: (%. obj sel) var)%. On recursive calls, the argument leftLiteral contains the literal that is the left part.)

```
(PROG (atom dollarFlg) (* Parse the next atom. Special treatment if preceded by dollar sign.)
  (COND
    ((EQ ruleParseChar dollarSign)
     (SETQ dollarFlg T)
     (SETQ ruleParseChar (GNC ruleParseSource))
     (SETQ atom (ParseAtom)))
    [COND
```

```
(PROG (chars token)
  CollectChars
    (SETQ chars (CONS ruleParseChar chars))
  NextChar
    (SETQ ruleParseChar (GNC ruleParseSource))
  (COND
    ((OR (NUMBERP ruleParseChar)
```

```

      (EQ ruleParseChar period))
      (GO CollectChars)))
(* * Check that token is valid number and return to ParseTokens.)
(SETQ token (PACK (DREVERSE chars)))
(COND
  ((NOT (NUMBERP token))
    (SETQ parseErrorFlg token)))
(RETURN token))
(* Set errorFlg if not valid number.)

```

**(ParseOneCharToken**

```

[LAMBDA NIL
(* mjs%: "9-FEB-83 14:25")

```

(\* Subroutine of ParseTokens. Recognizes ruleSetTokens consisting of a single character. Input string is in global variable ruleSetSource. Returns parsed reserved word.)

```

(PROG1 ruleParseChar
  (SETQ ruleParseChar (GNC ruleParseSource))))

```

**(ParsePlus**

```

[LAMBDA NIL
(* mjs%: "22-JAN-83 09:27")

```

(\* Subroutine of ParseTokens. Recognizes ruleSetTokens starting with plus -- either + or ++. Input string is in global variable ruleSetSource. Returns parsed token.)

```

(SETQ ruleParseChar (GNC ruleParseSource))
(COND
  ((EQ ruleParseChar plus)
    (SETQ ruleParseChar (GNC ruleParseSource))
    plusplus)
  (T
    plus))
(* Here for ++
(* Here for +

```

**(ParseString**

```

[LAMBDA NIL
; Edited 10-May-88 13:53 by hwl

```

(\* Subroutine of ParseTokens. Recognizes strings. Input string is in global variable ruleSetSource. Returns parsed string.)

```

(PROG (chars)
  (SETQ ruleParseChar (GNC ruleParseSource))
  [SETQ chars (while (AND ruleParseChar (NEQ ruleParseChar semicolon)
    (NEQ ruleParseChar stringSign))
    collect (PROG1 ruleParseChar
      (SETQ ruleParseChar (GNC ruleParseSource))))]
  [COND
    ((EQ ruleParseChar stringSign)
      (SETQ ruleParseChar (GNC ruleParseSource)))
    (T
      (SETQ parseErrorFlg ruleParseChar)
      (RS.WRITE "Missing end of string: " (MKSTRING chars)
      (RETURN (MKSTRING (PACK chars)))
      (* Error if scan did not end on a stringSign)

```

**(ParseTokens**

```

[LAMBDA (sourceRules)
; Edited 10-May-88 13:54 by hwl

```

(\* First pass of RuleSet compilation by parsing the ruleParseSource string into a list of tokens. Operates as a state machine for recognizing the tokens. During parsing uses global variables ruleParseChar and ruleSetSource. Value returned in the global variable tokens.)

```

(PROG [token everErrorFlg
  (oneCharTokens (CONSTANT (LIST asterisk slash quoteSign lpar rpar semicolon lbracket rbracket
    bang lbrace rbrace comma questionmark upArrow)))
  (skipChars (CONSTANT (LIST carriageReturn lineFeed space tab]
  (SETQ parseErrorFlg NIL)
  (SETQ ruleParseSource (COPYALL sourceRules))
  (SETQ ruleSetTokens NIL)
  NextChar
  (SETQ ruleParseChar (GNC ruleParseSource))

```

(\* Each State is a subroutine using global variables ruleParseChar and ruleSetSource. Each subroutine removes characters from ruleParseSource until its token is complete and returns the token as its value. Since the subroutine takes one more character than it needs, the global variable ruleParseChar is set to the first character for the next state.)

```

NextState
[SETQ token (COND
  ((NULL ruleParseChar)
    (GO Done))
  ((FMEMB ruleParseChar skipChars)
    (GO NextChar))
  ((NUMBERP ruleParseChar)

```

```

    (ParseNumber))
  ((OR (LetterP ruleParseChar)
    (EQ ruleParseChar dollarSign))
    (ParseLiteral))
  ((EQ ruleParseChar dot)
    (ParseDot))
  ((EQ ruleParseChar colon)
    (ParseColon))
  ((EQ ruleParseChar backSlash)
    (ParseBackSlash))
  ((FMEMB ruleParseChar oneCharTokens)
    (ParseOneCharToken))
  ((EQ ruleParseChar lessSign)
    (ParseLessSign))
  ((EQ ruleParseChar greaterSign)
    (ParseGreaterSign))
  ((EQ ruleParseChar leftArrow)
    (ParseLeftArrow))
  ((EQ ruleParseChar eqSign)
    (ParseEqSign))
  ((EQ ruleParseChar plus)
    (ParsePlus))
  ((EQ ruleParseChar minus)
    (ParseMinus))
  ((EQ ruleParseChar notSign)
    (ParseNotSign))
  ((EQ ruleParseChar stringSign)
    (ParseString))
  (T (RS.WRITE "Unexpected " ruleParseChar " in " (CADR ruleSetTokens)
    (CAR ruleSetTokens)
    ruleParseChar
    (SUBSTRING ruleParseSource 1 10))
    (SETQ everErrorFlg T)
    (GO NextChar]

(* * Here on return from state.)

[COND
  (parseErrorFlg (RS.WRITE "Unexpected " parseErrorFlg " in " (CADR ruleSetTokens)
    (CAR ruleSetTokens)
    parseErrorFlg
    (SUBSTRING ruleParseSource 1 10))
    (SETQ parseErrorFlg NIL)
    (SETQ everErrorFlg T))
  (T
    (SETQ ruleSetTokens (CONS token ruleSetTokens])
    (GO NextState)
  Done

(* * Here when done with Source. Add extra semicolon to end and reverse the list.)

(SETQ ruleSetTokens (CONS semicolon ruleSetTokens))
(SETQ ruleSetTokens (DREVERSE ruleSetTokens))
(SETQ parseErrorFlg everErrorFlg)
(RETURN parseErrorFlg])

```

**(ScanFor**

```

[LAMBDA (goodList stopList)                                     (* mjs%: "21-JAN-83 14:29")

(* Scans global variable Tokens looking for next occurrence of one of the ruleSetTokens on goodList.
Returns the first one found or NIL if none were found.)

(for token in ruleSetTokens until (FMEMB token stopList) thereis (FMEMB token goodList])

```

**(SkipRule**

```

[LAMBDA NIL                                                     (* mjs%: " 8-JUN-83 11:29")

(* * Pop the ruleSetTokens for the current rule through a semicolon.)

(PROG (token)
  (do (SETQ token (pop ruleSetTokens)) repeatuntil (OR (EQ token semicolon)
    (NULL ruleSetTokens])

```

**(UnParseTerm**

```

[LAMBDA (parsedTerm)                                           (* dgb%: "21-Feb-84 10:23")

(* * Returns a term in the ruleParseSource Rule Language given its parsed form.
Value is a string.)

(COND
  ((LITATOM parsedTerm)
    parsedTerm)
  ((NUMBERP parsedTerm)
    parsedTerm)

```

```

[ (LISTP parsedTerm)
  (COND
    ((EQ (CAR parsedTerm)
          ' \)
      (CONCAT ' \ (CADDR parsedTerm)))
    (T (CONCAT (UnParseTerm (CADR parsedTerm))
                (CAR parsedTerm)
                (CADDR parsedTerm)]
      (T (PAUSE "Bad Call to UnParseTerm."]))
  )
]

```

(\* Special case for LispVars)

:: Vars and constants for RuleSet parsing.

```

(RPAQQ RULEVARS
  (auditSpecification controlType debugVars oneShotBangFlg oneShotFlg parseErrorFlg reEditMenu rsArgs
    rsAuditClass rsAuditFlg rsAuditSpecification rsBreakFlg rsCompilerDebugFlg rsCompilerOptions
    rsInternalTaskVars rsInternalTempVars rsLispCompileFlg rsName rsNumRules rsPrintRuleFlg
    rsRuleAppliedFlg rsRuleClass rsRuleObjects rsSomeDeclChanged rsSomeRuleAuditFlg rsTaskFlg
    rsTraceFlg rsWhileCondition ruleAuditFlg ruleAuditSpecification ruleBreakFlg ruleLabel
    ruleMakeAuditRecordFlg ruleMetaTokens ruleNeedsAuditFlg ruleNumber ruleObject ruleParseChar
    ruleParseSource ruleRHSFlg ruleSetTokens ruleTraceFlg ruleVars taskVars tempVars wsClass wsVars))

(RPAQQ auditSpecification NIL)

(RPAQQ controlType NIL)

(RPAQQ debugVars NIL)

(RPAQQ oneShotBangFlg NIL)

(RPAQQ oneShotFlg NIL)

(RPAQQ parseErrorFlg NIL)

(RPAQQ reEditMenu NIL)

(RPAQQ rsArgs NIL)

(RPAQQ rsAuditClass NIL)

(RPAQQ rsAuditFlg NIL)

(RPAQQ rsAuditSpecification NIL)

(RPAQQ rsBreakFlg NIL)

(RPAQQ rsCompilerDebugFlg NIL)

(RPAQQ rsCompilerOptions NIL)

(RPAQQ rsInternalTaskVars NIL)

(RPAQQ rsInternalTempVars NIL)

(RPAQQ rsLispCompileFlg NIL)

(RPAQQ rsName NIL)

(RPAQQ rsNumRules NIL)

(RPAQQ rsPrintRuleFlg NIL)

(RPAQQ rsRuleAppliedFlg NIL)

(RPAQQ rsRuleClass NIL)

(RPAQQ rsRuleObjects NIL)

(RPAQQ rsSomeDeclChanged NIL)

(RPAQQ rsSomeRuleAuditFlg NIL)

(RPAQQ rsTaskFlg NIL)

(RPAQQ rsTraceFlg NIL)

(RPAQQ rsWhileCondition NIL)

(RPAQQ ruleAuditFlg NIL)

(RPAQQ ruleAuditSpecification NIL)

(RPAQQ ruleBreakFlg NIL)

(RPAQQ ruleLabel NIL)

```



```

{MEDLEY}<loops>users>rules>RULESP.;1

(RPAQQ ruleMakeAuditRecordFlg NIL)

(RPAQQ ruleMetaTokens NIL)

(RPAQQ ruleNeedsAuditFlg NIL)

(RPAQQ ruleNumber NIL)

(RPAQQ ruleObject NIL)

(RPAQQ ruleParseChar NIL)

(RPAQQ ruleParseSource NIL)

(RPAQQ ruleRHSFlg NIL)

(RPAQQ ruleSetTokens NIL)

(RPAQQ ruleTraceFlg NIL)

(RPAQQ ruleVars NIL)

(RPAQQ taskVars NIL)

(RPAQQ tempVars NIL)

(RPAQQ wsClass NIL)

(RPAQQ wsVars NIL)

(RPAQQ RULEVARS
  (auditSpecification controlType debugVars oneShotBangFlg oneShotFlg parseErrorFlg reEditMenu rsArgs
    rsAuditClass rsAuditFlg rsAuditSpecification rsBreakFlg rsCompilerDebugFlg rsCompilerOptions
    rsInternalTaskVars rsInternalTempVars rsLispCompileFlg rsName rsNumRules rsPrintRuleFlg
    rsRuleAppliedFlg rsRuleClass rsRuleObjects rsSomeDeclChanged rsSomeRuleAuditFlg rsTaskFlg
    rsTraceFlg rsWhileCondition ruleAuditFlg ruleAuditSpecification ruleBreakFlg ruleLabel
    ruleMakeAuditRecordFlg ruleMetaTokens ruleNeedsAuditFlg ruleNumber ruleObject ruleParseChar
    ruleParseSource ruleRHSFlg ruleSetTokens ruleTraceFlg ruleVars taskVars tempVars wsClass wsVars))

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS auditSpecification controlType debugVars oneShotBangFlg oneShotFlg parseErrorFlg reEditMenu rsArgs
  rsAuditClass rsAuditFlg rsAuditSpecification rsBreakFlg rsCompilerDebugFlg rsCompilerOptions
  rsInternalTaskVars rsInternalTempVars rsLispCompileFlg rsName rsNumRules rsPrintRuleFlg rsRuleAppliedFlg
  rsRuleClass rsRuleObjects rsSomeDeclChanged rsSomeRuleAuditFlg rsTaskFlg rsTraceFlg rsWhileCondition
  ruleAuditFlg ruleAuditSpecification ruleBreakFlg ruleLabel ruleMakeAuditRecordFlg ruleMetaTokens
  ruleNeedsAuditFlg ruleNumber ruleObject ruleParseChar ruleParseSource ruleRHSFlg ruleSetTokens
  ruleTraceFlg ruleVars taskVars tempVars wsClass wsVars)

)

(RPAQQ RULECONSTANTS
  [(asterisk (MKATOM "*"))
   (star (MKATOM "*"))
   (slash (MKATOM "/"))
   (backSlash (MKATOM "\"))
   (lessSign (MKATOM "<"))
   (lessEqSign (MKATOM "<="))
   (greaterSign (MKATOM ">"))
   (greaterEqSign (MKATOM ">="))
   (eqSign (MKATOM "="))
   (eqeqSign (MKATOM "=="))
   (membSign (MKATOM "<<"))
   (notSign (MKATOM "~"))
   (neqSign (MKATOM "~="))
   (quoteSign (MKATOM "'" ))
   (stringSign (MKATOM "%"))
   (lpar (MKATOM "("))
   (rpar (MKATOM ")"))
   (upArrow (MKATOM "^"))
   (rightArrow (MKATOM "->"))
   (leftArrow (MKATOM "-"))
   (leftArrowBang (MKATOM "_!"))
   (period (MKATOM "."))
   (dot period)
   (dotBang (MKATOM "!."))
   (dotdot (MKATOM ".."))
   (dotcomma (MKATOM ".,"))
   (dotDotStar (MKATOM "..*"))
   (colon (MKATOM ":"))
   (coloncolon (MKATOM "::"))
   (colonBang (MKATOM ":!"))
   (colonColonBang (MKATOM "::!"))
   (colonComma (MKATOM ":", ))
   (colonCommaBang (MKATOM ":", !"))
   (semicolon (MKATOM ";"))
   (lbrace (MKATOM "{"))
   (rbrace (MKATOM "}") )

```

```

(lbracket (MKATOM "["))
(rbracket (MKATOM "]"))
(comma (MKATOM ","))
(commaBang (MKATOM ",!"))
(questionmark (MKATOM "?"))
(bang (MKATOM "!"))
(oneBang (MKATOM "1!"))
(verticalbar (MKATOM "|"))
(atsign (MKATOM "@"))
(sharp (MKATOM "#"))
(dollarSign (MKATOM "$"))
(ampersand (MKATOM "&"))
(carriageReturn (CHARACTER 13))
(lineFeed (CHARACTER 10))
(crlf "
")
(space (CHARACTER 32))
(tab (CHARACTER 9))
(push (MKATOM "_+"))
(pop (MKATOM "_-"))
(minus (MKATOM "-"))
(unaryMinus (MKATOM "-1-"))
(plus (MKATOM "+"))
(plusplus (MKATOM "++"))
(minusminus (MKATOM "--"))
(endExpr 'endExpr)
(^noRuleApplied 'NoRuleApplied)
(compileTimeVars '(ruleNumber ruleLabel ruleObject))
(lispConstants (LIST NIL T))
(cyclicControlStructures '(WHILE1 WHILEALL WHILENEXT FOR1 FORALL))
(reservedRuleWords '(self ruleApplied))
(sendSpellings '(!_ _ SEND Send send))
(stopSpellings '(STOP Stop stop))
(thenSpellings '(THEN Then then ->))
(ifSpellings '(IF If if))

(DECLARE%: EVAL@COMPILE

(RPAQ asterisk (MKATOM "**"))

(RPAQ star (MKATOM "**"))

(RPAQ slash (MKATOM "/"))

(RPAQ backSlash (MKATOM "\"))

(RPAQ lessSign (MKATOM "<"))

(RPAQ lessEqSign (MKATOM "<="))

(RPAQ greaterSign (MKATOM ">"))

(RPAQ greaterEqSign (MKATOM ">="))

(RPAQ eqSign (MKATOM "="))

(RPAQ eqeqSign (MKATOM "=="))

(RPAQ membSign (MKATOM "<<"))

(RPAQ notSign (MKATOM "~"))

(RPAQ neqSign (MKATOM "~="))

(RPAQ quoteSign (MKATOM "'"))

(RPAQ stringSign (MKATOM "%"))

(RPAQ lpar (MKATOM "("))

(RPAQ rpar (MKATOM ")"))

(RPAQ upArrow (MKATOM "^"))

(RPAQ rightArrow (MKATOM "->"))

(RPAQ leftArrow (MKATOM "_"))

(RPAQ leftArrowBang (MKATOM "_!"))

(RPAQ period (MKATOM "."))

(RPAQ dot period)

(RPAQ dotBang (MKATOM "!."))

(RPAQ dotdot (MKATOM ".."))

```

```

(RPAQ dotcomma (MKATOM "."))
(RPAQ dotDotStar (MKATOM "..*"))
(RPAQ colon (MKATOM ":"))
(RPAQ coloncolon (MKATOM "::"))
(RPAQ colonBang (MKATOM "!:"))
(RPAQ colonColonBang (MKATOM "::!"))
(RPAQ colonComma (MKATOM ":","))
(RPAQ colonCommaBang (MKATOM ":",!"))
(RPAQ semicolon (MKATOM ";"))
(RPAQ lbrace (MKATOM "{"))
(RPAQ rbrace (MKATOM "}"))
(RPAQ lbracket (MKATOM "["))
(RPAQ rbracket (MKATOM "]"))
(RPAQ comma (MKATOM ","))
(RPAQ commaBang (MKATOM ",!"))
(RPAQ questionmark (MKATOM "?"))
(RPAQ bang (MKATOM "!"))
(RPAQ oneBang (MKATOM "1!"))
(RPAQ verticalbar (MKATOM "|"))
(RPAQ atsign (MKATOM "@"))
(RPAQ sharp (MKATOM "#"))
(RPAQ dollarSign (MKATOM "$"))
(RPAQ ampersand (MKATOM "&"))
(RPAQ carriageReturn (CHARACTER 13))
(RPAQ lineFeed (CHARACTER 10))
(RPAQ crLf "
")
(RPAQ space (CHARACTER 32))
(RPAQ tab (CHARACTER 9))
(RPAQ push (MKATOM "_+"))
(RPAQ pop (MKATOM "_-"))
(RPAQ minus (MKATOM "-"))
(RPAQ unaryMinus (MKATOM "-1-"))
(RPAQ plus (MKATOM "+"))
(RPAQ plusplus (MKATOM "++"))
(RPAQ minusminus (MKATOM "--"))
(RPAQQ endExpr endExpr)
(RPAQQ ^noRuleApplied NoRuleApplied)
(RPAQQ compileTimeVars (ruleNumber ruleLabel ruleObject))
(RPAQ lispConstants (LIST NIL T))
(RPAQQ cyclicControlStructures (WHILE1 WHILEALL WHILENEXT FOR1 FORALL))
(RPAQQ reservedRuleWords (self ruleApplied))
(RPAQQ sendSpellings (_! _ SEND Send send))
(RPAQQ stopSpellings (STOP Stop stop))

```

```

(RPAQQ thenSpellings (THEN Then then ->))

(RPAQQ ifSpellings (IF If if))

[CONSTANTS (asterisk (MKATOM "*" ))
  (star (MKATOM "*" ))
  (slash (MKATOM "/" ))
  (backSlash (MKATOM "\" ))
  (lessSign (MKATOM "<" ))
  (lessEqSign (MKATOM "<=" ))
  (greaterSign (MKATOM ">" ))
  (greaterEqSign (MKATOM ">=" ))
  (eqSign (MKATOM "=" ))
  (eqeqSign (MKATOM "==" ))
  (membSign (MKATOM "<<" ))
  (notSign (MKATOM "~" ))
  (neqSign (MKATOM "~=" ))
  (quoteSign (MKATOM "\"" ))
  (stringSign (MKATOM "%" ))
  (lpar (MKATOM "(" ))
  (rpar (MKATOM ")" ))
  (upArrow (MKATOM "^" ))
  (rightArrow (MKATOM "->" ))
  (leftArrow (MKATOM "-" ))
  (leftArrowBang (MKATOM "-!" ))
  (period (MKATOM "." ))
  (dot period)
  (dotBang (MKATOM "!" ))
  (dotdot (MKATOM ".." ))
  (dotcomma (MKATOM ".," ))
  (dotDotStar (MKATOM "..*" ))
  (colon (MKATOM ":" ))
  (coloncolon (MKATOM "::" ))
  (colonBang (MKATOM "!" ))
  (colonColonBang (MKATOM "::!" ))
  (colonComma (MKATOM ":", " "))
  (colonCommaBang (MKATOM ":", "!" ))
  (semicolon (MKATOM ";" ))
  (lbrace (MKATOM "{" ))
  (rbrace (MKATOM "}" ))
  (lbracket (MKATOM "[" ))
  (rbracket (MKATOM "]" ))
  (comma (MKATOM "," ))
  (commaBang (MKATOM "!" ))
  (questionmark (MKATOM "?" ))
  (bang (MKATOM "!" ))
  (oneBang (MKATOM "1!" ))
  (verticalbar (MKATOM "|" ))
  (atsign (MKATOM "@" ))
  (sharp (MKATOM "#" ))
  (dollarSign (MKATOM "$" ))
  (ampersand (MKATOM "&" ))
  (carriageReturn (CHARACTER 13))
  (lineFeed (CHARACTER 10))
  (crlf "
  ")
  (space (CHARACTER 32))
  (tab (CHARACTER 9))
  (push (MKATOM "_+" ))
  (pop (MKATOM "_-" ))
  (minus (MKATOM "-" ))
  (unaryMinus (MKATOM "-1-" ))
  (plus (MKATOM "+" ))
  (plusplus (MKATOM "++" ))
  (minusminus (MKATOM "--" ))
  (endExpr 'endExpr)
  (^noRuleApplied 'NoRuleApplied)
  (compileTimeVars '(ruleNumber ruleLabel ruleObject))
  (lispConstants (LIST NIL T))
  (cyclicControlStructures '(WHILE1 WHILEALL WHILENEXT FOR1 FORALL))
  (reservedRuleWords '(self ruleApplied))
  (sendSpellings '(_!
    _ SEND Send send))
  (stopSpellings '(STOP Stop stop))
  (thenSpellings '(THEN Then
    then ->))
  (ifSpellings '(IF If if]
)

```

:: Globals for the RuleSet compiler.

```

(SETQ GLOBALVARS (APPEND GLOBALVARS RULEVARS))

(PUTPROPS RULESP COPYRIGHT ("Venue" 1993))

```

---

### FUNCTION INDEX

FlushRule .....	1	ParseCompoundSeparator ..3	ParseLiteral .....	4	ParseString .....	6	
LetterP .....	1	ParseDot .....	3	ParseMinus .....	5	ParseTokens .....	6
Next?CompoundSeparator ..2		ParseEqSign .....	4	ParseNotSign .....	5	ScanFor .....	7
ParseAtom .....	2	ParseGreaterSign .....	4	ParseNumber .....	5	SkipRule .....	7
ParseBackSlash .....	2	ParseLeftArrow .....	4	ParseOneCharToken .....	6	UnParseTerm .....	7
ParseColon .....	2	ParseLessSign .....	4	ParsePlus .....	6		

---

### CONSTANT INDEX

ampersand .....	12	dot .....	12	lispConstants .....	12	rightArrow .....	12
asterisk .....	12	dotBang .....	12	lpar .....	12	rpar .....	12
atsign .....	12	dotcomma .....	12	membSign .....	12	semicolon .....	12
backSlash .....	12	dotdot .....	12	minus .....	12	sendSpellings .....	12
bang .....	12	dotDotStar .....	12	minusminus .....	12	sharp .....	12
carriageReturn .....	12	endExpr .....	12	negSign .....	12	slash .....	12
colon .....	12	eqeqSign .....	12	notSign .....	12	space .....	12
colonBang .....	12	eqSign .....	12	oneBang .....	12	star .....	12
coloncolon .....	12	greaterEqSign .....	12	period .....	12	stopSpellings .....	12
colonColonBang .....	12	greaterSign .....	12	plus .....	12	stringSign .....	12
colonComma .....	12	ifSpellings .....	12	plusplus .....	12	tab .....	12
colonCommaBang .....	12	lbrace .....	12	pop .....	12	thenSpellings .....	12
comma .....	12	lbracket .....	12	push .....	12	unaryMinus .....	12
commaBang .....	12	leftArrow .....	12	questionmark .....	12	upArrow .....	12
compileTimeVars .....	12	leftArrowBang .....	12	quoteSign .....	12	verticalbar .....	12
crlf .....	12	lessEqSign .....	12	rbrace .....	12	^noRuleApplied .....	12
cyclicControlStructures ..12		lessSign .....	12	rbracket .....	12		
dollarSign .....	12	lineFeed .....	12	reservedRuleWords .....	12		

---

### VARIABLE INDEX

auditSpecification .....	8	rsCompilerOptions .....	8	rsTraceFlg .....	8	RULEPARSEFNS .....	1
controlType .....	8	rsInternalTaskVars .....	8	rsWhileCondition .....	8	ruleParseSource .....	9
debugVars .....	8	rsInternalTempVars .....	8	ruleAuditFlg .....	8	ruleRHSFlg .....	9
oneShotBangFlg .....	8	rsLispCompileFlg .....	8	ruleAuditSpecification ..8		ruleSetTokens .....	9
oneShotFlg .....	8	rsName .....	8	ruleBreakFlg .....	8	ruleTraceFlg .....	9
parseErrorFlg .....	8	rsNumRules .....	8	RULECONSTANTS .....	9	ruleVars .....	9
reEditMenu .....	8	rsPrintRuleFlg .....	8	ruleLabel .....	8	RULEVARS .....	8,9
rsArgs .....	8	rsRuleAppliedFlg .....	8	ruleMakeAuditRecordFlg ..9		taskVars .....	9
rsAuditClass .....	8	rsRuleClass .....	8	ruleMetaTokens .....	9	tempVars .....	9
rsAuditFlg .....	8	rsRuleObjects .....	8	ruleNeedsAuditFlg .....	9	wsClass .....	9
rsAuditSpecification .....	8	rsSomeDeclChanged .....	8	ruleNumber .....	9	wsVars .....	9
rsBreakFlg .....	8	rsSomeRuleAuditFlg .....	8	ruleObject .....	9		
rsCompilerDebugFlg .....	8	rsTaskFlg .....	8	ruleParseChar .....	9		

---

### PROPERTY INDEX

RULESP .....	1
--------------	---

---