

File created: 31-Oct-2023 16:16:39 {WMEDLEY}<sources>LLSYMBOL.;2

edit by: rmk

previous date: 11-Jun-90 17:56:50 {WMEDLEY}<sources>LLSYMBOL.;1

Read Table: XCL

Package: LISP

Format: XCCS

```
(IL:RPAQQ IL:LLSYMBOLCOMS
  ;; Symbol functions.
  ;; SET , BOUNDP and REMPROP are the same as and shared with Interlisp-D
  ;; Where is the optimizer for CL:GETF?
  (IL:FUNCTIONS MAKUNBOUND SYMBOL-NAME SYMBOL-VALUE GET GETF GET-PROPERTIES)
  (IL:DECLARE\ : IL:DOCOPY IL:DONTEVAL@LOAD IL:DONTEVAL@COMPILE (IL:P (IL:MOVD 'IL:GETPROPLIST
                                                                    'SYMBOL-PLIST)))
  (IL:FUNCTIONS FBOUNDP FMAKUNBOUND SYMBOL-FUNCTION IL:SETF-SYMBOL-FUNCTION)
  (IL:COMS
    ;; GENSYM Code
    (IL:VARIABLES *GENSYM-COUNTER* *GENSYM-PREFIX* *GENTEMP-COUNTER*)
    (IL:FUNCTIONS GENSYM GENTEMP))
  (IL:FUNCTIONS COPY-SYMBOL IL:MAKE-KEYWORD KEYWORDP)
  (IL:PROP (IL:FILETYPE IL:MAKEFILE-ENVIRONMENT)
    IL:LLSYMBOL)))
```

;; Symbol functions.

;; SET , BOUNDP and REMPROP are the same as and shared with Interlisp-D

;; Where is the optimizer for CL:GETF?

```
(DEFUN MAKUNBOUND (SYMBOL)
  ;; Make a symbol unbound.
  ;; Unbound symbols are set to IL:NOBIND
  (IF (CONSTANTP SYMBOL)
    (PROGN (XCL::SET-CONSTANTP SYMBOL NIL)
      (PROCLAIM `(SPECIAL ,SYMBOL))))
  (SET SYMBOL 'IL:NOBIND)
  SYMBOL)

(DEFUN SYMBOL-NAME (SYMBOL)
  (IF (SYMBOLP SYMBOL)
    ;; Make a read-only string header displaced to the pname base
    (IL:%MAKE-ONED-ARRAY (IL:|ffetch| (IL:LITATOM IL:PNAMELENGTH) IL:|of| SYMBOL)
      'STRING-CHAR NIL (IL:|ffetch| (IL:LITATOM IL:FATPNAMEP) IL:|of| SYMBOL)
      T NIL (IL:|ffetch| (IL:LITATOM IL:PNAMEBASE) IL:|of| SYMBOL)
      1)
    (ERROR 'CONDITIONS:SIMPLE-TYPE-ERROR :EXPECTED-TYPE 'SYMBOL :CULPRIT SYMBOL)))
```

```
(DEFUN SYMBOL-VALUE (SYMBOL)
  ;; Like EVALV, but must give error if unbound - uses fact that \eval has an opcode which hooks into free variable microcode
  (IF (SYMBOLP SYMBOL)
    (IL:\EVAL SYMBOL)
    (ERROR 'CONDITIONS:SIMPLE-TYPE-ERROR :EXPECTED-TYPE 'SYMBOL :CULPRIT SYMBOL)))
```

```
(DEFUN GET (SYMBOL INDICATOR &OPTIONAL (DEFAULT NIL))
  ;; Look on the property list of SYMBOL for the specified INDICATOR. If this is found, return the associated value, else return DEFAULT.
  (GETF (IL:GETPROPLIST SYMBOL)
    INDICATOR DEFAULT))
```

```
(DEFUN GETF (PLACE INDICATOR &OPTIONAL (DEFAULT NIL))
  ;; Searches the property list stored in Place for an indicator EQ to Indicator. If one is found, the corresponding value is returned, else the Default is
  ;; returned.
  (DO ((PLIST PLACE (CDDR PLIST)))
    ((NULL PLIST)
      DEFAULT)
    (WHEN (EQ (CAR PLIST)
      INDICATOR)
      (IF (NOT (CONSP (CDR PLIST)))
        (ERROR "Malformed property list: ~s" PLACE)
        (RETURN (CADR PLIST))))))
```

```

(DEFUN GET-PROPERTIES (PLACE INDICATOR-LIST)
  (DO ((PLIST PLACE (CDDR PLIST))
      ((NULL PLIST)
       (VALUES NIL NIL NIL))
      (WHEN (MEMBER (CAR PLIST)
                    INDICATOR-LIST :TEST #'EQ)
          (IF (NOT (CONSP (CDR PLIST)))
              (ERROR "Malformed p-list: ~s" PLACE)
              (RETURN (VALUES (CAR PLIST)
                              (CADR PLIST)
                              PLIST))))))

(IL:DECLARE\ : IL:DOCOPY IL:DONTEVAL@LOAD IL:DONTEVAL@COMPILE

(IL:MOVD 'IL:GETPROPLIST 'SYMBOL-PLIST)
)

(DEFUN FBOUNDP (FN)
  (AND (SYMBOLP FN)
       (OR (IL:ARGTYPE FN)
           (MACRO-FUNCTION FN)
           (SPECIAL-FORM-P FN)
           T))

(DEFUN FMAKUNBOUND (SYMBOL)
  ;; Has lots of special knowledge of prop list names
  (SETF (SYMBOL-FUNCTION SYMBOL)
        NIL)
  (SETF (MACRO-FUNCTION SYMBOL)
        NIL)
  (REMPROP SYMBOL 'IL:SPECIAL-FORM)
  (REMPROP SYMBOL 'IL:CODE)
  (REMPROP SYMBOL 'IL:EXPR)
  SYMBOL)

(DEFUN SYMBOL-FUNCTION (SYMBOL &AUX (DEF (IL:GETD SYMBOL)))
  ;; this function is performance-critical, as it is used in the compilation of #'FOO => (CL:SYMBOL-FUNCTION 'FOO). Thus, this definition checks for
  ;; the GETD definition first. It might even be reasonable to open-code the GETD here. It *is* unreasonable to call MACRO-FUNCTION and
  ;; SPECIAL-FORM-P first.
  (COND
    (DEF
     ((SETQ DEF (MACRO-FUNCTION SYMBOL))
      (CONS ' :MACRO DEF))
      (SETQ DEF (SPECIAL-FORM-P SYMBOL))
      (CONS ' :SPECIAL-FORM DEF))
      (T (ERROR 'XCL:UNDEFINED-FUNCTION :NAME SYMBOL)))
    ; GETD returned non-NIL
    ; Return something representing the macro's implementation.
    ; Return something representing the special-form's
    ; implementation.

(DEFUN IL:SETF-SYMBOL-FUNCTION (SYMBOL DEFINITION)
  ;; NOTE: If you change this, be sure to change the undoable version on CMLUNDO!
  ;; inverse of SYMBOL-FUNCTION
  (IL:VIRGINFN SYMBOL T)
  (COND
    ((CONSP DEFINITION)
     ;; Either it's a LAMBDA form or one of the special lists put together by SYMBOL-FUNCTION for macros and special forms.
     (CASE (CAR DEFINITION)
       (:MACRO (SETF (MACRO-FUNCTION SYMBOL)
                    (CDR DEFINITION)))
       (:SPECIAL-FORM (SETF (GET SYMBOL 'IL:SPECIAL-FORM)
                           (CDR DEFINITION)))
       (T (IL:PUTD SYMBOL DEFINITION T))))
    ;; If it's (SETF (SYMBOL-FUNCTION 'FOO) 'BAR) then we give FOO the same definition as BAR. This isn't quite like Lucid and Symbolics, but
    ;; it will do for now.
    ((AND (SYMBOLP DEFINITION)
          (NOT (NULL DEFINITION)))
     (IL:PUTD SYMBOL (IL:GETD DEFINITION)
               T))
    ;; It's probably a compiled-code object or an interpreted closure. In any case, go ahead and put it in there; if it's illegal, we'll find out when we try
    ;; to apply it.
    (T (IL:PUTD SYMBOL DEFINITION T)))
  ;; (SETF (SYMBOL-FUNCTION ...) ...) is supposed to remove macro definitions. We only remove the ones that could come from DEFMACRO.
  (UNLESS (OR (NULL DEFINITION)
              (AND (CONSP DEFINITION)
                   (EQ (CAR DEFINITION)
                       :MACRO)))

```

```
(REMPROP SYMBOL 'IL:MACRO-FN)
DEFINITION)
```

```
:: GENSYM Code
```

```
(DEFVAR *GENSYM-COUNTER* 0)
```

```
(DEFVAR *GENSYM-PREFIX* "G")
```

```
(DEFVAR *GENTEMP-COUNTER* 0)
```

```
(DEFUN GENSYM (&OPTIONAL (X NIL X-P))
  (IF X-P
    (ETYPECASE X
      (STRING (SETQ *GENSYM-PREFIX* X))
      (INTEGER (SETQ *GENSYM-COUNTER* X))))
  (PROG1 (MAKE-SYMBOL (CONCATENATE 'STRING *GENSYM-PREFIX* (IL:MKSTRING *GENSYM-COUNTER*)))
    (SETQ *GENSYM-COUNTER* (1+ *GENSYM-COUNTER*)))))
```

```
(DEFUN GENTEMP (&OPTIONAL (PREFIX "T")
  (PACKAGE *PACKAGE*))
```

```
:: *gentemp-counter* holds a good guess for the suffix
```

```
(LET ((COUNTER *GENTEMP-COUNTER*)
  NAMESTRING)
  ; Use IL:MKSTRING rather than princ-to-string, since
  ; princ-to-string occurs late in the loadup
  (LOOP (SETQ NAMESTRING (CONCATENATE 'STRING PREFIX (IL:MKSTRING COUNTER)))
    (WHEN (NULL (FIND-SYMBOL NAMESTRING PACKAGE))
      (SETQ *GENTEMP-COUNTER* (1+ COUNTER))
      (RETURN (INTERN NAMESTRING PACKAGE)))
    (SETQ COUNTER (1+ COUNTER)))))
```

```
(DEFUN COPY-SYMBOL (SYM &OPTIONAL COPY-PROPS)
  (LET ((NEW-SYM (MAKE-SYMBOL (SYMBOL-NAME SYM))))
    (WHEN COPY-PROPS
      (IF (BOUNDP SYM)
        (SETF (SYMBOL-VALUE NEW-SYM)
          (SYMBOL-VALUE SYM)))
      (IF (FBOUNDP SYM)
        (SETF (SYMBOL-FUNCTION NEW-SYM)
          (SYMBOL-FUNCTION SYM)))
      (SETF (SYMBOL-PLIST NEW-SYM)
        (COPY-LIST (SYMBOL-PLIST SYM))))
    NEW-SYM))
```

```
(DEFUN IL:MAKE-KEYWORD (SYMBOL)
  (DECLARE (SPECIAL IL:*KEYWORD-PACKAGE*))
  (VALUES (INTERN (SYMBOL-NAME SYMBOL)
    IL:*KEYWORD-PACKAGE*)))
```

```
(DEFUN KEYWORDP (OBJECT)
  (AND (SYMBOLP OBJECT)
    (EQ (SYMBOL-PACKAGE OBJECT)
      IL:*KEYWORD-PACKAGE*)))
```

```
(IL:PUTPROPS IL:LLSYMBOL IL:FILETYPE COMPILE-FILE)
```

```
(IL:PUTPROPS IL:LLSYMBOL IL:MAKEFILE-ENVIRONMENT (:READTABLE "XCL" :PACKAGE "LISP"))
```

FUNCTION INDEX

COPY-SYMBOL3	GENTEMP3	KEYWORDP3	SYMBOL-FUNCTION2
FBOUNDP2	GET1	IL:MAKE-KEYWORD3	SYMBOL-NAME1
FMAKUNBOUND2	GET-PROPERTIES2	MAKUNBOUND1	SYMBOL-VALUE1
GENSYM3	GETF1	IL:SETF-SYMBOL-FUNCTION	.2		

VARIABLE INDEX

GENSYM-COUNTER3	*GENSYM-PREFIX*3	*GENTEMP-COUNTER*3
------------------	--------	-----------------	--------	-------------------	--------

PROPERTY INDEX

IL:LLSYMBOL3
-------------	--------