

File created: 26-Feb-2024 20:10:22 {WMEDLEY}<library>lafite>LAFITE.;19

edit by: rmk

changes to: (VARS LAFITECOMS LAFITEFILES)

previous date: 24-Feb-2024 11:56:21 {WMEDLEY}<library>lafite>LAFITE.;18

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

(RPAQQ LAFITECOMS

```
[(COMS (E (SETQ LAFITESYSTEMDATE (DATE)))
(VARS LAFITEVERSION# LAFITESYSTEMDATE))
(COMS (FNS LAFITE LAFITE.ON.FROM.BACKGROUND \LAFITE.OFF \LAFITE.START.PROC LAFITE.COMPUTE.CACHED.VARS
\LAFITE.PROCESS \LAFITE.START.ABORT \LAFITE.QUIT \LAFITE.RESTART \LAFITE.SUBQUIT
\LAFITE.QUIT.PROC \LAFITEDEFAULTHOST&DIR LAFITEDEFAULTHOST&DIR MAKELAFITECOMMANDWINDOW
EXTRACTMENUCOMMAND DOMAINLAFITECOMMAND LAFITE.TOGGLE.SERVER.TRACE)
(PROP ARGUMENTS LAFITE)
(FNS LAFITEMODE \LAFITE.INFER.MODE \LAFITE.SHOW.MODE \LAFITE.MODE.TITLE LAFITE.SHOW.MODE.P
LAFITE.ALL.MODES.P SET.LAFITE.MODE.INTERACTIVELY \LAFITE.COMPUTE.MODE.COMMANDS)
(PROP VARTYPE LAFITEMODELST)
(ADDVARS (LAFITEMODELST))
[INITVARS (\LAFITEMODE)
(\LAFITE.AUTHENTICATION.FAILURE)
(LAFITE.BACKGROUND.ITEM '("Mail" '(\LAFITE.MESSAGEFORM NIL NIL 'LEFT)
"Send an ordinary message. See subcommands for other
operations."
(SUBITEMS ("Turn Lafite on" '(\LAFITE.ON.FROM.BACKGROUND)
"Turn on Lafite, bringing up status window
and browsing default folder.")
("Send Mail" '(\LAFITE.MESSAGEFORM)
"Send a message. Prompts for type of
message.")
("Set Lafite Mode" ' (SET.LAFITE.MODE.INTERACTIVELY)
"Set or change Lafite's mail protocol mode.")]
(FNS \LAFITE.LOGIN \LAFITE.LOGIN.NOESTART LAFITE.PROMPT.FOR.LOGIN \LAFITE.REAUTHENTICATE))
(INITVARS * LAFITEPROFILEVARS)
(INITVARS * LAFITERANDOMGLOBALS)
(VARS * LAFITEMARKS)
(VARS LAFITECOMMANDMENUITEMS LAFITEUPDITEMENUITEMS LAFITESUBQUITMENUITEMS ANOTHERFOLDERMENUITEM)
(INITVARS (LAFITESTATUSWINDOW)
(\ACTIVELAFITEFOLDERS)
(\LAFITE.TEMPFILES)
(\LAFITE.MODE.CHOICES)
(LAFITESUBQUITMENU))
(ADDVARS (LAFITEMENUVARS LAFITESUBQUITMENU))
(COMS (INITVARS (\LAFITE.ACTIVE)
(\LAFITE.READY)
(\LAFITEDEFAULTHOST&DIR)
(\LAFITE.ACTIVE.MODES)
(\LAFITE.CURRENT.USER)
(LAFITE.USER.INFO)
(*LAFITE-WELL-KNOWN-MODES*)
(*LAFITE-LOGGING-IN*))
(ADDVARS (\SYSTEMCACHEVARS \LAFITE.READY \LAFITE.ACTIVE.MODES)
(LAFITE.PERSONAL.VARS LAFITEDEFAULTHOST&DIR LAFITE.SIGNATURE))
(FNS LAFITE.AROUNDEXIT \LAFITE.MARK.FOLDERS.OBSOLETE \LAFITE.CHECK.FOLDERS
\LAFITE.ASSURE.FOLDER.READY \LAFITE.AFTERLOGIN))
(COMS ; misc utilities
(FNS LA.RESETSHADE LA.MENU.ITEM NTHMESSAGE \LAFITE.MAKE.MSGARRAY \LAFITE.ADDMESSAGES.TO.ARRAY
\MAILFOLDER.DEFPRINT \LAFITEMSG.DEFPRINT LA.POSITION.FROM.REGION MAILFOLDERBUSY)
(CURSORS LA.CROSSCURSOR)
; Low level file functions
(FNS TOFILENAME DELETEMAILFOLDER \LAFITE.OPEN.FOLDER \LAFITE.REPORT.FILE.WONT.OPEN
\LAFITE.FOLDER.CHANGED \LAFITE.REBROWSE.FOLDER \LAFITE.FOLDER.CHANGED.MENU
\LAFITE.SET.FOLDER.STREAM \LAFITE.OPENSTREAM \LAFITE.CREATE.MENU \LAFITE.EOF
\LAFITE.CLOSE.FOLDER)
(FNS \LAFITE.DESCRIBE.FOLDER))
(COMS ; Make is easy to load new versions of Lafite
(FNS LOAD-LAFITE)
(VARS LAFITEFILES))
[DECLARE%: DOEVAL@COMPILE DONTCOPY (FILES (SOURCE)
LAFITE-DECLS)
(LOCALVARS . T)
(GLOBALVARS TEDIT.DEFAULT.MENU LAFITEFILES *COMPILED-EXTENSIONS*)
(P (CL:PROCLAIM ' (CL:SPECIAL *LAFITE-LOGGING-IN*)]
(INITRECORDS MAILFOLDER LAFITEMSG)
(SYSRECORDS MAILFOLDER LAFITEMSG)
[COMS (FNS \LAFITE.GLOBAL.INIT)
(DECLARE%: DONTVAL@LOAD DONTCOPY (FILES TEDIT ATTACHEDWINDOW)
(FILES LAFITE-BROWSE LAFITE-COMMANDS LAFITE-FOLDERS LAFITE-SEND LAFITE-MAIL LAFITE-SORT
LAFITE-TEDIT LAFITE-FIND LAFITE-MAILSCAVENGE)
(P * (PROGN LAFITE.PROCLAMATIONS))
; Proclaim user interface variables. Value is on LAFITE-DECLS
```

```

(P (\LAFITE.GLOBAL.INIT)
  (COND ((EQ MAKESYSNAME :LYRIC)
    (FILESLOAD (SYSLOAD)
      NSCHARPATCH)
    ; Patch to horrid Lyric NS chars bug
    (MOVD? 'PROMPTFORWARD 'TTYINPROMPTFORWARD NIL T]
  (DECLARE%: DOEVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVAR (ADDVARS (NLAMA)
    (NLAML)
    (LAMA LAFITE]))

```

```
(RPAQQ LAFITEVERSION# 10)
```

```
(RPAQQ LAFITESYSTEMDATE "26-Feb-2024 20:10:22")
```

```
(DEFINEQ
```

```
(LAFITE
```

```
[LAMBDA X
```

```
; Edited 13-Jun-88 10:47 by bvm
```

```

;;; The first argument should be :ON or :OFF. The second argument, if supplied, is the name of the mailfile Lafite should browse unless the second
;;; argument is NIL in which case no mailfile will be browsed. If there is no second argument then default to DEFAULTMAILFOLDERNAME mailfile --
;;; currently ACTIVE

```

```

(PROG ([CMD (COND
  ((< X 1)
    :ON)
  (T (ARG X 1]
  OPTIONS)
  RETRY
  (RETURN
    (CASE CMD
      ((:ON ON)
        (COND
          (\LAFITE.ACTIVE
            (TOTOPW LAFITESTATUSWINDOW)
            :ON)
          (T (\LAFITE.PROCESS
            \[, (FUNCTION \LAFITE.START.PROC)
            \[, (COND
              ((OR (<= X 1)
                (EQ (ARG X 2)
                  T))
              (DEFAULTMAILFOLDERNAME)
              (T (ARG X 2))))
            \[, (for I from 3 to X collect (LET ((OP (ARG X I)))
              (if (CL:KEYWORDP OP)
                then OP
                elseif (CL:SYMBOLP OP)
                then
                  ; Old interface wasn't with keywords, so help out
                  (CL:INTERN (CL:SYMBOL-NAME OP)
                    *KEYWORD-PACKAGE*)
                else (\ILLEGAL.ARG OP]
            'LAFITE)
            '(:ON)))
      ((:OFF OFF RESTART) (if (\LAFITE.OFF)
        then
          ; Successfully turned Lafite off
          (COND
            [(EQ CMD 'RESTART)
              (APPLY (FUNCTION LAFITE)
                (CONS :ON (for I from 2 to X collect (ARG X I)
                  (T :OFF))))
            (T (if (NEQ CMD (SETQ CMD (U-CASE CMD)))
              then (GO RETRY)
              else (LISPERROR "ILLEGAL ARG" CMD)))]))

```

```
(LAFITE.ON.FROM.BACKGROUND
```

```
[LAMBDA NIL
```

```
; Edited 13-Jun-88 11:18 by bvm
```

```
;; Called from background menu to turn lafite on.
```

```

(COND
  (\LAFITE.ACTIVE
    (TOTOPW LAFITESTATUSWINDOW)
    (PROMPTPRINT "Lafite is already on.))
  (T (\LAFITE.PROCESS \[, (FUNCTION \LAFITE.START.PROC)
    \[, DEFAULTMAILFOLDERNAME NIL)
    'LAFITE])

```

```
; Already on!
```

```
(\LAFITE.OFF
```

```
[LAMBDA NIL
```

```
; Edited 6-Jun-88 19:53 by bvm
```

```
;; If Lafite is on, turn it off. Returns T if successfully off
```

```

(OR (NULL \LAFITE.ACTIVE)
  (PROGN
    (COND

```

```
; Lafite was on
```

; Zap the initializer

; Edited 10-Aug-89 17:21 by bvm

```
; Used by anyone creating browsers or otherwise concerned with
; changes to \ACTIVE\AFITE\FOLDERS
; Used by \LAFITE.CLOSE.OTHER.FOLDERS or anyone who
; needs access to multiple arbitrary folders
```

; Edited 3-Jun-92 17:46 by bvm

```

seif (EQ FIELD :ORIGINAL)
then (LIST "Original-" (FUNCTION

```

```

LAFITE.HANDLE.ORIGINAL.FIELD
))
else (LIST FIELD (FUNCTION
LAFITE.EAT.UNDESIRABLE.FIELD])
; Clear cached menus
(for VAR in LAFITEMENUVARS do
  (SET VAR NIL))
(for FOLDER in \ACTIVELAFITEFOLDERS do (for W in (fetch (MAILFOLDER FOLDERDISPLAYWINDOWS) of FOLDER)
  when (WINDOWP W) do (WINDOWPROP W 'TEDIT.MENU.COMMANDS
    \LAFITE.DISPLAY.COMMANDS)
    (WINDOWPROP W 'TEDIT.MENU NIL)))

(LET [ (OLDABBREVS \LAFITE.PSEUDO.DEVICES)
      (NEWABBREVS (DREMOVE
        NIL
        (for PAIR in LAFITE.HOST.ABBREVS bind FIELDS NAMES
          collect (if [AND [for STR in (SETQ NAMES (if (LISTP (SETQ NAMES (CAR PAIR)))
            then (APPEND NAMES)
            else (LIST NAMES)))
          always (AND (STRINGP STR)
            (EQ (NTHCHARCODE STR -1)
              (CHARCODE ":"))
            (for TAIL on (SETQ FIELDS (UNPACKFILENAME.STRING (CADR PAIR)))
              by (CDDR TAIL) always (FMEMB (CAR TAIL)
                ' (HOST DIRECTORY DEVICE)
                ; CAR is list of pseudo-devices (must be strings ending in colon),
                ; CDR is unpacked fields
                (CONS NAMES FIELDS)
            else (PRINTOUT PROMPTWINDOW T "Bad host abbreviation: " PAIR)
              NIL]
        (if [NOT (PROG1 (EQUAL (CDR \LAFITE.PSEUDO.DEVICES)
          NEWABBREVS)
            (SETQ \LAFITE.PSEUDO.DEVICES (AND NEWABBREVS (CONS (CONS NIL (fetch UNPACKEDHOST&DIR
              of \LAFITEDEFAULTHOST&DIR))
              NEWABBREVS)))]
          then (\LAFITE.RECOMPUTE.FOLDER.NAMES OLDABBREVS)))
; Finally, reauthenticate user, in case there is any mode-specific caching we care about.
(LAFITECLEARCACHE])

```

(\LAFITE.PROCESS

```

[LAMBDA (FORM NAME ALLOWLOGOUT RESTARTABLE) (* bvm%: "25-Mar-84 17:16")

```

;;; Creates a process running FORM which by default is not restartable and will not permit LOGOUT while it is running

```

(ADD.PROCESS FORM 'NAME NAME 'RESTARTABLE (OR RESTARTABLE 'NO)
  'BEFOREEXIT
  (COND
    (ALLOWLOGOUT NIL)
    (T 'DON'T]))

```

(\LAFITE.START.ABORT

```

[LAMBDA NIL (* bvm%: "25-Mar-84 16:44")
  (COND
    ((AND RESETSTATE (NEQ \LAFITE.ACTIVE T))
      (CLOSEW LAFITESTATUSWINDOW)
      (SETQ LAFITESTATUSWINDOW (SETQ \LAFITE.ACTIVE)))

```

(\LAFITE.QUIT

```

[LAMBDA (ITEM MENU BUTTON) (* bvm%: " 7-Nov-84 11:48")
  (COND
    ((EQ BUTTON 'MIDDLE)
      (\LAFITE.SUBQUIT ITEM MENU))
    (T (\LAFITE.PROCESS (LIST (FUNCTION \LAFITE.QUIT.PROC)
      (KWOTE ITEM)
      (KWOTE MENU))
      'LAFITEQUIT]))

```

(\LAFITE.RESTART

```

[LAMBDA (ITEM MENU) ; Edited 8-Jun-88 12:08 by bvm
  (COND
    ((\LAFITE.QUIT.PROC ITEM MENU)
      (LAFITE :ON]))

```

(\LAFITE.SUBQUIT

```

[LAMBDA (ITEM MENU) ; Edited 13-Jun-88 10:49 by bvm
  (PROG ((MODES (\LAFITE.COMPUTE.MODE.COMMANDS))
    (ITEMS LAFITESUBQUITMENUITEMS)
    COMMAND LOGINS LOGINITEM)
    [COND
      ((OR (NOT (EQUAL \LAFITE.MODE.CHOICES (SETQ \LAFITE.MODE.CHOICES MODES)))
        (NULL LAFITESUBQUITMENU))
        ; Recompute menu
        (if (CDR MODES)
          then
            ; Only include modes if there's more than one--boring otherwise

```

```

      (SETQ ITEMS (APPEND ITEMS MODES)))
    (if [AND (SETQ LOGINITEM (LA.MENU.ITEM (FUNCTION \LAFITE.LOGIN)
      ITEMS))
      (SETQ LOGINS (for MODE in LAFITEMODELST bind FN when (AND (LISTP (CDR MODE))
        (SETQ FN (fetch (LAFITEOPS LOGIN)
          of MODE)))
        collect ` (, (CONCAT (CAR MODE)
          " Login")
          ',FN
          , (CONCAT "Change the name and/or password for " (CAR MODE)
            " operation."])
      then
        (SETQ ITEMS (DSUBST (LIST (CAR LOGINITEM)
          (CADR LOGINITEM)
          (CADDR LOGINITEM)
          (APPEND (CADDR LOGINITEM)
            LOGINS))
            LOGINITEM ITEMS)))
      (SETQ LAFITESUBQUITMENU (LAFITE.CREATE.MENU ITEMS "Mode Change"]
    (COND
      ((LISTP (SETQ COMMAND (MENU LAFITESUBQUITMENU))) ; Change mode command
        (LAFITEMODE (CAR COMMAND)))
      (COMMAND ; Arbitrary other command
        (LAFITE.PROCESS ` (, COMMAND ', ITEM ', MENU)
          'LAFITEQUIT]))

```

(\LAFITE.QUIT.PROC

; Edited 3-May-89 19:19 by bvm

```

  [LAMBDA (ITEM MENU)
    (RESETLST
      (LA.RESETSHADE ITEM MENU)
      (OBTAIN.MONITORLOCK \LAFITE.BROWSELOCK NIL T)
      (OBTAIN.MONITORLOCK \LAFITE.MAINLOCK NIL T)
      (PROG ((HOW? 0)
        MENUREG)
        (OR \LAFITE.ACTIVE (RETURN T))
        (COND
          ([for WINDOW in LAFITECURRENTEDITORWINDOWS do (COND
            ((OPENWP WINDOW)
              (SETQ $$VAL (TOTOPW WINDOW)))
            ([WINDOWP (SETQ WINDOW (WINDOWPROP WINDOW
              'ICONWINDOW]
              (SETQ $$VAL (EXPANDW WINDOW]
            (printout PROMPTWINDOW T "There are open/undelivered message composition windows -- can't
              quit")
            (RETURN)))
          [for FOLDER in \ACTIVE\LA\FITE\FOLDERS when (fetch (MAILFOLDER BROWSERWINDOW) of FOLDER)
            do (SETQ HOW? (LOGOR HOW? (LAB.UPDATE.NEEDED? FOLDER]
          [COND
            ((EQ HOW? 0) ; Nothing to do but close them
              (SETQ HOW? (FUNCTION \LAFITE.FINISH.UPDATE)))
            (T
              ;; Determine what to do with open browsers. Essentially same as the CLOSEFN for a browser, but we offer a single menu
              ;; that offers all the choices that the most particular window might need
              (SETQ HOW? (\LAFITE.CREATE.MENU [APPEND (fetch (MENU ITEMS) of (LAB.CHOOSE.UPDATE.MENU HOW?
                :CLOSE))
                ' ("Don't Quit" NIL "Abort the Quit command"]
                "How should browsers be closed?" T))
              (SETQ MENUREG (WINDOWPROP (WFROMMENU MENU)
                'REGION))
              (SETQ HOW? (OR (MENU HOW? (create POSITION
                XCOORD _ (- (fetch (REGION RIGHT) of MENUREG)
                  (fetch (MENU IMAGEWIDTH) of HOW?))
                YCOORD _ (- (fetch (REGION BOTTOM) of MENUREG)
                  (fetch (MENU IMAGEHEIGHT) of HOW?)))
                T)
              (RETURN NIL]
          [for FOLDER in (APPEND \ACTIVE\LA\FITE\FOLDERS) bind BROWSERWINDOW
            do (COND
              ((NOT (SETQ BROWSERWINDOW (fetch (MAILFOLDER BROWSERWINDOW) of FOLDER)))
                (\LAFITE.CLOSE.FOLDER FOLDER T))
              (T (CL:FUNCALL HOW? BROWSERWINDOW FOLDER :EXIT]
          (SETQ \ACTIVE\LA\FITE\FOLDERS)
          (AND \LAFITE.OUTBOX (CLOSEW (fetch OBWINDOW of \LAFITE.OUTBOX)))
          (COND
            (\LAFITEPROFILECHANGED (\LAFITE.WRITE.PROFILE)))
          (SETQ AROUNDEXITFNS (REMOVE (FUNCTION LAFITE.AROUNDEXIT)
            AROUNDEXITFNS))
          (if NIL
            then
              (for FILE in \LAFITE.TEMPFILES do
                (CLOSEF? FILE)
                (DELFIL FILE))
              (SETQ \LAFITE.TEMPFILES)
              (SETQ \LAFITE.ACTIVE NIL)
              (DEL.PROCESS (FUNCTION LAFITEMAILWATCH))
              (* (* ; "Don't remove this, since it continues to look at login
                changes") (SETQ \AFTERLOGINFNS
                  (REMOVE (QUOTE \LAFITE.AFTERLOGIN)

```

```

\AFTERLOGINFNS)) (LAFITECLEARCACHE))

(COND
  ((OPENWP LAFITESTATUSWINDOW)
   (CLOSEW LAFITESTATUSWINDOW)))
[SETQ \LAFITE.MODE.CHOICES (SETQ LAFITEFORMFILES (SETQ \LAFITE.LAST.STATUS (SETQ
\LAFITEDFAULTHOST&DIR
(SETQ
LAFITE.UPDATE.MENU.HASH
(SETQ LAFITEMAINMENU
(SETQ
LAFITESTATUSWINDOW
NIL])

(for VAR in LAFITEMENUVARS do ; Clear cached menus
  (SET VAR NIL))
(RETURN T)))]

```

(\LAFITEDEFAULTHOST&DIR

; Edited 10-Feb-89 12:53 by bvm

```

[LAMBDA (HOST&DIR)
  (PROG ((*UPPER-CASE-FILE-NAMES* NIL)
    (OLDHOST&DIR (fetch PACKEDHOST&DIR of \LAFITEDEFAULTHOST&DIR))
    UNPACKED CANONICAL)
    (COND
      ((OR (NULL HOST&DIR)
        (STRING-EQUAL OLDHOST&DIR HOST&DIR))
        (RETURN HOST&DIR))
      (COND
        ((NULL (SETQ CANONICAL (DIRECTORYNAME HOST&DIR)))
         (printout PROMPTWINDOW T "Warning: " HOST&DIR " not a recognized directory"))
        (T (SETQ HOST&DIR CANONICAL)))
      (SETQ UNPACKED (UNPACKFILENAME.STRING HOST&DIR))
      (SETQ \LAFITEDEFAULTHOST&DIR (create DEFAULTHOST&DIR
        PACKEDHOST&DIR _ (PACKFILENAME.STRING UNPACKED)
        UNPACKEDHOST&DIR _ UNPACKED))
      (RETURN OLDHOST&DIR))
  )

```

; User wants the value, or there is no change
; now make sure its a legitimate HOST&DIR

; set both the visible and invisible variables

(\LAFITEDEFAULTHOST&DIR

(* bvm%: "22-Feb-84 16:27")

[LAMBDA (HOST&DIR)

;;; Temporary definition until we can do it right

(SETQ LAFITEDEFAULTHOST&DIR HOST&DIR)

(\MAKELAFITECOMMANDWINDOW

(* bvm%: " 5-May-86 16:23")

```

[LAMBDA NIL
  (PROG ((FONTHEIGHT (FONTPROP LAFITEMENUFONT 'HEIGHT))
    MENUW MENUWREGION POSITION HEIGHT WIDTH STATUSWINDOW)
    [SETQ MENUW (MENUWINDOW (SETQ LAFITEMAINMENU (create MENU
      ITEMS _ LAFITECOMMANDMENUITEMS
      WHENSELECTEDFN _ (FUNCTION NIL)
      CENTERFLG _ T
      TITLE _ (OR (\LAFITE.MODE.TITLE)
        "L a f i t e")
      MENUFONT _ LAFITEMENUFONT
      MENUTITLEFONT _ LAFITETITLEFONT]
      (SETQ WIDTH (IMAX [fetch (REGION WIDTH) of (SETQ MENUWREGION (WINDOWPROP MENUW 'REGION)
        LAFITESTATUSWINDOWMINWIDTH))
      [SETQ HEIGHT (HEIGHTIFWINDOW (FIX (FTIMES FONTHEIGHT 1.5])
      (SETQ POSITION (OR LAFITESTATUSWINDOWPOSITION (GETBOXPOSITION WIDTH (IPLUS HEIGHT (fetch (REGION HEIGHT
        )
        of MENUWREGION))
        NIL NIL NIL "Specify position of the Lafite
        Command Menu."))
      [SETQ STATUSWINDOW (CREATEW (MAKEWITHINREGION (create
        REGION
        LEFT _ (fetch (POSITION XCOORD) of POSITION)
        BOTTOM _ (IPLUS (fetch (POSITION YCOORD)
          of POSITION)
          (fetch (REGION HEIGHT)
            of MENUWREGION))
        WIDTH _ WIDTH
        HEIGHT _ HEIGHT]
        (DSPFONT LAFITEMENUFONT STATUSWINDOW)
        (ATTACHWINDOW MENUW STATUSWINDOW 'BOTTOM)
        [WINDOWPROP STATUSWINDOW 'BUTTONEVENTFN (FUNCTION (LAMBDA (WINDOW)
          (COND
            ((LASTMOUSESTATE (NOT UP))
             (SETQ \LAFITE.LAST.STATUS)
              (\LAFITE.WAKE.WATCHER]
            (WINDOWPROP STATUSWINDOW 'MAINWINDOWMINSIZE (CONS 0 HEIGHT))
            (WINDOWPROP STATUSWINDOW 'MAINWINDOWMAXSIZE (CONS MAX.SMALLP HEIGHT))
            (OPENW STATUSWINDOW)
            (CLEARW STATUSWINDOW)
            [WINDOWPROP STATUSWINDOW 'YPOS (IDIFFERENCE (DSPYPOSITION NIL STATUSWINDOW)
              (FIXR (FTIMES FONTHEIGHT 0.2])
            (RETURN (SETQ LAFITESTATUSWINDOW STATUSWINDOW))
  )

```

(EXTRACTMENUCOMMAND

[LAMBDA (ITEM) ; Edited 3-Sep-87 15:28 by bvm:

;; Extract the "command" from a menu item. ITEM is in form (label form helpstring)

```
(COND
  ((NLISTP ITEM)
   ITEM)
  ((CADR ITEM)
   (EVAL (CADR ITEM)))
  (T (CAR ITEM]))
```

(DOMAINLAFITECOMMAND

[LAMBDA (ITEM MENU BUTTON) ; Edited 3-Sep-87 18:00 by bvm:

```
(CL:FUNCALL (EXTRACTMENUCOMMAND ITEM)
  ITEM MENU BUTTON])
```

(LAFITE.TOGGLE.SERVER.TRACE

[LAMBDA NIL ; Edited 24-Jul-92 15:14 by bvm

```
(LET [(CHOICE (MENU (create MENU
  ITEMS _ ' ("Quiet" 0 "Don't report server")
            ("Report" T "Just report server in prompt window")
            ("Require Confirmation" :ASK "Require approval for posting server
            choice"))
  CENTERFLG _ T
  TITLE _ "Trace Posting Server?"])
  (if CHOICE
    then (PRINTOUT PROMPTWINDOW T "NSMAIL-TRACE-SERVERS* = " (SETQ *NSMAIL-TRACE-SERVERS*
      (AND (NEQ CHOICE 0)
           CHOICE]))
```

)

(PUTPROPS LAFITE ARGNAMES (NIL (ON/OFF MAILFILE . OPTIONS) . U))

(DEFINEQ

(LAFITEMODE

[LAMBDA (MODE) ; Edited 9-May-88 15:53 by bvm

```
(PROG1 (fetch LAFITEMODE of \LAFITEMODE)
  [COND
    (MODE (while [LITATOM (CDR (SETQ MODE (OR (ASSOC MODE LAFITEMODELST)
      (\ILLEGAL.ARG MODE])
    do (SETQ MODE (CDR MODE)))
  (COND
    ((NEQ (fetch LAFITEMODE of \LAFITEMODE)
      (fetch LAFITEMODE of (SETQ \LAFITEMODE MODE)))
     ; Mode changed, kick mailwatcher
    (COND
      (\LAFITE.ACTIVE (\LAFITE.SHOW.MODE)
        (WITH.MONITOR \LAFITE.MAILSERVERLOCK (\LAFITE.WAKE.WATCHER]))))
```

(\LAFITE.INFER.MODE

[LAMBDA NIL (* bvm%: "21-Dec-84 22:43")

```
(COND
  ([SETQ \LAFITEMODE (OR (AND LAFITEMODEDEFAULT (ASSOC LAFITEMODEDEFAULT LAFITEMODELST))
    (PROG [(CHOICES (for x in LAFITEMODELST collect x when (LISTP (CDR X)
      (RETURN (AND CHOICES (NULL (CDR CHOICES))
        (CAR CHOICES]
    (AND LAFITESTATUSWINDOW (\LAFITE.SHOW.MODE))
    \LAFITEMODE])
```

(\LAFITE.SHOW.MODE

[LAMBDA NIL (* bvm%: "30-Oct-84 16:53")

```
(PROG ((TITLE (\LAFITE.MODE.TITLE))
  (MENU LAFITEMAINMENU))
  (COND
    (TITLE (replace (MENU TITLE) of MENU with TITLE)
      (UPDATE/MENU/IMAGE MENU)
      (REDISPLAYW (WFROMMENU MENU]))
```

(\LAFITE.MODE.TITLE

[LAMBDA NIL ; Edited 5-May-88 12:24 by bvm

;;; If user wants mode shown in Lafite status window, this returns a suitable title for that window

```
(AND \LAFITEMODE (LAFITE.SHOW.MODE.P)
  (CONCAT "L a f i t e (" (fetch LAFITEMODE of \LAFITEMODE)
    ") "])
```

(LAFITE.SHOW.MODE.P

[LAMBDA NIL

; Edited 5-May-88 12:02 by bvm

;; True if the current mode should be displayed.

```
(SELECTQ LAFITESHOWMODEFLG
  (ALWAYS T)
  (NIL NIL)
  (> [for X in LAFITEMODELST count (LISTP (CDR (LISTP X)
    1]))
```

(LAFITE.ALL.MODES.P

[LAMBDA (OP)

; Edited 9-May-88 17:15 by bvm

;; True if we should use all modes for the operation designated by OP. Currently known ops are :POLL, :GETMAIL, :ANSWER.

```
(if (LISTP LAFITE.USE.ALL.MODES)
  then (FMEMB OP LAFITE.USE.ALL.MODES)
  else (OR (EQ LAFITE.USE.ALL.MODES T)
    (EQ LAFITE.USE.ALL.MODES OP))
```

(SET.LAFITE.MODE.INTERACTIVELY

[LAMBDA NIL

; Edited 13-Jun-88 10:36 by bvm

;; Called from background menu to set Lafite's mode.

```
(LET ((*PRINT-CASE* :UPCASE)
  CHOICE)
  (CL:FORMAT PROMPTWINDOW "~2%%Lafite's current mode is ~A.
    Use menu to specify the new mode.~@[
    Mode affects SendMail only; mail is still retrieved in all modes.~]"
    (if \LAFITEMODE
      then (fetch (LAFITEOPS LAFITEMODE) of \LAFITEMODE)
      else "not set")
    (EQ LAFITE.USE.ALL.MODES T))
  (AND (SETQ CHOICE (MENU (\LAFITE.CREATE.MENU (\LAFITE.COMPUTE.MODE.COMMANDS)
    "Mode choices")))
    (LAFITEMODE (CAR CHOICE]))
```

(\LAFITE.COMPUTE.MODE.COMMANDS

[LAMBDA NIL

; Edited 13-Jun-88 10:27 by bvm

;; Returns a list of menu items "xx Mode" for changing Lafite's mode. The result of calling MENU on this is a list whose car is the desired mode.

```
(for MODE in LAFITEMODELST when (LISTP (CDR MODE)) collect `((CONCAT (CAR MODE)
  " Mode")
  `((, (CAR MODE))
  "Change to this mode of mail sending/retrieving"))
```

)

(PUTPROPS LAFITEMODELST VARTYPE ALIST)

(ADDTovar LAFITEMODELST)

(RPAQ? \LAFITEMODE)

(RPAQ? \LAFITE.AUTHENTICATION.FAILURE)

(RPAQ? LAFITE.BACKGROUND.ITEM

```
'("Mail" '(\LAFITE.MESSAGEFORM NIL NIL 'LEFT)
  "Send an ordinary message. See subcommands for other operations."
  (SUBITEMS ("Turn Lafite on" '(\LAFITE.ON.FROM.BACKGROUND)
    "Turn on Lafite, bringing up status window and browsing default folder.")
    ("Send Mail" '(\LAFITE.MESSAGEFORM)
    "Send a message. Prompts for type of message.")
    ("Set Lafite Mode" '(\SET.LAFITE.MODE.INTERACTIVELY)
    "Set or change Lafite's mail protocol mode.")))
```

(DEFINEQ

(\LAFITE.LOGIN

[LAMBDA NIL

; Edited 8-Jun-88 12:50 by bvm

```
(if [AND (\LAFITE.OFF)
  (LAFITE.PROMPT.FOR.LOGIN NIL (FUNCTION (LAMBDA NIL
    (SETQ LAFITEDEFAULTHOST&DIR (TTYINPROMPTFORWORD
      "Host&dir for mail files: "
      (OR LAFITEDEFAULTHOST&DIR
        LOGINHOST/DIR)
      "Specify, in form {host}<dir>
      the location of the mail files
      for the user you just logged
      in.")]

  then (LAFITE :ON])
```

(\LAFITE.LOGIN.NOESTART

[LAMBDA NIL

; Edited 7-Jun-88 19:33 by bvm

(\LAFITE.PROMPT.FOR.LOGIN])

(\LAFITE.PROMPT.FOR.LOGIN

[LAMBDA (HOST AFTERLOGINFN)

; Edited 8-Jun-88 12:42 by bvm

;; Prompt for login to HOST in a little window near the status window. If login is successful, then apply AFTERLOGINFN to HOST while the
 ;; ttydisplaystream is still in the interaction window.

(RESETLST

```
[LET* ((TOPLEFT (OR LAFITESTATUSWINDOWPOSITION (CURSORPOSITION)))
      (HEIGHT (HEIGHTIFWINDOW (TIMES 5 (FONTPROP DEFAULTFONT 'HEIGHT))
                               NIL 8))
      (W (CREATEW (MAKEWITHINREGION (create REGION
                                           LEFT _ (fetch XCOORD of TOPLEFT)
                                           BOTTOM _ (- (fetch YCOORD of TOPLEFT)
                                                         HEIGHT)
                                           WIDTH _ 400
                                           HEIGHT _ HEIGHT))
                NIL 8)))
      (RESETSAVE NIL (LIST 'CLOSEW W))
      (RESETSAVE (TTYDISPLAYSTREAM W))
      (WINDOWADDPROP W 'CLOSEFN (FUNCTION (LAMBDA (WINDOW)
                                           (\CARET.DOWN)
                                           (LET [(P (WINDOWPROP WINDOW 'PROCESS)]
                                                (if (AND P (NEQ P (THIS.PROCESS)))
                                                    then
                                                    ; user explicit close--kill the process
                                                    (DEL.PROCESS P)
                                                    )
                                                )
                                           (RESETSAVE (TTY.PROCESS T))
                                           (AND (LOGIN HOST)
                                                (OR (NULL AFTERLOGINFN)
                                                  (CL:FUNCALL AFTERLOGINFN HOST))))))])
```

(\LAFITE.REAUTHENTICATE

[LAMBDA (ITEM MENU)

(DECLARE (IGNORE ITEM MENU))

; Edited 18-Jul-88 12:25 by bvm

;; Reauthenticate using the current login, rather than prompting for anything new.

(\LAFITE.AFTERLOGIN NIL])

)

(RPAQ? LAFITEPROFILEVARS

```
((LAFITEDEFAULTHOST&DIR NIL)
 (LAFITE.SIGNATURE NIL)
 (LAFITEBUFFERSIZE 20)
 (LAFITEIFFFROMMETHENSEENFLG T)
 [LAFITEMENUFONT (FONTCREATE ' (HELVETICA 10 BOLD)]
 [LAFITETITLEFONT (FONTCREATE ' (HELVETICA 12 BOLD)]
 [LAFITEDISPLAYFONT (FONTCREATE ' (TIMESROMAN 10)]
 [LAFITEFIXEDWIDTHFONT (COND ((EQ (CHARWIDTH (CHARCODE "i")
                                           DEFAULTFONT)
                                   (CHARWIDTH (CHARCODE "W")
                                           DEFAULTFONT))
                               ; Yes, user has not changed default to a variable width font
                               (T (FONTCREATE ' (GACHA 10]
 (LAFITEHARDCOPYFONT LAFITEDISPLAYFONT)
 [LAFITEBROWSERFONT (FONTCREATE ' (GACHA 10]
 [LAFITEMSGICONFONT (FONTCREATE ' (HELVETICA 8]
 (LAFITE.FOLDER.MENU.FONT NIL)
 (LAFITEINFO.NAME "Lafite.info")
 (DEFAULTMAILFOLDERNAME "Active.mail")
 (LAFITEMAIL.EXT "mail")
 (LAFITESTATUSWINDOWMINWIDTH 200)
 (LAFITESTATUSWINDOWPOSITION '(735 . 650))
 (LAFITE.DONT.DISPLAY.HEADERS NIL)
 (LAFITE.DONT.FORWARD.HEADERS NIL)
 (LAFITE.DONT.HARDCOPY.HEADERS NIL)
 (LAFITEDEBUGFLG NIL)
 (LAFITEMODEDEFAULT NIL)
 (LAFITESHOWMODEFLG T)
 (LAFITE.USE.ALL.MODES T)))
```

; Yes, user has not changed default to a variable width font

```
(RPAQ? LAFITEDEFAULTHOST&DIR NIL)
(RPAQ? LAFITE.SIGNATURE NIL)
(RPAQ? LAFITEBUFFERSIZE 20)
(RPAQ? LAFITEIFFFROMMETHENSEENFLG T)
(RPAQ? LAFITEMENUFONT (FONTCREATE ' (HELVETICA 10 BOLD)))
(RPAQ? LAFITETITLEFONT (FONTCREATE ' (HELVETICA 12 BOLD)))
```

(RPAQ? LAFITEDEFAULTHOST&DIR NIL)

(RPAQ? LAFITE.SIGNATURE NIL)

(RPAQ? LAFITEBUFFERSIZE 20)

(RPAQ? LAFITEIFFFROMMETHENSEENFLG T)

(RPAQ? LAFITEMENUFONT (FONTCREATE ' (HELVETICA 10 BOLD)))

(RPAQ? LAFITETITLEFONT (FONTCREATE ' (HELVETICA 12 BOLD)))

```
(RPAQ? LAFITEDISPLAYFONT (FONTCREATE '(TIMESROMAN 10)))
```

```
(RPAQ? LAFITEFIXEDWIDTHFONT
[COND ((EQ (CHARWIDTH (CHARCODE "i")
                     DEFAULTFONT)
           (CHARWIDTH (CHARCODE "w")
                     DEFAULTFONT))
```

; Yes, user has not changed default to a variable width font

```
    DEFAULTFONT)
(T (FONTCREATE '(GACHA 10))
```

```
(RPAQ? LAFITEHARDCOPYFONT LAFITEDISPLAYFONT)
```

```
(RPAQ? LAFITEBROWSERFONT (FONTCREATE '(GACHA 10)))
```

```
(RPAQ? LAFITEMSGICONFONT (FONTCREATE '(HELVETICA 8)))
```

```
(RPAQ? LAFITE.FOLDER.MENU.FONT NIL)
```

```
(RPAQ? LAFITEINFO.NAME "Lafite.info")
```

```
(RPAQ? DEFAULTMAILFOLDERNAME "Active.mail")
```

```
(RPAQ? LAFITEMAIL.EXT "mail")
```

```
(RPAQ? LAFITESTATUSWINDOWMINWIDTH 200)
```

```
(RPAQ? LAFITESTATUSWINDOWPOSITION '(735 . 650))
```

```
(RPAQ? LAFITE.DONT.DISPLAY.HEADERS NIL)
```

```
(RPAQ? LAFITE.DONT.FORWARD.HEADERS NIL)
```

```
(RPAQ? LAFITE.DONT.HARDCOPY.HEADERS NIL)
```

```
(RPAQ? LAFITEDEBUGFLG NIL)
```

```
(RPAQ? LAFITEMODEDEFAULT NIL)
```

```
(RPAQ? LAFITESHOWMODEFLG T)
```

```
(RPAQ? LAFITE.USE.ALL.MODES T)
```

```
(RPAQ? LAFITERANDOMGLOBALS ((UNSUPPLIEDFIELDSTR "---")
                              (LAFITEBUSYWAITTIME 1000)
                              (LAFITEITEMBUSYSHADE 43605)
                              (LAFITEEOL "
")))
"
```

```
(RPAQ? UNSUPPLIEDFIELDSTR "---")
```

```
(RPAQ? LAFITEBUSYWAITTIME 1000)
```

```
(RPAQ? LAFITEITEMBUSYSHADE 43605)
```

```
(RPAQ? LAFITEEOL "
")
```

```
(RPAQ? LAFITEMARKS
((SEENMARK (CHARCODE SP))
 (UNSEENMARK (CHARCODE ?))
 (MOVETOMARK (CHARCODE m))
 (FORWARDMARK (CHARCODE f))
 (ANSWERMARK (CHARCODE a))
 (HARDCOPYBATCHMARK (CHARCODE H))
 (HARDCOPYMARK (CHARCODE h))
 (HEARDMARK (CHARCODE @))))
```

```
(RPAQ? SEENMARK (CHARCODE SP))
```

```
(RPAQ? UNSEENMARK (CHARCODE ?))
```

```
(RPAQ? MOVETOMARK (CHARCODE m))
```

```
(RPAQ? FORWARDMARK (CHARCODE f))
```

```
(RPAQ? ANSWERMARK (CHARCODE a))
```

```
(RPAQ? HARDCOPYBATCHMARK (CHARCODE H))
```

```
(RPAQ? HARDCOPYMARK (CHARCODE h))
```

```
(RPAQ? HEARDMARK (CHARCODE @))
```

```
(RPAQ? LAFITECOMMANDMENUITEMS (("Browse" '\LAFITE.BROWSE "Browse a mail file; MIDDLE for subcommands")
 ("Send Mail" '\LAFITE.MESSAGEFORM "Open a message composition window; MIDDLE
for choice of forms"))
```

```
("Quit" '\LAFITE.QUIT "Update and close all mail files and stop Lafite")))
```

(RPAQQ LAFITEUPDITEMENUITEMS

```
((("Do Hardcopy Only" '\LAFITE.HARDCOPYONLY.PROC "Will print batched hardcopy but not update file")
("Write out changes only" '\LAFITE.UPDATE.PROC "Will update physical file to reflect new marks and
deletions")
("Update table of contents only" (FUNCTION \LAFITE.UPDATE.PROC)
"Write table of contents file to speed next browse of this folder")
("Expunge deleted messages" '\LAFITE.EXPUNGE.PROC "Will rewrite mail file, expunging all deleted
messages")
("Write changes in sorted order" '\LAFITE.EXPUNGE.PROC "Will rewrite mail file so that the messages are
permanently stored in the order in which they now appear in the browser.")
("Expunge & Write out changes (sorted)" '\LAFITE.EXPUNGE.PROC "Will rewrite mail file, expunging deleted
messages and writing writing the rest in the order in which they now appear in the browser.")
("Just close" '\LAFITE.FINISH.UPDATE "Just close the window - don't touch the mail file.")
("Just shrink" '\LAFITE.FINISH.UPDATE "Just shrink the window - don't touch the mail file.")))
```

(RPAQQ LAFITESUBQUITMENUITEMS

```
((("Quit" '\LAFITE.QUIT "Turn Lafite off")
("Restart" '\LAFITE.RESTART "Turn Lafite off then back on")
("Login" '\LAFITE.LOGIN "Change the global username/password and restart Lafite with the new user."
(SUBITEMS ("Just re-authenticate" '\LAFITE.REAUTHENTICATE "Re-authenticate currently logged-in
user.")
("Login without restarting" '\LAFITE.LOGIN.NOESTART "Change the global login but don't
restart Lafite (keep the same folders open, etc)")
("NS Login" '\NSMAIL.LOGIN "Change the name and/or password for NS operation.")))
("Recache" '\LAFITE.COMPUTE.CACHED.VARS "Make Lafite recompute cached information based on current
variable settings")
("Server trace" '\LAFITE.TOGGLE.SERVER.TRACE "Change setting of *NSMAIL-TRACE-SERVERS*")))
```

```
(RPAQQ ANOTHERFOLDERMENUITEM ("** Other Folder **" '%##ANOTHERFILE## "You will be asked to specify another
mail filename"))
```

```
(RPAQQ? LAFITESTATUSWINDOW )
```

```
(RPAQQ? \ACTIVE\LAFFITEFOLDERS )
```

```
(RPAQQ? \LAFFITE.TEMPFILES )
```

```
(RPAQQ? \LAFFITE.MODE.CHOICES )
```

```
(RPAQQ? LAFITESUBQUITMENU )
```

```
(ADDTOTVAR LAFITEMENUVARS LAFITESUBQUITMENU)
```

```
(RPAQQ? \LAFFITE.ACTIVE )
```

```
(RPAQQ? \LAFFITE.READY )
```

```
(RPAQQ? \LAFFITEDEFAULTHOST&DIR )
```

```
(RPAQQ? \LAFFITE.ACTIVE.MODES )
```

```
(RPAQQ? \LAFFITE.CURRENT.USER )
```

```
(RPAQQ? LAFITE.USER.INFO )
```

```
(RPAQQ? *LAFFITE-WELL-KNOWN-MODES* )
```

```
(RPAQQ? *LAFFITE-LOGGING-IN* )
```

```
(ADDTOTVAR \SYSTEMCACHEVARS \LAFFITE.READY \LAFFITE.ACTIVE.MODES)
```

```
(ADDTOTVAR LAFITE.PERSONAL.VARS LAFITEDEFAULTHOST&DIR LAFITE.SIGNATURE)
```

```
(DEFINEQ
```

(LAFITE.AROUNDEXIT

```
[LAMBDA (EVENT) ; Edited 9-May-88 15:57 by bvm
(SELECTQ EVENT
((BEFORELOGOUT)
(RESETLST
(for FOLDER in \ACTIVE\LAFFITEFOLDERS when (OBTAIN.MONITORLOCK (fetch (MAILFOLDER FOLDERLOCK)
of FOLDER)
T T)
do (\LAFFITE.CLOSE.FOLDER FOLDER T)))
(SETQ \LAFFITE.ACTIVE.MODES NIL))
((AFTERLOGOUT AFTERSAVEVM AFTERSYSOUT AFTERMAKESYS)
(COND
((EQ \LAFFITE.ACTIVE T)
(\LAFFITE.REINITIALIZING)
(\LAFFITE.AFTERLOGIN) ; Check for changed user
(RESTART.PROCESS 'LAFITEMAILWATCH)
(\LAFFITE.MARK.FOLDERS.OBSOLETE))))
NIL])
```

(\LAFITE.MARK.FOLDERS.OBSOLETE

[LAMBDA NIL

; Edited 7-Jun-88 16:14 by bvm

;;; On returning from LOGOUT check to see that all the mailfiles are in a consistence state -- the user might have run Laurel and screwed up Lafite's
 ;;; data, or run Lafite from another machine

```
(COND
  ((AND \ACTIVE\LA\FITE\FOLDERS (NOT \LA\FITE\READY))
    (WITH.MONITOR \LA\FITE\BROWSELOCK
      (COND
        ((NOT \LA\FITE\READY)
          (SETQ \ACTIVE\LA\FITE\FOLDERS (for FOLDER in \ACTIVE\LA\FITE\FOLDERS
            when (COND
              ((NULL (fetch (MAILFOLDER BROWSERWINDOW) of FOLDER))
                (\LA\FITE\CLOSE\FOLDER FOLDER T)
                ; Not really active, forget it
              (NIL)
              (T) ; Mark all folders as needing checking
                (if (EQ (fetch (MAILFOLDER BROWSERSTATUS) of FOLDER)
                  LAS.READY)
                  then (replace (MAILFOLDER BROWSERSTATUS)
                    of FOLDER with LAS.LOGGED.OUT))
              (T)
            collect FOLDER))
          (\LA\FITE\PROCESS (LIST (FUNCTION \LA\FITE\CHECK\FOLDERS))
            'LA\FITE\CHECK T T)))
        (SETQ \LA\FITE\READY T))
```

(\LAFITE.CHECK.FOLDERS

[LAMBDA NIL

; Edited 15-Dec-87 17:48 by bvm:

;; Background task that goes around checking that everyone's ok.

```
(\LA\FITE\READ\PROFILE T) ; Get any changes to profile that happened while logged out.
(for FOLDER in \ACTIVE\LA\FITE\FOLDERS when (EQ (fetch (MAILFOLDER BROWSERSTATUS) of FOLDER)
  LAS.LOGGED.OUT)
  do (ERSETQ (\LA\FITE\ASSURE\FOLDER\READY FOLDER))
```

(\LAFITE.ASSURE.FOLDER.READY

[LAMBDA (FOLDER)

; Edited 15-Oct-87 14:57 by bvm:

```
(WITH.MONITOR (fetch (MAILFOLDER FOLDERLOCK) of FOLDER)
  (if (EQ (fetch (MAILFOLDER BROWSERSTATUS) of FOLDER)
    LAS.LOGGED.OUT)
    then
      (PROG1 (\LA\FITE\OPEN\FOLDER FOLDER 'INPUT NIL)
        (\LA\FITE\CLOSE\FOLDER FOLDER T))
    else T)))
```

; Open and close the file. The opening code will take care of
 ; interesting conditions.

(\LAFITE.AFTERLOGIN

[LAMBDA (HOST USER)

; Edited 22-Aug-88 16:38 by bvm

;; Called when LOGIN gets new info. If HOST = NIL, this is the global login, which means we should get new data

```
(COND
  ((AND (NULL HOST)
    (NOT *LA\FITE\LOGGING-IN*))
    (LA\FITE\CLEARCACHE)
    (LET ((*LA\FITE\LOGGING-IN* T)
      (OLDUSER (CAR \LA\FITE\CURRENT\USER))
      NEWUSER OLDDATA NEWDATA)
      (if (NOT (STRING-EQUAL OLDUSER (SETQ NEWUSER (LA\FITE\USER\NAME\FROM\LOGIN NIL T)
        then ; Compute new current user
          ; Logged in user changed. Clear all those "personal" variables
          ; that would be affected
          [SETQ OLDDATA (CDR (CL:ASSOC OLDUSER LA\FITE\USER\INFO :TEST 'STRING-EQUAL))
            (for VAR in LA\FITE\PERSONAL\VARS bind VALUE when (SETQ VALUE (EVALV VAR))
              do (if OLDDATA
                then (LISTPUT OLDDATA VAR VALUE)
                else (push NEWDATA VAR VALUE))
              (SET VAR NIL))
            (if NEWDATA
              then (push LA\FITE\USER\INFO (CONS OLDUSER NEWDATA)))
          ;; Now restore any saved data for new user
          (if (SETQ NEWDATA (CL:ASSOC NEWUSER LA\FITE\USER\INFO :TEST 'STRING-EQUAL))
            then (for TAIL on (CDR NEWDATA) by (CDDR TAIL) do (SET (CAR TAIL)
              (CADR TAIL))
            (AND \LA\FITE\ACTIVE (\LA\FITE\WAKE\WATCHER])
```

)

;; misc utilities

(DEFINEQ

(LA.RESETSHADE

[LAMBDA (ITEM MENU OLDSHADE)

; Edited 23-Aug-88 12:40 by bvm

;;; Shades ITEM in MENU to indicate Lafite is busy, leaves something on resetlst to unshade it

(if ITEM
then(RESETSAVE (SHADEITEM ITEM MENU LAFITEITEMBUSYSHADE)
(LIST (FUNCTION SHADEITEM)
ITEM MENU (OR OLDSHADE WHITESHADE]))

; Don't do when some program calls without an item

(LA.MENU.ITEM

[LAMBDA (FN MENU)

; Edited 7-Jun-88 19:15 by bvm

;; Returns the menu item executed by FN in MENU. This beats searching by the label because someone might want to change the label. Menu
;; items are assumed to be of the form (label 'fn --). MENU can also be just a list of items.(find ITEM in (OR (LISTP MENU)
(fetch (MENU ITEMS) of MENU))
suchthat (EQ FN (CADR (LISTP (CADR ITEM))))**(NTHMESSAGE**[LAMBDA (MESSAGES N)
(ELT MESSAGES N)]

(* bvm%: " 3-Jan-84 12:11")

(\LAFITE.MAKE.MSGARRAY

[LAMBDA (SIZE OLDARRAY OLDSIZE)

(* bvm%: " 3-Jan-84 11:07")

;;; Creates an array at least large enough to hold SIZE message descriptors. If OLDARRAY is given, its elements up to OLDSIZE are copied into the
;;; new array(PROG [(NEWARRAY (ARRAY (IMAX (+ SIZE 32)
(CEIL SIZE 64))
' POINTER]
[COND
(OLDARRAY (for I from 1 to OLDSIZE do (SETA NEWARRAY I (ELT OLDARRAY I)
(RETURN NEWARRAY))**(\LAFITE.ADDMESSAGES.TO.ARRAY**

[LAMBDA (MSGARRAY MESSAGELIST FIRSTMSG# LASTMSG#)

(* bvm%: " 3-Jan-84 11:26")

;;; Adds to MSGARRAY the messages from MESSAGELIST, which should be numbered FIRSTMSG# thru LASTMSG# --- returns a new array if
;;; MSGARRAY wasn't large enough[COND
((OR (NULL MSGARRAY)
(> LASTMSG# (ARRAYSIZE MSGARRAY)))
(SETQ MSGARRAY (\LAFITE.MAKE.MSGARRAY LASTMSG# MSGARRAY (SUB1 FIRSTMSG#]
[COND
((NEQ (fetch (LAFITEMSG %#) of (CAR MESSAGELIST))
FIRSTMSG#)
(SHOULDNT)))
(for MSG in MESSAGELIST as MSG# from FIRSTMSG# do (SETA MSGARRAY MSG# MSG))
MSGARRAY])**(\MAILFOLDER.DEFPRINT**[LAMBDA (FOLDER STREAM)
(\DEFPRINT.BY.NAME FOLDER STREAM (OR (fetch (MAILFOLDER SHORTFOLDERNAME) of FOLDER)
(fetch (MAILFOLDER VERSIONLESSFOLDERNAME) of FOLDER))
"Mail Folder on"])

; Edited 11-Dec-87 17:22 by bvm:

(\LAFITEMSG.DEFPRINT[LAMBDA (MSG STREAM)
(\DEFPRINT.BY.NAME MSG STREAM (fetch (LAFITEMSG %#) of MSG)
"Lafite msg #"])

; Edited 21-Apr-89 16:07 by bvm

(LA.POSITION.FROM.REGION

[LAMBDA (REG XOFFSET YOFFSET)

; Edited 18-Apr-89 14:43 by bvm

;; Returns a POSITION at the lower left corner of REG, optionally offset by XOFFSET and YOFFSET (T means entire window dimension).

(create POSITION
XCOORD _ (+ (fetch (REGION LEFT) of REG)
(SELECTQ XOFFSET
(NIL 0)
(T (fetch (REGION WIDTH) of REG))
XOFFSET))
YCOORD _ (+ (fetch (REGION BOTTOM) of REG)
(SELECTQ YOFFSET
(NIL 0)
(T (fetch (REGION HEIGHT) of REG))
YOFFSET])

(MAILFOLDERBUSY

```
[LAMBDA (MAILFOLDER)
  (RESETFORM (CURSOR LA.CROSSCURSOR)
    (BLOCK LAFITEBUSYWAITTIME])
)
```

(* bvm%: "29-Dec-83 18:11")

```
(RPAQ LA.CROSSCURSOR (CURSORCREATE 'X
                                'NIL 8 8))
```

;; Low level file functions

(DEFINEQ

(TOCFILENAME

[LAMBDA (FOLDER)

; Edited 1-May-89 12:58 by bvm

;; Return the name of the toc file corresponding to mail file FOLDER (a folder object or full file name).

```
(if FOLDER
  then (if (type? MAILFOLDER FOLDER)
    then (SETQ FOLDER (fetch (MAILFOLDER FULLFOLDERNAME) of FOLDER)))
  (PACKFILENAME.STRING 'EXTENSION (CONCAT (UNPACKFILENAME.STRING FOLDER 'EXTENSION)
    LAFITETOC.EXT)
    'BODY FOLDER]))
```

(DELETEMAILFOLDER

[LAMBDA (FOLDER)

; Edited 30-Sep-87 15:48 by bvm:

;;; deletes the associated files and tells Lafite to forget about that mail file

```
(PROG ((FULL (fetch (MAILFOLDER FULLFOLDERNAME) of FOLDER))
  STREAM)
  (if FULL
    then (if (AND (SETQ STREAM (fetch (MAILFOLDER FOLDERSTREAM) of FOLDER))
      (OPENP STREAM))
      then (SETQ FULL (CLOSEF STREAM)))
    (DELFIL FULL)
    (DELFIL (TOCFILENAME FULL))
    (FORGETMAILFILE (OR (fetch (MAILFOLDER SHORTFOLDERNAME) of FOLDER)
      (LA.SHORTFILENAME FULL LAFITEMAIL.EXT))
```

(\LAFITE.OPEN.FOLDER

[LAMBDA (FOLDER ACCESS IFCHANGED PROMPTFOLDER)

; Edited 5-Aug-93 19:48 by bvm

;;; For Interlisp-D it's too inefficient to keep opening and closing the mail file so we will keep it open --- If the file wants to be open for INPUT do just that
 ;;; -- it may want to be a read-only mail file -- otherwise open it for BOTH --- FILE is always a fully qualified file name

;;; IFCHANGED controls what to do if the stream has changed since we last used it. :IGNORE means don't bother checking, since I don't care. :OK
 ;;; means rebrowse as necessary, but return the stream. NIL means return NIL if there was a change, after rebrowsing.

;;; If PROMPTFOLDER is given, will prompt to confirm creating file if it doesn't exist

```
(PROG ((*UPPER-CASE-FILE-NAMES* NIL)
  (STREAM (fetch (MAILFOLDER FOLDERSTREAM) of FOLDER))
  [DESIREDACCESS (COND
    ((EQ ACCESS 'INPUT)
      ACCESS)
    (T 'BOTH]
  (RECOG (AND PROMPTFOLDER 'OLD))
  NEWLENGTH NEWDATE NEWSTDATE CHANGED WASOPEN CONDITION)
  RETRY
  (COND
    ((OR (NOT STREAM)
      (NOT (OPENP STREAM DESIREDACCESS)))
    (if STREAM
      then
        ;; Have to close file to reopen for BOTH. We do this before date fussing in the hopes that this will force the device to
        ;; really talk to the server. It might not help, though--the device's GETFILEINFO might still choose to give us an old
        ;; cached date.
        (COND
          ((OPENP STREAM)
            (CLOSEF STREAM)))
        (replace (MAILFOLDER FOLDERSTREAM) of FOLDER with (SETQ STREAM NIL)))
      (if (EQ (fetch (MAILFOLDER BROWSERSTATUS) of FOLDER)
        LAS.OUT.OF.DATE)
        then
```

; Shouldn't happen--leftover from rebrowse folder. Get out of
; here

```
(ERROR!))
[CL:MULTIPLE-VALUE-SETQ (STREAM CONDITION)
  (IGNORE-ERRORS [if (AND (EQ DESIREDACCESS 'BOTH)
    (fetch (MAILFOLDER FOLDEREOPTR) of FOLDER)
    (NEQ IFCHANGED :IGNORE))
  then
```

```

;; Opening for output in general changes the creationdate, so we won't be able to check from the new
;; stream whether the creationdate matches. So we have to obtain the current creation date without
;; opening for write--hope GETFILEINFO works well enough. We further assume that nobody
;; changed the file in the brief interval between getting this info and opening for write. This can be a
;; faulty assumption for devices that are willing to keep a file open even though the server connection
;; went away, but it seems the best we can do.
      (SETQ NEWDATE (GETFILEINFO (fetch (MAILFOLDER FULLFOLDERNAME)
                                         of FOLDER)
                                ' ICREATIONDATE])

;; Finally open it. Ask for big buffers if there's a browser for it.
      (\LAFITE.OPENSTREAM (fetch (MAILFOLDER FULLFOLDERNAME) of FOLDER)
        DESIREDACCESS NIL (FUNCTION \LAFITE.EOF)
        (fetch (MAILFOLDER BROWSERWINDOW) of FOLDER)
        'LAFITE]

(if CONDITION
  then
    (if (AND (EQ RECOG 'OLD)
              (TYPEP CONDITION 'XCL:FILE-NOT-FOUND))
      then
        (if (LAB.MOUSECONFIRM PROMPTFOLDER "Click LEFT to confirm creating ~A"
              (fetch (MAILFOLDER SHORTFOLDERNAME) of FOLDER))
          then (SETQ RECOG 'NEW)
              (SETQ ACCESS 'BOTH)
              (GO RETRY)
          else
            ; Disconfirmed the create request.
            ; Some problem opening file. Avoid break window--just abort.
            (\LAFITE.REPORT.FILE.WONT.OPEN FOLDER CONDITION)
            (ERROR!))
        ; Failed to open
      )
    ; Just couldn't find it, so maybe create it. If RECOG was NEW,
    ; we normally shouldn't be getting this error
    (if (LAB.MOUSECONFIRM PROMPTFOLDER "Click LEFT to confirm creating ~A"
          (fetch (MAILFOLDER SHORTFOLDERNAME) of FOLDER))
      then (SETQ RECOG 'NEW)
          (SETQ ACCESS 'BOTH)
          (GO RETRY)
      else
        ; Disconfirmed the create request.
        ; Some problem opening file. Avoid break window--just abort.
        (\LAFITE.REPORT.FILE.WONT.OPEN FOLDER CONDITION)
        (ERROR!))
    ; So that LA.PRINTCOUNT won't introduce CR's. Would be nice if PRINTNUM could be given a PRIN3 mode
    (LINELENGTH MAX.SMALLP STREAM))
  (SETQ NEWLENGTH (GETEOFPTR STREAM))
  (SETQ NEWESTDATE (GETFILEINFO STREAM ' ICREATIONDATE))
  (if (OR (EQ IFCHANGED :IGNORE)
          (NULL (fetch (MAILFOLDER FOLDEREOPTR) of FOLDER))
          (NULL (fetch (MAILFOLDER MESSAGEDESCRIPTORS) of FOLDER))))
    then
      (replace (MAILFOLDER FOLDEREOPTR) of FOLDER with NEWLENGTH)
      ; first time opened, just store the info
    elseif [OR (NOT (EQL NEWLENGTH (fetch (MAILFOLDER FOLDEREOPTR) of FOLDER)))
               (AND (OR NEWDATE (SETQ NEWDATE NEWESTDATE))
                     (NOT (EQL NEWDATE (fetch (MAILFOLDER FOLDERCREATIONDATE) of FOLDER))
                           ; Folder has changed since we last touched it. (Use eql instead
                           ; of = to work around as yet unknown problem where the folder's
                           ; field is NIL).
                           ; We hadn't gotten around to verifying this one after logout
                           ; yet--well, it's ok now.
                           (replace (MAILFOLDER BROWSERSTATUS) of FOLDER with LAS.READY))
                     (replace (MAILFOLDER FOLDERSTREAM) of FOLDER with STREAM)))
    then
      (RETURN (\LAFITE.FOLDER.CHANGED FOLDER STREAM DESIREDACCESS IFCHANGED)))
  (replace (MAILFOLDER FOLDERCREATIONDATE) of FOLDER with (OR NEWESTDATE 0))
  (if (EQ (fetch (MAILFOLDER BROWSERSTATUS) of FOLDER)
          LAS.LOGGED.OUT)
    then
      (replace (MAILFOLDER BROWSERSTATUS) of FOLDER with LAS.READY))
  (replace (MAILFOLDER FOLDERSTREAM) of FOLDER with STREAM))
  (RETURN STREAM])

```

(\LAFITE.REPORT.FILE.WONT.OPEN

[LAMBDA (FOLDER C FILENAME)

; Edited 22-Aug-88 19:25 by bvm

;; Called to report an error involved in trying to open FILENAME belonging to FOLDER. C is the condition. FOLDER can be NIL.

```

(LAB.FORMAT FOLDER T "Failed~@[ to open ~A because~]: ~A" (if (OR (TYPEP C 'XCL:FILE-WONT-OPEN)
                                                                (TYPEP C 'XCL:PATHNAME-ERROR)
                                                                (TYPEP C 'XCL:FILE-NOT-FOUND))
  then
    ; Report handler includes the name already (In Lyric, file-not-found is a subtype of pathname-error,
    ; but not in Medley, where we might instead want to replace both file-wont-open and file-not-found
    ; with parent file-error)
    NIL
  elseif FILENAME
  else (fetch (MAILFOLDER FULLFOLDERNAME)
              of FOLDER))

```

C])

(\LAFITE.FOLDER.CHANGED

[LAMBDA (FOLDER STREAM DESIREDACCESS IFCHANGED)

; Edited 7-Jun-88 17:17 by bvm

;; Called by LAFITE.OPEN.FOLDER when changed detected.

```

(if (AND LAFITEDEBUGFLG (EQ (fetch (MAILFOLDER BROWSERSTATUS) of FOLDER)
                              LAS.READY))
  then
    ; This is only funny if it didn't happen after logout.
    (HELP "Folder has changed--RETURN to proceed.")
  (LET* ((BROWSERWINDOW (fetch (MAILFOLDER BROWSERWINDOW) of FOLDER))

```

```

(WASOPEN (OPENWP BROWSERWINDOW))
(OLDEOF (fetch (MAILFOLDER FOLDEREOPTR) of FOLDER))
(NEWEOF (GETEOPTR STREAM))
MSG LEN ASKFLG HOW)
(ALLOW.BUTTON.EVENTS) ; Don't hoard mouse if we got called directly from mouse proc.
(replace (MAILFOLDER BROWSERSTATUS) of FOLDER with LAS.OUT.OF.DATE)
(replace (MAILFOLDER FOLDERCREATIONDATE) of FOLDER with (GETFILEINFO STREAM 'ICREATIONDATE))
(replace (MAILFOLDER FOLDEREOPTR) of FOLDER with NEWEOF)
(replace (MAILFOLDER FOLDERSTREAM) of FOLDER with STREAM)
(if (fetch (MAILFOLDER FOLDERNEEDSUPDATE) of FOLDER)
  then
    ;; Want to do something more careful here if folder has changes.
    (SETQ HOW (if (AND (>= (GETEOPTR STREAM)
                          (fetch (MAILFOLDER FOLDEREOPTR) of FOLDER))
                  (PROGN
                     ; Stream is not shorter than we remember. See if our current last
                     ; message is still at the start of a message.
                     [SETFILEPTR STREAM (fetch (LAFITEMSG BEGIN)
                                                  of (SETQ MSG (NTHMESSAGE (fetch (MAILFOLDER
                                                                                          MESSAGEDESCRIPTORS
                                                                                          )
                                                                                          of FOLDER)
                                                  (fetch (MAILFOLDER
                                                                                          %#OFMESSAGES)
                                                                                          of FOLDER])
                     (LA.READSTAMP STREAM))
                     (SETQ LEN (LA.READCOUNT STREAM))
                     (= LEN (fetch (LAFITEMSG MESSAGELENGTH) of MSG)))
                  then
                    ;; Folder contains changes, and folder has apparently only been appended to, or had changes written
                    ;; but not expunge. Offer to write out current changes before proceeding.
                    (SETQ ASKFLG T)
                    "but apparently not expunged. However, you have unsaved changes."
                  else
                    ;; There are unsaved changes, but folder looks expunged--too bad.
                    "apparently by one or more Expunges, so you can't save your changes.)))
    (COND
      ((NOT WASOPEN) ; Want the messages we print to be noticed.
       (if (NOT ASKFLG)
         then
           ; If we were shrunk, don't bother redisplaying when we expand.
           (replace (MAILFOLDER BROWSERUPDATEFROMHERE) of FOLDER with NIL))
       (OPENWP BROWSERWINDOW))
      (LAB.FORMAT FOLDER "~&Folder has changed since you last accessed it...~@[~A~]" HOW)
      (\LAFITE.REBROWSE.FOLDER FOLDER STREAM ASKFLG (NOT WASOPEN)
        DESIREDACCESS IFCHANGED]))

```

(\LAFITE.REBROWSE.FOLDER

```

[LAMBDA (FOLDER STREAM ASK CLOSEFLG DESIREDACCESS IFCHANGED DELETE-TOC)
  ; Edited 13-Sep-88 18:41 by bvm

  ;; Rebrowses FOLDER because something changed. STREAM is current stream open on folder. If ASK is true, then we put up a menu asking
  ;; whether to save current changes (caller verifies that this is interesting to do). If CLOSEFLG, then folder is shrunk at end. If DELETE-TOC is
  ;; true, the TOC is deleted before rebrowsing. DESIREDACCESS and IFCHANGED are per the change action desired of
  ;; \LAFITE.OPEN.FOLDER.

  (LET ((BROWSERWINDOW (fetch (MAILFOLDER BROWSERWINDOW) of FOLDER))
        TOCFILE)
    [if ASK
      then
        ; Offer to write out current changes before proceeding.
        (PROG NIL
          RETRY
            (LAB.FORMAT FOLDER "%Do you want to save the changes before fetching the new contents?"

              (CASE (\LAFITE.FOLDER.CHANGED.MENU FOLDER)
                (:CLOSE
                 (\LAFITE.FINISH.UPDATE BROWSERWINDOW FOLDER :EXIT)
                 (ERROR!))
                ((NIL) ; Don't try to save anything
                 )
                (T ; Try doing an Update changes only
                 [if (NOT (OPENP STREAM 'OUTPUT))
                   then (CLOSEF STREAM)
                     (CL:MULTIPLE-VALUE-BIND (NEWSTREAM CONDITION)
                      (IGNORE-ERRORS (\LAFITE.OPENSTREAM (fetch (MAILFOLDER FULLFOLDERNAME)
                                                                of FOLDER)
                                                                'BOTH NIL (FUNCTION \LAFITE.EOF)
                                                                T
                                                                'LAFITE)))
                     (if CONDITION
                       then ; Failed to open for output
                          (\LAFITE.REPORT.FILE.WONT.OPEN FOLDER CONDITION)
                          (GO RETRY))
                     (replace (MAILFOLDER FOLDERSTREAM) of FOLDER with (SETQ STREAM NEWSTREAM)
                      )
                     (replace (MAILFOLDER FOLDERCREATIONDATE) of FOLDER
                      with (GETFILEINFO STREAM 'ICREATIONDATE))
                     (replace (MAILFOLDER FOLDEREOPTR) of FOLDER with (GETEOPTR STREAM)))])

```



```

(LAB.FORMAT FOLDER "~%")
(RESETLST
  (LET ((*UPPER-CASE-FILE-NAMES* NIL)
        (LAFITEVERIFYFLG T)
        [*LAFITE-VERIFY-ACTION* (FUNCTION (LAMBDA (MSG FOLDER STREAM)
; This message not where we expected, so punt it
          (LAB.FORMAT FOLDER " (Failed on
            #~D) " (fetch (LAFITEMSG %#)
              of MSG))
          (RETFROM (FUNCTION
            WRITEFOLDERMARKBYTES]
            (MENU (fetch (MAILFOLDER BROWSERMENU) of FOLDER)))
            (LA.RESETSHADE (LA.MENU.ITEM (FUNCTION \LAFITE.UPDATE)
              MENU)
              MENU)
            (\LAFITE.UPDATE.FOLDER FOLDER)))
; Take the conservative approach--flush the toc and reparse.
    (SETQ DELETE-TOC T)))
(if [AND DELETE-TOC (SETQ TOCFILE (INFILEP (TOCFILENAME (fetch (MAILFOLDER FULLFOLDERNAME) of FOLDER]
  then (DELFILE TOCFILE))
(LAB.PROMPTPRINT FOLDER " Rebrowsing...")
(CLEARW BROWSERWINDOW)
;; It might be nice to restore the old selection if possible...(save current selection, then call LOADMAILFOLDER, select the same numbered
;; messages, then call LAB.DISPLAYFOLDER)
(if (LAB.LOADFOLDER FOLDER)
  then
    (COND
      (CLOSEFLG (\LAFITE.FINISH.UPDATE BROWSERWINDOW FOLDER :SHRINK)))
      (CASE IFCHANGED
        (:OK
          (\LAFITE.OPEN.FOLDER FOLDER DESIREDACCESS))
          ; Return (possibly new) stream after rebrowse
        ((NIL)
          (NIL)
          ; Return NIL to indicate change
          NIL)
        (T
          ; Abort operation.
          (ERROR!)))
    else
      ; Failed. Don't let anything more happen here
      (ERROR!))

```

(\LAFITE.FOLDER.CHANGED.MENU

```

[LAMBDA (FOLDER)
; Edited 20-Apr-89 19:35 by bvm
;; Put up a menu asking whether to save changes before rebrowsing folder. Returns one of T (save), NIL (don't), or :CLOSE (forget it altogether).
(LET [(REG (WINDOWPROP (fetch (MAILFOLDER BROWSERMENUWINDOW) of FOLDER)
  'REGION))
      (ITEMS ' ("Save current changes first" T "Attempt to write out the unsaved new marks and deletions
        before rebrowsing the folder.")
        ("Just rebrowse" NIL "Forget any changes I have made to the browser--just get the new
        contents.")
        ("Close Browser" :CLOSE "Close the browser now, forgetting any changes.")
      (MENU (create MENU
        ITEMS _ ITEMS
        MENUFONT _ LAFITEMENUFONT
        CENTERFLG _ T
        MENUROWS _ 1
        ITEMWIDTH _ (MAX (QUOTIENT (fetch (REGION WIDTH) of REG)
          3)
          (STRINGWIDTH (CAAR ITEMS)
            LAFITEMENUFONT)))
        (PROGN
          (LA.POSITION.FROM.REGION REG))
        T])
; Position menu over the browser's menu

```

(\LAFITE.SET.FOLDER.STREAM

```

[LAMBDA (FOLDER STREAM)
; Edited 30-Sep-87 16:45 by bvm:
;; Called from the few places that open/create a stream without going thru lafite.open.folder--stores in FOLDER all the info you like to cache about
;; STREAM. Returns STREAM
(LET ((FULL (FULLNAME STREAM)))
  (replace (MAILFOLDER FULLFOLDERNAME) of FOLDER with FULL)
  (replace (MAILFOLDER SHORTFOLDERNAME) of FOLDER with (LA.SHORTFILENAME FULL LAFITEMAIL.EXT))
  (replace (MAILFOLDER FOLDEROFPTR) of FOLDER with (GETEOFPTR STREAM))
  (replace (MAILFOLDER FOLDERCREATIONDATE) of FOLDER with (GETFILEINFO STREAM 'ICREATIONDATE))
  (replace (MAILFOLDER FOLDERSTREAM) of FOLDER with STREAM)
  STREAM])

```

(\LAFITE.OPENSTREAM

```

[LAMBDA (FILE ACCESS RECOG EOFFN BIGBUFS TYPE)
; Edited 8-Sep-88 14:27 by bvm
(LET* [( *UPPER-CASE-FILE-NAMES* NIL)
        (S (OPENSTREAM FILE ACCESS RECOG ` (,@[AND EOFFN `((ENDOFSTREAMOP ,EOFFN)
          ,@[AND BIGBUFS `((BUFFERS ,LAFITEBUFFERSIZE]
          ,@[AND TYPE `((TYPE ,TYPE)
        (if (AND TYPE (NEQ TYPE 'TEXT))
          then
            ; Force the stupid device to have eol CR, no matter what it
            ; thought (take that, Maiko)

```

```

    (SETFILEINFO S 'EOL 'CR))
S])

```

(\LAFITE.CREATE.MENU

```

[LAMBDA (ITEMS TITLE DONTCHANGEOFFSET) ; Edited 23-Aug-88 18:30 by bvm
;; Create a Lafite menu using its font. Optional title. DONTCHANGEOFFSET inhibits setting the CHANGEOFFSETFLG field.
(create MENU
  ITEMS _ ITEMS
  MENUFONT _ LAFITEMENUFONT
  TITLE _ TITLE
  CENTERFLG _ T
  CHANGEOFFSETFLG _ (NOT DONTCHANGEOFFSET])

```

(\LAFITE.EOF

```

[LAMBDA (STREAM) ; Edited 24-Jun-2021 19:16 by rmk:
;; End of stream op for Lafite mail folders. Return endless EOLS's so that parses eventually stop. This is now done in a format independent way.
;; We create a byte stream for the current external format of stream, print an EOL on to it, and then keep returning the bytes that encode the EOL. If
;; there is a need for an XCCS charset shift or any other magic, that will show up in the byte stream
(LET (BYTESTREAM)
  (IF [NULL (SETQ BYTESTREAM (STREAMPROP STREAM 'BYTESTREAM)]
      THEN (SETQ BYTESTREAM (\FORMATBYTESTREAM STREAM NIL)) ; First time, set it up
      (STREAMPROP STREAM 'BYTESTREAM BYTESTREAM)
      (TERPRI BYTESTREAM)
      (SETFILEPTR BYTESTREAM 0)
      (BIN BYTESTREAM)
  ELSEIF (BIN BYTESTREAM)
  ELSE ;; Ran off the end, Reset to make sure it remains consistent with STREAM after it has been reading our bytes
    (\FORMATBYTESTREAM STREAM BYTESTREAM)
    (TERPRI BYTESTREAM)
    (SETFILEPTR BYTESTREAM 0)
    (BIN BYTESTREAM])

```

(\LAFITE.CLOSE.FOLDER

```

[LAMBDA (MAILFOLDER REALLYP) ; Edited 14-Oct-87 20:18 by bvm:
;;; If MAILFOLDER is open for output, make sure it is completely written out. If REALLYP then actually close the file
(LET ((STREAM (fetch (MAILFOLDER FOLDERSTREAM) of MAILFOLDER)))
  (COND
    ([AND STREAM (COND
      ((OPENP STREAM 'OUTPUT)
       (FORCEOUTPUT STREAM T) ; Due to Leaf bug, best to do the FORCEOUTPUT first even if
                               ; we're really closing it
      (replace (MAILFOLDER FOLDERCREATIONDATE) of MAILFOLDER with (GETFILEINFO STREAM
                                                                    'ICREATIONDATE)) ; Update creation date in case it's a device where writing to it
                                                                    ; affects it (always true over savevm for some devices)
      REALLYP)
      (T (AND REALLYP (OPENP STREAM) ; Yes, close it for real
        (PROG1 (CLOSEF STREAM)
          (replace (MAILFOLDER FOLDERSTREAM) of MAILFOLDER with NIL))))))
  )

```

(DEFINEQ

(\LAFITE.DESCRIBE.FOLDER

```

[LAMBDA (FOLDER) ; Edited 7-Sep-88 18:55 by bvm
  (LAB.FORMAT FOLDER "File ~A contains ~D messages ~@[ (~D deleted) ~]in ~D pages." (fetch (MAILFOLDER
                                                                                               FULLFOLDERNAME
                                                                                               of FOLDER)
    (fetch (MAILFOLDER %OFMESSAGES) of FOLDER)
    [AND (fetch (MAILFOLDER FOLDERNEEDSEXPUNGE) of FOLDER)
      (for I from 1 to (fetch (MAILFOLDER %OFMESSAGES) of FOLDER)
        bind (MESSAGES _ (fetch (MAILFOLDER MESSAGEDESCRIPTORS) of FOLDER))
        count (fetch (LAFITEMSG DELETED?) of (NTHMESSAGE MESSAGES I]
      (FOLDHI (fetch (MAILFOLDER FOLDEREOFPTR) of FOLDER)
        BYTESPERPAGE])
  )

```

;; Make is easy to load new versions of Lafite

(DEFINEQ

(\LOAD-LAFITE

```

[LAMBDA (DIR SOURCEP) ; Edited 23-Feb-2024 23:02 by rmk
; Edited 3-May-89 18:39 by bvm

```

```

;; Load Lafite from a specified directory (or the dir where we find the first file). If SOURCEP true we load the sources PROP, else the compiled files
;; SYSLOAD. When loading compiled, we only load files that are noted as already loaded, since those are the only ones that won't be
;; automatically loaded by the FILES command in file LAFITE (which must have been loaded if this function is defined).
(SETQ DIR (MKLIST DIR))
(for FILE in (if SOURCEP
  then LAFITEFILES
  else (REMOVE 'LAFITE-DECLS LAFITEFILES))
  bind F when (OR SOURCEP (GET FILE 'FILEDATES))
  collect (if (SETQ F (if SOURCEP
    then (FINDFILE FILE T DIR)
    else (FINDFILE-WITH-EXTENSIONS FILE DIR *COMPILED-EXTENSIONS*)))
    then [SETQ F (LOAD F (COND
      ((NOT SOURCEP)
       'SYSLOAD)
      ((EQ F 'LAFITE-DECLS)
       T)
      (T 'PROP)
    ]
    [if (NULL DIR)
      then
        ; Fix dir for subsequent loading
        (SETQ DIR (LIST (PACKFILENAME.STRING 'NAME NIL 'EXTENSION NIL 'VERSION NIL
          'BODY F]
      F
    else (CONCAT FILE " not found"]])
)

(RPAQQ LAFITEFILES (LAFITE-DECLS LAFITE-BROWSE LAFITE-COMMANDS LAFITE-FOLDERS LAFITE-MAIL LAFITE-SEND
  LAFITE-SORT LAFITE-TEDIT LAFITE-NSMAIL OLDNSMAIL LAFITE-NEWSMAIL LAFITE-FIND
  LAFITE-MAILSCAVENGE LAFITE))

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(FILESLoad (SOURCE)
  LAFITE-DECLS)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(LOCALVARS . T)
)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS TEDIT.DEFAULT.MENU LAFITEFILES *COMPILED-EXTENSIONS*)
)

(CL:PROCLAIM ' (CL:SPECIAL *LAFITE-LOGGING-IN*))
)

(/DECLAREDATATYPE 'MAILFOLDER
  ' (FLAG FLAG FLAG FLAG FLAG (BITS 3)
    POINTER FLAG FLAG FLAG FLAG FLAG FLAG FLAG FLAG FLAG POINTER POINTER POINTER POINTER POINTER WORD WORD
    WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD WORD
    POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER
    POINTER POINTER POINTER)
  ;; ---field descriptor list elided by lister---
  ' 66)

(/DECLAREDATATYPE 'LAFITEMSG
  ' (FLAG FLAG FLAG FLAG FLAG (BITS 3)
    BYTE WORD POINTER POINTER WORD WORD FLAG FLAG FLAG FLAG FLAG POINTER FLAG FLAG FLAG FLAG FLAG POINTER
    POINTER POINTER FIXP)
  ;; ---field descriptor list elided by lister---
  ' 18)

(ADDTovar SYSTEMRECLST
  (DATATYPE MAILFOLDER ((BROWSERPROMPTDIRTY FLAG)
    (BROWSERPROMPTGREW FLAG)
    (FOLDERNEEDSUPDATE FLAG)
    (FOLDERNEEDSEXPUNGE FLAG)
    (FOLDERBEINGUPDATED FLAG)
    (BROWSERSTATUS BITS 3)
    (FULLFOLDERNAME POINTER)
    (FOLDEROKTOSHRINK FLAG)
    (FOLDERGETSMail FLAG)
    (FOLDEROUTOFORDER FLAG)
    (NIL 5 FLAG)
    (VERSIONLESSFOLDERNAME POINTER)
    (SHORTFOLDERNAME POINTER)
    (FOLDERSTREAM POINTER)
    (MESSAGEDESCRIPTORS POINTER)
    (FOLDERLOCK POINTER)
    (%#OFMESSAGES WORD)
    (TOCLASTMESSAGE# WORD)
    (BROWSERFONTHEIGHT WORD)
    (BROWSERFONTASCENT WORD)

```

```

(BROWSERFONTDESCENT WORD)
(BROWSERMAXXPOS WORD)
(ORDINALXPOS WORD)
(DATEXPOS WORD)
(FROMXPOS WORD)
(FROMMAXXPOS WORD)
(SUBJECTXPOS WORD)
(BROWSERDIGITWIDTH WORD)
(FIRSTSELECTEDMESSAGE WORD)
(LASTSELECTEDMESSAGE WORD)
(FIRSTCHANGEDMESSAGE WORD)
(CURRENTPROMPTLINE WORD)
(CURRENTDISPLAYEDSTREAM POINTER)
(BROWSEREXTENT POINTER)
(BROWSERORIGIN POINTER)
(FOLDERDISPLAYREGION POINTER)
(BROWSERWINDOW POINTER)
(BROWSERMENU POINTER)
(BROWSERMENUWINDOW POINTER)
(BROWSERPROMPTWINDOW POINTER)
(ORIGINALBROWSERTITLE POINTER)
(FOLDERDISPLAYWINDOWS POINTER)
(FOLDEREOPFTR POINTER)
(DEFAULTMOVETOFILE POINTER)
(CURRENTDISPLAYEDMESSAGE POINTER)
(BROWSERUPDATEFROMHERE POINTER)
(BROWSERLAYOUT POINTER)
(FOLDERCREATIONDATE POINTER)
(HARDCOPYMESSAGES POINTER)
(HARDCOPYSTREAM POINTER)))
(DATATYPE LAFITEMSG ((PARSED? FLAG)
(DELETED? FLAG)
(SEEN? FLAG)
(DATEKNOWN? FLAG)
(DATEFETCHED? FLAG)
(MODEBITS BITS 3)
(MARKCHAR BYTE)
(%# WORD)
(BEGIN POINTER)
(MESSAGELENGTH POINTER)
(STAMPLENGTH WORD)
(TOCLENGTH WORD)
(MESSAGELENGTHCHANGED? FLAG)
(SELECTED? FLAG)
(MSGFROMMECHECKED? FLAG)
(MSGFROMMETRUTH FLAG)
(DATE POINTER)
(NIL FLAG)
(MARKSCHANGEDINFILE? FLAG)
(MARKSCHANGEDINTOC? FLAG)
(NIL FLAG)
(FROM POINTER)
(SUBJECT POINTER)
(TO POINTER)
(IDATE FIXP))))

```

(DEFINEQ

(\LAFITE.GLOBAL.INIT

[LAMBDA NIL

; Edited 21-Apr-89 16:10 by bvm

; need to do this so you can send a message without 'starting'

; lafite

(DECLARE (GLOBALVARS BackgroundMenu BackgroundMenuCommands))

(LET ([OLDITEM (OR (CL:ASSOC "SendMail" BackgroundMenuCommands :TEST 'STRING-EQUAL)

(CL:ASSOC "Mail" BackgroundMenuCommands :TEST 'STRING-EQUAL]

(NEWITEM LAFITE.BACKGROUND.ITEM))

[SETQ BackgroundMenuCommands (if OLDITEM

then (SUBST NEWITEM OLDITEM BackgroundMenuCommands)

else (APPEND BackgroundMenuCommands (LIST NEWITEM]

(SETQ BackgroundMenu NIL))

(LAFITE.INIT.PARSETABLES)

(SETQ \LAFITE.MAILSERVERLOCK (CREATE.MONITORLOCK "Lafite Mail Servers"))

; Used by anyone who calls \LAFITE.GET.USER.DATA or

; otherwise tries to muck with \LAFITEUSERDATA

; For reading and writing the profile

(SETQ LAFITEPROFILERDTBL (COPYREADTABLE 'ORIG))

(DEFPRINT 'MAILFOLDER (FUNCTION \MAILFOLDER.DEFPRINT))

(DEFPRINT 'LAFITEMSG (FUNCTION \LAFITEMSG.DEFPRINT))

(if \LAFITEMODE

then

; There was a mode enabled on entry. Reset it in case of

; incompatible mode records

(SETQ \LAFITEMODE (ASSOC (CAR \LAFITEMODE)

LAFITEMODELIST)))

(for MODE in LAFITEMODELIST when (LISTP (CDR MODE)) do (\LAFITE.REGISTER.MODE MODE))

NIL])

)

(DECLARE%: DONTVAL@LOAD DOCOPY

(FILESLOAD TEDIT ATTACHEDWINDOW)

(FILESLOAD LAFITE-BROWSE LAFITE-COMMANDS LAFITE-FOLDERS LAFITE-SEND LAFITE-MAIL LAFITE-SORT LAFITE-TEDIT
LAFITE-FIND LAFITE-MAILSCAVENGE)(CL:PROCLAIM ' (GLOBAL ANSWERMARK BROWSERMARKXPOSITION DEFAULTMAILFOLDERNAME LAFITE.2COLUMN.MENU.MIN.ITEMS
LAFITE.AUTO.MOVE.MENU LAFITE.BACKGROUND.ITEM LAFITE.BROWSER.ICON.PREFERENCE
LAFITE.BROWSER.LAYOUTS LAFITE.DISPLAY.SIZE LAFITE.DONT.DISPLAY.HEADERS
LAFITE.DONT.FORWARD.HEADERS LAFITE.DONT.HARDCOPY.HEADERS LAFITE.DUMMY.HALF.SHADE
LAFITE.DUMMY.SHADE LAFITE.EDITOR.LAYOUTS LAFITE.EDITOR.SIZE LAFITE.EXTRA.DISPLAY.COMMANDS
LAFITE.EXTRA.MOVE.ITEMS LAFITE.FOLDER.ICON LAFITE.FOLDER.MENU.FONT LAFITE.HOST.ABBREVS
LAFITE.LOOKS.SUBCOMMANDS LAFITE.MIDDLE.UPDATE LAFITE.PROFILE.VARS LAFITE.SIGNATURE
LAFITE.USE.ALL.MODES LAFITEBROWSERFONT LAFITEBROWSERICONMENU LAFITEBROWSERICONMENUITEMS
LAFITEBROWSERMENUITEMS LAFITEBROWSERREGION LAFITEBUFFERSIZE LAFITEBUSYWAITTIME
LAFITECLOSEITEM LAFITECOMMANDMENUITEMS LAFITEDEFAULTHOST&DIR LAFITEDELETEDLINEHEIGHT
LAFITEDISPLAYAFTERDELETEFLG LAFITEDISPLAYFONT LAFITEDISPLAYREGION LAFITEDL.EXT
LAFITEDLDIRECTORIES LAFITEENDOFMESSAGEFONT LAFITEENDOFMESSAGESTR LAFITEEXTRAMENUFLG
LAFITEEXTRAMENUITEMS LAFITEFIXEDWIDTHFONT LAFITEFORM.EXT LAFITEFORMFILES LAFITEFROMFRACTION
LAFITEHARDCOPY.MIN.TOC LAFITEHARDCOPYBATCHFLG LAFITEHARDCOPYBATCHSHADE LAFITEHARDCOPYFONT
LAFITEHARDCOPYSEPARATOR LAFITEIFFROMMETHENSEENFLG LAFITEINFO.NAME LAFITEMAIL.EXT
LAFITEMENUFONT LAFITEMENUVARS LAFITEMINFROMCHARS LAFITEMODEDEFAULT LAFITEMODELST
LAFITEMOVETOCONFIRMFLG LAFITEMSGICONFONT LAFITENEWPAGEFLG LAFITESHOWMODEFLG
LAFITESTATUSWINDOWMINWIDTH LAFITESTATUSWINDOWPOSITION LAFITESUBBROWSEMENUEITEMS
LAFITESUBQUITMENUITEMS LAFITETITLEFONT LAFITETOC.EXT LAFITEUPDATEMENUITEMS MOVETOMARK))

(CL:PROCLAIM ' (CL:SPECIAL LAFITEVERIFYFLG))

(\LAFITE.GLOBAL.INIT)

(COND
 (EQ MAKESYSNAME :LYRIC)
 (FILESLOAD (SYSLOAD)
 NSCHARPATCH) ; Patch to horrid Lyric NS chars bug
 (MOVD? 'PROMPTFORWORD 'TTYINPROMPTFORWORD NIL T)))
)

(DECLARE%: DOEVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILERVARS

(ADDTOVAR **NLAMA**)(ADDTOVAR **NLAML**)(ADDTOVAR **LAMA** LAFITE)
)

FUNCTION INDEX

DELETEMAILFOLDER	14	SET.LAFITE.MODE.INTERACTIVELY	8	\LAFITE.OFF	2
DOMAINLAFITECOMMAND	7	TOCFILENAME	14	\LAFITE.OPEN.FOLDER	14
EXTRACTMENUCOMMAND	7	\LAFITE.ADDMESSAGES.TO.ARRAY	13	\LAFITE.OPENSTREAM	17
LA.MENU.ITEM	13	\LAFITE.AFTERLOGIN	12	\LAFITE.PROCESS	4
LA.POSITION.FROM.REGION	13	\LAFITE.ASSURE.FOLDER.READY	12	\LAFITE.QUIT	4
LA.RESETSHADE	12	\LAFITE.CHECK.FOLDERS	12	\LAFITE.QUIT.PROC	5
LAFITE	2	\LAFITE.CLOSE.FOLDER	18	\LAFITE.REAUTHENTICATE	9
LAFITE.ALL.MODES.P	8	\LAFITE.COMPUTE.MODE.COMMANDS	8	\LAFITE.REBROWSE.FOLDER	16
LAFITE.AROUNDEXIT	11	\LAFITE.CREATE.MENU	18	\LAFITE.REPORT.FILE.WONT.OPEN	15
LAFITE.COMPUTE.CACHED.VARS	3	\LAFITE.DESCRIBE.FOLDER	18	\LAFITE.RESTART	4
LAFITE.ON.FROM.BACKGROUND	2	\LAFITE.EOF	18	\LAFITE.SET.FOLDER.STREAM	17
LAFITE.PROMPT.FOR.LOGIN	9	\LAFITE.FOLDER.CHANGED	15	\LAFITE.SHOW.MODE	7
LAFITE.SHOW.MODE.P	8	\LAFITE.FOLDER.CHANGED.MENU	17	\LAFITE.START.ABORT	4
LAFITE.TOGGLE.SERVER.TRACE	7	\LAFITE.GLOBAL.INIT	20	\LAFITE.START.PROC	3
LAFITEDEFAULTHOST&DIR	6	\LAFITE.INFER.MODE	7	\LAFITE.SUBQUIT	4
LAFITEMODE	7	\LAFITE.LOGIN	8	\LAFITEDEFAULTHOST&DIR	6
LOAD-LAFITE	18	\LAFITE.LOGIN.NORESTART	8	\LAFITEMSG.DEFPRINT	13
MAILFOLDERBUSY	14	\LAFITE.MAKE.MSGARRAY	13	\MAILFOLDER.DEFPRINT	13
MAKELAFITECOMMANDWINDOW	6	\LAFITE.MARK.FOLDERS.OBSOLETE	12		
NTHMESSAGE	13	\LAFITE.MODE.TITLE	7		

VARIABLE INDEX

LAFITE-LOGGING-IN	11	LAFITEDEBUGFLG	10	LAFITESUBQUITMENU	11
LAFITE-WELL-KNOWN-MODES	11	LAFITEDEFAULTHOST&DIR	9	LAFITESUBQUITMENUITEMS	11
ANOTHERFOLDERMENUITEM	11	LAFITEDISPLAYFONT	10	LAFITESYSTEMDATE	2
ANSWERMARK	10	LAFITEEOL	10	LAFITETITLEFONT	9
DEFAULTMAILFOLDERNAME	10	LAFITEFILES	19	LAFITEUPDATEMENUITEMS	11
FORWARDMARK	10	LAFITEFIXEDWIDTHFONT	10	LAFITEVERSION#	2
HARDCOPYBATCHMARK	10	LAFITEHARDCOPYFONT	10	MOVETOMARK	10
HARDCOPYMARK	10	LAFITEIFFFROMMETHENSEENFLG	9	SEENMARK	10
HEARDMARK	10	LAFITEINFO.NAME	10	SYSTEMRECLST	19
LA.CROSSCURSOR	14	LAFITEITEMBUSYSHADE	10	UNSEENMARK	10
LAFITE.BACKGROUND.ITEM	8	LAFITEMAIL.EXT	10	UNSUPPLIEDFIELDSTR	10
LAFITE.DONT.DISPLAY.HEADERS	10	LAFITEMARKS	10	\ACTIVELAFITEFOLDERS	11
LAFITE.DONT.FORWARD.HEADERS	10	LAFITEMENUFONT	9	\LAFITE.ACTIVE	11
LAFITE.DONT.HARDCOPY.HEADERS	10	LAFITEMENUVARS	11	\LAFITE.ACTIVE.MODES	11
LAFITE.FOLDER.MENU.FONT	10	LAFITEMODEDEFAULT	10	\LAFITE.AUTHENTICATION.FAILURE	8
LAFITE.PERSONAL.VARS	11	LAFITEMODELST	8	\LAFITE.CURRENT.USER	11
LAFITE.SIGNATURE	9	LAFITEMSGICONFONT	10	\LAFITE.MODE.CHOICES	11
LAFITE.USE.ALL.MODES	10	LAFITEPROFILEVARS	9	\LAFITE.READY	11
LAFITE.USER.INFO	11	LAFITERANDOMGLOBALS	10	\LAFITE.TEMPFILES	11
LAFITEBROWSERFONT	10	LAFITESHOWMODEFLG	10	\LAFITEDEFAULTHOST&DIR	11
LAFITEBUFFERSIZE	9	LAFITESTATUSWINDOW	11	\LAFITEMODE	8
LAFITEBUSYWAITTIME	10	LAFITESTATUSWINDOWMINWIDTH	10	\SYSTEMCACHEVARS	11
LAFITECOMMANDMENUITEMS	10	LAFITESTATUSWINDOWPOSITION	10		

PROPERTY INDEX

LAFITE	7	LAFITEMODELST	8
--------------	---	---------------------	---
