Proposal for Loops manual contents.

This ordering is based on the Interlisp Reference manual. Numbers in [[]]'s indicate the coresponding sections in the (new) IRM.

[[Volume 1 -- Language]]

Introduction [[1]]

Classes [[2]]

- The hierarchy
- Tofu
- Object
- Class
- LispClassTable

Instances [[3]]

MetaClasses [[4]]

- The Golden Braid
- MetaClass
- AbstractClass

AnnotatedValues [[5]]

- `NotSetValue`

Methods [[6]]

- Categories
- `DefaultComment`
- `SubclassResponsibility`

Conditionals and Iterative Statements [[9]]

- Date type predicates
  - `Object?`
  - `Class?`
  - `Instance?`
  - `(type? annotatedValue` *`form`*`)`
- Other predicates
  - `HasIV`, `HasIV!`, `HasCV`
  - `Understands`
  - `InstOf`, `InstOf!`
- Interative statements
  - `in-supers-of`

Message sending forms [[10]]

- List all message sending forms (even if described elsewhere)
- Looking up methods
  - `FetchMethod`
  - `FetchMethodOrHelp`

Miscellaneous [[12]]

System version information
Pattern match functions
FEATURES

[[Volume 2 -- Environment]]
Browsing and Exec Level Commands [[13]]
UNDOable version of PutValue?
LASTWORD set by DefineMethods
LASTCLASS set by DefineClass
Loops Icon
Browsers, in general
MaxLatticeHeight
MaxLatticeWidth
Class Browsers
File Browsers
Other Browsers
Top level commands
DefineClass
DefineMethod
Errors and Breaks [[14]]
LoopsDebugFlg
ErrorOnNameConflict
IVMissing
IVValueMissing
MessageNotUnderstood
Breaking and Tracing [[15]]
Breaking and Tracing IV access
Breaking and Tracing methods
Gauges
Editing [[16]]
File Package [[17]]
Compiling [[18]]
Macros for GetValue, PutValue
Refering to Loops objects in compiled code
Masterscope [[19]]
DWIM [[20]]
No method, but a fn=> use the fn. How about other way?
Performance Issues [[22]]
Garbage Collection
Space
Speed
Caching

ClearAllCaches
Method lookup caches
IV Lookup caches
Processes [[23]]
_Process, _Process!

[[Volume 3 -- Input/Output]]
Reading and Printing [[25]]
The # read macro character
How Classes print
How Instances print
ObjectAlwaysPPFlag
ObjectDontPPFlag
How AnnotatedValues print
DefaultActiveValueClassName
UIDs
When assigned
User Input/Output Packages [[26]]
Inspector
Extensions to ?=
Loops windows [[28]]

[[Loops Library Packages Manual]]
Virtual Copies [[no chapter]]
Composite Objects [[no chapter]]

[[Release Notes]]
Installation
Customer Support
Conversion From old Loops
Future Directions